

Control method for a turnstile device, terminal, turnstile device and system

TECHNICAL FIELD

The present invention relates to a turnstile device, in particular to a control
5 method for a turnstile device, a terminal, a turnstile device and a system.

BACKGROUND

Identity authentication via a turnstile device is usually required for admittance in subways, railway stations or office buildings and other public places.

10 Most of the existing turnstile devices are based on card swiping operation to achieve user authentication. However, in such places as subways, high-speed railway stations and other places with high passenger throughput, cards may easily get lost when users pass the turnstile device channel of a turnstile device by swiping cards, and users often forget to bring cards, so that they cannot timely
15 swipe card to enter or exit the station, resulting in inconvenience for users.

Although some turnstile devices have already used face recognition for access control of turnstile devices, which requires networking of turnstile devices to transmit images collected by cameras on turnstile devices to an Internet server and to control admittance via turnstile devices after image authentication.

20 Because the network is prone to delays, making turnstile devices prone to failure of normal opening, delayed opening, and so on, and such turnstile devices are prone to breakdown in case of high passenger throughput, resulting in traffic congestions, so that no extensive application is possible.

25 SUMMARY

The present invention aims to solve the technical problem to enable convenient and fast opening of a turnstile device channel without swiping a card by the user.

The object of the present invention is to provide a turnstile device, a termi-

nal, a turnstile device and a system to enable convenient and fast opening of a turnstile device channel without swiping a card by the user.

In order to achieve the above-mentioned object, the present invention provides a control method for a turnstile device comprising following steps:

5 Acquiring a first face feature value of a user sent by a terminal;

 Acquiring and processing a face image of the user collected by a first camera module to acquire a second face feature value;

 Matching the first face feature value and the second face feature value according to a preset matching rule;

10 Opening the turnstile device channel of the turnstile device in case of a successful matching.

 Further, as a preferred option, the step of acquiring a first face feature value of a user sent by a terminal includes:

15 Establishing a Bluetooth wireless communication connection with the terminal and receiving the first face feature value via a Bluetooth wireless communication channel.

 Further, as a preferred option, the step of acquiring and processing a face image of the user collected by a first camera module to acquire a second face feature value includes: Acquiring a face image of the user collected by the first camera module in real time; Displaying the face image by a first display module in real time; Processing the face image according to a preset image algorithm to acquire a second face feature value; and clearing the previously cached data when the storage capacity of the face image collected in real time is greater than a preset value.

25 Further, as a preferred option, the step of opening the turnstile device channel of the turnstile device in case of a successful matching includes: Determining based on the entries and exits data acquired from the terminal whether the current entries and exits data contains entries information in case of a successful matching; Opening the turnstile device channel and sending the entries information to

the terminal to update the entries and exits data with the entries information if it is determined that the entries and exits data does not include the entries information and the current turnstile device channel is an entry channel; and opening the turnstile device channel and sending exits information to the terminal to update the entries and exits data with the exits information if it is determined that the entries and exits data includes the entries information and the current turnstile device channel is an exit channel.

Further, as a preferred option, after the step of opening the turnstile device channel of the turnstile device in case of a successful matching, the method includes further: Deleting automatically the first face feature value and the second face feature value previously stored according to the recording time when the data storage capacity of the cumulatively acquired first face feature value and second face feature value exceeds a preset data volume.

The present application further provides a control method for a turnstile device comprising following steps:

Receiving a first face feature value sent by a server, wherein the server processes the user's face image according to a preset image algorithm to acquire the first face feature value;

Sending the first face feature value to the turnstile device.

Further, as a preferred option, before the step of receiving a first face feature value sent by a server, the method includes further: Acquiring a face image of the user; and transmitting the face image to the server.

Further, as a preferred option, the step of sending the first face feature value to the turnstile device includes: Establishing a Bluetooth wireless communication connection with the turnstile device; and sending the first face feature value to the turnstile device via a Bluetooth wireless communication channel.

Further, as a preferred option, the method includes further: Sending entries and exits data to the turnstile device; Receiving the entries information sent by the turnstile device and updating the entries and exits data with the entries information.

mation; and receiving the exits information sent by the turnstile device and updating the entries and exits data with the exits information.

The present application further provides a turnstile device comprising:

5 A wireless transmission device for acquiring a first face feature value of a user sent by a terminal;

A face recognition device used for acquiring and processing a face image of the user collected by a first camera module to acquire a second face feature value and for matching the first face feature value and the second face feature value according to a preset matching rule;

10 A control device for opening the turnstile device channel of the turnstile device in response to an instruction after a successful matching by the face recognition device.

Further, as a preferred option, the wireless transmission device includes a first Bluetooth module for establishing a Bluetooth wireless communication connection with the terminal and receiving the first face feature value via a Bluetooth
15 wireless communication channel.

Further, as a preferred option, the face recognition device includes: A first camera module for collecting a face image of the user in real time; A first display module for displaying the face image in real time; A matching module for processing the face image according to a preset image algorithm to acquire a second
20 face feature value and for matching the first face feature value and the second face feature value according to a preset matching rule; and a data storage module for storing the face image and clearing the previously cached data via the processor when the face image data collected in real time is larger than a preset value.
25

Further, as a preferred option, the control device includes: A data analysis module for determining based on the entries and exits data acquired from the terminal whether the current entries and exits data contains entries information after responding to an instruction after a successful matching by the face recogni-

tion device; and a turnstile device channel opening module for: Opening the turnstile device channel and sending entries information to the terminal to update the entries and exits data with the entries information if the data analysis module determines that the entries and exits data does not include the entries information
5 and the current turnstile device channel is an entry channel; and opening the turnstile device channel and sending exits information to the terminal to update the entries and exits data with the exits information if the data analysis module determines that the entries and exits data includes the entries information and the current turnstile device channel is an exit channel.

10 Further, as a preferred option, the face recognition device further includes a data clearing module for deleting automatically the first face feature value and the second face feature value previously stored according to the recording time when the data storage capacity of the cumulatively acquired first face feature value and second face feature value exceeds a preset data volume.

15 The present application further provides a terminal comprising a wireless communication device for receiving a first face feature value sent by a server and sending the first face feature value to the turnstile device, wherein the server processes the user's face image acquired according to a preset image algorithm to acquire the first face feature value.

20 Further, as a preferred option, the wireless communication device includes: A network transmission module for receiving the first face feature value sent by the server; and a second Bluetooth module for establishing a Bluetooth wireless communication connection with the turnstile device and sending the first face feature value to the turnstile device via a Bluetooth wireless communication
25 channel.

Further, as a preferred option, the terminal further includes an image collection device for acquiring the face image of the user; wherein the network transmission module is also used for transmitting the face image to the server.

Further, as a preferred option, the second Bluetooth module are further used

for: Sending entries and exits data to the turnstile device; Receiving the entries information sent by the turnstile device and updating the entries and exits data with the entries information; and receiving the exits information sent by the turnstile device and updating the entries and exits data with the exits information.

5 The present application further provides a turnstile device access control system comprising a turnstile device and a terminal described above, the terminal being used for opening the turnstile device channel of the turnstile device.

Compared with the existing technology, the beneficial effect of the present invention is mainly embodied in that the present invention enables users to open a
10 turnstile device channel in a convenient and fast way without swiping a card.

BRIEF DESCRIPTION OF THE DIAGRAMS

Figure 1 is a flowchart of the control method for a turnstile device in a first embodiment of the present invention;

15 Figure 2 is a flowchart of the control method for a turnstile device in a second embodiment of the present invention;

Figure 3 is a flowchart of the Step S1 in the second embodiment of the present invention;

Figure 4 is a flowchart of the Step S2 in the second embodiment of the present invention;
20

Figure 5 is a flowchart of the Step S4 in the second embodiment of the present invention;

Figure 6 is another flowchart of the Step S4 in the second embodiment of the present invention;

25 Figure 7 is a flowchart of the control method for a turnstile device in a third embodiment of the present invention;

Figure 8 is a flowchart of the control method for a turnstile device in a fourth embodiment of the present invention;

Figure 9 is a flowchart of the Step S103 in the fourth embodiment of the

present invention;

Figure 10 is a flowchart of the Steps S104 to S106 in the third embodiment of the present invention;

Figure 11 is a block diagram of the circuit module of the turnstile device in a
5 fifth embodiment of the present invention;

Figure 12 is a block diagram of the circuit module of the turnstile device in a sixth embodiment of the present invention;

Figure 13 is a block diagram of the circuit module of the terminal in a seventh embodiment of the present invention;

10 Figure 14 is a block diagram of the circuit module of the terminal in an eighth embodiment of the present invention;

Figure 15 is a block diagram of the circuit module of the system in the seventh embodiment of the present invention;

15 Figure 16 is a block diagram of the circuit module of the system in a ninth embodiment of the present invention.

Reference signs: Turnstile device 6, wireless transmission device 61, first Bluetooth module 611, face recognition device 62, first camera module 621, first display module 622, matching module 623, data storage module 624, data clearing module 625, control device 63, data analysis module 631, turnstile device
20 channel opening module 632, terminal 9, wireless communication device 91, network transmission module 911, second Bluetooth module 912, image collection device 92, second camera module 921, second display module 922.

DETAILED DESCRIPTION OF THE INVENTION

25 The control method and the system for the turnstile device of the present invention are described below in details with reference to the drawings, which represents preferred embodiments of the present invention. It is understood that those skilled in this field can modify the present invention and still realize the beneficial effect of the present invention. The following description should

therefore be understood as being widely known to those skilled in this field and not as a restriction on the present invention.

The technical solutions disclosed in the embodiments of the present invention are applied to turnstile devices and terminals. The terminals can be mobile phones, tablets, smart wearable devices, personal digital assistants, mobile sale devices and other electronic devices that can be held by users, and the terminals can record terminal motion data, upload user's face image or collect user's face image and so on. Smart wearable devices can be wristband smart wearable devices, or smart wearable devices that can be worn on a user's upper limb, such as an intelligent wearable device that can be worn on a user's finger.

Embodiment 1

Refer to Figure 1. The present embodiment provides a control method for a turnstile device. The control method is used for a turnstile device and comprises following steps:

- Step S1: Acquiring a first face feature value of a user sent by a terminal;
- Step S2: Acquiring and processing a face image of the user collected by a first camera module to acquire a second face feature value;
- Step S3: Matching the first face feature value and the second face feature value according to a preset matching rule;
- Step S4: Opening the turnstile device channel of the turnstile device in case of a successful matching.

Specifically, the user uploads the user's face image acquired by a second camera module on the terminal via the terminal, for example, via a mobile phone, to a server on the Internet. A first face feature value is acquired by processing the face image based on a preset image algorithm, such as Baidu image algorithm, 360 image algorithm, Google image algorithm, etc. by the server and then sent to turnstile device via the terminal.

After acquiring the face image of the user collected by the first camera module, the turnstile device can acquire a second face feature value through an

offline processing via the preset image algorithm, such as Baidu image algorithm, 360 image algorithm, etc., and then match the first face feature value and the second face feature value according to a preset matching algorithm. If the matching is successful, a turnstile barrier used to open and close the turnstile device channel in the turnstile device can receive an open signal to open the turnstile device channel, allowing passengers to pass. If the matching is unsuccessful, the turnstile device channel remains closed. Preferably, the same algorithm is used for the image algorithms in steps S1 and S2, which can achieve higher matching degree, avoid the issue of failed matching and recognition due to the image algorithm's recognition precision, and improve the reliability of turnstile device and its control method in this application.

As can be seen from the above steps, the control method of the present application makes it unnecessary for the turnstile device to transmit the collected image to the Internet via a network, that is, a real-time second face feature value is acquired through offline processing, so as to enable convenient and fast opening of the turnstile device channel when the first face feature value sent by the terminal is acquired by the turnstile device, and the second face feature value and the first face feature value are matched. In this way, the issue of turnstile device breakdown or delayed opening due to network delays in the face image checking process for turnstile devices in the state of the art is solved. The turnstile device need not prestore the user's image during use, which reduces the work load of turnstile device, simplifies the operation, shortens the image authentication time of turnstile device, and improves the efficiency of turnstile device, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after the loss of the cards.

Specifically, the step S1 in this embodiment can also be preceded by step S2 and followed by step S3, so this embodiment does not limit or specify the sequence in which turnstile device acquires the first face image feature and the

second face image feature.

In addition, it is worth noting that first camera module can be the first camera module with which the turnstile device is equipped, or a separately provided module, which is not limited or specified in this embodiment.

5

Embodiment 2

Refer to Figure 2. The present embodiment provides a control method for a turnstile device. The control method is used for a turnstile device and comprises following steps:

- 10 Step S1: Acquiring a first face feature value of a user sent by a terminal;
- Step S2: Acquiring and processing a face image of the user collected by a first camera module to acquire a second face feature value;
- Step S3: Matching the first face feature value and the second face feature value according to a preset matching rule;
- 15 Step S4: Opening the turnstile device channel of the turnstile device in case of a successful matching.

Specifically, the user uploads the user's face image acquired by a second camera module on the terminal via the terminal, for example, via a mobile phone, to a server on the Internet. A first face feature value is acquired by processing the face image based on a preset image algorithm, such as Baidu image algorithm, 360 image algorithm, Google image algorithm, etc. by the server and then sent to turnstile device via the terminal.

20

After acquiring the face image of the user collected by the first camera module, the turnstile device can acquire a second face feature value through an offline processing via the preset image algorithm, such as Baidu image algorithm, 360 image algorithm, etc., and then match the first face feature value and the second face feature value according to a preset matching algorithm. If the matching is successful, a turnstile barrier used to open and close the turnstile device channel in the turnstile device can receive an open signal to open the turnstile de-

25

vice channel, allowing passengers to pass. If the matching is unsuccessful, the turnstile device channel remains closed. Preferably, the same algorithm is used for the image algorithms in steps S1 and S2, which can achieve higher matching degree, avoid the issue of failed matching and recognition due to the image algorithm's recognition precision, and improve the reliability of turnstile device and its control method in this application.

As can be seen from the above steps, the control method of the present application makes it unnecessary for the turnstile device to transmit the collected image to the Internet via a network, that is, a real-time second face feature value is acquired through offline processing, so as to enable convenient and fast opening of the turnstile device channel when the first face feature value sent by the terminal is acquired by the turnstile device, and the second face feature value and the first face feature value are matched. In this way, the issue of turnstile device breakdown or delayed opening due to network delays in the face image checking process for turnstile devices in the state of the art is solved. The turnstile device need not prestore the user's image during use, which reduces the work load of turnstile device, enables adaption to working environments with high passenger throughput, simplifies the operation, shortens the image authentication time of turnstile device, and improves the efficiency of turnstile device, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after the loss of the cards.

Specifically, as shown in Figures 3 and 4, the step S1 in this embodiment can also be preceded by step S2 and followed by step S3, so this embodiment does not limit or specify the sequence in which turnstile device acquires the first face image feature and the second face image feature.

Specifically, the step S1 can include:

Step S11: Establishing a Bluetooth wireless communication connection with the terminal;

Step S12: Receiving the first face feature value via a Bluetooth wireless communication channel.

The turnstile device is connected to the terminal via Bluetooth wireless communication connection and receives the first face feature value, which takes
5 advantage of the Bluetooth transmission speed and large transmission volume, ensures fast transmission of face feature value with a large data volume to the turnstile device, avoids delays, guarantees the smooth execution of subsequent steps and shortens the time needed to pass the turnstile device.

Obviously, the turnstile device in this embodiment can also realize the wire-
10 less communication connection between the turnstile device and the terminal through other wireless communication connections, such as Infrared wireless communication and WIFI wireless communication.

Further, as a preferred option, as shown in Figure 4, the step S2 can include:

Step S21: Acquiring a face image of the user collected by the first camera
15 module in real time;

Step S22: Displaying the face image by a first display module in real time;

Step S23: Processing the face image according to a preset image algorithm to acquire a second face feature value.

Displaying the user's face image collected by the first camera module in real
20 time through the first display module can enable the user to observe the displayed image, and quickly move into the collection area of the first camera module, which makes it more convenient for the first camera module to collect the user's face image, shortens the collection time of turnstile device, and improves the traffic efficiency.

25 The step S2 further includes:

Step S24: Clearing the previously cached data when the storage capacity of the face image collected in real time is greater than a preset value.

As can be seen from the description above, the above step can reduce the storage space occupied by real-time face images, reduce the manufacturing cost

and work load of the turnstile device and enable better adaption to situations with large passenger throughput.

In addition, it should be noted that the step S22 can also be a non-essential step for the step S2 of this embodiment, for example, by asking the user to stand
5 in the specified collection area, the displaying through the first display module can be omitted.

The step S24 can also be preceded by step S21 and followed by step S23, so the sequence among the steps S21 to S24 is neither limited nor further specified here.

10 Further, as a preferred option, as shown in Figure 5, when the current turnstile device channel is an entry channel, the step S4 can include:

Step S41: Determining based on the entries and exits data acquired from the terminal whether the current entries and exits data contains entries information in case of a successful matching;

15 Step S42: Opening the turnstile device channel and sending the entries information to the terminal to update the entries and exits data with the entries information if it is determined that the entries and exits data does not include the entries information.

20 Further, as a preferred option, as shown in Figure 6, when the current turnstile device channel is an exit channel, the step S4 can include:

Step S41': Determining based on the entries and exits data acquired from the terminal whether the current entries and exits data contains entries information in case of a successful matching;

25 Step S42': Opening the turnstile device channel and sending exits information to the terminal to update the entries and exits data with the exits information if it is determined that the entries and exits data includes the entries information.

As can be seen from the description above, when the turnstile device matches first face feature value and second face feature value successfully, it can be

determined based on the acquired entries and exits data whether the user has entered the station or not, so that the corresponding turnstile device can judge whether the user has entered the station based on the entries and exits data and decide whether to open the turnstile device channel to avoid undesirable opening
5 of the turnstile device channel.

It is worth noting that the updating of entries and exits data with entries information or exits information can take place by incorporating the same into the entries and exits data based on time sequence or by replacement and by incorporating the replaced data into a historical data records, which is neither limited nor
10 further specified in this embodiment.

It is worth noting that the method further includes the following step after step S41:

Determining the amount to be deducted based on the entries and exits data.

It can be seen that the turnstile device can determine the amount to be deducted based on the entries and exits information recorded in the entries and exits
15 data and the deduction rules. Here, it is necessary to explain that the entries and exits data in this embodiment cannot only include entries and exits information, but also include business data such as deduction rules, which is not further specified here.

20 After step S4, the present embodiment further includes:

Step S5: Deleting automatically the first face feature value and the second face feature value previously stored according to the recording time when the data storage capacity of the cumulatively acquired first face feature value and second face feature value exceeds a preset data volume.

25 It can be seen that this step can enable effective use of the storage space of the turnstile device, eliminating the concerns that the turnstile device cannot operate normally due to excessive storage capacity of the generated data when users pass the turnstile device, which helps meet the demand of large passenger traffic.

The preset data volume in this embodiment, such as the number of data en-

tries stored, can be determined by the current turnstile device storage space, working environment, daily passenger traffic and other factors.

In addition, the storage capacity of the first face feature value and second face feature value data cumulatively acquired in step S6 can also be transmitted
5 to a server via the back-end transmission or terminal transmission connected with the turnstile device, so as to achieve backup of turnstile access data.

Embodiment 3

Refer to Figure 7. The present embodiment provides a control method for a
10 turnstile device. The control method is used for a terminal and comprises following steps:

Step S102: Receiving a first face feature value sent by a server, wherein the server processes the face image according to a preset image algorithm to acquire the first face feature value;

15 Step S103: Sending the first face feature value to the turnstile device.

Specifically, in this application, the user can control the opening of the turnstile device terminal of the turnstile device via the terminal, for example a smart wrist watch, a mobile phone, etc., upload the user's face image to server through the local database or retrieve the user's face image stored in the server, so that
20 server can acquire the first face feature value by processing face image based on the preset image algorithm, such as Baidu image algorithm, 360 image algorithm, Google image algorithm, etc., and then send it to the terminal.

When users need to pass turnstile device, they can send the first face feature value to turnstile device via the terminal to open the turnstile device channel of
25 the turnstile device.

The control method of this application enables users to use a terminal that can receive the first face feature value to send the first face feature value to the turnstile device, which can easily and quickly open the turnstile device channel. In this way, the issue of turnstile device breakdown or delayed opening due to

network delays in the face image checking process for turnstile devices in the state of the art is solved. The turnstile device need not prestore the user's image during use, which reduces the work load of turnstile device, enables adaption to working environments with high passenger throughput, simplifies the operation, shortens the image authentication time of turnstile device, and improves the efficiency of turnstile device, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after the loss of the cards.

It should be noted that in this embodiment, the user can be registered through an APP in the terminal, and then the first face feature value corresponding to the registered user's face image can be acquired from server, wherein the first face feature value can be the user's face image collected by the user through other terminal, such as a mobile phone, a computer, etc., and the user's face image can be uploaded to server through the local database, or the user's face image stored in the server can be retrieved, then the first face feature value is acquired after image processing by the server.

Embodiment 4

Refer to Figure 8. The present embodiment provides a control method for a turnstile device. The control method is used for a terminal and comprises following steps:

Step S102: Receiving a first face feature value sent by a server, wherein the server processes the face image according to a preset image algorithm to acquire the first face feature value;

Step S103: Sending the first face feature value to the turnstile device.

Specifically, in this application, the user can control the opening of the turnstile device terminal of the turnstile device via the terminal, for example a smart wrist watch, a mobile phone, etc., upload the user's face image to server through

the local database or retrieve the user's face image stored in the server, so that server can acquire the first face feature value by processing face image based on the preset image algorithm, such as Baidu image algorithm, 360 image algorithm, Google image algorithm, etc., and then send it to the terminal.

5 When users need to pass turnstile device, they can send the first face feature value to turnstile device via the terminal to open the turnstile device channel of the turnstile device.

 The control method of this application enables users to use a terminal that can receive the first face feature value to send the first face feature value to the
10 turnstile device, which can easily and quickly open the turnstile device channel. In this way, the issue of turnstile device breakdown or delayed opening due to network delays in the face image checking process for turnstile devices in the state of the art is solved. The turnstile device need not prestore the user's image during use, which reduces the work load of turnstile device, enables adaption to
15 working environments with high passenger throughput, simplifies the operation, shortens the image authentication time of turnstile device, and improves the efficiency of turnstile device, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after
20 the loss of the cards.

 Further, as a preferred option, as shown in Figure 8, the present embodiment includes the following before step S102:

 Step S100: Acquiring a face image of the user;

 Step S101: Transmitting the face image to the server.

25 As can be seen from above, in this application, the user's face image can also be acquired through terminal, such as through the second camera module, or from terminal's local database, and transmitted to server, so as to facilitate the user's operation of the terminal and simplify the process.

 Specifically, the user can register a user's account on terminal's APP, and

then upload the user's face image to server through the APP, or acquire the user's face image via terminal's second camera module and upload it to the server, and the user can check the uploaded face image or the captured face image through the second display module, so that the uploaded image meets the specification of feature extraction and is close to the standard face image. Here, it is important to note that the terminal APP in this embodiment can register multiple user accounts and upload face images of corresponding users to achieve face-swiping through the same terminal after switching of user account to pass the turnstile.

Specifically, as shown in Figure 9, the step S103 includes:

Step S1031: Establishing a Bluetooth wireless communication connection with the turnstile device;

Step S1032: Sending the first face feature value to the turnstile device via a Bluetooth wireless communication channel.

In this way, the terminal in the present application is connected to the turnstile device via Bluetooth wireless communication connection and sends the first face feature value, which takes advantage of the Bluetooth transmission speed and large transmission volume, ensures fast transmission of face feature value with a large data volume to the turnstile device, avoids delays, guarantees the smooth execution of subsequent steps and shortens the time needed to pass the turnstile device.

Further, as shown in Figure 10, the control method in the present embodiment further includes:

Step 104: Sending entries and exits data to the turnstile device;

Step 105: Receiving the entries information sent by the turnstile device and updating the entries and exits data with the entries information;

Step 106: Receiving the exits information sent by the turnstile device and updating the entries and exits data with the exits information;

As can be seen from the description above, when sending entries and exits data to turnstile device through terminal and receiving entries and exits infor-

mation to update entries and exits data, that is, through data transmission between terminal and turnstile device and through data update, the turnstile device can judge whether the user has entered the station based on the entries and exits data acquired from the terminal and decide whether to open the turnstile device channel to avoid undesirable opening of the turnstile device channel.

It is worth noting that the updating of entries and exits data with entries information or exits information can take place by incorporating the same into the entries and exits data based on time sequence or by replacement and by incorporating the replaced data into a historical data records, which is neither limited nor further specified in this embodiment.

It is notable that the above steps S104 to S106 may be carried out either before or after the steps S101 or after the steps S103 or simultaneously, and this embodiment does not limit or specify the sequence between the steps S104 to S106 and the steps S101 to S103.

15

Embodiment 5

As shown in Figure 11, the present embodiment provides a turnstile device comprising:

A wireless transmission device 61 for acquiring a first face feature value of a user sent by a terminal 9;

A face recognition device 62 used for acquiring and processing a face image of the user collected by a first camera module 621 to acquire a second face feature value and for matching the first face feature value and the second face feature value according to a preset matching rule;

A control device 63 for opening the turnstile device channel of the turnstile device 6 in response to an instruction after a successful matching by the face recognition device 62.

As can be seen from the above, the turnstile device 6 of the present application doesn't need to transmit the collected image to the Internet via a network,

that is, a real-time second face feature value is acquired through offline processing, so as to enable convenient and fast opening of the turnstile device channel when the first face feature value sent by the terminal 9 is acquired by the turnstile device 6, and the second face feature value and the first face feature value are matched. In this way, the issue of turnstile device 6 breakdown or delayed opening due to network delays in the face image checking process for turnstile devices 6 in the state of the art is solved. The turnstile device 6 need not prestore the user's image during use, which reduces the work load of turnstile device 6, simplifies the operation, shortens the image authentication time of turnstile device 6, and improves the efficiency of turnstile device 6, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after the loss of the cards.

15 Embodiment 6

As shown in Figure 12, the present embodiment provides a turnstile device comprising:

A wireless transmission device 61 for acquiring a first face feature value of a user sent by a terminal 9;

20 A face recognition device 62 used for acquiring and processing a face image of the user collected by a first camera module 621 to acquire a second face feature value and for matching the first face feature value and the second face feature value according to a preset matching rule;

A control device 63 for opening the turnstile device channel of the turnstile device 6 in response to an instruction after a successful matching by the face recognition device 62.

As can be seen from the above, the turnstile device 6 of the present application doesn't need to transmit the collected image to the Internet via a network, that is, a real-time second face feature value is acquired through offline pro-

cessing, so as to enable convenient and fast opening of the turnstile device channel when the first face feature value sent by the terminal 9 is acquired by the turnstile device 6, and the second face feature value and the first face feature value are matched. In this way, the issue of turnstile device 6 breakdown or delayed opening due to network delays in the face image checking process for turn-
5 stile devices 6 in the state of the art is solved. The turnstile device 6 need not prestore the user's image during use, which reduces the work load of turnstile device 6, simplifies the operation, shortens the image authentication time of turnstile device 6, and improves the efficiency of turnstile device 6, so that users do
10 not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after the loss of the cards.

Specifically, the wireless transmission device 61 in the present embodiment includes a first Bluetooth module 611 for establishing a Bluetooth wireless communication connection with the terminal 9 and receiving the first face feature
15 value via a Bluetooth wireless communication channel.

As can be seen from above, the turnstile device 6 is connected to the terminal 9 via Bluetooth wireless communication connection and receives the first face feature value, which takes advantage of the Bluetooth transmission speed and
20 large transmission volume, ensures fast transmission of face feature value with a large data volume to the turnstile device 6, avoids delays, guarantees the smooth execution of subsequent steps and shortens the time needed to pass the turnstile device 6.

Obviously, the wireless transmission device 61 in this embodiment can also
25 be other wireless communication devices, such as Infrared wireless communication module, WIFI module and other wireless communication modules, in order to realize the wireless communication between turnstile device 6 and the terminal 9.

Further, as a preferred option, the face recognition device 62 in the present

embodiment includes: A first camera module 621 for collecting a face image of the user in real time; A first display module 622 for displaying the face image in real time; and a matching module 623 for processing the face image according to a preset image algorithm to acquire a second face feature value and for matching
5 the first face feature value and the second face feature value according to a preset matching rule.

Displaying the user's face image collected by the first camera module 621 in real time through the first display module 622 can enable the user to observe the displayed image, and quickly move into the collection area of the first camera
10 module 621, which makes it more convenient for the first camera module 621 to collect the user's face image, shortens the collection time of turnstile device 6, and improves the traffic efficiency.

Further, as a preferred option, the face recognition device 62 in the present embodiment further includes a data storage module 624 for storing the face im-
15 age and clearing the previously cached data via the processor when the face image data collected in real time is larger than a preset value, so as to reduce the storage space occupied by the real-time collected face image, reduce the manufacturing cost of turnstile device 6 and its workload, which can help better deal with the situation with large passenger flow.

20 It is notable that data storage module 624 in this embodiment is also used to store the first face feature value and the second face feature value, and when matching module 623 works, the first face feature value and the second face feature value data stored by the data storage module 624 is retrieved and matched. If the matching is successful, an instruction signal is sent to the control device 63.

25 Further, as a preferred option, when the turnstile device 6 is an entry turnstile device 6, the control device 63 includes:

A data analysis module 631 for determining based on the entries and exits data acquired from the terminal 9 whether the current entries and exits data contains entries information after responding to an instruction after a successful

matching by the face recognition device 62;

An turnstile device channel opening module 632 for opening the turnstile device channel and sending entries information to the terminal 9 to update the entries and exits data with the entries information if the data analysis module 631
5 determines that the entries and exits data does not include the entries information and the current turnstile device channel is an entry channel.

Further, as a preferred option, when the turnstile device 6 is an exit turnstile device 6, the control device 63 includes:

A data analysis module 631 for determining based on the entries and exits
10 data acquired from the terminal 9 whether the current entries and exits data contains entries information after responding to an instruction after a successful matching by the face recognition device 62;

A turnstile device channel opening module 632 for opening the turnstile device channel and sending exits information to the terminal 9 to update the entries
15 and exits data with the exits information if the data analysis module 631 determines that the entries and exits data includes the entries information and the current turnstile device channel is an exit channel.

For example, the control device 63 in this embodiment is an industrial control computer which, after receiving the instruction signal sent by the face recognition device 62, acquires the user's entries and exits data via the wireless transmission device 61, and analyzes the entries and exits data through the data analysis module 631.
20

As can be seen from the description above, when the turnstile device 6 matches first face feature value and second face feature value successfully, it can
25 be determined based on the acquired entries and exits data whether the user has entered the station or not, so that the corresponding turnstile device 6 can judge whether the user has entered the station based on the entries and exits data and decide whether to open the turnstile device channel to avoid undesirable opening of the turnstile device channel.

It is worth noting that the updating of entries and exits data with entries information or exits information can take place by incorporating the same into the entries and exits data based on time sequence or by replacement and by incorporating the replaced data into a historical data records, which is neither limited nor
5 further specified in this embodiment.

It is worth noting that the data analysis module 631 is also used for determining the amount to be deducted based on the entries and exits data.

It can be seen that the turnstile device 6 can determine the amount to be deducted based on the entries and exits information recorded in the entries and exits
10 data and the deduction rules. Here, it is necessary to explain that the entries and exits data in this embodiment cannot only include entries and exits information, but also include business data such as deduction rules, which is not further specified here.

Further, as a preferred option, the face recognition device 62 in the present
15 embodiment further includes a data clearing module 625 for deleting automatically the first face feature value and the second face feature value previously stored according to the recording time when the data storage capacity of the cumulatively acquired first face feature value and second face feature value exceeds a preset data volume.

It can be seen that the data clearing module 625 can enable effective use of
20 the storage space of the turnstile device, eliminating the concerns that the turnstile device 6 cannot operate normally due to excessive storage capacity of the data of the first face feature value and the second face feature value generated when users pass the turnstile device, which helps meet the demand of large passenger traffic.
25

The preset data volume in this embodiment, such as the number of data entries stored, can be determined by the storage space of the current turnstile device 6, the working environment, daily passenger traffic and other factors.

In addition, the data clearing module 625 can also transmit the storage ca-

capacity of the first face feature value and second face feature value data cumulatively acquired to the server 10 via the back-end transmission or transmission of the terminal 9 connected with the turnstile device 6, so as to achieve back-up of turnstile access data.

5

Embodiment 7

As shown in Figure 13, the present embodiment provides a terminal comprising:

10 A wireless communication device 91 for receiving a first face feature value sent by a server 10 and sending the first face feature value to the turnstile device 6, wherein the server 10 processes the face image according to a preset image algorithm to acquire the first face feature value.

As can be seen from the above description, the terminal 9 of this application can receive the first face feature value, so that users can use the terminal 9 to send
15 the first face feature value to the turnstile device 6, which can easily and quickly open the turnstile device channel. In this way, the issue of turnstile device 6 breakdown or delayed opening due to network delays in the face image checking process for turnstile devices 6 in the state of the art is solved. The turnstile device 6 need not prestore the user's image during use, which reduces the work load of
20 turnstile device 6, enables adaption to working environments with high passenger throughput, simplifies the operation, shortens the image authentication time of turnstile device 6, and improves the efficiency of turnstile device 6, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized
25 usage of bus cards and other cards after the loss of the cards.

It should be noted that in this embodiment, the user can be registered through an APP in the terminal 9, and then the first face feature value corresponding to the registered user's face image can be acquired from server 10, wherein the first face feature value can be the user's face image collected by the

user through other terminal 9, such as a mobile phone, a computer, etc., and the user's face image can be uploaded to server 10 through the local database, or the user's face image stored in the server 10 can be retrieved, then the first face feature value is acquired after image processing by the server 10. Here, it is important to note that the terminal APP in this embodiment can register multiple user accounts and upload face images of corresponding users to achieve face-swiping through the same terminal after switching of user account to pass the turnstile.

10 Embodiment 8

As shown in Figure 14, the present embodiment provides a terminal comprising:

A wireless communication device 91 for receiving a first face feature value sent by a server 10, wherein the server 10 processes the face image according to a preset image algorithm to acquire the first face feature value, so as to send the first face feature value to the turnstile device 6.

As can be seen from the above description, the terminal 9 of this application can receive the first face feature value, so that users can use the terminal 9 to send the first face feature value to the turnstile device 6, which can easily and quickly open the turnstile device channel. In this way, the issue of turnstile device 6 breakdown or delayed opening due to network delays in the face image checking process for turnstile devices 6 in the state of the art is solved. The turnstile device 6 need not prestore the user's image during use, which reduces the work load of turnstile device 6, enables adaption to working environments with high passenger throughput, simplifies the operation, shortens the image authentication time of turnstile device 6, and improves the efficiency of turnstile device 6, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after the loss of the cards.

Further, as a preferred option, the wireless communication device 61 includes: A network transmission module 911 for receiving the first face feature value sent by the server 10; and a second Bluetooth module 912 for establishing a Bluetooth wireless communication connection with the turnstile device 6 and sending the first face feature value to the turnstile device 6 via a Bluetooth wireless communication channel. With the Bluetooth wireless connection to the turnstile device 6, the first face feature value acquired from server 10 is sent to the turnstile device 6 by the network transmission module 911, which takes advantage of the Bluetooth transmission speed and large transmission volume, ensures fast transmission of face feature value with a large data volume to the turnstile device 6, avoids delays, guarantees the smooth execution of subsequent steps and shortens the time needed to pass the turnstile device 6.

Further, as a preferred option, the terminal 9 in the present embodiment further includes an image collection device 92 for acquiring the face image of the user; wherein the network transmission module 911 is also used for transmitting the face image to the server 10. In this way, the user can also acquire the user's face image through the terminal 9, such as through the second camera module 921, or from the local database of the terminal 9, and transmit the face image to the server 10, so as to facilitate the user's operation of the terminal 9 and simplify the process.

Specifically, the user can register a user's account on an APP at the terminal 9, and then upload the user's face image to server 10 through the APP, or acquire the user's face image via terminal 9's second camera module and upload it to the server 10, and the user can check the uploaded face image or the captured face image through the second display module, so that the uploaded image meets the specification of feature extraction and is close to the standard face image. The network transmission module 911 can be a 4G module, a WiFi module, etc. Here, it is important to note that the terminal APP in this embodiment can register multiple user accounts and upload face images of corresponding users to achieve

face-swiping through the same terminal after switching of user account to pass the turnstile.

Further, as a preferred option, the second camera module 921 is further used for:

5 Sending entries and exits data to the turnstile device 6;

Receiving the entries information sent by the turnstile device 6 and updating the entries and exits data with the entries information;

Receiving the exits information sent by the turnstile device 6 and updating the entries and exits data with the exits information.

10 As can be seen from the description above, the terminal 9 in the present application can also be used for sending entries and exits data to the turnstile device 6 and receiving entries and exits information to update entries and exits data, that is, through data transmission between the terminal 9 and the turnstile device 6 and through data update, the so that the turnstile device 6 can judge whether the
15 user has entered the station based on the entries and exits data acquired from the terminal 9 and decide whether to open the turnstile device channel to avoid undesirable opening of the turnstile device channel.

It is worth noting that the updating of entries and exits data with entries information or exits information can take place by incorporating the same into the
20 entries and exits data based on time sequence or by replacement and by incorporating the replaced data into a historical data records, which is neither limited nor further specified in this embodiment.

Embodiment 9

25 The present application further provides a turnstile device access control system which, as shown in Figures 15 and 16, includes a turnstile device in any of the above embodiments and a terminal in any of the above embodiments, the terminal being used for opening the turnstile device channel of the turnstile device.

As can be seen from the above embodiments, the system of the present application makes it unnecessary for the turnstile device 6 to transmit the collected image to the Internet via a network, that is, a real-time second face feature value is acquired through offline processing, so as to enable convenient and fast opening of the turnstile device channel when the first face feature value sent by the terminal 9 is acquired by the turnstile device 6, and the second face feature value and the first face feature value are matched. In this way, the issue of turnstile device 6 breakdown or delayed opening due to network delays in the face image checking process for turnstile devices 6 in the state of the art is solved. The turnstile device 6 need not prestore the user's image during use, which reduces the work load of turnstile device 6, enables adaption to working environments with high passenger throughput, simplifies the operation, shortens the image authentication time of turnstile device 6, and improves the efficiency of turnstile device 6, so that users do not need to carry electronic cards, making it easier for users to travel around. In addition, it can also prevent the loss suffered by users due to the unauthorized usage of bus cards and other cards after the loss of the cards.

Specifically, as shown in Figure 15, the turnstile device 6 in the system of the present embodiment includes:

A wireless transmission device 61 for acquiring a first face feature value of a user sent by a terminal 9;

A face recognition device 62 used for acquiring and processing a face image of the user collected by a first camera module 621 to acquire a second face feature value and for matching the first face feature value and the second face feature value according to a preset matching rule;

A control device 63 for opening the turnstile device channel of the turnstile device 6 in response to an instruction after a successful matching by the face recognition device 62.

The terminal 9 in the system of the present embodiment includes:

A wireless communication device 91 for receiving a first face feature value

sent by a server 10, wherein the server 10 processes the user's face image according to a preset image algorithm to acquire the first face feature value, so as to send the first face feature value to the turnstile device 6.

The terminal 9 of this application can receive the first face feature value sent
5 by the server 10 via the wireless communication device 91 and turnstile device 6
can receive the first face feature value sent by the terminal via data transmission
between the wireless transmission device 61 and wireless communication device
91, and process the user's face image collected by the first camera module
through the face recognition device 62 to acquire a second face feature value and
10 after matching the first face feature value with the second face feature value, it
can send an instruction to the control device (63) to easily and quickly open the
turnstile device channel.

Further, as a preferred option, the wireless transmission device 61 of the
turnstile device 6 includes a first Bluetooth module 611 for establishing a Blue-
15 tooth wireless communication connection with the terminal 9 and receiving the
first face feature value via a Bluetooth wireless communication channel.

As shown in Figure 15, the wireless communication device of the terminal
includes: A network transmission module 911 for receiving the first face feature
value sent by the server 10; and a second Bluetooth module 912 for establishing a
20 Bluetooth wireless communication connection with the first Bluetooth module
611 of the turnstile device 6 and sending the first face feature value, the entries
and exits data and other information to the turnstile device 6 via a Bluetooth
wireless communication channel.

As can be seen from the above, the turnstile device 6 and the terminal 9 of
25 the system can be connected via Bluetooth wireless communication connection to
transmit the first face feature value, which ensures fast transmission of face fea-
ture value with a large data volume to the turnstile device 6, avoids delays, guar-
antees the smooth execution of subsequent steps and shortens the time needed to
pass the turnstile device 6. Obviously, the wireless transmission device 61 in this

embodiment can also be other wireless communication devices, such as Infrared wireless communication module, WIFI module and other wireless communication modules, in order to realize the wireless communication between turnstile device 6 and the terminal 9, without being limited to Bluetooth module.

5 Further, as a preferred option, the face recognition device 62 of the turnstile device 6 includes: A first camera module 621 for collecting a face image of the user in real time; A first display module 622 for displaying the face image in real time; and a matching module 623 for processing the face image according to a preset image algorithm to acquire a second face feature value and for matching
10 the first face feature value and the second face feature value according to a preset matching rule.

Displaying the user's face image collected by the first camera module 621 in real time through the first display module 622 can enable the user to observe the displayed image, and thus quickly move into the collection area of the first camera module 621, which makes it more convenient for the first camera module 621
15 to collect the user's face image, shortens the collection time of turnstile device 6, and improves the traffic efficiency.

Further, as a preferred option, the face recognition device 62 in the present embodiment further includes a data storage module 624 for storing the face image and clearing the previously cached data via the processor when the face image data collected in real time is larger than a preset value, so as to reduce the storage space occupied by the real-time collected face image, reduce the manufacturing cost of turnstile device 6 and its workload, which can help better deal with the situation with large passenger flow.

25 It is notable that data storage module 624 in this embodiment is also used to store the first face feature value and the second face feature value, and when matching module 623 works, the first face feature value and the second face feature value data stored by the data storage module 624 is retrieved and matched. If the matching is successful, an instruction signal is sent to the control device 63.

Further, as a preferred option, when the turnstile device 6 is an entry turnstile device 6, the control device 63 includes:

A data analysis module 631 for determining based on the entries and exits data acquired from the terminal 9 whether the current entries and exits data contains entries information after responding to an instruction after a successful matching by the face recognition device 62;

An turnstile device channel opening module 632 for opening the turnstile device channel and sending entries information to the terminal 9 to update the entries and exits data with the entries information if the data analysis module 631 determines that the entries and exits data does not include the entries information and the current turnstile device channel is an entry channel.

Further, as a preferred option, when the turnstile device 6 is an exit turnstile device 6, the control device 63 includes:

A data analysis module 631 for determining based on the entries and exits data acquired from the terminal 9 whether the current entries and exits data, for example the entries and exits data acquired via the first Bluetooth module 611 as shown in Figure 14 and sent by the terminal 9, contains entries information after responding to an instruction after a successful matching by the face recognition device 62, and for analyzing the entries and exits data to determine whether the current entries and exits data contains entries information.

A turnstile device channel opening module 632 for opening the turnstile device channel and sending exits information to the terminal 9 to update the entries and exits data with the exits information if the data analysis module 631 determines that the entries and exits data includes the entries information and the current turnstile device channel is an exit channel.

For example, the control device 63 in this embodiment can be an industrial control computer which, after receiving the instruction signal sent by the face recognition device 62, acquires the user's entries and exits data via the first Bluetooth module 611 in the wireless transmission device 61, and analyzes the entries

and exits data through the data analysis module 631.

As can be seen from the description above, when the turnstile device 6 matches first face feature value and second face feature value successfully, it can be determined based on the acquired entries and exits data whether the user has entered the station or not, so that the corresponding turnstile device 6 can judge whether the user has entered the station based on the entries and exits data and decide whether to open the turnstile device channel to avoid undesirable opening of the turnstile device channel.

It is worth noting that the updating of entries and exits data with entries information or exits information can take place by incorporating the same into the entries and exits data based on time sequence or by replacement and by incorporating the replaced data into a historical data records, which is neither limited nor further specified in this embodiment.

It is worth noting that the data analysis module 631 is also used for determining the amount to be deducted based on the entries and exits data.

It can be seen that the turnstile device 6 can determine the amount to be deducted based on the entries and exits information recorded in the entries and exits data and the deduction rules. Here, it is necessary to explain that the entries and exits data in this embodiment cannot only include entries and exits information, but also include business data such as deduction rules, which is not further specified here.

Further, as a preferred option, the face recognition device 62 in the present embodiment further includes a data clearing module 625 for deleting automatically the first face feature value and the second face feature value previously stored according to the recording time when the data storage capacity of the cumulatively acquired first face feature value and second face feature value exceeds a preset data volume, for example, when the data clearing module 625 detects that the first face feature value and the second face feature value cumulatively stored in the data storage module 624 exceeds the preset data volume, the first

face feature value and the second face feature value previously stored will be automatically deleted according to the recording time.

It can be seen that the data clearing module 625 can enable effective use of the storage space of the turnstile device, eliminating the concerns that the turn-
5 stile device 6 cannot operate normally due to excessive storage capacity of the data of the first face feature value and the second face feature value generated when users pass the turnstile device, which helps meet the demand of large passenger traffic.

The preset data volume in this embodiment, such as the number of data en-
10 tries stored, can be determined by the storage space of the current turnstile device 6, the working environment, daily passenger traffic and other factors.

In addition, the data clearing module 625 can also transmit the storage capacity of the first face feature value and second face feature value data cumulatively acquired to the server 10 via the back-end transmission or transmission of
15 the terminal 9 connected with the turnstile device 6, so as to achieve back-up of turnstile access data.

Further, as a preferred option, the terminal 9 in the present embodiment further includes an image collection device 92 for acquiring the face image of the user; wherein the network transmission module 911 is also used for transmitting
20 the face image to the server 10. In this way, the user can also acquire the user's face image through the terminal 9, such as through the second camera module 921, or from the local database of the terminal 9, and transmit the face image to the server 10, so as to facilitate the user's operation of the terminal 9 and simplify the process.

25 Specifically, the user can register a user's account on an APP at the terminal 9, and then acquire the user's face image via terminal 9's second camera module and upload it to the server 10, and the user can check the uploaded face image or the captured face image through the second display module, so that the uploaded image meets the specification of feature extraction and is close to the standard

face image. The network transmission module 911 can be a 4G module, a WiFi module, etc.

As shown in Figure 16, the interaction between the terminal 9 and the turnstile device 6 is described below to briefly explain the working principle of the system:

On the terminal side, the user first uses the terminal 9 to execute the actions in the following steps S100 to S102:

Step S100: Acquiring a face image of the user;

Step S101: Transmitting the face image to the server 10;

Step S102: Receiving a first face feature value sent by the server 10, wherein the server 10 processes the face image according to a preset image algorithm to acquire the first face feature value;

After the user approaches the turnstile device 6 with the terminal 9, the action of the following steps S103 is initiated:

Step S103: Sending the first face feature value to the turnstile device 6.

On the turnstile device side, actions of the following steps S1 to S5 are performed during the data interaction between the turnstile device 6 and the terminal 9:

Step S1: Acquiring a first face feature value of a user sent by the terminal 9;

Step S2: Acquiring and processing a face image of the user collected by the first camera module 621 to acquire a second face feature value;

Step S3: Matching the first face feature value and the second face feature value according to a preset matching rule;

Step S4: Opening the turnstile device channel of the turnstile device 6 in case of a successful matching.

If the matching by the matching module 623 of the turnstile device 6 is unsuccessful, the turnstile device channel remains closed.

Before the turnstile device 6 performs the above step S4, the terminal 9 performs the action of the step 104 below:

Step 104: Sending entries and exits data to the turnstile device 6;

After the terminal 9 performs the step 104 below, the turnstile device 6 performs the action of the step S4:

When the current turnstile device 6 is an entry turnstile and thus the turnstile
5 device channel is an entry channel, the specific process of step S4 performed by the turnstile device 6 is described below:

Step S41: Determining based on the entries and exits data acquired from the terminal 9 whether the current entries and exits data contains entries information in case of a successful matching;

10 Step S42: Opening the turnstile device channel and sending the entries information to the terminal 9 to update the entries and exits data with the entries information if it is determined that the entries and exits data does not include the entries information.

When the current turnstile device 6 is an exit turnstile and thus the turnstile
15 device channel is an exit channel, the step S4 performed by the turnstile device 6 is described below:

Step S41': Determining based on the entries and exits data acquired from the terminal 9 whether the current entries and exits data contains entries information in case of a successful matching;

20 Step S42': Opening the turnstile device channel and sending exits information to the terminal 9 to update the entries and exits data with the exits information if it is determined that the entries and exits data includes the entries information.

When the terminal 9 is carried by the user and passes the turnstile device
25 channel of the entry turnstile, the action after the step 105 below is performed:

Step 105: Receiving the entries information sent by the turnstile device 6 and updating the entries and exits data with the entries information;

When the terminal 9 is carried by the user and passes the turnstile device channel of the exit turnstile, the action after the step 106 below is performed:

Step 106: Receiving the exits information sent by the turnstile device 6 and updating the entries and exits data with the exits information.

In addition, the turnstile device 6 of the system of this embodiment may refer to the aforementioned embodiments 1 to 2 and 5 to 6, and the terminal 9 of the system of this embodiment may also refer to the aforementioned embodiments 3 to 4 and 7 to 8, and the specific structure and working principle thereof are not further described here.

The description above only covers preferred embodiments of the present invention, and does not restrict the present invention in any way. Any changes such as equivalent substitution or modification of the disclosed technical scheme and the technical content of the present invention made by any technical personnel skilled in this technical field without deviating from the contents of the technical scheme of the present invention shall be within the scope of the technical scheme of the present invention.

CLAIMS

1. A control method for a turnstile device, characterized in that it includes following steps:
Acquiring a first face feature value of a user sent by a terminal;
Acquiring and processing a face image of the user collected by a first camera
5 module to acquire a second face feature value;
Matching the first face feature value and the second face feature value according to a preset matching rule;
Opening the turnstile device channel of the turnstile device in case of a successful matching.
- 10 2. The control method of a turnstile device according to claim 1, characterized in that the step of acquiring a first face feature value of a user sent by a terminal includes:
Establishing a Bluetooth wireless communication connection with the terminal;
Receiving the first face feature value via a Bluetooth wireless communication
15 channel.
3. The control method of a turnstile device according to claim 1, characterized in that the step of acquiring and processing a face image of the user collected by a first camera module to acquire a second face feature value includes:
Acquiring a face image of the user collected by the first camera module in real
20 time;
Displaying the face image by a first display module in real time;
Processing the face image according to a preset image algorithm to acquire a second face feature value;
Clearing the previously cached data when the storage capacity of the face image
25 collected in real time is greater than a preset value.
4. The control method of a turnstile device according to claim 1, characterized in that the step of opening the turnstile device channel of the turnstile device in case of a successful matching includes:

Determining based on the entries and exits data acquired from the terminal whether the current entries and exits data contains entries information in case of a successful matching;

Opening the turnstile device channel and sending the entries information to the terminal to update the entries and exits data with the entries information if it is
5 determined that the entries and exits data does not include the entries information and the current turnstile device channel is an entry channel;

Opening the turnstile device channel and sending exits information to the terminal to update the entries and exits data with the exits information if it is deter-
10 mined that the entries and exits data includes the entries information and the current turnstile device channel is an exit channel.

5. The control method of a turnstile device according to claim 1, characterized in that after the step of opening the turnstile device channel of the turnstile device in case of a successful matching, it includes further:

15 Deleting automatically the first face feature value and the second face feature value previously stored according to the recording time when the data storage capacity of the cumulatively acquired first face feature value and second face feature value exceeds a preset data volume.

6. A control method for a turnstile device, characterized in that it includes fol-
20 lowing steps:

Receiving a first face feature value sent by a server, wherein the server processes the user's face image according to a preset image algorithm to acquire the first face feature value;

Sending the first face feature value to the turnstile device.

25 7. The control method of a turnstile device according to claim 6, characterized in that before the step of receiving a first face feature value sent by a server, it includes further:

Acquiring a face image of the user;

Transmitting the face image to the server.

8. The control method of a turnstile device according to claim 6, characterized in that the step of sending the first face feature value to the turnstile device includes: Establishing a Bluetooth wireless communication connection with the turnstile device;

Sending the first face feature value to the turnstile device via a Bluetooth wireless communication channel.

9. The control method of a terminal according to claim 6, characterized in that it includes further:

10 Sending entries and exits data to the turnstile device;

Receiving the entries information sent by the turnstile device and updating the entries and exits data with the entries information;

Receiving the exits information sent by the turnstile device and updating the entries and exits data with the exits information.

10. A turnstile device, characterized in that it includes:

A wireless transmission device for acquiring a first face feature value of a user sent by a terminal;

A face recognition device used for acquiring and processing a face image of the user collected by a first camera module to acquire a second face feature value and for matching the first face feature value and the second face feature value according to a preset matching rule;

A control device for opening the turnstile device channel of the turnstile device in response to an instruction after a successful matching by the face recognition device.

11. The turnstile device according to claim 10, characterized in that the wireless transmission device includes:

A first Bluetooth module for establishing a Bluetooth wireless communication connection with the terminal and receiving the first face feature value via a Blue-

tooth wireless communication channel.

12. The turnstile device according to claim 10, characterized in that the face recognition device includes:

A first camera module for collecting a face image of the user in real time;

5 A first display module for displaying the face image in real time;

A matching module for processing the face image according to a preset image algorithm to acquire a second face feature value and for matching the first face feature value and the second face feature value according to a preset matching rule;

10 A data storage module for storing the face image and clearing the previously cached data via the processor when the face image data collected in real time is larger than a preset value.

13. The turnstile device according to claim 10, characterized in that control device includes:

15 A data analysis module for determining based on the entries and exits data acquired from the terminal whether the current entries and exits data contains entries information after responding to an instruction after a successful matching by the face recognition device;

A turnstile device channel opening module for:

20 Opening the turnstile device channel and sending entries information to the terminal to update the entries and exits data with the entries information if the data analysis module determines that the entries and exits data does not include the entries information and the current turnstile device channel is an entry channel;

Opening the turnstile device channel and sending exits information to the terminal to update the entries and exits data with the exits information if the data analysis module determines that the entries and exits data includes the entries information and the current turnstile device channel is an exit channel.

14. The turnstile device according to claim 10, characterized in that face recogni-

tion device includes further:

A data clearing module for deleting automatically the first face feature value and the second face feature value previously stored according to the recording time when the data storage capacity of the cumulatively acquired first face feature value and second face feature value exceeds a preset data volume.

15. A terminal, characterized in that it includes:

A wireless communication device for receiving a first face feature value sent by a server and sending the first face feature value to the turnstile device, wherein the server processes the user's face image acquired according to a preset image algorithm to acquire the first face feature value.

16. The terminal according to claim 15, characterized in that the wireless communication device includes:

A network transmission module for receiving the first face feature value sent by the server;

15 A second Bluetooth module for establishing a Bluetooth wireless communication connection with the turnstile device and sending the first face feature value to the turnstile device via a Bluetooth wireless communication channel.

17. The terminal according to claim 16, characterized in that it includes further:

An image collection device for acquiring the face image of the user;

20 wherein the network transmission module is also used for transmitting the face image to the server.

18. The terminal according to claim 16, characterized in that second Bluetooth module is further used for:

Sending entries and exits data to the turnstile device;

25 Receiving the entries information sent by the turnstile device and updating the entries and exits data with the entries information;

Receiving the exits information sent by the turnstile device and updating the entries and exits data with the exits information.

19. A turnstile device access control system, characterized in that it includes a turnstile device according to any one of the claims 10 to 14 and a terminal according to any one of the claims 15 to 18, the terminal being used for opening the turnstile device channel of the turnstile device.