

Description

Field of the invention

This invention relates to a heater for heating a heat shrinkable tube fitted over a junction between optical fiber cables or electric cables.

Prior art

Fig. 1 shows one conventional heater 100 of the type described which comprises a rectangular base 102, a pair of support members 104 and 104 fixedly mounted on a top surface of the base 102 at opposite ends thereof, a pair of parallel spaced shield plates 106 and 106 fixedly mounted on the top surface of the base 102 and disposed between the pair of support members 104 and 104, and three electric heating elements 108a, 108b and 108a disposed between the pair of shield plates 106 and 106 and spaced therealong. In operation, a heat shrinkable tube 110 is fitted over two optical fiber cables 112 and 112 to cover a junction 114 between their conductors 116 and 116. Then, the two optical fiber cables 112 and 112 are placed on the pair of support members 104 and 104 with the heat shrinkable tube 110 disposed above the three heating elements 108a, 108b and 108a. Then, the heating elements 108a, 108b and 108a are operated to heat the heat shrinkable tube 110 so that the tube 110 is shrunk radially inwardly to seal the joint 114. During this heating operation, if the opposite end portions of the heat shrinkable tube 110 are first shrunk, air is entrapped in the central portion of the tube 110 intermediate the opposite end portions. Such residual or entrapped air affects the reinforcement of the cable joint portion by the tube 110. Therefore, it is necessary to shrink the heat shrinkable tube 110 from the central portion toward the opposite end portions. One method is to heat the central heating element 108a at a temperature slightly higher than the temperature at which the other two heating elements 108a and 108a are heated. Another alternative is to first heat the central heating element 108b for a predetermined period of time to shrink the central portion of the tube 110 and then to start the heating of the other two heating elements 108a and 108a to shrink the opposite end portions of the tube 110. Thus, two kinds of heating elements to be operated at different heating temperatures are required for carrying out the former method. And, the latter method requires the three heating elements and a timer means for sequentially operating them in a manner described above. Therefore, the conventional heater is rather complicated in construction and expensive. Such heaters are described in US-A-4460820.

Summary of the invention

It is therefore an object of this invention to provide a heater for heating a heat shrinkable tube fitted over an elongated member which heater is simple in construction and less expensive to manufacture.

According to the present invention, there is

provided a heater for heating a heat shrinkable tube fitted over an elongated member, which heater comprises:

a base having an elongated support plate, adapted to support said elongated member carrying said heat shrinkable tube; and

a heating element;

wherein said support plate is made of a thermally conductive material and said support plate comprises:

a central portion defined by said heating element attached to the underside of said support plate; and

end portions extending outwardly in opposite directions from said central portion;

further wherein the heater comprises elongated plates of thermally conductive material upstanding from an outer surface of said support plate and extending along said central portion and said end portions of said support plate;

whereby when said heating element is activated, heat is transferred to said central portion of the support plate and thence to the end portions and plates so that the central portion of said heat shrinkable tube above said central portion is heated first, and thus said tube is heat shrunk at its central portion first and then towards its opposite ends.

Brief description of the drawings

Fig. 1 is a perspective view of a heater provided in accordance with the prior art;

Fig. 2 is a perspective view of a heater provided in accordance with the present invention;

Fig. 3 is a top plan view of the heater of Fig. 2;

Fig. 4 is a side elevational view of the heater of Fig. 2;

Fig. 5 is an end view of the heater of Fig. 2;

Fig. 6 is a diagrammatical illustration showing temperature profiles of a top wall of a base of the heater of Fig. 2 in accordance with the time of heating;

Figs. 7(a) to 7(d) are schematic views showing a sequential shrinkage of a heat shrinkable tube heated by the heater of Fig. 2;

Fig. 8 is a diagrammatical illustration showing a temperature increase at the central portion of the top wall of the base and the temperature increase at points of the top wall spaced 5 mm outwardly respectively from the opposite ends of a heating element of the heater of Fig. 2;

Fig. 9 is a diagrammatical illustration showing temperature profiles of the lower ends of elongated plates of the base in the direction of a length thereof as well as a temperature profile of the upper end of each elongated plate five minutes after the heating element is heated;

Fig. 10 is a side elevational view of a modified heater; and

Figs. 11 and 12 are views similar to Fig. 2 but showing further modified heaters, respectively.

Description of the preferred embodiments of the invention

A heater 10 shown in Figs. 2 to 5 comprises an

elongated box-shaped base 12 made of a thermally-conductive sheet such as a stainless steel sheet, a pair of opposed elongated plates 14 and 14 fixedly mounted on an outer surface of a top wall or support plate 12a of the base 12 in parallel spaced relation to each other and extending along an entire length thereof, and an elongated heating element 16 of a rectangular shape fixedly mounted on an inner surface of the top wall 12a and held in contact therewith, the heating element 16 being disposed intermediate opposite ends of the base 12. Therefore, that portion of the top wall 12a with which the heating element 16 held in contact serves as a heating portion 12b. A pair of integral mounting lugs 18 and 18 of stainless steel are extend perpendicularly from the opposite end walls 12d and 12d, respectively. The heater 10 is adapted to be mounted on a suitable support through the mounting lugs 18 and 18.

The heating element 16 comprises a positive temperature coefficient thermistor (PTC thermistor) of which resistance increases with an increase of its temperature and increases abruptly when the temperature reaches a predetermined level so that the temperature increase is substantially stopped. Such a PTC thermistor is also known as "posistor" in the trade. One example of such a PTC thermistor is a barium titanate-based semi-conductor. The heating element 16 may be of any other suitable type such as a heating resistor composed of a nichrome wire.

In operation, a heat shrinkable tube 110 is fitted loosely over two optical fiber cables 112 and 112 to cover a junction between their fibers 116 and 116. Then, the two connected optical fiber cables 112 and 112 are placed on the base top wall 12a and fitted inbetween the pair of elongated plates 14 and 14 with the opposite end portions of the heat shrinkable tube 110 disposed outwardly of the heating portion 12b of the top wall 12a. In this condition, the heat shrinkable tube 110 is held in contact with the opposed plates 14 and 14. Then, the heating element 16 is energized so that it is heated to heat the heating portion 12b of the top wall 12a for shrinking the heat shrinkable tube 110 radially inwardly. At this time, the opposite end portions 12d and 12d of the top wall 12a disposed outwardly of the heating portion 12b of the top wall 12a are not yet heated as indicated by a curve A in Fig. 6. Subsequently, the heat generated by the heating element 16 begins to be transferred toward the opposite ends of the top wall 12a and the temperature of the heating element 16 reaches the predetermined level, so that the temperature of the heating portion 12b also becomes substantially constant as indicated by curve B in Fig. 6. In this condition, the opposite end portions 12d and 12d of the top wall 12a have not yet reached a predetermined level. Subsequently, the opposite end portions of the top wall 12a reach the predetermined level through the heat transfer as indicated a curve C in Fig. 6 and at this time the temperature profile of the top wall 12a becomes substantially constant. In this


case, the temperature of the top wall 12a at any given point along the length of the top wall 12a is substantially uniform in a transverse direction, and therefore this does not need to be considered. The pair of elongated plates 14 and 14 held in contact with the heat shrinkable tube 110 assist in the heat shrinkage of the tube 110. The inner surfaces of the opposed elongated plates 14 and 14 and that portion of the top wall 12a lying between the opposed plates 14 and 14 are coated with polytetrafluoroethylene to prevent the heat shrinkable tube 110 and the optical fiber cables from being fused thereto during the heating operation.

With this method, the heat shrinkable tube 110 is shrunk radially inwardly first at its central portion and then at its opposite end portions as shown in Figs. 7(a) to 7(d), so that the tube 110 is fitted tightly over the joint portion between the two optical fiber cables 112 and 112. Thus, since the heat shrinkable tube 110 is heat shrunk from its central portion toward its opposite ends, no air is entrapped in the shrunk tube 110.

The pair of mounting lugs 18 and 18 can serve as radiator means for radiating the heat for lowering the temperature of the opposite end portions 12d and 12d of the top wall 12a. In this case, the mounting lugs 18 and 18 are mounted directly on the heat conductive support. On the other hand, if it is desired to maintain the opposite end portions of the top wall 12a at higher temperatures, the mounting lugs 18 and 18 are mounted on the support through a thermal insulating material.

Example

The heat shrinkage of the heat shrinkable tube 110 fitted over two optical fiber cables was carried out using the heater 10 of Fig. 2 for experimental purposes. The base 12 had a length of 70 mm, a width of 20 mm, and a height of 9 mm. Each of the elongated plates 14 and 14 had a length of 70 mm and a height of 8 mm. The heating element 16 had a length of 50 mm and a width of 20 mm. Each of the mounting lugs 18 and 18 has a square shape one side of which was 15 mm. The heat shrinkable tube 110 had a length of 60 mm, an inner diameter of 1.5 mm and an outer diameter of 4 mm. The base 12, the pair of elongated plates 14 and 14 and the pair of mounting lugs 18 and 18 were made of a stainless steel sheet having a thickness of 0.5 mm. The results obtained are shown in Figs. 8 and 9. Fig. 8 shows the temperature increase at the central portion of the top wall 12a disposed in registry with the central portion of the heating element 16 and the temperature increase at the opposite end portions of the top wall 12a that is, at points of the top wall 12a spaced 5 mm outwardly from the opposite ends of the heating element 16. Fig. 9 shows temperature profiles of the lower ends of the elongated plates 14 and 14 in the direction of a length thereof as well as a temperature profile of the upper end of each elongated plate 14 five minutes after the heating element 16 is heated. As can be



seen from Fig. 8, the temperature difference between the central portion of the top wall 12a and the opposite end portions of the top wall 12a becomes substantially constant about one minute after the heating element 16 is heated. Also, as can be seen from Fig. 9, the temperature gradient of the top wall 12a from its central portion toward its opposite end portions is substantially constant. Therefore, the heat shrinkable tube 110 was suitably shrunk from its central portion toward its opposite end portions.

Fig. 10 shows a modified heater 10a which differs from the heater 10 of Fig. 2 in that each of opposed elongated plates 14 and 14 has enlarged opposite end portions 14a and 14a which serve as radiator means for radiating the heat.

Fig. 11 shows another modified heater 10b which differs from the heater 10 of Fig. 2 in that a plurality of fins 22 of stainless steel are formed on and extend outwardly from each of opposite end walls 12c and 12c of the base 12 so as to serve as radiator means for radiating the heat.

Fig. 12 shows a modified heater 10c which differs from the heater 10 of Fig. 2 in that a plurality of juxtaposed fins 24 of stainless steel are formed on the top wall 12a on each of four corner portions thereof.

Claims

1. A heater (10) for heating a heat shrinkable tube (110) fitted over an elongated member (112), which heater comprises:

a base (12) having an elongated support plate (12a), adapted to support said elongated member (112) carrying said heat shrinkable tube (110); and a heating element (16);

characterised in that said support plate (12a) is made of a thermally conductive material and said support plate (12a) comprises:

a central portion (12b) defined by said heating element (16) attached to the underside of said support plate (12a); and

end portions (12d) extending outwardly in opposite directions from said central portion (12b);

further characterised in that the heater (10) comprises a pair of parallel spaced elongated plates (14) of thermally conductive material upstanding from an outer surface of said support plate (12a) and extending along said central portion (12b) and said end portions (12d) of said support plate (12a);

whereby when said heating element (16) is activated, heat is transferred to said central portion (12b) of the support plate (12a) and thence to the end portions (12d) and plates (14) so that the central portion of said heat shrinkable tube (110) above said central portion (12b) is heated first, and thus said tube (110) is heat shrunk at its central portion first and then towards its opposite ends.

2. A heater according to claim 1, in which said heating element (16) comprises a positive temperature coefficient thermistor (PCT thermis-

tor) of which resistance increases with an increase of its temperature and increases abruptly when the temperature reaches a predetermined level so that the temperature increase is substantially stopped.

3. A heater according to claim 1, in which said base (12) is of an elongated box-shaped base having a top wall (12a) serving as said support plate (12a), the heat shrinkable tube (110) being adapted to be fitted inbetween said pair of elongated plates (14).

4. A heater according to claim 1, in which said support plate (12a) has a pair of radiator means (24) provided respectively on the opposite end portions (12d) thereof for efficiently radiating the heat transferred from said heating element, said radiator means comprising fins (24).

5. A heater according to claim 3, in which said base has a pair of end walls, said base having a pair of radiator means (22) provided respectively on said end walls (12c) for efficiently radiating the heat transferred from said heating element, each of said radiator means comprising at least one fin (22).

6. A heater according to claim 3, in which each of said elongated opposed plates (14) has enlarged end portions (14a) for enhancing the radiation of the heat transferred from said heating element (16).

Patentansprüche

1. Heizgerät zum Erwärmen eines unter Wärme schrumpfbaren Schlauchabschnitts (110), der ein langgestrecktes Teil (112) umgibt, mit einem Gehäuse (12), welches eine langgestreckte Trägerplatte (12a) zur Aufnahme des langgestreckten Teils (112) mit dem unter Wärme schrumpfbaren Schlauchabschnitt (110) aufweist, und mit einem Heizelement (16), dadurch gekennzeichnet, daß die Trägerplatte (12a) aus wärmeleitfähigem Material besteht und einen Mittelbereich (12b), der durch das Heizelement (16) festgelegt ist, welches an der Unterseite der Trägerplatte (12a) angeordnet, sowie Endbereiche (12d) aufweist, die sich an den Mittelbereich (12b) beidseitig in entgegengesetzten Richtungen anschließen, daß das Heizgerät (10) ein Paar parallel zueinander und abständig angeordneter Platten (14) aus wärmeleitfähigem Material aufweist, die vertikal abgehend von der äußeren Oberfläche der Trägerplatte (12a) und sich über den Mittelbereich (12b) und die Endbereiche (12d) der Trägerplatte (12a) hinwegersteckend vorgesehen sind, und daß bei eingeschaltetem Heizelement (16) Wärme zum Mittelbereich (12b) der Trägerplatte (12a) und von dort zu den Einbereichen (12d) und den Platten (14) übertragen wird, so daß der Mittelteil des unter Wärme schrumpfbaren Schlauchabschnitts (110), der sich über dem Mittelbereich (12b) befindet, zuerst erwärmt und damit zuerst aufgeschrumpft wird, während seine beiden Endteile nachfolgend aufgeschrumpft werden.

2. Heizgerät nach Anspruch 1, dadurch gekennzeichnet, daß das Heizelement (16) einen Thermi-



seen from Fig. 8, the temperature difference between the central portion of the top wall 12a and the opposite end portions of the top wall 12a becomes substantially constant about one minute after the heating element 16 is heated. Also, as can be seen from Fig. 9, the temperature gradient of the top wall 12a from its central portion toward its opposite end portions is substantially constant. Therefore, the heat shrinkable tube 110 was suitably shrunk from its central portion toward its opposite end portions.

Fig. 10 shows a modified heater 10a which differs from the heater 10 of Fig. 2 in that each of opposed elongated plates 14 and 14 has enlarged opposite end portions 14a and 14a which serve as radiator means for radiating the heat.

Fig. 11 shows another modified heater 10b which differs from the heater 10 of Fig. 2 in that a plurality of fins 22 of stainless steel are formed on and extend outwardly from each of opposite end walls 12c and 12c of the base 12 so as to serve as radiator means for radiating the heat.

Fig. 12 shows a modified heater 10c which differs from the heater 10 of Fig. 2 in that a plurality of juxtaposed fins 24 of stainless steel are formed on the top wall 12a on each of four corner portions thereof.

Claims

1. A heater (10) for heating a heat shrinkable tube (110) fitted over an elongated member (112), which heater comprises:

a base (12) having an elongated support plate (12a), adapted to support said elongated member (112) carrying said heat shrinkable tube (110); and a heating element (16);

characterised in that said support plate (12a) is made of a thermally conductive material and said support plate (12a) comprises:

a central portion (12b) defined by said heating element (16) attached to the underside of said support plate (12a); and

end portions (12d) extending outwardly in opposite directions from said central portion (12b);

further characterised in that the heater (10) comprises a pair of parallel spaced elongated plates (14) of thermally conductive material upstanding from an outer surface of said support plate (12a) and extending along said central portion (12b) and said end portions (12d) of said support plate (12a);

whereby when said heating element (16) is activated, heat is transferred to said central portion (12b) of the support plate (12a) and thence to the end portions (12d) and plates (14) so that the central portion of said heat shrinkable tube (110) above said central portion (12b) is heated first and thus said tube (110) is heat shrunk at its central portion first and then towards its opposite ends.

2. A heater according to claim 1, in which said heating element (16) comprises a positive temperature coefficient thermistor (PCT thermis-

tor) of which resistance increases with an increase of its temperature and increases abruptly when the temperature reaches a predetermined level so that the temperature increase is substantially stopped.

3. A heater according to claim 1, in which said base (12) is of an elongated box-shaped base having a top wall (12a) serving as said support plate (12a), the heat shrinkable tube (110) being adapted to be fitted inbetween said pair of elongated plates (14).

4. A heater according to claim 1, in which said support plate (12a) has a pair of radiator means (24) provided respectively on the opposite end portions (12d) thereof for efficiently radiating the heat transferred from said heating element, said radiator means comprising fins (24).

5. A heater according to claim 3, in which said base has a pair of end walls, said base having a pair of radiator means (22) provided respectively on said end walls (12c) for efficiently radiating the heat transferred from said heating element, each of said radiator means comprising at least one fin (22).

6. A heater according to claim 3, in which each of said elongated opposed plates (14) has enlarged end portions (14a) for enhancing the radiation of the heat transferred from said heating element (16).

Patentansprüche

1. Heizgerät zum Erwärmen eines unter Wärme schrumpfbaren Schlauchabschnitts (110), der ein langgestrecktes Teil (112) umgibt, mit einem Gehäuse (12), welches eine langgestreckte Trägerplatte (12a) zur Aufnahme des langgestreckten Teils (112) mit dem unter Wärme schrumpfbaren Schlauchabschnitt (110) aufweist, und mit einem Heizelement (16), dadurch gekennzeichnet, daß die Trägerplatte (12a) aus wärmeleitfähigem Material besteht und einen Mittelbereich (12b), der durch das Heizelement (16) festgelegt ist, welches an der Unterseite der Trägerplatte (12a) angeordnet, sowie Endbereiche (12d) aufweist, die sich an den Mittelbereich (12b) beidseitig in entgegengesetzten Richtungen anschließen, daß das Heizgerät (10) ein Paar parallel zueinander und abständig angeordneter Platten (14) aus wärmeleitfähigem Material aufweist, die vertikal abstehend von der äußeren Oberfläche der Trägerplatte (12a) und sich über den Mittelbereich (12b) und die Endbereiche (12d) der Trägerplatte (12a) hinwegerstreckend vorgesehen sind, und daß bei eingeschaltetem Heizelement (16) Wärme zum Mittelbereich (12b) der Trägerplatte (12a) und von dort zu den Endbereichen (12d) und den Platten (14) übertragen wird, so daß der Mittelteil des unter Wärme schrumpfbaren Schlauchabschnitts (110), der sich über dem Mittelbereich (12b) befindet, zuerst erwärmt und damit zuerst aufgeschrumpft wird, während seine beiden Endteile nacheinander aufgeschrumpft werden.

2. Heizgerät nach Anspruch 1, dadurch gekennzeichnet, daß das Heizelement (16) einen Thermi-



stor mit positivem Temperaturkoeffizient (PCT-Thermistor) aufweist, dessen Widerstand mit steigender Temperatur ansteigt und bei Erreichen einer bestimmten Temperaturgrenze abrupt anwächst, so daß eine weitere Temperaturerhöhung im wesentlichen gestoppt wird.

3. Heizgerät nach Anspruch 1, dadurch gekennzeichnet, daß das Gehäuse (12) langgestreckte, kastenartige Gestalt mit einer oberen Wandung, die als Trägerplatte (12a) dient, aufweist, und daß der unter Wärme schrumpfbare Schlauchabschnitt (110) zur Aufnahme zwischen den beiden langgestreckten Platten (14) ausgebildet ist.

4. Heizgerät nach Anspruch 1, dadurch gekennzeichnet, daß die Trägerplatte (12a) an beiden Endbereichen (12d) angeordnete, paarweise vorgesehene Radiatoren zur wirksamen Abstrahlung von Wärme, die von dem Heizelement übertragen wird, trägt, und daß die Radiatoren Rippen (4) aufweisen.

5. Heizgerät nach Anspruch 3, dadurch gekennzeichnet, daß das Gehäuse paarweise angeordnete Endwandungen (12c) aufweist, die jeweils mit an den Endwandungen angeordneten Radiatoren zur wirksamen Abstrahlung von Wärme, die von dem Heizelement übertragen wird, versehen sind, und daß jeder Radiator mindestens eine Rippe (22) aufweist.

6. Heizgerät nach Anspruch 3, dadurch gekennzeichnet, daß jede der beiden langgestreckten Platten (14) vergrößerte Endstücke (14a) zur Verstärkung der Abstrahlung von Wärme, die von dem Heizelement (16) übertragen wird, aufweist.

Revendications

1. Un appareil de chauffage (10) pour tube rétractable à chaud (110), monté sur un organe allongé (112) et comprenant:

une base (12) présentant une plaque support (12a) allongée, adaptée pour supporter ledit organe allongé (112) portant ledit tube rétractable à chaud (110); et

un élément chauffant (16);

caractérisé en ce que ladite plaque support (12a) est constituée d'un matériau conducteur de la chaleur et ladite plaque support (12a) comprenant:

une partie centrale (12b) définie par ledit élément chauffant (16) fixé à la face inférieure de ladite plaque support (12a); et

des parties d'extrémité (12d) s'étendant vers l'extérieur, dans des directions opposées partant de la partie centrale (12b);

caractérisé en outre en ce que l'appareil chauffant (10) comporte deux plaques allongées (14)

espacées parallèlement, en matériau conducteur de la chaleur, s'élevant d'une surface extérieure de ladite plaque support (12a) et s'étendant le long de ladite partie centrale (12b) et desdites parties d'extrémités (12d) de ladite plaque support (12a);

de manière que, lorsque ledit élément chauffant (16) est activé, il se produise un transfert de chaleur vers ladite partie centrale (12b) de la plaque support (12a) et par conséquent vers les parties d'extrémité (12d) et les plaques (14), de façon que la partie centrale dudit tube rétractable (110) située au-dessus de ladite partie centrale (12b) soit chauffée en premier, et qu'ensuite, ledit tube (110) subisse un retrait à chaud en sa partie centrale en premier, qui se propage ensuite vers ses extrémités opposées.

2. Un appareil de chauffage selon la revendication 1, dans lequel ledit élément chauffant (16) comprend une thermistance à coefficient de température positif (thermistance PTC) dont la résistance augmente lorsque sa température augmente et augmente de façon brusque lorsque la température atteint un niveau prédéterminé, de façon que son augmentation soit pratiquement stoppée.

3. Un appareil de chauffage selon la revendication 1, dans lequel ladite base (12) est une base en forme de boîte allongée comportant une paroi supérieure (12a) servant de plaque support (12a), le tube rétractable à chaud (110) étant adapté pour être monté entre lesdites deux plaques allongées (14).

4. Un appareil de chauffage selon la revendication 1, dans lequel ladite plaque support (12a) comporte deux moyens radiants (24), respectivement prévus sur ses parties d'extrémité opposées (12d), afin de rayonner efficacement la chaleur transférée depuis ledit élément chauffant, lesdits moyens rayonnants comprenant des ailettes (24).

5. Un appareil de chauffage selon la revendication 3, dans lequel ladite base comporte deux parois d'extrémité et deux moyens rayonnants (22) respectivement prévus sur lesdites parois d'extrémité (12c) afin de rayonner efficacement la chaleur transférée depuis ledit élément chauffant, chacun desdits moyens rayonnants comprenant au moins une ailette (22).

6. Un appareil de chauffage selon la revendication 3, dans lequel chacune desdites plaques allongées (14) comporte des parties d'extrémité élargies (14a) pour améliorer le rayonnement de la chaleur transférée depuis ledit élément chauffant (16).

