

- 1 -

METHOD AND APPARATUS FOR REMOVAL OF OIL FROM UTILITY GAS STREAM

CROSS REFERENCE TO RELATED APPLICATIONS

- 5 [0001] This application claims the benefit of U. S. Provisional Application No. 61/125,939, filed 30 April 2008.

FIELD OF THE INVENTION

- [0002] This invention relates generally to methods of processing gaseous slip streams. More specifically, the invention relates to a process and apparatus for removing oil from a
10 process slip stream used as a utility gas in a utility component.

BACKGROUND

- [0003] This section is intended to introduce the reader to various aspects of art, which may be associated with exemplary embodiments of the present invention, which are described and/or claimed below. This discussion is believed to be helpful in providing the
15 reader with information to facilitate a better understanding of particular techniques of the present invention. Accordingly, it should be understood that these statements are to be read in this light, and not necessarily as admissions of prior art.

- [0004] Environmentally conscious and efficient recovery of oil and gas from hydrocarbon reservoirs is a multidimensional problem that has become one of the world's
20 toughest energy challenges. Injection of various gasses into such reservoirs is now utilized for sequestration, pressure maintenance, or enhanced oil recovery operations. In recent years, injection compressor technology has advanced to the point that development plans for some oil and gas fields incorporate them to inject acid or sour gas in underground formations for sequestration or enhanced oil recovery (EOR) operations. The compressor shafts are
25 typically sealed using dry gas seals (DGS) which utilize the principle of sealing between a stationary face against a rotating face by using a gas fluid film. This "seal gas" provides the lubrication and cooling properties needed by the seal for long and reliable operation. Seal gas should be free of particulates, liquids, and heavy components that condense out of the seal gas when expanded across the seal faces.

- 30 [0005] Typically, dry seal compressors pressurize injection gas streams (e.g. acid or sour gas streams) to pressures in excess of about 4,000 pounds per square inch absolute (psia) with stream flow rates in excess of 100 million standard cubic feet per day (SCFD). To operate without failure, the seals in the compressors should be lubricated with a gas stream that will not condense a liquid phase as its pressure drops when it expands across the seal

- 2 -

faces. The seal gas pressure is greater than the compressor suction pressure, but less than the compressor discharge pressure.

[0006] One strategy for producing a non-condensing seal gas is to compress a purified low pressure (e.g. less than about 800 psia) methane or nitrogen stream in a reciprocating compressor. Reciprocating compressors are lubricated with cylinder oil that has some miscibility with the gas, especially at high (e.g. greater than about 2,000 psia) pressures. After compression, the gas stream contains oil in the form of either vapor or entrained droplets. The vapor generally can not be filtered out and at high pressures filtration of entrained droplets is typically inefficient. Thus the oil in the high pressure methane stream will have a liquid phase that is either entrained or “drops out” of the gas when the pressure is dropped through the seals or at pressure regulators that control the pressure to the seals. This cylinder oil “carry-over” into the seal gas is expected to damage and cause premature failure of standard dry seal compressors, resulting in significant down-time and lost production.

[0007] In some situations, such as high pressure sour gas service, the seal gas has been obtained from a utility source such as a fuel gas system. Fuel gas is predominantly composed of methane, but can contain some amounts of heavier hydrocarbons, CO₂, N₂ and small quantities of H₂S. A typical source of fuel gas for compressor applications is a slip stream taken from the process gas being fed to the dry seal compressor. At low pressures (e.g. similar to the suction pressure of the dry seal compressor), many different technologies such as absorption, gas/liquid phase separation, and glycol dehydration can be used to condition a slip stream for use as fuel gas.

[0008] Purifying a slip stream taken from the high pressure discharge of the dry seal compressor is technically challenging. The fuel gas or gas from another utility gas source is then compressed and used as seal gas. Such gas is used to avoid the liquid contamination or liquid drop out encountered by using the process gas. This requires additional process and separation units to generate the fuel gas and a separate seal gas booster compressor (e.g. a reciprocating compressor), which can itself be a source of oil and particulate contamination. A reciprocating compressor is usually used for this service due to the high compression ratios and low flows. Reciprocating compressors of this type are typically lubricated with cylinder oil that has some miscibility with the gas, especially at high pressures. Thus, it can not be filtered out at high pressure but condenses or “drops out” of the gas when the pressure is dropped through the seals or at pressure regulators that control the pressure to the seals. This

- 3 -

cylinder oil “carry-over” into the seal gas may damage and cause premature failure of standard DGS’s.

[0009] U.S. Pat. No. 5,976,221 discloses a method of oil removal from vapor utilizing polymeric adsorption. Such a method only removes about 99.9% of the oil. Such results are
5 good, but even a small amount of oil can damage a DGS and cause significant downtime.

[0010] U.S. Pat. No. 4,325,565 discloses a method of oil removal including heating the gas stream to fully vaporize the oil in the stream before adsorbing the oil. Although this technique appeared to be effective, it requires additional energy use and processing equipment to achieve beneficial results.

10 [0011] Hence, an improved method of removing oil from process gas for use in dry seals is needed.

SUMMARY

[0012] In one embodiment, a system for treating a gaseous feed stream is provided. The system includes: a selective component removal system, comprising a gaseous feed
15 stream inlet configured to pass a gaseous feed stream into a swing adsorption unit having at least one structured adsorbent bed. In the system, the gaseous feed stream includes a volume of oil droplets and a volume of oil vapor and has a pressure of at least about 1,000 pounds per square inch; the at least one structured adsorbent bed is configured to remove at least a portion of the volume of oil droplets and a portion of the volume of oil vapor to provide a
20 substantially oil-free gaseous outlet stream; and the at least one structured adsorbent bed is regenerated in a kinetic swing adsorption process.

[0013] In another embodiment of the present invention, a method of treating a gaseous feed stream is provided. The method includes: providing a gaseous feed stream having a volume of oil therein; treating the gaseous feed stream using a selective component
25 removal system having at least one swing adsorption process unit to form a utility stream for use in a utility component, wherein the at least one swing adsorption process unit includes a structured adsorbent bed configured to remove at least a portion of the volume of oil; regenerating the swing adsorption process unit in a calcination process; feeding the utility stream into the utility component, wherein the utility stream is compatible with the utility
30 component; and utilizing the utility stream in the utility component.

[0014] In a third embodiment of the invention, a structured adsorbent contactor is provided. The contactor includes: an inlet end; an outlet end; and a plurality of open flow channels extending from the inlet end to the outlet end, wherein a portion of the

- 4 -

plurality of open flow channels are sealed at the inlet end and the remainder of the plurality of flow channels are sealed at the outlet end, and wherein the surface of the open flow channels are comprised of an adsorbent material having a selectivity for a first component over a second component of a mixture greater than one.

5 **BRIEF DESCRIPTION OF THE DRAWINGS**

[0015] The foregoing and other advantages of the present technique may become apparent upon reading the following detailed description and upon reference to the drawings in which:

10 [0016] FIG. 1 is an illustration of a conventional system to prepare a seal gas from a gaseous feed stream;

[0017] FIG. 2 is an illustration of a selective component removal system to prepare a seal gas from a gaseous feed stream in accordance with the present invention;

[0018] FIG. 3 is a flow chart of a process to prepare a seal gas from a gaseous feed stream using the system of FIG. 2;

15 [0019] FIG. 4 illustrates an exemplary embodiment of a process schematic of the SCRS of FIG. 2 operated according to the method of FIG. 3;

[0020] FIGs. 5A-5B illustrate exemplary embodiments of parallel channel contactor structured adsorbent bed designs for use in the system of FIGs. 2 and 4 and processes of FIG. 3;

20 [0021] FIG. 6 is an illustration of an exemplary segmented contactor, which may be used in combination with the adsorbent beds as disclosed in FIGs. 2 and 5A-5B;

[0022] FIG. 7 illustrates an exemplary graph comparing the phase envelopes of a treated seal gas and an untreated seal gas; and

25 [0023] FIG. 8 illustrates an exemplary graph of an oil front advancing through an adsorbent channel based on modeling of the Langmuir isotherm.

DETAILED DESCRIPTION

30 [0024] In the following detailed description and example, the invention will be described in connection with its preferred embodiments. However, to the extent that the following description is specific to a particular embodiment or a particular use of the invention, this is intended to be illustrative only. Accordingly, the invention is not limited to the specific embodiments described below, but rather, the invention includes all alternatives, modifications, and equivalents falling within the true scope of the appended claims.

- 5 -

[0025] The term “structured adsorbent bed,” as used herein means a volume of adsorbent materials that have a structural relationship to each other, wherein the structural relationship is maintained even when the materials are not contained in a vessel. The term excludes a bed comprising adsorbent particles simply dumped into a vessel. Exemplary structural relationships include, for example, a monolithic “brick,” layered surfaces, 5 channeled monoliths, and the like. Structured adsorbents contain at least a selective adsorbent material and a plurality of substantially parallel flow channels. The selective adsorbent material is comprised of high surface area solids and excludes polymeric or inorganic material. However, the structured adsorbent bed may also include a “binder” to hold adsorbent particles together. This binder may be a polymeric or inorganic material. The 10 structured adsorbent bed may also contain a material that acts as a thermal mass serving to limit the temperature rise of the structured adsorbent bed when molecules are selectively adsorbed.

[0026] The term “selective component removal system (SCRS),” as used herein, 15 means a system or group of components configured to have a selectivity of a first component greater than a second component (one of the components typically being a gaseous component), for example, a higher adsorption of oil than of methane. The SCRS may include any means of selectivity, unless particularly specified and may include compressors, filters, and other equipment specifically related to the selective removal of the first component from 20 the second component.

[0027] The term “high surface area solid,” as used herein means a volume of solids consisting essentially of mesoporous solids and microporous solids.

[0028] The term “kinetic swing adsorption process” includes processes such as pressure swing adsorption (PSA), thermal swing adsorption (TSA), calcination, and partial 25 pressure swing or displacement purge adsorption (PPSA), including combinations of these processes. These swing adsorption processes can be conducted with rapid cycles, in which case they are referred to as rapid cycle thermal swing adsorption (RCTSA), rapid cycle pressure swing adsorption (RCPSA), and rapid cycle partial pressure swing or displacement purge adsorption (RCPPSA). The term swing adsorption also includes these rapid cycle 30 processes. Some examples of swing adsorption processes and their application to natural gas separations are provided in U.S. Serial No. 60/930,827, U.S. Serial No. 60/930,826, U.S. Serial No. 60/931,000, and U.S. Serial No. 60/930,993, and U.S. Serial No. 60/930,998, which are hereby incorporated by reference.

- 6 -

[0029] Pressure swing adsorption (PSA) processes operate on the principal that under pressure gasses tend to be adsorbed within the pore structure of microporous or mesoporous adsorbent materials or within the free volume of polymeric materials. The higher the pressure, the more gas is adsorbed. When the pressure is reduced, the gas is released, or
5 desorbed. PSA processes can be used to separate gasses in a mixture because different gasses tend to fill the micropore or free volume of the adsorbent to different extents. If a gas mixture, such as natural gas, for example, is passed under pressure through a vessel containing polymeric or microporous adsorbent that fills with more nitrogen than methane, part or all of the nitrogen will stay in the sorbent bed, and the gas coming out of the vessel
10 will be enriched in methane. When the bed reaches the end of its capacity to adsorb nitrogen, it can be regenerated by reducing the pressure, thereby releasing the adsorbed nitrogen. It is then ready for another cycle.

[0030] Temperature swing adsorption (TSA) processes operate on the same principle as PSA processes. When the temperature of the adsorbent is increased, the gas is released, or
15 desorbed. By cyclically swinging the temperature of adsorbent beds, TSA processes can be used to separate gases in a mixture when used with an adsorbent that selectively picks up one or more of the components in the gas mixture.

[0031] Rapid cycle pressure swing adsorption (RCPSA) can be constructed with a dynamic (e.g. rotary) valving system to conduct the gas flow through a rotary adsorber
20 module that contains a number of separate adsorbent bed compartments or "tubes," each of which is successively cycled through the sorption and desorption steps as the rotary module completes the cycle of operations. The rotary sorber module is normally comprised of multiple tubes held between two seal plates on either end of the rotary sorber module wherein the seal plates are in contact with a stator comprised of separate manifolds wherein the inlet
25 gas is conducted to the RCPSA tubes and the processed purified product gas and the tail gas exiting the RCPSA tubes are conducted away from the rotary sorber module. By suitable arrangement of the seal plates and manifolds, a number of individual compartments or tubes may pass through the characteristic steps of the complete cycle at any given time. In contrast, with conventional PSA, the flow and pressure variations, required for the RCPSA
30 sorption/desorption cycle, changes in a number of separate increments on the order of seconds per cycle, which smoothes out the pressure and flow rate pulsations encountered by the compression and valving machinery. In this form, the RCPSA module includes valving elements angularly spaced around the circular path taken by the rotating sorption module so

- 7 -

that each compartment is successively passed to a gas flow path in the appropriate direction and pressure to achieve one of the incremental pressure/flow direction steps in the complete RCPSA cycle.

[0032] The term “swing adsorption unit,” as used herein, means a system including a structured adsorbent bed that is capable of undergoing at least an adsorption step and a regeneration step, wherein at least one of the temperature and pressure is varied (or “swung”) over a significant change in magnitude (e.g. from a low value to a high value). In certain embodiments, the swing adsorption unit may conduct one of the swing adsorption protocols (PSA, RCPSA, TSA, RCTSA, PPSA, RCPPSA, and combinations of these).

[0033] To prepare a gaseous feed stream for use in utilities such as dry gas seal (DGC) compressors, classes of separation applications that must be performed include dew point control, sweetening/detoxification, corrosion protection/control, dehydration, heating value, conditioning, and purification. A few examples of utilities that encompass one or more classes of applications are generation of fuel gas, seal gas, non-potable water, blanket gas, instrument and control gas, refrigerant, inert gas, and hydrocarbon recovery.

[0034] The present invention relates to swing adsorption units and processes for removing oil from seal gas to prevent condensation across the seal face and cause premature failure of standard dry seal compressors. Swing adsorption units contain a structured adsorbent bed. During the adsorption cycle, an selective adsorbent material in the swing adsorption bed removes entrained oil droplets and vapor from the high pressure seal gas. Materials that are suitable selective adsorbent material include high surface area solids such as alumina, mesoporous, or microporous solids. A binder, filler, heat adsorbing material, or combinations of these may also be incorporated with the selective adsorbent material. To enhance the efficiency of the adsorption and meet seal gas purity requirements it is preferred that the selective adsorbent material (“adsorbent”) be incorporated as a structured adsorbent bed. Structured adsorbents useable with the present invention may be formatted as parallel channel contactors or as a “soot-filter” like monolith or combinations of these. These structures contain a multitude of substantially parallel flow channels surrounded by selective adsorbent material. Before an adsorption front breaks through to the end of the structured adsorbent bed a regeneration cycle is initiated. Because the oil is strongly adsorbed (e.g. a high ratio of selectivity for oil over the carrier fluid, which may be natural gas), preferred regeneration techniques involve heating the adsorbent, passing a purge material through the adsorbent that displaces the adsorbed oil, and calcination.

- 8 -

[0035] If the structured adsorbent bed is thermally regenerated or calcined, it is possible to incorporate a heater and heat exchanger so that hot gas does not pass through the valves controlling flow into and out of the structured adsorbent bed. In many instances this arrangement can be advantageous because several high pressure valves contain elastomeric seals or components that cannot be operated at temperatures in excess of approximately 250 degrees Celsius (°C).

[0036] Cylinder oils act as lubricants for independently lubricated cylinders, such as reciprocating compressors. Cylinder oils lubricate valves, the piston ring/cylinder liner wall interface and provide a dynamic gas seal. Cylinder oils are available in a range of grades with different viscosities, viscosity index (i.e. temperature dependent viscosity) and additive packages that reduce friction, reduce corrosion, disperse colloidal materials, and reduce oxidation. It is preferred that the viscosity of the cylinder oil at 40°C as determined by ASTM test method D445/446 be in a range from 75 to 300 CSt and the viscosity at 100°C be in a range from 15 to 60 CSt. It is preferred that the ISO viscosity grade as determined by ISO test method 3448 be in a range from 70 to 300. It is also desired that the viscosity index as determined by ASTM D2270 be in a range from 215 to 250. The base stock from which the cylinder oil is formulated may be natural (i.e. mineral), synthetic, or a blend of natural and synthetic materials. An example of a cylinder oil that is a blend of natural and synthetic materials is an oil formulated from a mineral oil base stock with an oligomeric polyisobutylene viscosifying agent.

[0037] In a preferred embodiment, the cylinder oil is a synthetic composed of a random copolymer of ethylene oxide and propylene oxide. These ethylene oxide / propylene oxide random copolymers are often referred to as polyglycols and have solubility in cold water. In a more preferred embodiment the average molecular weight of the polyglycol as determined by gel permeation chromatography is in a range between 500 gram/mole and 10,000 gram/mole. In an even more preferred embodiment the average molecular weight of the polyglycol as determined by gel permeation chromatography is in a range between 1,200 gram/mole and 2,500 gram/mole.

[0038] Although many types of oil may be utilized in the present invention, it is preferred to use low ash or ash free cylinder oil. Ash content of the oil can be assessed by burning the oil and weighing the residue, for example by thermo gravimetric analysis (TGA). A low ash oil is taken to be one which has a residue after full oxidation (or burning) of less than 0.5 weight percent (wt%) of the formulated cylinder oil and in a preferred embodiment

- 9 -

the ash content is less than 0.01 wt% of the formulated cylinder oil. An example of a synthetic cylinder oil with an ash content less than 0.01 wt% is an oligomer of ethylene and propylene oxide.

[0039] Referring now to the figures, FIG. 1 is an illustration of a conventional system to prepare a seal gas from a gaseous feed stream. The system **100** includes a selective component removal system (SCRS) **101** with a low pressure gas stream **102** as an inlet gas, a seal gas compressor **104** to produce a pressurized seal gas stream **106** for a filter unit **108** (e.g. a coalescing filter) to produce a filtered seal gas stream **110** as an outlet gas. The filtered seal gas stream **110** is sent to a seal gas control panel **112**, which separates the stream **110** into low pressure seal gas **114**, medium pressure seal gas **116**, and high pressure seal gas **118**. The system **100** further includes a sour process gas stream **120** fed into a low pressure sour gas injection compressor **122**, medium pressure sour gas injection compressor **124**, and high pressure sour gas injection compressor **126**, which produces a pressurized sour gas stream **128** to injection wells **130**. The injection compressors **122**, **124**, and **126** operate using the low, medium, and high pressure seal gasses **114**, **116**, **118**, respectively.

[0040] Low pressure (LP) stream **102** may have pressures below about 800 pounds per square inch absolute (psia), while pressurized stream **106** may have pressures above about 1,500 psia up to about 3,500 psia. The LP gas stream **102** may have a variety of component percentages. In one exemplary embodiment, LP stream **102** is a fuel gas stream substantially comprising methane (e.g. from about 60 mol % to about 90 mol %), other light hydrocarbon components (e.g. ethane, propane, butane, etc.), and nitrogen, but also including very low amounts of "contaminants" such as water, carbon dioxide, and hydrogen sulfide (e.g. from about 0 mol % to about 0.001 mol %). In other embodiments, the LP stream **102** may be a treated slip stream from the sour process gas stream **120**, a high purity nitrogen stream, or some other gaseous stream having low contaminant content. Pressurized stream **106** has substantially the same composition as LP stream **102**, but additionally including oil vapor and droplets (e.g. mist).

[0041] Coalescing filters **108** can only remove the mist and cannot significantly reduce the vapor saturation of oil in the gas stream. Thus, when the oil saturated gas stream **110** passes across the seal face (in the compressor **122**, **124**, or **126**) some amount of liquid (oil) will drop out. As such, even with a perfect coalescing filter **108** some amount of liquid will drop out in the seal and the compressor **122**, **124**, or **126** will not properly operate as a

- 10 -

dry seal compressor. Particularly at high pressures, the operation of coalescing filters can be far from ideal and a portion of the oil mist is expected to pass through the filter into the seal of the compressor. The amount of liquid oil entering the seals is expected to be much greater than the amount carried as vapor. These amounts can be sufficient to increase the friction in the seals causing wear and premature failure of the seals.

[0042] FIG. 2 is an illustration of a selective component removal system to prepare a seal gas from a gaseous feed stream in accordance with the present invention. Functionally equivalent components of system **100** and system **200** are given the same reference numbers for convenience. The selective component removal system (SCRS) **202** includes a low pressure gas stream **102** as an inlet gas, a seal gas compressor **104** to produce a pressurized seal gas stream **106** for a swing adsorption unit **204** having a structured adsorbent bed **206** to produce a substantially oil-free seal gas stream **208** as an outlet gas. For use with the present invention, it is preferred that the composition of the low pressure stream **102** be such that components in the stream do not drop out as liquids when it is pressurized and expands across the seal faces.

[0043] To determine if a component will drop out as a liquid, a phase envelope for the fuel gas composition may be calculated. This calculation is performed using generally accepted equations of state such as the Peng-Robinson equation. Also, the gas composition modeled should not include any compressor oil that is picked-up from the seal gas compressor **104**. An exemplary commercial software package that can be used to predict this phase envelope is Hysys 2004.1 available from Aspen Technology. This phase envelope can be displayed as a plot with pressure on the y axis and enthalpy on the x-axis. Expansion across the seal faces is taken to be similar in behavior to a valve expansion and is a vertical line on such a plot. The x-axis intercept of the vertical line is the molar enthalpy of the compressed fuel gas at the temperature and pressure it is utilized as a seal gas. As long as the composition along the vertical line is entirely gaseous and the line does not cross through a two phase region, then the low pressure stream has a composition suitable for use.

[0044] If the expansion enters a two phase region, then the low pressure stream **102** must be conditioned before it can be used in the process. In this case, an optional conditioning unit **203** is utilized to condition the low pressure process stream **102** to produce a conditioned gas stream **205** to feed to the compressor **104**. This conditioning unit **203** removes condensable components so that a two phase region is not encountered when the gas expands across the seal faces. In one example, if the low pressure process stream **102** is a

- 11 -

fuel gas containing excessive amounts of heavy hydrocarbons then a conditioning unit **203** containing a heavy hydrocarbon removal apparatus is utilized to form the conditioned gas stream **205**. Heavy hydrocarbon removal apparatuses include adsorption units or a cooling unit to induce gas/liquid phase separation. In another example, the low pressure process stream **102** is a fuel gas nearly saturated with water. In this case conditioning unit **203** is configured to remove water with devices such as thermal swing adsorbers or glycol dehydrators. A more specific example of the phase envelope is provided in connection with FIG. 7 below.

[0045] The swing adsorption unit **204** and adsorbent bed **206** are configured to remove at least a portion of the oil mist and the oil vapor from the gas **106** so that it will not condense and cause premature failure of dry seal compressors **122**, **124**, **126**. The structured adsorbent bed **206** may be a packed bed, structured adsorbent, a structured adsorbent contactor or a contactor containing an adsorbent. The structured adsorbent bed **206** is regenerated in a swing adsorption process.

[0046] Although the SCRS **202** may be used in a system similar to the system **100**, it may be used in any system for removing oil from a gaseous stream for use in a dry seal compressor. In one specific embodiment, the system may integrate an accumulator with the seal gas control panel **112** or replace the control panel **112** with an accumulator. Further, any number and combination of dry seal compressors **122**, **124**, and **126** may be used, including any combination of low, medium, and high pressure gas streams **114**, **116**, and **118**. In yet another embodiment, the dry seal compressors **122**, **124**, **126** may be used to compress a substantial carbon dioxide stream for enhanced oil recovery or sequestration. Note, that compressors **122**, **124**, and **126** may be any device or group of devices that utilize a dry gas stream to operate and includes at least a compressor, a compressor string, a turbo-expander compressor, a turbo-expander generator, a pump, a fired steam boiler, a fired process heater, a gas engine, a hermetically sealed direct-drive electric motor, turbomachinery equipped with magnetic bearings, and a gas turbine.

[0047] As discussed above, the inlet gas stream **102** may include numerous compositions and be supplied from a variety of sources. For example, the inlet gas stream **102** may include at least one hydrocarbon component. When the inlet gas stream **102** contains natural gas or associated gas, a product stream may be produced. Such a product stream is at least a purified gas stream that is transferred to market by pipeline, or a liquefied natural gas, or natural gas liquids, or a gas stream that is injected into the subsurface in

- 12 -

locations such as the producing field, an underground aquifer, another geological formation, or a combination of these different products and locations. In one alternative embodiment, a slip stream **212A** or **212B** is provided from the gaseous stream **120** or the injection stream **128**, respectively, directed to a filtering unit **214**, and fed to the inlet stream **102** for cleanup
5 and use as a dry gas seal stream **114**, **116**, or **118**.

[0048] In high pressure applications such as injection operations, it is preferable to operate the swing adsorption unit **204** with an inlet stream **106** in a range from at least about 100 bar to at least about 500 bar and more preferably in a range from about 200 to about 400 bar, and even more preferably in a range from about 250 bar to at least about 350 bar which
10 is dependent on the compressor suction or sealing pressure. These pressures are in excess of those used in conventional swing adsorption units.

[0049] FIG. 3 is a flow chart of a process to prepare a seal gas from a gaseous feed stream using the system of FIG. 2. As such, FIG. 3 may be best understood with reference to FIG. 2. The method **300** starts at block **302** and further includes providing **304** a gaseous
15 stream including oil **106**, treating **306** the gaseous feed stream **106** in a swing adsorption process unit **204** using a structured adsorbent bed **206** to remove at least a portion of the volume of oil, regenerating **308** the structured adsorbent bed **206** in a calcination process to produce a utility gas stream **210**, feeding **310** the utility gas stream **210** to a utility component (e.g. compressors **122**, **124**, or **126**), and utilizing **312** the treated gas stream **210** in the utility
20 component (e.g. as a dry seal gas in a dry seal compressor). The process **300** ends at block **314**.

[0050] In the adsorption process **306** the gaseous feed **102** (or **105**) is passed through a bed of solid adsorbent material **206**. Exemplary suitable adsorbent materials for this process may be a packed bed, structured adsorbent, a structured adsorbent contactor or a
25 contactor containing an adsorbent. Molecules in the feed **102** adsorb on the solid adsorbent material. Components of the gaseous feed that are more strongly adsorbed are removed from the stream, or at least their concentration decreases significantly below their initial concentration in the gaseous feed.

[0051] In the case when fuel gas or sour gas is used as a source of dry seal gas, oil is
30 the most strongly adsorbed component owing to its higher molecular weight and stronger interactions with solid adsorbent materials as compared to lighter components in the gaseous feed such as methane, ethane, N₂, CO₂ and H₂S. Both oil vapor and entrained droplets are adsorbed on the solid adsorbent materials. Thus, in the adsorption process, most of the oil is

- 13 -

effectively removed from the stream of lighter components to provide a substantially oil-free gaseous outlet stream. Adsorption processes can be performed in a non-equilibrium regime which exploits the difference in diffusion times between small and large molecules. Small components in the gaseous input stream diffuse faster than bulkier oil molecules. This results in effective removal of oil from the outlet stream. Adsorption is an exothermic process, and desorption or regeneration of solid adsorbent material may include a temperature swing process, high-temperature calcination, a pressure swing process, an inert purge, or any combination thereof. These kinetic swing adsorption/desorption processes can be conducted with rapid cycles.

10 [0052] FIG. 4 illustrates an exemplary embodiment of a process schematic of the SCRS of FIG. 2 operated according to the method of FIG. 3. As such, FIG. 4 may be best understood with reference to FIGs. 2 and 3. The system **400** includes a selective component removal system **202** having a kinetic swing adsorption unit **204**, a gas inlet stream **102**, a reciprocating compressor **104** that produces a pressurized gaseous stream **106** to an optional filter **108**, which produces an inlet gas stream **402** through inlet valve **402b** for the swing adsorption unit (SAU) **204**. Note that, although a conditioning unit **203** is not shown, such a unit is an optional feature. The SAU **204** includes a housing **404**, a gaseous purge stream inlet **406** with purge inlet valve **406b**, a structured adsorbent bed **206** with a heater **408** configured to heat the bed **206** for regeneration **308**. The SAU **204** further includes a cooling fluid **410**, an outlet heat exchanger **412**, a vent stream outlet **414** and valve **414b**, a utility gas stream outlet **416** and valve **416b**.

25 [0053] The SCRS **202** may further include optional features such as a cooling jacket **420**, an electric pre-heater **422** and an accumulator **418**. In one embodiment, the inlet gas stream **106** may be directed through the filter **108** and control valve **402b** into the adsorption unit **204**. The filter **108** may remove any extraneous particles that could contaminate and deactivate the adsorbent bed **206** and may be a coalescing or particulate filter. The control valves **402b** and **406b** may regulate the flow of fluids fed into the SAU **204**. The streams may be connected by tubulars, which may be constructed from corrosion resistant alloys, carbon steel, or other materials, but preferably the tubulars are capable of handling fluids at high pressure, such as above about 100 bar.

30 [0054] In one exemplary embodiment of the SCRS **202**, the SAU **204** is a thermal swing adsorption unit, where inlet gas **102** is treated **306** by feeding it into the adsorption bed **206** where contaminants such as the oil are adsorbed onto the bed **206**. In the regeneration

- 14 -

step **308**, the swing adsorption cycle depressurizes the bed **206** and thermally swings the bed **206** to a temperature sufficient for calcination (e.g. from at least about 250°C to about 500°C) with the bed heater **408**, and flows a low pressure air stream from purge inlet **406**, or some combination thereof. After the calcination is complete, the bed **206** is cooled and
5 repressurized before another adsorption step **306** is begun. Cooling can be accomplished with either an optional water cooling jacket **420** or by flowing inlet gas **402** (either low pressure or pressurized) through the bed **206**, or by flowing cooling fluid through separate heating/cooling channels in a bed configured as a contactor **206**. After cooling, the bed **206** is ready to receive another charge of inlet gas **402** having oil vapor and droplets.

10 [0055] Additionally, the heat exchanger **412** is configured to utilize cooling fluid **410** to reduce the temperature of hot gas **416** coming out of the swing adsorption unit **204** to a sufficiently low temperature that it can be passed through the valve **416b**. Optionally, the selective component removal system (SCRS) **202** may contain a filter (not shown) downstream to catch dust or particulates that may come out of the structured adsorbent bed
15 **206**.

[0056] The exit gas stream **416** may be directed to an accumulator **418** and/or a gas control panel **112** to regulate the flow of utility or seal gas **114**, **116**, and **118** to utility components or dry gas seal compressors **122**, **124**, and **126**.

[0057] The choice of valve technologies depends in part on the pressure, composition,
20 and temperature of the inlet stream **402** or **106**, and the temperature of any required heating or cooling fluids (e.g. **410**). In all cases, the valves **402b**, **406b**, **414b**, and **416b** have a sealing surface or packing that prevents leakage of components out of the valve body. The amount of leakage out of the valve body depends on the differential pressure between the atmosphere surrounding the valve and the stream or streams controlled by the valve. When
25 the feed stream is fed at high pressures (e.g., greater than 70 bar) the leakage rate from the valves can be an important safety and operational concern. For example, if the adsorption unit **204** processes H₂S containing sour or acid gas even small amounts of leakage can be a significant safety and operational concern. In one exemplary embodiment of the present invention, valve or valve sets **402b**, **406b**, **414b**, and **416b** are enclosed in individual
30 housings pressurized to a pressure greater than 10% of the feed stream **402** or **106** pressure and in a more preferred embodiment the housings are pressurized to a pressure greater than

- 15 -

90% of the feed stream **402** or **106** pressure. There may also be sensors to detect any potential release of H₂S, which can present a safety hazard.

[0058] In an exemplary embodiment, the swing adsorption unit **204** contains multiple adsorption beds **206A-206X** (only one shown). Preferably, at least a portion of the beds
5 **206A-206X** will be undergoing regeneration **308**, while others are undergoing the adsorption step **306**. One example of a multiple-bed pressure swing adsorption configuration and method is provided in U.S. Pat. No. 7,276,107, which is hereby incorporated by reference for teachings regarding multiple bed pressure swing adsorption (PSA) systems. The system and steps of the PSA approach are slightly modified for a temperature swing approach. An
10 example of a unit with multiple adsorption beds **206A-206X** is one that processes 5-10 10⁶ standard cubic feet per day (SCFD) of pressurized (e.g. about 330 bar) fuel, nitrogen or other essentially oxygen free gasses.

[0059] In one exemplary design for a swing adsorption unit **204** having multiple structured adsorbent beds **206A-206X**, each structured adsorbent bed is contained inside a
15 single tube about four meters long, having about a two inch diameter, wherein the swing adsorption unit **204** contains six such tubes. Each tube has its own control valves **402b**, **406b**, **414b**, **416b**, heater **408**, cooling jacket **420** and heat exchanger **412**. The adsorption step **306** may be carried out for about 6 hours and the total time for depressurization, regeneration, bed cooling, and repressurization may be about 6 hours. During the adsorption
20 step **306** the gas residence time in the adsorbent bed is between about 0.1 and about 100 seconds, preferably between 0.5-2 seconds.

[0060] After the high pressure (330 bar) adsorption step **306** the bed **206** is depressurized to 1-20 atmospheres and preferably 1-2 atmospheres. Air or pressurized air **406** is then introduced and the structured adsorbent bed **206** is electrically heated to about
25 350°C with the heater **408** wrapped around the outside of the tube. An internal heater could also be used and it is also possible to preheat the air **406** in preheater **422** before it enters the bed **206**. The hot air **406** will calcine the oil adsorbed on the structured adsorbent, converting it to a gaseous CO₂ stream, and in some cases other gaseous products such as CO. The hot exit gas **416** leaves the adsorbent bed **206**, which is cooled by a heat exchanger **412** before
30 reaching the outlet valve **416b**. After calcination **308** the bed **206** is cooled and purged with nitrogen before repressurization with inlet gas **402**.

- 16 -

[0061] In one exemplary embodiment, the calcination process is designed so that a thermal or calcination wave advances through the structured adsorbent bed **206**. A thermal wave is taken to be a sharp temperature gradient or thermal front that moves through the contactor or adsorbent bed during the regeneration step. The speed at which the thermal front (i.e. region with sharp temperature gradient) moves is referred to as the velocity of the thermal wave which does not have to be constant. One exemplary method of introducing a thermal wave into a calcination process is to heat only the beginning of the bed **206** or contactor to a temperature such that a calcination reaction proceeds to remove adsorbed oil. This can be accomplished by passing hot air into the bed or contactor at a rate such that it rapidly transfers heat to the bed or contactor and thermally equilibrates with the mass of the bed or contactor. An alternative exemplary method includes externally heating only the adsorbent at the beginning of the bed **206**. Once the calcination reaction has ignited, the released heat is carried down the bed **206** or contactor allowing a sharp reaction front to proceed through the bed **206** or contactor. In this manner, the oil in the adsorbent calcines (e.g. burns) in a front. Such a front is similar in nature to the reaction front that passes through a lit cigar. Several different alternative regeneration methods may also be employed. These include thermally swinging the adsorbent bed **206** to desorb the oil as well as displacing the oil with a purge gas or washing media. It is possible to conduct the oil displacement at high pressures and in some designs the thermal desorption could occur at high pressure. In all cases the regeneration step **308** follows an adsorption step **306**.

[0062] Examples of structured adsorbent materials that may be used in the structured adsorbent bed **206** include high surface area (greater than about 10 square meters per gram (m^2/gm) and preferably greater than $75 \text{ m}^2/\text{gm}$) solids such as alumina titania or zirconia, microporous zeolites (preferably zeolites with particle sizes less than about 1 micron (μm)), other microporous materials, mesoporous materials, ordered mesoporous materials, and layered solids with intercalating properties such as clays, layered silicates and layered oxides. Non-limiting examples of these materials include carbons, activated carbons, charcoal, cationic zeolites, high silica zeolites, highly siliceous ordered mesoporous materials, sol gel materials, aluminophosphates (ALPO) materials (microporous and mesoporous materials containing predominantly aluminum phosphorous and oxygen), silicon aluminophosphates (SAPO) materials (microporous and mesoporous materials containing predominantly silicon aluminum phosphorous and oxygen), MOF materials (microporous and mesoporous

- 17 -

materials comprised of a metal organic framework) and ZIF materials (microporous and mesoporous materials comprised of zeolitic imidazolate frameworks).

[0063] In one preferred embodiment, the zeolites are highly siliceous having 12 or 14 and higher membered rings in their framework structure. Highly siliceous zeolites are taken to be zeolites with a silicon to aluminum (Si/Al) ratio greater than 50:1, preferably greater than 200:1. Examples of such high silica molecular sieves having 12 membered rings in their framework include: Zeolite beta, BEC (beta polymorph C), EMT (hex faujasite), IFR (MCM-58), IWR (ITQ-24), IWV (ITQ-27), IWW (ITQ-22), MEI (ZSM-18), MOR (mordenite), MOZ (ZSM-10), MSE (MCM-68), MTW (ZSM-12), SFE (SSZ-48), SFO (SSZ-51), SSY (SSZ-60), VET (VPI-8) and ITQ-21. Examples of high silica molecular sieves having 14 and higher membered rings include: ETR (EST-34, Ga-silicate), CFI (CIT-5), DON (UTD-1), SFH (SSZ-53), SFN (SSZ-59), and UTL (IM-12). Ordered mesoporous materials are for example: the M41S family - MCM-41, MCM-48, MCM-50; SBA materials -15, 16, -11, -1 and MSU. Ordered mesoporous materials of the M41S family are especially suitable for oil adsorption from gaseous streams. More specifically, highly siliceous MCM-41 materials with uniform cylindrical channels of 4-10 nm in diameter and specific surface area of 100-1,500 m²/g and the particle size in the range of 0.1-10 micron, preferably less than 1 micron, are expected to have favorable adsorption properties for oil vapor and droplets. Highly siliceous molecular sieves have an oil adsorption isotherm that is expected to be very strong at temperatures below about 100°C, even when the oil is carried in a gas stream at pressures in excess of about 300 bar.

[0064] In one preferred embodiment, the structured adsorbent bed 206 includes ordered mesoporous materials. Examples of ordered mesoporous materials include the M41S family of materials, SBA materials, MSU materials, and mesoporous materials derived from layered silicates such as kanemite, carbon replicas of mesoporous materials, and organo-inorganic mesoporous composites. A description of these types of ordered mesoporous materials is given in "Studies in Surface Science and Catalysis" Vol. 148 (Elsevier 2004), the portions of which providing examples of ordered mesoporous materials are hereby incorporated by reference.

[0065] In an exemplary embodiment, the adsorbent bed 206 contains a material selected from the M41S family of materials (e.g. MCM-41, MCM-48, and MCM-50). These materials are preferred because they are readily synthesized, are thermally stable to temperatures greater than 500°C, and contain well defined uniform pore sizes that can be

- 18 -

tailored in a range from about 20 to 100 angstroms (10^{-10} m). This thermal stability reduces the amount of degradation of the adsorbent during a calcination process that may be used to regenerate the adsorbent. The Si/Al ratio of the M41S family materials can be in a range from 5:1 to 100,000:1 (effectively aluminum free). It is preferred to use materials from the M41S family with a large Si/Al ratio (e.g. greater than about 200:1). Channel systems in these materials may be uni-dimensional (e.g. MCM-41) or three-dimensional (e.g. MCM-48). Materials with either uni-dimensional or three-dimensional channels can be used in the adsorbent bed **206**. The SBA materials (e.g., SBA -15, 16, -11, -1) are also thermally stable to temperatures greater than 500°C as well as MSU materials, and mesoporous material derived from layered silicates such as kanemite. Organo-inorganic mesoporous composites are less preferred when a high temperature calcination process is used to regenerate the adsorbent.

[0066] In another preferred embodiment, a low acidity microporous or mesoporous material such as alumina, high silica molecular sieves, and highly siliceous mesoporous materials may be used. One of the reasons that alumina, high silica molecular sieves, and highly siliceous mesoporous materials are preferred for use in a swing adsorption system **204** that removes oil is that they have low acidity and have less of a tendency to crack and coke adsorbed oil if the swing adsorption unit is heated during a thermal regeneration or calcinations step **308**.

[0067] It should be noted that the materials described above generally have pore sizes less than about 10 nm (100 Angstrom (Å)) and all of the materials have pore sizes greater than about 0.4 nm (4 Å). As such, it is preferred to conduct this process with a structured adsorbent material that has a pore structure in the 0.4 to 10 nm range. In one preferred embodiment, the pore structure for the adsorbent material is in 0.5 to 100 nm range and in an even more preferred embodiment the pore structure is in the 0.5 to 90 nm range. All of these adsorbent materials have a selectivity greater than 1 with respect to methane for heavy hydrocarbons (hydrocarbons containing more than two carbon atoms).

[0068] The swing adsorption unit **204** preferably contains an adsorbent bed **206** containing either beaded or pelletized adsorbent particles, a structured adsorbent formed as a parallel channel contactor, an adsorbent that is formed as a structured flow through adsorbent, or combinations of these. The physical architecture of the adsorbent bed or contactor **206** used depends on whether the contactor is internally heated or externally heated during the regeneration process. With internally heated beds or contactors, the gas or fluid

- 19 -

used to heat the contactor during the regeneration step directly contacts the adsorbent material. As such, the gas or fluid used to heat the bed or contactor during regeneration passes through the same macropore volume that the compressed gas stream **106** did during the adsorption step. The gas or fluid used to heat and regenerate the adsorbent can flow co-
5 current, counter-current or orthogonal (i.e., crossflow) to the direction that the compressed gas stream **106** flowed during the adsorption step. Externally heated contactors have a separate set of channels to carry gasses or fluids used to heat and cool the contactor **206**. In one preferable embodiment, the separate set of channels are sealed so that gasses used to heat and cool the contactor do not mix with the oil or reaction products liberated during the
10 regeneration step **308**.

[**0069**] In another preferred embodiment, the adsorbent bed **206** in the swing adsorption unit **204** is formed using a parallel channel (or parallel passage) contactor with a structured adsorbent. In a parallel channel contactor there exists at least one set of flow channels that are substantially parallel. The parallel channel (or parallel passage) contactor
15 with a structured adsorbent allows for efficient mass transfer with a minimum of pressure drop. Efficient mass transfer between the gas stream and the adsorbent is extremely important to remove low concentrations of oil. Approaches to constructing parallel passage contactors with structured adsorbents have been disclosed in US2006/0169142, US2006/0048648, WO2006/074343, WO2006/017940, WO2005/070518, and
20 WO2005/032694.

[**0070**] Non-limiting examples of geometric shapes of parallel channel contactors include various shaped monoliths having a plurality of substantially parallel channels extending from one end of the monolith to the other; a plurality of tubular members, stacked layers of adsorbent sheets with and without spacers between each sheet; multi-layered spiral
25 rolls, spiral wound adsorbent sheets, bundles of hollow fibers, as well as bundles of substantially parallel solid fibers. The adsorbent can be coated onto these geometric shapes or the shapes can, in many instances, be formed directly from the adsorbent material, or combinations of the adsorbent material, a binder, and a material that limits the temperature change from the heat of adsorption.

30 [**0071**] An example of a geometric shape formed directly from the adsorbent would be the extrusion of a zeolite/polymer composite into a monolith. Another example of a geometric shape formed directly from the adsorbent would be extruded or spun hollow fibers made from a zeolite/polymer composite. An example of a geometric shape that is coated

- 20 -

with the adsorbent is a thin flat steel sheet coated with a microporous, low mesopore, adsorbent film, such as a zeolite film. The directly formed or coated adsorbent layer can be itself structured into multiple layers of the same or different adsorbent materials. Multi-layered adsorbent sheet structures are taught in United States Patent Application Publication
5 No. 2006/0169142, which is incorporated herein by reference. When parallel plates are used to form the parallel channel, a spacer may be present in the space of the parallel channel. An example of a spacer-less parallel passage contactor is provided in US2004/0197596 and an example of a parallel passage contactor with a high density adsorbent structure is given in US2005/0129952.

10 [0072] The parallel channel contactor also contains either a mesoporous or microporous adsorbent that is used to remove oil. The parallel channel contactor also contains both mesopores and macropores resulting from space between particles (adsorbent, binder particles, and heat control particles or materials) used to form the contactor. Mesopores and macropores are known in the art to improve the mass transfer characteristics
15 of adsorbents used in either a parallel channel contactor or conventional packed bed contactors. Improvements in mass transfer characteristics from the presence of mesopores and macropores in conventional packed bed contactors have been widely discussed. *See*, for example U.S. Patent Nos. 6,436,171 and 6,284,021. Improvements in mass transfer characteristics from the presence of mesopores and macropores in parallel channel contactors
20 are discussed in EP1413348. The teaching in the field has been that a large number of mesopores and macropores are needed in an adsorbent particle or layer of adsorbent in order to have mass transfer characteristics good enough to operate a swing adsorption cycle. It is unexpected that adequate mass transfer characteristics can be attained without a significant amount of mesopores and/or macropores providing easy access to the micropore structure in
25 the adsorbent where selective separation occurs.

[0073] However, it has recently been discovered that it is possible to construct parallel channel contactors that have good mass transfer characteristics along with a low volume of mesopores and macropores, as disclosed in the following applications: PCT App. Nos. PCT/US2008/06071; PCT/US2008/06076; PCT/US2008/06068; PCT/US2008/06073;
30 and PCT/US2008/06067, which are hereby incorporated by reference.

[0074] The configuration of the structured adsorbent bed **206** also depends on the method used to regenerate the adsorbent. When the structured adsorbent is regenerated in a calcination or thermal swing process, heat may be supplied indirectly by a heater **408** or heat

- 21 -

may be directly supplied by flowing a gas or fluid **402** or **406** through a preheater **422** through the structured adsorbent bed **206** or by directly electrically heating (not shown) a structured adsorbent bed **206** (formulated with appropriate electrical conductivity). If heat is electrically supplied (externally or internally) it can be advantageous to segment the heating element to facilitate the passage of a thermal wave along the length of the structured adsorbent bed **206**. It is also possible to configure a parallel channel contactor with separate passages that allow heating and cooling fluids or gasses to flow so that they do not contact the adsorbent. For example, the parallel channel contactor can be configured like a shell and tube heat exchanger with the adsorbent coated on the tube walls of the heat exchanger. Another exemplary configuration includes a hollow fiber, spiral wound or monolithic contactor in the form of a membrane like module with an impermeable coating separating the heating and cooling passages from those carrying the gas being treated.

[0075] FIGs. 5A-5B illustrate exemplary embodiments of parallel channel contactor structured adsorbent bed designs for use in the system of FIGs. 2 and 4 and processes of FIG. 3. As such, FIGs. 5A-5B may be best understood with reference to FIGs. 2-4. FIG. 5A shows a monolithic parallel channel contactor **500A** in an isometric view **502A**, a cut-out view **502B**, and a detail view **502C**. The cylindrical monolith **500A** contains a plurality of parallel flow channels **504A-504X**. These flow channels **504A-504X** (which may be cumulatively referred to as flow channels **504**) can have diameters (channel gap) from about 5 to about 1,000 microns, preferably from about 50 to about 250 microns, as long as all channels **504** of a given contactor have substantially the same size channel gap. The channels can be formed having a variety of shapes including, but not limited to, round, square, triangular, and hexagonal. The space between the channels is occupied by the structured adsorbent **505**. As shown the channels **504** occupy about 25% of the volume of the monolith **500A** and the adsorbent **505** occupies about 75% of the volume of the monolith **500A**. The adsorbent **505** can occupy from about 50% to about 98% of the volume of the monolith **500A**. Adsorbent layer **506** thickness can also vary. For example, when the channel diameter is in a range from about 50 to about 250 microns it is preferred that the thickness of the adsorbent layer **506**, in the case wherein the entire contactor is not comprised of the adsorbent, be in a range from about 25 to about 2,500 microns. For a 50 micron diameter channel, the preferred range of thickness for the adsorbent layer **506** is from about 25 to about 300 microns, more preferred range from about 50 to about 250 microns.

- 22 -

[0076] The cross-sectional view **502B** along the longitudinal axis showing feed channels **504** extending through the length of the monolith with the walls of the flow channels **504** formed entirely from adsorbent **505** plus binder. The cross section view **502C** shows the adsorbent layer **506** comprised of solid adsorbent (e.g. microporous or mesoporous) particles **510A-510X (510)** and solid particles (thermal mass) **508A-508X (508)** that act as heat sinks. The adsorbent layer **506** may further include a blocking agent (not shown) and open meso and micropores **512A-512X (512)** between the particles **510** and **508**. As shown, the microporous adsorbent particles **510** occupy about 60% of the volume of the adsorbent layer **506** and the particles of thermal mass **508** occupy about 5% of the volume. With this composition, the voidage (e.g. flow channels) is about 55% of the volume occupied by the microporous adsorbent particles **510**. The volume of the adsorbent **510** (e.g. microporous or meosporous) can range from about 25% of the volume of the adsorbent layer **506** to about 98% of the volume of the adsorbent layer **506**. In practice, the volume fraction of solid particles **508** used to control heat will range from about 0% to about 75%, preferably about 5% to about 75%, and more preferably from about 10% to about 60% of the volume of the adsorbent layer **506**. A blocking agent fills the desired amount of space or voids left between particles **508** and **510** so that the volume fraction of open mesopores and macropores **512** in the adsorbent layer **506** is less than about 20%.

[0077] FIG. 5B shows an alternative exemplary embodiment of a monolithic parallel channel contactor **500B** in an isometric view **502A**, a cut-out view **502B**, and a detail view **502C**. The contactor **500B** is a structured flow through adsorbent contactor having parallel channels **504A-504X (504)** similar to the contactor **500A**, but wherein alternate channels are closed at one end by a plug **503A-503X (503)**. The flow pattern **507** through the monolith **500B** is similar to that of a monolithic soot filter often used in the automotive industry. Gas entering the open flow channels **504** flows through the adsorbent layer **506** via the pores **512** and exits through an adjacent channel **503**.

[0078] The structured flow through adsorbent contactor **500B** provides highly efficient mass transfer but is generally constructed with greater pressure drop than a parallel channel contactor **500A**. This extremely efficient mass transfer between the gas stream **507** and the adsorbent **505** can be important in removing oil down to low concentrations. For many compressor oils it is possible to drop the oil concentration in the purified stream **208**

- 23 -

coming out of the contactor to less than 10 ppm by weight and preferable less than 10 ppb by weight.

[0079] When the monolith **500A** or **500B** is used in a gas separation process that relies on a kinetic separation (e.g. process **300**) it is advantageous for the microporous adsorbent particles **510** to be substantially the same size. It is preferred that the standard deviation of the volume of the individual microporous adsorbent particles **510** be less than 100% of the average particle volume for kinetically controlled processes. In a more preferred embodiment the standard deviation of the volume of the individual microporous adsorbent particles **510** is less than 50% of the average particle volume. The particle size distribution for zeolite adsorbents can be controlled by the method used to synthesize the particles. It is also possible to separate pre-synthesized microporous adsorbent particles by size using methods such as a gravitational settling column. It may also be advantageous to use uniformly sized microporous adsorbent or polymeric particles in equilibrium controlled separations.

[0080] Monoliths **500A** and **500B** may be formed, for example, directly from structured microporous or mesoporous adsorbents **505**. If the microporous or mesoporous adsorbent **505** is a zeolite, for example, the monolith can be prepared by extruding an aqueous mixture containing effective amounts of a solid binder, zeolite and adsorbent, solid heat control particles, and polymer. The solid binder can be colloidal sized silica or alumina that is used to bind the zeolite and solid heat control particles together. The effective amount of solid binder will typically range from about 0.5 to about 50% of the volume of the zeolite and solid heat control particles used in the mixture. If desired, silica binder materials can be converted in a post processing step to zeolites using hydrothermal synthesis techniques and, as such, they are not always present in a finished monolith. A polymer is optionally added to the mixture for rheology control and to give greater extrudate strength. The extruded monolith **500** is cured by firing it in a kiln where the water evaporates and the polymer burns away, thereby resulting in a monolith of desired composition. After curing the monolith **500**, the adsorbent layer **506** will have only about 20 to about 40 vol% mesopores and macropores. A predetermined amount of these pores can be filled with a blocking agent in a subsequent step such as by vacuum impregnation.

[0081] Another method by which a monolith **500** can be formed directly from a microporous or mesoporous adsorbent **505** is by extruding a polymer and microporous adsorbent mixture. Preferred microporous adsorbents for use in extrusion processes are

- 24 -

carbon molecular sieves and zeolites. Non-limiting examples of polymers suitable for the extrusion process include epoxies, thermoplastics, and curable polymers such as silicone rubbers that can be extruded without an added solvent. When these polymers are used in the extrusion process, the resulting product will preferably have a low volume fraction of meso and macropores in the adsorbent layer.

[0082] FIG. 6 is an illustration of an exemplary segmented contactor, which may be used in combination with the adsorbent beds as disclosed in FIGs. 2 and 5A-5B. As such, FIG. 6 may be best understood with reference to FIGs. 2 and 5A-5B. The segmented contactor **600** includes a tubular housing **602** for containing multiple adsorbent beds **606A-606D**, which are separated by seals **604A-604E**. The seals **604A-604E** prevent flow from bypassing the contactors **606A-606D**, which may be selected from any combination of the contactors **500A-500B**. For example, contactor **606A** may be a parallel channel monolithic contactor **500A** and contactors **606B-606D** are structured flow through adsorbent contactors **500B**. In another example, one or all of the contactors **606A-606D** may be a flow through adsorbent.

[0083] The segmented contactor arrangement **600** is configured to beneficially mitigate the effect of variances in the size of flow channels **504** in parallel channel contactors **500A** or **500B**. In the segmented contactor **600** gas flowing out of one parallel channel contactor **606A** enters the next contactor **606B**. Besides mitigating the effect of variances in channel size, this arrangement allows the use of different adsorbent materials in different contactors **606A-606D**. Utilizing multiple adsorbent materials can be advantageous to ensure optimum removal of oil by removing species that interfere with oil adsorption as well as allowing for use of adsorbents with different pore sizes to optimally remove different molecular weight oil molecules. The seals **604A-604E** may be made from a sealing material such as graphite. Such a segmented arrangement also mitigates the effect of stress built-up from thermal expansion if the swing adsorption unit **204** is regenerated in a thermal swing or calcination process.

[0084] In a preferred embodiment, the swing adsorption unit contains both segmented parallel channel contactors and flow through adsorbents. This embodiment offers excellent contacting properties without introducing significantly larger pressure drops (e.g. greater than 200 psi) through the swing adsorption unit **204**.

- 25 -

EXAMPLES

[0085] Example 1: Example of fuel gas composition that will not condense in the seals.

5 [0086] Sources of seal gas can include any convenient extraction point in a gas production or treating process, such as at compressor discharge, as long as the discharge pressure is greater than the suction pressure of the compressor being sealed (i.e., the pressure needed to form a dry gas seal in a compressor). When the pressure of the gas is lowered (e.g., throttling across the seal), the temperature can drop such that some of the seal gas condenses.

10 [0087] FIG. 7 illustrates an exemplary graph comparing the phase envelopes of a treated seal gas and an untreated seal gas. The graph 700 relates pressure 702 in bar absolute (bara) and enthalpy 704 in kilo-calories per kilogram moles (kcal/kg·mol). A phase envelope of an untreated gas 706 is shown along with line 708 indicating an isenthalpic throttling of the untreated gas 706 across the seal. The exemplary seal gas 706 is taken from compressor
15 discharge at 388 bara and has a composition similar to the following:

- 26 -

Component	Mol fraction
N2	0.0108
H2S	0.1622
CO2	0.0324
Methane	0.5932
Ethane	0.1084
Propane	0.0579
i-Butane	0.0081
n-Butane	0.0157
i-Pentane	0.0041
n-Pentane	0.0037
n-Hexane	0.0019
n-Heptane	0.0007
COS	0.0001
M-Mercaptan	0.0002
NBP[O]116	0.0003
NBP[O]135	0.0001

[0088] As shown in the graph **700**, when the pressure reaches about 70 bara, some components of the gas begin to condense (e.g., the gas reaches its dewpoint as indicated by the phase envelope **706**). This “two-phase region” is circled by oval **710**. Further expansion causes more of the gas to condense. Formation of these condensed liquids could damage the seal. To alleviate this problem, certain components of the seal gas are removed (e.g., 95% of the H₂S, 90% of C₅+) resulting in a treated gas having a treated gas phase envelope **712** with a complimentary line **714** denoting isenthalpic throttling of the treated gas **712** across the seal. As shown, in the treated case, the gas **712** does not enter the two phase region upon throttling, thus ensuring that seal gas remains “dry”. To achieve this result, the adsorbent material selectively removed the H₂S and the C₅+ material, and enriched the stream in methane. To achieve this result the selectivity for the H₂S with respect to methane must be greater than 5 and the selectivity of the C₅+ components with respect to methane must be greater than 5.

[0089] Example 2: The shape of the adsorption front that moves through a parallel channel contactor **500A** during the oil adsorption step is modeled. This modeling used a competitive Langmuir isotherm to predict the loading of oil in the adsorbent **505**. For the targeted adsorbents, the adsorption strength (e.g. selectivity) of the oil is expected to be so large that a sharp or shock wave like adsorption front moves through the contactor **500A**.

- 27 -

This type of behavior allows the adsorbent volume in the contactor **500A** to be used efficiently, minimizing the adsorbent volume required and maximizing the length of an adsorption cycle.

[0090] This model simulates a single channel **504A** of a solid adsorbent **506** without open mesoporous voids, open macropores, or heat adsorbing material. Due to symmetry it is sufficient to model a single channel **504A**. The modeling follows an oil adsorption front that moves through the contactor **500A** in an adsorption step **306** that follows after a calcination step **308**. After the calcination step **308**, all oil has been removed from the adsorbent layer **506**. At this point, the fugacity in the channel **504A** is near 1 bara, and the channel **504A** is filled with air. Air is purged from the channel **504A** with nitrogen and the channel **504A** is then pressurized with a fuel gas containing oil vapor (e.g. fuel gas stream **106**). For the simulation, the vapor fugacity of the oil is taken to be 6×10^{-5} bar, and the total fugacity of the fuel gas **106** at the entrance to the channel **504A** at the end of the pressurization step is 300 bara. The total time to pressurize the 5 μm channel **504A** used in the simulation is 1.04 seconds. When the pressurization is completed and the channel fugacity drop along channel **504A** reaches 3.2 bar/m, fuel gas is allowed to flow through the channel **504A** with a superficial velocity of 0.091 meters per second (m/s) at 373 Kelvin (K). At this flow rate, the 0.012 centipoise (cP) fuel gas **106** has the same fugacity drop along the channel **504A** as that at the end of the pressurization step of 3.2 bar/m. In the simulation, the adsorbent thickness is taken to be 3 μm and the channel length is taken to be 1 m. The model is based on the actual parallel channel contactor, and is suitably scaled to capture the transport phenomena occurring in the full system **204**.

[0091] The oil adsorption from the flowing gas stream is described with a linear driving force model (LDF) that employs a competitive Langmuir adsorption isotherm. The product of the Langmuir adsorption coefficient (b_{oil}) and fugacity (P_{oil}) for oil was taken to be 4, corresponding to adsorption in the non-linear region of the isotherm. The Langmuir adsorption coefficient (b_{gas}) for the fuel gas ($3.89 \times 10^{-7} \text{ Pa}^{-1}$) was based on representative values for methane adsorption in mesoporous adsorbents such as the M41S family of materials. For many oils in several different mesoporous adsorbents the Langmuir adsorption coefficients ("b values") are expected to be greater than that used in this simulation. A larger b value will lead to an even sharper adsorption front than those modeled in this example. The characteristic time scale for adsorption defined by the LDF constant of 0.1 seconds is chosen to match the physical properties expected for the mesoporous adsorbent layer. As such, the

- 28 -

LDF time constant is much smaller than the gas residence time in the flow channel. Because of the small channel dimension (5 μm) the model is justified in neglecting axial dispersion of the gas within the channel. Because of the high gas fugacity and low oil concentrations (Oil Mole Fraction = 2×10^{-7}) the heat capacity of the fuel gas limits the temperature rise and the adsorption process can be modeled as isothermal.

[0092] FIG. 8 illustrates an exemplary graph of an oil front advancing through an adsorbent channel based on modeling of the Langmuir isotherm. The graph **800** plots oil pressure (P_{oil}) **802** in bar versus length **804** in meters. The simulation takes place over a 50,000 second time frame. The oil fronts **806**, **808**, **810**, **812** and **814** represent fugacity profiles at times of 0, 12,500, 25,000, 37,500 and 50,000 seconds, respectively. As shown, the oil fugacity profiles form a sharp adsorption front within about 0.08 m of the adsorbent bed inlet. The oil fugacity measured in the channel at a point immediately past the adsorption front suggests that greater than 99.99999 percent of the oil has been removed from the feed. This also suggests that the product exiting the channel outlet is essentially pure fuel gas for long periods of time extending past the time simulated above. This behavior will remain the same at lower oil partial fugacities. Simulations performed using thicker adsorbent beds suggest that the propagation of the oil adsorption front will be further restricted to an even smaller region of the bed close to the inlet. If an oil mist (i.e. liquid and vapor) is present, a sharp front still advances through the channel, but because of the increased oil concentration, proceeds further along the channel than shown in graph **800**. For the results described, the selectivity of the adsorbent with respect to methane must be greater than 10 and preferable greater than 100, and even more preferable greater than 1000.

[0093] Example 3: To establish conditions under which oil could be calcined, a 2 gram sample of mesoporous MCM-41 zeolite was loaded with about a 1,900 gram/mole polyglycol compressor oil. The zeolites were loaded by contacting the MCM-41 zeolite with the polyglycol oil in an amount close to incipient wetness. This required approximately 0.24 grams of oil. To further reduce the amount of oil that is not adsorbed in the zeolite the samples were placed in a vacuum oven and held at 125°C for 12 hours at a pressure of less than 1 millimeter of mercury (mmHg) – about 0.00133 bar. When the samples were removed from the vacuum oven the amount of oil adsorbed was found to be greater than 10 wt% of the sample mass. To measure the rate at which this oil can be removed by calcination, thermogravimetric (TGA) experiments were performed. The batch of oil containing MCM-41 material was divided into about 2 to about 25 milligram (mg) samples that were

- 29 -

repetitively placed in the TGA. The TGA was operated with air and each sample was allowed to sit for more than 1 hour at 125°C after being introduced into the TGA on a platinum pan whose weight was known. For each sample, the temperature was then stepped up to the temperature where calcination was to be studied and the rate of weight loss recorded. Each sample was held at the calcination temperature for more than 30 minutes and then the temperature was increased to a final temperature greater than 550°C. At temperatures as low as 300°C all of the oil burned or calcined off in less than 1 minute. This was approximately the amount of time required to heat the sample to the calcination temperature. These rapid kinetics and complete removal of oil were seen in experiments where the calcination temperature was 325, 350, 375, 400 and 450°C. At temperatures between 225 and 275°C a slower but steady loss of oil due to calcination was observed. To prove that this weight loss was due to calcination the TGA protocol was repeated using nitrogen rather than air. With nitrogen, very slow weight losses with time constants in the hour to several day range were recorded. As might be expected the rate of weight loss increased with increasing temperature.

[0094] Example 4: This example illustrates a contactor that removes about 2 gram / minute of compressor oil from about a 5 MMSCFD fuel gas that has been compressed to 330 bara. When the stream is discharged from the compressor it is at a temperature between 85 and 115°C. The fuel gas has the composition shown in the table below. When the fuel gas is fed into dry seals at a temperature near that at which it is discharged from the compressor it will not enter a 2 phase region as it expands across the seal faces. The only liquid that appears as the gas expands across the seal faces comes from the compressor oil. In this example, the compressor oil is a polyglycol with a number average molecular weight of 1,900 gram/mole.

- 30 -

Molecular Component	Mole %
H ₂ O	0.0006
N ₂	1.4644
H ₂ S	0.0001
CO ₂	0.0004
Methane	80.5117
Ethane	14.6952
Propane	3.1856
i-Butane (C ₄)	0.0650
n-Butane (C ₄)	0.0691
i-Pentane	0.0040
n-Pentane	0.0020
n-Hexane	0.0002
n-Heptane	0.0018

[0095] Monolithic parallel channel contactors of the type shown in Figures 5A and 5B are used to remove oil from the compressed fuel gas stream. In one exemplary system, a total of six about 40 cm long monolithic parallel channel contactors are stacked inside a 2.5 meter long, 3 inch diameter tube. In this example, three of each contactor style are stacked within the tubes. The contactors are held in place within the tube with either a ceramic packing material or with pyrolytic graphite gaskets. The monoliths are formed from alumina bound MCM-41 zeolite and the six monoliths contain a total of 10 kilograms of MCM-41. Size of the individual MCM-41 particles is 1 micron. The amount of zeolite needed in each tube is sized by measurements at lower pressures of the adsorption capacity for saturated oil vapor in MCM-41 samples. These measurements show that MCM-41 is capable of adsorbing about 15 wt% of saturated oil vapor and / or liquid droplets of about 1900 molecular weight oil at temperatures of about 100°C. At high pressure conditions, similar adsorption capacities are expected and a square oil adsorption isotherm is still predicted (i.e. a very high b value for a Langmuir Isotherm).

[0096] Flow channels in the monoliths are 500 micron in diameter and occupy 10-30% of the crosssectional area of the monoliths. The 5 MMSCFD fuel gas flow is split between four 2.5 meter long tubes and the adsorption step is carried out for 12 hours. At the end of a 12 hour adsorption step the oil adsorption front has not broken through to the end of the tubes. When the adsorption step is completed four other tubes that have finished regeneration **308** are valved on-line to continue removing oil (i.e. they start the adsorption step **306**). The four tubes that have been undergoing an adsorption step are regenerated **308**. The tubes are regenerated by depressurizing them to 4 atmospheres (about 4 bar) and

- 31 -

beginning to flow compressed air that has been heated to 325°C through the tubes. Air flow rate in each tube during this phase of the regeneration process is between 1 and 50 SCFM, and the hot air is flowed for a time between 5 and 40 minutes at which point the front of the first monolith has heated-up to the point that a calcination reaction has been initiated. Heat released from the calcination reaction can be in a range from 1-20 kilowatts. To limit the temperature rise as the calcination reaction proceeds, long duration pulses of nitrogen are introduced. The duration of the nitrogen pulses can be 2-50 times longer than the air pulses. The calcination process is completed in less than 6 hours and the tubes are cooled for 4 hours by flowing either compressed air or pressurized nitrogen through them before another adsorption step is begun.

[0097] While the present invention may be susceptible to various modifications and alternative forms, the exemplary embodiments discussed above have been shown only by way of example. However, it should again be understood that the invention is not intended to be limited to the particular embodiments disclosed herein. Indeed, the present invention includes all alternatives, modifications, and equivalents falling within the true spirit and scope of the appended claims.

CLAIMS

1. A system for treating a gaseous feed stream, comprising: a selective component removal system, comprising: a gaseous feed stream inlet configured to pass a gaseous feed stream into a swing adsorption unit having at least one
5 structured adsorbent bed comprising a high surface area solid, the high surface area solid being selected from the group consisting of aluminas, carbons, activated carbon, charcoal, cationic zeolites, high silica zeolites, highly siliceous ordered mesoporous materials, sol gel materials, ALPO materials (microporous and mesoporous materials containing predominantly aluminum phosphorous and
10 oxygen), SAPO materials (microporous and mesoporous materials containing predominantly silicon aluminum phosphorous and oxygen), MOF materials (microporous and mesoporous materials comprised of a metal organic framework) and ZIF materials (microporous and mesoporous materials comprised of zeolitic imidazolate frameworks), wherein:
- 15 the gaseous feed stream includes a volume of oil droplets and a volume of oil vapor and has a pressure of at least about 1,000 pounds per square inch;
- the at least one structured adsorbent bed is configured to remove at least a portion of the volume of oil droplets and a portion of the volume of oil vapor to provide a substantially oil-free gaseous outlet stream; and
- 20 the at least one structured adsorbent bed is regenerated in a kinetic swing adsorption process.
2. The system of claim 1, wherein the kinetic swing adsorption process is selected from the group consisting of a calcination process, a temperature swing process, a pressure swing process, an inert purge process, and any combination
25 thereof.
3. The system of claim 1 or 2, wherein the system is configured to remove the volume of oil droplets and vapor in a sharp adsorption front as modeled by a Langmuir isotherm.

4. The system of any one of claims 1 to 3, wherein the at least one structured adsorbent bed is regenerated by raising the temperature of the structured adsorbent bed to at least about 250°C.
5. The system of any one of claims 1 to 3, wherein the structured adsorbent bed is regenerated by a thermal wave process.
6. The system of any one of claims 1 to 3, wherein the structured adsorbent bed is regenerated by a gas or fluid flowed co-currently, counter-currently, or orthogonally (e.g. crossflow) to a flow direction of the gaseous feed stream.
7. The system of any one of the preceding claims, further comprising a fluid impermeable housing substantially surrounding the swing adsorption unit.
8. The system of claim 7, wherein the fluid impermeable housing is operable at up to about 10,000 pounds per square inch.
9. The system of any one of the preceding claims, wherein the structured adsorbent bed is selected from the group consisting of a parallel channel contactor, a structured flow through adsorbent contactor, a flow through adsorbent, and any combination thereof.
10. The system of claim 9, further comprising a segmented contactor configured to house at least two structured adsorbent beds, wherein each pair of structured adsorbent beds is separated by a seal.
11. The system of any one of the preceding claims, wherein the oil is a substantially ash-free oil.
12. The system of any one of the preceding claims, wherein the oil is a synthetic composed of a random copolymer of ethylene oxide and propylene oxide.

13. The system of claim 12, wherein the random copolymer of ethylene oxide and propylene oxide has an average molecular weight greater than about 1,200 gram/mole and less than or equal to about 2,500 gram/mole.
14. The system of any one of the preceding claims, further comprising a cooling jacket operatively engaging the at least one structured adsorbent bed.
15. The system of any one of claims 2 to 14, further comprising a heater selected from the group consisting of an indirect electric adsorbent bed heater, a direct electric adsorbent bed heater, a direct gas heating fluid, and any combination thereof.
16. The system of any one of the preceding claims, further comprising a heat exchanger configured to utilize cooling fluid to cool the substantially oil-free gaseous outlet stream.
17. The system of any one of the preceding claims, further comprising an accumulator configured to hold the substantially oil-free gaseous outlet stream.
18. The system of any one of the preceding claims, wherein the high surface area solid has a surface area greater than about 10 square meters per gram (m^2/gm).
19. The system of any one of claims 3 to 18, wherein greater than 99.99999 percent of the oil is removed from the gaseous feed stream.
20. The system of any one of the preceding claims, wherein the high surface area solid is a 12-14 ring zeolite with a Si to Al ratio of more than about 50:1.
21. The system of any one of the preceding claims, wherein the high surface area solid is an ordered mesoporous material of the M41S family.
22. The system of any one of the preceding claims, further comprising a conditioning unit.

23. A method of treating a gaseous feed stream, comprising:
providing a gaseous feed stream having a volume of oil therein;
treating a portion of the gaseous feed stream using a selective component
removal system having at least one swing adsorption process unit to form a utility
5 stream for use in a utility component, wherein the at least one swing adsorption
process unit includes a structured adsorbent bed comprising a high surface area
solid, the high surface area solid being selected from the group consisting of
aluminas, carbons, activated carbon, charcoal, cationic zeolites, high silica
zeolites, highly siliceous ordered mesoporous materials, sol gel materials, ALPO
10 materials (microporous and mesoporous materials containing predominantly
aluminum phosphorous and oxygen), SAPO materials (microporous and
mesoporous materials containing predominantly silicon aluminum phosphorous
and oxygen), MOF materials (microporous and mesoporous materials comprised
of a metal organic framework) and ZIF materials (microporous and mesoporous
15 materials comprised of zeolitic imidazolate frameworks) and configured to remove
at least a portion of the volume of oil;
regenerating the swing adsorption process unit in a calcination process;
feeding the utility stream into the utility component, wherein the utility
stream is compatible with the utility component and wherein the utility stream is a
20 dry seal gas; and
utilizing the utility stream in the utility component.
24. The method of claim 23, wherein the gaseous feed stream contains at
least one hydrocarbon component.
25. The method of claim 23, wherein the gaseous feed stream is a compressor
25 discharge stream.
26. The method of claim 23, wherein the gaseous feed stream is a high
pressure process stream.
27. The method of any one of claims 23-26, wherein the gaseous feed stream
is at a pressure above the critical point of the gaseous feed stream.

28. The method of claim 26, wherein the gaseous feed stream is at a pressure of from at least about 100 bar to at least about 500 bar.

29. The method of claim 26, wherein the gaseous feed stream is at a pressure of from at least about 200 bar to at least about 320 bar.

5 30. The method of any one of claims 23-29, wherein the utility component is selected from the group consisting of a compressor, a compressor string, a turbo-expander compressor, a turbo-expander generator, a pump, a fired steam boiler, a fired process heater, a gas engine, a hermetically sealed direct-drive electric motor, turbomachinery equipped with magnetic bearings, and a gas turbine.

10 31. The method of claim 30, wherein the utility stream is utilized as a dry seal gas for at least one of a dry gas seal, a labyrinth seal, and a mechanical seal in the at least one utility component.

32. The method of claim 31, wherein the at least one swing adsorption process unit is selected from the group of units consisting of a pressure swing adsorption
15 (PSA) unit, a thermal swing adsorption (TSA) unit, a partial pressure swing or displacement purge adsorption (PPSA) unit, a rapid cycle thermal swing adsorption (RCTSA) unit, a rapid cycle pressure swing adsorption (RCPSA) unit, a rapid cycle partial pressure swing or displacement purge adsorption (RCPPSA) unit, a compact PSA, a compact TSA, a compact PPSA, and any combination
20 thereof.

33. The method of claim 32, wherein the selective component removal system (SCRS) further comprises at least one of an absorption unit, a membrane separation unit, a molecular sieve, a distillation tower, and a glycol contactor.

34. The system of any one of claims 1 to 21, wherein the structured adsorbent
25 bed comprises:
an inlet end;
an outlet end; and

a plurality of open flow channels extending from the inlet end to the outlet end, wherein a portion of the plurality of open flow channels are sealed at the inlet end and the remainder of the plurality of flow channels are sealed at the outlet end, and wherein the surface of the open flow channels are comprised of a structured adsorbent material having a selectivity for a first component of a mixture over a second component of the mixture greater than one.

35. The system of claim 9 or 10, wherein the contactor has less than about 20 volume percent of its open pore volume in pores with diameters greater than about 20 angstroms and less than about one micron.
- 10 36. The system of claim 34 or 35, wherein the adsorbent material has a selectivity for oil over CH₄ greater than about 10.
37. The system of any one of claims 1 to 23 or 34 to 36 wherein the structured microporous adsorbent is a zeolite selected from the group consisting of MFI, faujasite, and Beta.
- 15 38. The system of claim 37, wherein the structured mesoporous adsorbent is selected from the M41S family.
39. The system of claim 38, wherein the structured microporous adsorbent is an 12-14 ring zeolite with a Si to Al ratio of more than about 50:1.