

CLAIMS

What is claimed is:

1. A method of attaching a fabric material to a cable comprising the steps of positioning an adhesive on opposed layers of fabric, positioning a cable between the layers, and attaching the adhesive of one layer to the adhesive of the other layer to confine the cable between the layers.
2. The method of claim 1 whereon the adhesive is positioned on generally the entire surface of each layer of fabric, and said step of attaching includes the step of attaching the layers to the cable.
3. The method of claim 2 wherein said step of attaching includes the step of forming wings on opposed sides of the cable.
4. The method of claim 3 wherein the step of forming wings is accomplished by attaching the lateral edges of the layers of fabric to each other.
5. The method of claim 1 wherein the adhesive is positioned at the lateral edges of the layers of fabric, and said step of attaching includes the step of attaching the lateral edges of the layers of fabric to each other.
6. The method of claim 5 wherein said step of attaching forms wings on opposed sides of the cable.
7. The method of claim 1 further comprising the step of forming the layers by folding a single sheet of fabric material.
8. The method of claim 7 wherein the adhesive is positioned on the lateral edges of the sheet of fabric material.

9. The method of claim 8 further comprising the step positioning a release strip on the adhesive at each lateral edge of the sheet.
10. The method of claim 9 wherein said step of positioning a cable is accomplished by moving the cable between the lateral edges of the sheet.
11. The method of claim 10 further comprising the step of removing the release strips after the cable has been positioned between the lateral edges of the sheet, and thereafter performing attaching step.
12. An apparatus to be inserted into a longitudinally extending conduit comprising a cable, and a fabric encasing said cable and forming at least one wing extending outwardly from said cable .
13. The apparatus of claim 12 wherein two wings extend outwardly from the cable at generally diametrically opposite positions.