

INVISIBLE SETTING AND METHODS AND TOOLS FOR EFFECTING SAME

FIELD AND BACKGROUND OF THE INVENTION

The present invention, in some embodiments thereof, relates to an invisible
5 setting for diamonds and other precious stones that are faceted, and methods and tools
for effecting such settings.

Invisible settings have been around for many years and have been very
successful. The traditional invisible mounting involves fitting a protrusion of the
setting, or mounting medium into a groove pre-formed in the stone. The groove is
10 hidden behind the face of the stone, hence the face hiding the mounting, which therefore
becomes invisible. The setting or mounting medium may be the metal body of the ring
or other jewelry item.

A well-known problem with invisible mountings is the ease with which the
stone is able to fall out of the mounting. The setting can often change shape over time.
15 The finger on which the ring is mounted may change shape over time, or the metal may
expand or contract with changes in temperature, so that what began as a tight fit may
get looser over time until the stone falls out. Where multiple stones are mounted in a
row, if the setting bends in a particular direction all of the stones are liable to fall out.

A further issue with invisible settings is the time and skilled labor required to set
20 a stone, or replace a stone after it falls out. A tight fit is required by making a secure
mounting at a location that cannot be seen, and the stones themselves are generally quite
small. Setting a single stone typically takes in excess of twenty minutes in the hands of
a skilled setter.

US 6,112,552 teaches an invisible gemstone setting having channels into which
25 the grooved gemstones are snapped and secured. Each channel is provided with
opposing flexible prong members extending from the base of the gemstone setting. As
the grooved gemstones are snapped into the channels the prong members flex outwardly
as the gemstones are pushed downwards into the channels. The prong members snap
into engagement with the gemstones to securely hold the gemstones within the
30 channels. When the channels are filled the setting becomes invisible.

Again, the gemstone is more easily mounted but the same problem arises that if
the setting changes shape, the initially firm grip on the gemstone is liable to be lost.

Current invisible setting technologies allow setting of hard stones into semi-hard metal mountings, and are practically limited to setting of diamonds in gold. Use of softer stones or softer or harder metals result in breakage of the stone during setting (e.g., when the stone is soft and the metal hard) and/or falling off of the stone during use (e.g., when the metal is soft and readily distorts).

SUMMARY OF THE INVENTION

The present embodiments provide a separate mounting for holding the grooved gemstone, which separate mounting is held within but is not part of the gemstone setting. Thus changes in shape in the setting have no bearing on how firmly the gemstone is held. The jewelry setting no longer needs to include the protrusion for fitting into the gemstone groove, as this is now part of the separate mounting. Instead however the setting may incorporate hollows or openings for holding the mountings.

According to an aspect of some embodiments of the present invention there is provided a mounting for holding a grooved gemstone invisibly to a setting, the mounting having a first end with extensions to receive the gemstone and protrusions extending inwardly from the extensions to fit within respective mounting grooves of the grooved gemstone, the mounting further comprising a holding configuration for lockingly holding the mounting to the setting.

The holding configuration may be designed to undergo distortion when fitting into the setting, the distortion lockingly holding the respective mounting to the setting.

In an embodiment, the holding configuration is connected to the extensions to press the protrusions inwardly onto the groove when the holding configuration is distorted against contouring of the setting.

In an embodiment, the mounting is configured to be deformed upon pulling inwardly about contouring on the setting, the deformation being such as to lever the extensions to push the protrusion inwardly into the groove.

In an embodiment, the holding configuration is configured to protrude at least partially from a base part of the setting, the holding configuration being deformable about the setting by a deformation tool applied to the second end to catch the mounting into the setting and to lever the protrusions into the groove.

In an embodiment, the holding configuration is configured to protrude at least partially from a base part of the setting, the holding configuration comprising a

breakable portion that deforms the mounting prior to being broken away therefrom, to catch the mounting into the setting and to lever the protrusions into the groove.

In an embodiment, the breakable portion is designed to be broken off using a shaped mounting tool.

5 The holding configuration may include a weakened portion for preferential deformation when being mounted.

The mounting may simultaneously close over the grooved gemstone and deform into the setting with a single application of force.

10 The mounting may include a concave base portion flattenable to provide the deformation.

Flattening may be provided by a breakable portion attached to the base portion.

15 Flattening may be provided by a tool inserted via a hole into the base portion, or the tool may be a threaded tool designed to thread around a screw end at the base, or the tool may be an insertion tool that forces the base to open along a weakening or gap. The mounting extensions may be resilient.

20 According to a second aspect of the present embodiments a setting for gemstones may be provided which comprises a plurality of locations for holding respective gemstone mountings, each location being shaped to close upper protrusions of the mounting into a groove of a grooved gemstone to hold the gemstone to the setting. The closing may be achieved by deforming the respective mounting as it is pressed into position in the setting.

In an embodiment, the setting may be contoured to push upper parts of respective mountings inwardly to lock onto the groove when the setting is pushed downwardly into the location.

25 The respective shapes built into the setting may be open at a lower end to allow a deformable or breakable holding portion of the mounting to extend from the lower end for the deformation or breakage causing the deformation.

The setting may be provided with a tool to carry out the deformation or breakage causing the deformation.

30 A protective rim may extend around the outside of the setting. The material of the setting may be a soft metal such as silver or brass.

According to a third aspect of the present invention there is provided a method of mounting a grooved gemstone to a setting comprising:

providing a setting having a mounting location.

providing a mounting, the mounting having arms and protrusions at a distal end of the arms to fit into grooves of the grooved gemstone.

pressing the mounting into the mounting space, the pressing causing contouring on the mounting location to press the arms inwardly to lock the protrusions into the grooves, thereby mounting the gemstone.

The method of the present embodiments may be carried out by a robot arm.

According to a fourth aspect of the present invention there is provided a mounting for invisible placing of a grooved gemstone within a setting, the mounting being separate and distinct from both the setting and the gemstone and having both a setting attachment for attachment to the setting and a gemstone attachment for attaching a gemstone.

According to a fifth aspect of the present invention there is provided a method of mounting a flawed gemstone to a setting comprising:

providing a gemstone having grooves and flaws in proximity to the grooves;

providing a setting having a mounting space.

providing a mounting, the mounting having arms and protrusions at a distal end of the arms to fit into grooves of the grooved gemstone.

pressing the mounting into the mounting space, the pressing causing contouring on the mounting space to press the arms inwardly to lock the protrusions into the grooves, thereby mounting the gemstone via inward pressure on a body of the gemstone and not relying on structural resilience of the flaws.

The flaw may be an inclusion and typically causes structural weakening.

According to a sixth aspect of the present invention there is provided a gemstone cut with grooves dedicated for invisible setting, the gemstone having an inclusion causing structural weakening of the gemstone, the inclusion being in close proximity to one of the grooves, the inclusion weakening the gemstone in the close proximity of the grooves, making the gemstone more likely to chip as compared to a gemstone having an otherwise similar, but more centered, inclusion.

According to a seventh aspect of the present invention there is provided an item of jewelry comprising a setting, a plurality of mountings for mounting gemstones and a plurality of gemstones mounted on the plurality of mountings and invisibly mounted on the setting, whereby the setting and the plurality of mountings are made of different materials.

According to an eighth aspect of the present invention there is provided an item of jewelry comprising a setting and a plurality of mountings, each mounting for holding a grooved gemstone invisibly to the setting, respective mountings having a first end with extensions to receive a respective gemstone and protrusions extending inwardly from the extensions to fit within corresponding mounting grooves of the grooved gemstone, each mounting further comprising a holding configuration configured to undergo distortion when fitting into the setting, the distortion lockingly holding the respective mounting to the setting.

According to a ninth aspect of the present invention there is provided a method of mounting a grooved gemstone to a setting comprising:

pressing said gemstone into a mounting to locate grooves of said gemstone into protrusions of said mounting, and

inserting said mounting into said setting.

According to a tenth aspect of the present invention there is provided a mounting for holding a grooved gemstone invisibly to a setting, the mounting having a first end with extensions to receive the gemstone and protrusions extending inwardly from said extensions to fit within respective mounting grooves of the grooved gemstone, the mounting further comprising a holding configuration to insert said mounting into a location in said setting.

According to an eleventh aspect of the present invention there is provided a method of making jewelry using false gemstones made of material weaker than a gemstone, the method comprising:

mounting said false gemstone to a setting by:

providing a setting having a mounting space,

providing a mounting, the mounting having arms and protrusions at a distal end of said arms to fit into grooves of said false gemstone,

pressing said mounting into said mounting space, said pressing causing
contouring on said mounting space to press said arms inwardly to lock said
protrusions into said grooves, thereby mounting said false gemstone via inward
pressure on a body of said false gemstone and not relying on structural resilience
of said false gemstone.

According to a twelfth aspect of the present embodiments there is provided an
item of jewelry comprising a setting, a plurality of mountings for mounting gemstones
and a plurality of gemstones mounted on said plurality of mountings and invisibly
mounted on said setting, wherein said setting forms a non-planar surface comprising a
curvature in at least one dimension.

According to a thirteenth aspect of the present invention there is provided an
item of jewelry comprising a setting, a plurality of mountings for mounting gemstones
and a plurality of gemstones mounted on said plurality of mountings and invisibly
mounted on said setting, wherein said setting forms a plane having an area of at least
twenty square centimeters.

Unless otherwise defined, all technical and/or scientific terms used herein have
the same meaning as commonly understood by one of ordinary skill in the art to which
the invention pertains. Although methods and materials similar or equivalent to those
described herein can be used in the practice or testing of embodiments of the invention,
exemplary methods and/or materials are described below. In case of conflict, the patent
specification, including definitions, will control. In addition, the materials, methods, and
examples are illustrative only and are not intended to be necessarily limiting.

BRIEF DESCRIPTION OF THE DRAWINGS

Some embodiments of the invention are herein described, by way of example
only, with reference to the accompanying drawings. With specific reference now to the
drawings in detail, it is stressed that the particulars shown are by way of example and
for purposes of illustrative discussion of embodiments of the invention. In this regard,
the description taken with the drawings makes apparent to those skilled in the art how
embodiments of the invention may be practiced.

In the drawings:

FIG. 1A is a simplified schematic diagram showing a mounting according to an
embodiment of the present invention holding a gemstone;

FIG. 1B is a variation of the mounting of FIG. 1A;

FIGS. 2A-2C are views from different angles of a setting designed with spaces to accept mountings according to FIG. 1;

FIG. 3A is a simplified diagram showing a mounting according to FIG. 1 being
5 fixed into position in the setting of FIG. 2 using a deformation tool;

FIG. 3B is a simplified diagram showing a mounting according to FIG. 1B being fixed into position in the setting of FIG. 2 using another deformation tool;

FIG. 4 is a simplified diagram showing use of the deformation tool of FIG. 3 from a direct angle;

10 FIG. 5 is a simplified diagram showing a row of mounting according to an embodiment of the present invention;

FIG. 6 is simplified diagram showing insertion of a gemstone onto a mounting according to the present embodiments;

15 FIG. 7 is a simplified diagram showing a row of three mounted gemstones following the insertion procedure of FIG. 6;

FIGS. 8A-8D are simplified diagrams illustrating an embodiment of a mounting in which a breakable end is used to straighten a concave base to fix the mounting into the setting;

20 FIGS. 9A-9F are a series of simplified diagrams illustrating the use of a removable tool to straighten a concave base to fix the mounting into the setting;

FIG. 10 is a simplified perspective view of a further mounting according to the present embodiments in which a screw-end is provided to the base to allow for an external threaded tool to distort the base to clasp the gemstone;

FIG. 11 is a side view of the mounting of FIG. 10;

25 FIGS. 12A-12F illustrate succeeding stages in mounting and clasp a gemstone into the mounting of FIG. 10;

FIG. 13 is a three-dimensional schematic diagram showing a flat version of the invisible setting of the present embodiments, in which numerous small gemstones are mounted in a matrix;

30 FIG. 14 is a three-dimensional schematic diagram showing a version of the invisible setting of the present embodiments in which a matrix is provided that is similar

to that of FIG. 13, except that the matrix is curved in the longitudinal direction to give a wave effect;

FIG. 15 is a three-dimensional schematic diagram showing a version of the invisible setting of the present embodiments in which a two layer matrix setting for a ring has a convex shape;

FIG. 16 shows a version of the invisible setting of the present embodiments where the matrix provides a concave shape for a ring;

FIG. 17 shows a version of the invisible setting of the present embodiments with a curve shaped setting on the upper part of a ring; and

FIG. 18 is a version of the invisible setting of the present embodiments which provides a spherical-shaped mounting on a chain.

DESCRIPTION OF SPECIFIC EMBODIMENTS OF THE INVENTION

The present invention, in some embodiments thereof, relates to an invisible setting for diamonds and other precious stones in jewelry, and methods and tools for effecting such settings. In the present embodiments a mounting is used to hold the gemstone within the setting, so that the process of fixing the gemstone in position is made easier and so that distortions to the setting over time do not affect the integrity of the way in which the gemstone is held.

In the present disclosure the term "gemstone" is used to refer not only to diamonds and other precious and semiprecious stones, but also to glass, metals, plastic and anything else that can be made into a decorative mounting for jewelry and like products.

As will be explained in greater detail below, the mounting relies less than traditional settings on the strength of the stone to retain the stone in place, and thus the invisible setting with the mounting of the present embodiments is suitable for flawed gemstones and for weaker materials altogether.

Top grade gemstones consist of alexandrites, aquamarines, diamonds, emeralds, garnet, opals, pearls, rubies, sapphires, spinels and topaz. More generally, there are over 130 types of minerals that have been used as gemstones.

These include, but not limited to:

Agate

- Alexandrite and other varieties of chrysoberyl
Andalusite
Axinite
Benitoite
5 Aquamarine and other varieties of beryl
Bixbite (Red beryl)
Cassiterite
Chrysocolla
Chrysoprase
10 Clinohumite
Iolite
Danburite
Diamond
Diopside
15 Dioptase
Dumortierite
Emerald
Feldspar (moonstone)
Garnet
20 Hambergite
Hematite
Jade – jadeite and nephrite
Jasper
Kornerupine
25 Kunzite
Lapis lazuli
Malachite
Natural moissanite
Obsidian
30 Olivine (Peridot)
Opal (Girasol)
Pyrite

Quartz and its varieties:

Agate

Amethyst (cardinal gem)

Citrine

5 Chalcedony (bloodstone)

Onyx

Tiger's-eye

Ruby

Sapphire dark blue

10 Spinel

Sugilite

Tanzanite and other varieties of zoisite

Topaz

Turquoise

15 Tourmaline

Variscite

Zeolite (Thomsonite), and

Zircon

In addition, artificial or synthetic materials that have been used as gems include:

20 High lead glass

Synthetic corundum

Synthetic cubic zirconia

Synthetic spinel

Synthetic moissanite

25 Synthetic alexandrite

Synthetic opal

Synthetic turquoise

Synthetic diamond

Synthetic quartz

30 Synthetic beryl

cristinite

YAG yttrium aluminium garnet

Organic materials may also be used as gems, and examples include:

Amber

Ammonite - from fossils formed from the shells of extinct ammonites.

Bone

5 Coral

Ivory

Jet (lignite)

Nacre (Mother of pearl) and

Pearl.

10 The settings and mountings may be made of injection molded or printed or other plastic, titanium, gold, silver, stainless steel, ceramic, brass, pewter, glass, and base metals in general.

In addition to jewelry, the embodiments may be applied to mounting of gemstones as defined above, on fashion bags, leather bags, purses and wallets, directly
15 on clothing and accessories, including spectacles, on white goods, on personal articles such as watches, pens, mobile telephones and mobile phone covers, etc., on other consumer articles and also to mounting on vehicles or parts of vehicles, such as the steering and dashboard on luxury cars, and onto buildings and parts of buildings. Thus precious or semi-precious stones and crystals may be set into the walls of foyers or
20 bathrooms and the like.

Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not necessarily limited in its application to the details of construction and the arrangement of the components and/or methods set forth in the following description and/or illustrated in the drawings and/or the Examples. The
25 invention is capable of other embodiments or of being practiced or carried out in various ways.

Referring now to the drawings, Figure 1A shows a mounting 10 which holds a grooved gemstone 12 invisibly to a setting such as a ring or other item of jewelry. The mounting 10 has a first end 14 designed to hold the gemstone 12 at groove 16 using
30 protrusions 18 of two oppositely facing arms 20 and 22. The protrusions 18 extend inwardly from the arms 20 and 22 to fit the groove. The mounting 10 further has a holder 24 for holding the mounting to the setting.

Fig. 1B likewise has a mounting for fitting gemstones. However a gap 26 in the base of the mounting provides snap-on functionality for the mounting, as will be described in greater detail below.

Reference is now made to Figs. 2A to 2C, which show different views of a setting 30 having spaces 32 for placing the gemstones in the mountings. Some of the spaces are shown filled with already mounted gemstones 34.

Fig. 2A shows a perspective view of the setting. Fig. 2B shows a view from above and Fig. 2C shows a view from below. As seen in Fig. 2C the spaces 32 extend to openings 36 in the underside of the setting through which the holders 24 may poke through during the mounting process, as will be explained hereinbelow.

Reference is now made to Fig. 3, which shows in greater detail how the mounting 10 with the gemstone 12 held in its arms is mounted within one of spaces 32 to the setting 30. The mounting is snapped into the space 32 so that holder 24 extends outwardly from opening 36. The walls of holder 24 are then deformed outwardly around the opening. The deformation has the effect of jamming the mounting into the space, but also presses the walls of the mounting against the convex contouring 42 of the space so that the convex contouring levers the arms 20 and 22 to press into grooves 16 of the gemstone.

That is to say, the setting comprises spaces for holding mountings. Each space is shaped with a bulge or contoured, to hold the mounting and at the same time deform the mounting to close the arms into the gemstone groove. In other words, the space is contoured to lock the mounting into the setting and at the same time push the arms or upper parts of the mountings inwardly to lock onto the gemstone groove when the setting is pushed downwardly into the space, as discussed.

Returning to Fig. 1B, and the mounting, and more specifically, the holder 24, is designed to be deformed when pulled into the setting. The holder 24 is hollow, and has an open slit 26 down one side. Furthermore the cylindrical outer walls 27 of the holder are relatively thin along their length in between base 28 and the meeting point 29 with the arms. The relatively thin walls combined with the open slit provide a relatively weakened portion of the mounting to provide for controlled deformation, allowing a specifically desired deformation to be preferentially caused by the mounting.

As shown in Fig. 3A, the deformation may be carried out by a beveling tool 44 or the like. Beveling of the base 28 of the holder 24, as discussed, causes the arms 20 and 22 to close over the gemstone and hold the gemstone more strongly via the groove.

Fig. 3B shows the use of an equivalent tool for the embodiment of Fig. 1B. In the embodiment of Fig. 1B the base is flexible because of gap 26 which is constructed therein. Tool 46 comprises a head 47 which is inserted into the base of the mounting to force the two sides of the mounting apart and thus allow the gemstone to be snapped into place.

Fig. 4 is the same as Fig. 3 but viewed directly from the front so that the deformation of the base 28 of the holder 24 about the opening 36 is more clearly shown.

Fig. 5 shows a mounting 50 with a gemstone being placed downwardly into a space in the setting 52 prior to the deformation shown in Fig. 4. In use, a setting shaped as explained above with spaces for the mountings, is used. A mounting 50 having arms and protrusions at a distal end of the arms, is fitted with a gemstone and is pressed in the direction of arrow 54 when the arms fit into the gemstone grooves as explained above. Simultaneous pressing of the gemstone into the mounting and pushing the mounting into the space provides a single click action in which the pressure causes the contouring on the setting to distort the mounting to simultaneously catch the mounting into the space and press the arms inwardly to lock the protrusions into the gemstone grooves.

Typically gemstones are mounted in rows and columns. Three adjacent mountings are shown in the figure, and once the rows and columns of gemstones are filled, the mounting is invisible to the outside observer.

Reference is now made to Fig. 6, which illustrates a gemstone 60 being placed in a mounting 62. Typically the gemstone may simply be placed face down on a surface and then the mounting is pressed down onto the gemstone allowing the protrusions 64 at the end of the arms 66 to snap into grooves 68.

Fig. 7 shows three mounted gemstones in a row.

Reference is now made to Figs. 8A - 8D, which are simplified diagrams of a third embodiment of the mounting in which the holder includes a break-off portion to carry out the deformation. Mounting 80, holding gemstone 81, comprises a pole portion 82 at the end of holder 84. The arm arrangement for holding the gemstone is unchanged and the holder 84 works in the same way to bias the arms to hold the

gemstone tighter following deformation. As shown in Fig. 8A the mounting is pressed into the space in the setting via contouring 86 on the setting which deforms the mounting as it passes. The mounting 80 is snapped into the setting to the position shown in Fig. 8B and then the pole portion 82 is pulled to deform the holder further by flattening floor 88, initially concave, of the holder 82. The pole portion is broken off during the deformation to leave a clean setting and a holder with a flattened floor 88.

The breakable portion 82 may be designed to be broken off using a shaped mounting tool (not shown).

In either of the above embodiments, the mounting may simultaneously close over the grooved gemstone and deform into the setting with a single application of force.

Fig. 8C illustrates the gemstone in situ on the mounting after the breakable portion 82 has been removed.

Reference is now made to Figs. 9A–9E, which show stages in the use of a variation of the embodiment of Fig. 8.

In the variation of Figs 9A to 9E breakable pole portion 82 is replaced by a removable tool. Removable tool 90 comprises a cylindrical pole portion 92 and a flanged end 94. The cylindrical pole portion 92 fits into a correspondingly shaped hole 96 in concave base portion 98 of mounting 100. Fig. 9A shows the pole over the hole prior to insertion and Fig. 9B shows the pole after insertion with the flanged end pulled against the hole 96. As shown in Fig. 9B the mounting is inverted for insertion of the stone 101 and then as shown in Fig. 9C the mounting with the tool and stone are inserted into the setting 102 with the tool extending through hole 104 in the setting. As shown in Fig. 9D the mounting is pressed into position in the setting and then the tool is pulled from below. The pull from below releases the tool from the mounting, at the same time flattening the concavity of the base portion 98 and levering the arms to push inward on the gemstone.

Fig. 9E shows the gemstone in situ with the tool prior to tool removal.

Reference is now made to FIG. 10, which is a simplified perspective view of a further mounting 110 according to the present embodiments. In FIG. 10, a screw-end 112 is provided to the base 114 of mounting 110 to allow for an external threaded tool to distort the base 114 to clasp the gemstone 116.

FIG. 11 is a side view of the mounting of FIG. 10.

FIGS. 12A – 12F illustrate succeeding stages in mounting and clasping a gemstone into the mounting of Fig. 10. Fig. 12A shows the holder pressed over the inverted gemstone to snap fit the gemstone from above. Fig. 12B shows the gemstone snapped into the mounting following the snap-fit operation of Fig. 12A.

In FIG. 12C the mounting is lowered in the direction of arrow 118 onto setting 120. In Fig. 12D threaded tool 122 is lined up with the screw-end 112 and in FIG. 12E the screw end is threaded into the threaded tool to distort base 114 and reinforce the holding of the gemstone by the mounting.

Finally in Fig. 12F the threaded tool is removed from the mounting, which mounting is now firmly held in the setting.

The different embodiments listed herein can be used with automation, such as CNC devices and robot arms. The embodiments of Figs 9A to 9F and Figs 10 – 12F are particularly suitable for use with a robot arm.

Reference is now made to Fig. 13, which shows a flat or planar version 130 of the invisible setting of the present embodiments, in which numerous small gemstones are mounted in a matrix. A protruding rim 132 surrounding the matrix around the edge guards the matrix from damage, say from a fall.

Fig. 14 shows a version 140 of the invisible setting of the present embodiments in which a matrix is provided that is similar to that of Fig. 13, except that the matrix is curved in the longitudinal direction to give a wave effect. A surrounding protruding rim 142 is shown. Thus the surface of the matrix is non-planar.

More generally, the surface may be convex, concave, curved in one dimension, curved in two dimensions or even curved in three dimensions, as in the following examples.

Fig. 15 shows a version 150 of the invisible setting of the present embodiments in which a two layer matrix setting for a ring has a convex shape. Different color stones are shown in each layer 152, 154 respectively, although it will be appreciated that different colors may be mixed in the same layer, or different layers may share the same colors. Likewise the stones may be of different material, thus rubies and sapphires etc. Each layer has its own separate surrounding rim, 156, 158.

Fig. 16 shows a version 160 of the invisible setting of the present embodiments where the matrix provides a concave shape for a ring. Again, a surrounding rim 162 is provided.

Fig. 17 shows a version 170 of the invisible setting of the present embodiments with a curve shaped setting on the upper part of a ring.

Fig. 18 is a version 180 of the invisible setting of the present embodiments which provides a spherical-shaped mounting on a chain.

Embodiments of the present invention may be used with flawed gemstones, and particularly where the flaws in the gemstones are in the region of the grooves cut in the gemstones to carry out the invisible mounting. Generally the flaws are inclusions within the gemstone which weaken the crystal structure and render it mechanically weaker. With prior art mountings gemstones in which the flaws are in the proximity of the grooves are not used simply because the mechanical pressures of the invisible mounting are too much to bear for the lessened mechanical strength of the flaw. However in the present embodiments the substantial mechanical force is directed inwards and thus the support is provided by the body of the gemstone. Hence for the first time it is possible to use gemstones having flaws around the periphery and particularly near the grooves, for invisible mounting.

As well as flawed gemstones, it is also possible, for the same reason, to use weaker kinds of gemstone, as well as glass and other non-gemstone grade material. Thus, the present embodiments may be used to make realistic jewelry with invisible settings using glass and like material and false gemstones or soft gemstones.

The settings themselves may be constructed of any kind of metal, including both hard metals and soft metals, and including steel, platinum, gold, silver and brass.

The settings and mountings may alternatively be made of plastic. Certain products to which the embodiments are applied are generally made of plastic, such as mobile phone covers. Other products may require prototypes, and prototype settings may be made of plastic and then coated with metal as necessary.

In the case of plastic products and prototypes, a design may be prepared using a CAD package. The CAD design may then be used as the input to a 3D printer to create the setting. The setting may be coated with gold, silver, or other metals as appropriate and the mountings and gemstones may be inserted using any of the methods discussed

above. The prototype may then be inspected by the customer, and a mass-production tool prepared as necessary.

It is expected that during the life of a patent maturing from this application many relevant pulse shaping and symbol decoding technologies will be developed and the scope of the corresponding terms in the present description are intended to include all such new technologies *a priori*.

The terms "comprises", "comprising", "includes", "including", "having" and their conjugates mean "including but not limited to".

The term "consisting of" means "including and limited to".

As used herein, the singular form "a", "an" and "the" include plural references unless the context clearly dictates otherwise.

It is appreciated that certain features of the invention, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable subcombination or as suitable in any other described embodiment of the invention. Certain features described in the context of various embodiments are not to be considered essential features of those embodiments, unless the embodiment is inoperative without those elements.

Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad scope of the appended claims.

All publications, patents and patent applications mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual publication, patent or patent application was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present invention. To the extent that section headings are used, they should not be construed as necessarily limiting.

WHAT IS CLAIMED IS:

1. A mounting for holding a grooved gemstone invisibly to a setting, the mounting having a first end with extensions to receive the gemstone and protrusions extending inwardly from said extensions to fit within respective mounting grooves of the grooved gemstone, the mounting further comprising a holding configuration for lockingly holding said mounting to said setting.

2. The mounting of claim 1, wherein the holding configuration is connected to said extensions to press said protrusions inwardly onto said groove when said holding configuration is distorted against contouring of said setting.

3. The mounting of claim 1, or claim 2, wherein the mounting is configured to be deformed upon pulling inwardly about contouring on said setting, said deformation being such as to lever said extensions to push said protrusion inwardly into said groove.

4. The mounting of claim 1, 2 or 3, wherein said holding configuration is configured to protrude at least partially from a base part of said setting, said holding configuration being deformable about said setting by a deformation tool applied to said second end to catch said mounting into said setting and to lever said protrusions into said groove.

5. The mounting of claim 1, 2, 3 or 4, wherein said holding configuration is configured to protrude at least partially from a base part of said setting, said holding configuration comprising a breakable portion that deforms said mounting prior to being broken away therefrom, to catch said mounting into said setting and to lever said protrusions into said groove.

6. The mounting of claim 5, wherein said breakable portion is designed to be broken off using a shaped mounting tool.

7. The mounting of any one of the preceding claims, comprising a weakened portion for preferential deformation when being mounted.

8. The mounting of claim 7, configured to simultaneously close over said grooved gemstone and deform into said setting with a single application of force.

9. The mounting of claim 3, comprising a concave base portion being flattenable to provide said deformation.

10. The mounting of claim 9, wherein said flattening is provided by a breakable portion attached to said base portion.

11. The mounting of claim 10, wherein said flattening is provided by a tool inserted via a hole into said base portion.

12. The mounting of any one of the preceding claims, wherein said extensions are resilient.

13. A setting for gemstones comprising a plurality of locations for holding respective gemstone mountings, each location being shaped to close upper protrusions of said mounting into a groove of a grooved gemstone to hold said gemstone to said setting.

14. The setting of claim 13, being contoured to push upper parts of respective mountings inwardly to lock onto said groove when said setting is pushed downwardly into said location.

15. The setting of claim 13 or claim 14, wherein respective shapes are open at a lower end to allow a deformable or breakable holding portion of said mounting to extend from said lower end for said deformation or breakage causing said deformation.

16. The setting of claim 15, provided with a tool to carry out said deformation or breakage causing said deformation.

17. The setting of any one of claims 13 to 16, comprising a soft metal.

18. The setting of any one of claims 13 to 17, further comprising a protruding rim extending around the setting.

19. A method of mounting a grooved gemstone to a setting comprising:
mounting said gemstone into a mounting to locate grooves of said gemstone into protrusions of said mounting, and
attaching said mounting to said setting.

20. The method of claim 19, wherein said attaching is subsequent to said mounting.

21. A method of mounting a grooved gemstone to a setting comprising:
providing a setting having a mounting location,
providing a mounting, the mounting having arms and protrusions at a distal end of said arms to fit into grooves of said grooved gemstone,
pressing said mounting into said mounting location, said pressing causing contouring on said mounting location to press said arms inwardly to lock said protrusions into said grooves, thereby mounting said gemstone.

22. The method of claim 21, carried out by a robot arm.

23. A mounting for invisible placing of a grooved gemstone within a setting, the mounting being separate and distinct from both said setting and said gemstone and having both a setting attachment for attachment to said setting and a gemstone attachment for attaching a gemstone.

24. A method of mounting a flawed gemstone to a setting comprising:

providing a gemstone having grooves and flaws in proximity to said grooves;

providing a setting having a mounting space,

providing a mounting, the mounting having arms and protrusions at a distal end of said arms to fit into grooves of said grooved gemstone,

pressing said mounting into said mounting space, said pressing causing contouring on said mounting space to press said arms inwardly to lock said protrusions into said grooves, thereby mounting said gemstone via inward pressure on a body of said gemstone and not relying on structural resilience of said flaws.

25. A gemstone cut with grooves dedicated for invisible setting, the gemstone having an inclusion causing structural weakening of said gemstone, said inclusion being in close proximity to one of said grooves, said inclusion weakening the gemstone in said close proximity of said grooves, making the gemstone more likely to chip as compared to a gemstone having an otherwise similar, but more centered, inclusion.

26. An invisible setting comprising a plurality of the gemstone of claim 25.

27. A plurality of the gemstone of claim 25.

28. A gemstone mounting device containing a plurality of the gemstone of claim 25.

29. A soft gemstone cut with grooves dedicated for the mounting of any one of claims 1 to 12 or the setting of any one of claims 13 to 19.

30. An item of jewelry comprising a setting, a plurality of mountings for mounting gemstones and a plurality of gemstones mounted on said plurality of mountings and invisibly mounted on said setting, whereby said setting and said plurality of mountings are made of different materials.

31. An item of jewelry comprising a setting and a plurality of mountings, each mounting for holding a grooved gemstone invisibly to said setting, respective mountings having a first end with extensions to receive a respective gemstone and protrusions extending inwardly from said extensions to fit within corresponding mounting grooves of the grooved gemstone, each mounting further comprising a holding configuration for lockingly holding said respective mounting to said setting.

32. The mounting of any one of claims 1 - 12, wherein said holding configuration is configured to undergo distortion when fitting into said setting, said distortion for said lockingly holding said respective mounting to said setting.

33. The item of jewelry of claim 28, wherein said holding configuration is configured to undergo distortion when fitting into said setting, said distortion for said lockingly holding said respective mounting to said setting.

34. A mounting for holding a grooved gemstone invisibly to a setting, the mounting having a first end with extensions to receive the gemstone and protrusions extending inwardly from said extensions to fit within respective mounting grooves of the grooved gemstone, the mounting further comprising a holding configuration securely locate said mounting into a location in said setting.

35. The setting of any one of claims 13 to 18, wherein said location is shaped to deform said respective mounting to cause said closing.

36. A method of making jewelry using false gemstones made of material weaker than a gemstone, the method comprising:

mounting said false gemstone to a setting by:

providing a setting having a mounting space,

providing a mounting, the mounting having arms and protrusions at a distal end of said arms to fit into grooves of said false gemstone,

pressing said mounting into said mounting space, said pressing causing contouring on said mounting space to press said arms inwardly to lock said

protrusions into said grooves, thereby mounting said false gemstone via inward pressure on a body of said false gemstone and not relying on structural resilience of said false gemstone.

37. An item of jewelry comprising a setting, a plurality of mountings for mounting gemstones and a plurality of gemstones mounted on said plurality of mountings and invisibly mounted on said setting, wherein said setting forms a non-planar surface comprising a curvature in at least one dimension.

38. An item of jewelry comprising a setting, a plurality of mountings for mounting gemstones and a plurality of gemstones mounted on said plurality of mountings and invisibly mounted on said setting, wherein said setting forms a plane having an area of at least twenty square centimeters.

39. A method of making the setting of any one of claims 13 to 18 or 35, or the mounting of any one of claims 1 - 12, 32 and 34, comprising:
using a CAD package to design the setting or mounting; and
using a 3D printer to produce the setting or mounting according to the design.