



(51) International Patent Classification:
B07B 13/10 (2006.01) **B03B 9/04** (2006.01)

(21) International Application Number:
PCT/NL2009/050165

(22) International Filing Date:
1 April 2009 (01.04.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2001431 2 April 2008 (02.04.2008) NL

(71) Applicant (for all designated States except US): **Technische Universiteit Delft** [NL/NL]; Stevinweg 1, NL-2628 CN Delft (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BERKHOUT, Simon Peter Maria** [NL/NL]; Molensingel 117, NL-2614 LC Delft (NL). **REM, Peter Carlo** [NL/NL]; Jaagpad 5B, NL-2288 AB Rijswijk (NL).

(74) Agent: **VAN BREDA, Jacques**; Weteringschans 96, NL-1017 XS Amsterdam (NL).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SEPARATION-APPARATUS



(57) Abstract: The invention relates to a separation-apparatus (1) for separating from a particle-stream (4) at least a first fraction with particles (3) of a first group of dimensions, and a second fraction with particles (3) of a second group of dimensions, comprising an infed-device (2) for the particle-stream (4), a rotatable drum (5) having at its circumference (13) plates (6,6'), each plate having a radially extending hitting surface for the particles, at least a first receiving area (11,11') proximal to the drum (5) for receipt therein of particles of the first fraction, and at least a second receiving area (12,12') distant from the drum (5) for receipt therein of particles of the second fraction, wherein the apparatus has a housing (16) so as to protect the particles (3) from outside weather-conditions, allowing that the particles (3) of the particle-stream (4) to be processed by said apparatus (1) have dimensions in the range 0-15mm.

