

Description

FIELD OF THE INVENTION AND RELATED ART STATEMENT

FIELD OF THE INVENTION

The present invention relates to a radiator assembly fixed to a substrate via soldered metal plate, and particularly it relates to a radiator which can be separated or disassembled from a substrate by using a typical common tool in order to be used as recycling resources after retirement of the assembly including the radiator.

DESCRIPTION OF THE RELATED ART

Recently, an aluminum radiator, which is manufactured by an extrusion molding, is widely used in an electronic apparatus, which comprises a substrate having many electronic devices mounted at high density. The radiator is usually made of aluminum block since it can be manufactured by easy treatment and have excellent heat-conductivity. Such aluminum radiators prevent the appearance of malfunction or destruction caused by heat of an electronic device, such as a semiconductor device. And the semiconductor device attached to such aluminum radiator is operated in excellent performance.

In view of an environmental disruption of the globe and the recycling of resources, disassembly and classification of the electronic apparatus to be scrapped have lately been attracting considerable attention. It becomes one of the most importance matter in an electronic apparatus in recent years that many kinds of electronic devices in electronic apparatus are assembled so as to be easily disassembled and classified into same material in order to recycle the resources. Particularly, since the large block of aluminum wares were made by consuming a great amount of electricity in smelting, the aluminum ware is preferably used as recycling.

Next, a way of disassembly for such aluminum ware, especially a conventional aluminum radiator, is described with reference to FIG 5. FIG.5 is a perspective view of the conventional aluminum radiator 30 mounted on a substrate 80. As shown in FIG.5, a semiconductor device 10 to be cooled is fixed to the conventional aluminum radiator 30 through an insulation sheet 20 such as a mica sheet by tightening a screw 40. Since the aluminum radiator 30 can not be fixed directly to the substrate 80 by soldering, the aluminum radiator 30 is fixed to metal plates 50 by caulked joints 30a, and the metal plates 50 formed in a flat plate are fixed to the substrate 80 by soldering. By the above-mentioned way, the conventional aluminum radiator 30 is firmly fixed to the substrate 80 usually.

Therefore, in case that the electronic apparatus

is retired, it is desirable that many kinds of the electronic devices in the electronic apparatus are disassembled and classified in the same material. However, the conventional radiator 30 of the electronic device can not be easily separated from the substrate 80 by a typical or ordinary tool, and semiconductor device only can be separated from the conventional radiator 30 by removing the screw 40 with a screwdriver tool. As a result, the substrate 80 having the conventional radiator 30 must be scrapped with the other electronics in spite of the usable material as recycling resources.

OBJECT AND SUMMARY OF THE INVENTION

An object of the present invention is to provide a radiator assembly which can be easily separated from a substrate of an electronic apparatus in order to be used as recycling resources in a manner of a typical tool when the electronic apparatus is retired.

In order to achieve the above-mentioned object, the radiator assembly for a substrate comprises:

a substrate for mounting an electronic device;
a fitting plate fixed to the substrate by at least a welding joint; and

a radiator for cooling an electronic device which is heat-conductively attached to the radiator which is coupled to the fitting plate by mechanical connecting means, the radiator having at least a hollow forming at least an aperture for receiving a pry tool between the fitting plate and the radiator.

And, another radiator assembly in accordance with the present invention comprises:

a substrate for mounting an electronic device;
a radiator for cooling the electronic device which is heat-conductively attached to the radiator; and

a fitting plate which is fixed to the substrate by at least a welding joint, the fitting plate being coupled to the radiator by mechanical connecting means, the fitting plate having swelled portions forming apertures for receiving a pry tool between the fitting plate and the radiator.

In the radiator assembly in accordance with the present invention which is configured above, the radiator assembly is constructed to have apertures between the radiator and the fitting plate so as to be inserted a typical tool for separating between the radiator and the fitting plate. When an electronic device, such as a semiconductor device fitted to the radiator assembly is retired, a radiator of the radiator assembly can be easily separated from the fitting plate fixed to the substrate in a manner that the apertures are pried open with a typical tool, such as screwdriver thereby the separated radiator can be used as recycling resources.

While the novel features of the invention are set forth particularly in the appended claims, the inven-

tion, both as to organization and content, will be better understood and appreciated, along with other objects and features thereof, from the following detailed description taken in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG.1 is a perspective view showing a radiator assembly of a first embodiment of the present invention.

FIG.2 is a perspective view showing the radiator assembly of FIG.1 on a way of a disassembly.

FIG.3 is a perspective view showing a radiator assembly of a second embodiment of the present invention.

FIG.4 is a perspective view showing the radiator assembly of FIG.3 on a way of a disassembly.

FIG.5 is the perspective view showing the conventional radiator mounted on the substrate.

It will be recognized that some or all the Figures are schematic representations for purposes of illustration and do not necessarily depict the actual relative sizes or locations of the elements shown.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Hereafter, radiator assemblies to be mounted on a substrate as preferred embodiments of the present invention are described with reference to the accompanying drawings of FIGs.1 to 4.

< First embodiment >

FIG.1 is a perspective view showing a radiator assembly of the first embodiment embodying the present invention. FIG.2 is a perspective view showing the radiator assembly of FIG.1 on a way of a disassembly.

In FIG.1, a semiconductor device 1 is thermally conductively attached to a radiator 3 with an insulation sheet 2 such as a mica sheet by tightening a screw 4 inbetween. The radiator 3 having plural cooling fins is manufactured by an extrusion molding of aluminum. Two metallic fitting plates 5, 5 are attached to the radiator 3 at both side faces. The fitting plate 5 is slid and fitted into each-other-opposing two grooves 3a, 3a, which are formed on vertical edge portions of side wall 3d of the radiator 3 as shown in FIG.1. The fitting plate 5 is firmly fixed at the predetermined position of the side wall 3d by caulking at plural portions 3b, 3b, 3b, 3b of guide rails of the grooves 3a, 3a. The side wall 3d is formed to have two belt-shaped hollows 3c, 3c, namely two substantially vertical straight grooves. Two apertures 7, 7 are formed by attaching the fitting plates 5 to the side wall 3d of the radiator 3, because the side wall 3d has the belt-shaped hollows 3c, 3c. The apertures 7 are arranged to be close to the caulked joints 3b connecting between the fitting plate 5 and the side wall 3d of the

radiator 3. The aperture 7 have a grooved shape to be easily inserted by a typical tool, such as a slotted screwdriver 6. The radiator 3 is firmly fixed to the substrate 8 in a manner that the fitting plates 5 are fixed to the substrate 8 by soldering.

Next, with reference to FIGs.1 and 2 description is made on a way of separating or disassembling the above-mentioned radiator assembly, which has been fixed to the substrate 8 through the fitting plates 5 by caulking and soldering.

In case the radiator 3 fixed to the substrate 8 as shown in FIG.1 is separated from the substrate 8, the semiconductor device 1 is initially separated from the radiator 3 by removing the screw 4 with a typical tool, such as a Philip screwdriver 9 as shown in FIG.2.

In the next step, the aperture 7, which is formed by attaching the fitting plate 5 to the side wall 3d having the belt-shaped hollows 3c, is inserted by a slotted screwdriver 6. And, the fitting plate 5 is pried from the side wall 3d by pushing in the slotted screwdriver 6 in the aperture 7 thereby removing the caulked edge part of the fitting plate 5 from the caulked joints 3b as shown in FIG.2.

Then, into the other aperture 7, which is arranged on the same side wall 3d (right side aperture in FIG.2), the slotted screwdriver 6 is also inserted and the other aperture 7 is pried open, thereby removing the fitting plate 5 from the side wall 3d of the radiator 3. As a result, the radiator 3 is separated from one fitting plate 5.

Separation of the radiator 3 from the other fitting plate 5 (which is hidden behind the radiator 3 in FIG.2) is carried out in the same way as the above-mentioned separating. Consequently, the aluminum radiator 3 is entirely removed from the substrate 8 for use as recycling resources.

< Second embodiment >

Hereafter, a second embodiment of a radiator assembly for a substrate in accordance with the present invention is described concerning the accompanying drawings of FIGs.3 and 4. FIG.3 is a perspective view showing a radiator assembly of the second embodiment embodying the present invention. FIG.4 is a perspective view showing the radiator assembly of FIG.3 on a way of a disassembly. Corresponding parts and components to the first embodiment are shown by the same numerals and marks, and the description thereon made in the first embodiment similarly apply. Differences and features of this second embodiment from the first embodiment are as follows.

In FIG.3, a semiconductor device 1 is thermally conductively attached to a radiator 3 with an insulation sheet 2, such as a mica sheet, by tightening a screw 4 inbetween. The radiator 3 having plural cooling fins is manufactured by an extrusion molding of aluminum. Two metallic fitting plates 15, 15 are at-

tached to the radiator 3 at both side faces. The fitting plate 15 is slid and fitted into each-other-opposing two grooves 3a, 3a, which are formed vertical on edge portions of side wall 3d of the radiator 3 as shown in FIG.3. The fitting plate 15 is firmly fixed at the predetermined position of the side wall 3d by caulking at plural portions 3b, 3b, 3b, 3b of guide rails of the grooves 3a, 3a. The fitting plate 15 is formed to have two swelled portions 15a, 15a like two pockets. Two apertures 7, 7 are formed by attaching the fitting plate 15 to the side wall 3d of the radiator 3 because the fitting plate 15 has the swelled portions 15a. The apertures 7 are arranged close to the caulked joints 3b connecting between the fitting plate 15 and the side wall 3d of the radiator 3. The aperture 7 have a slotted shape so as to easily receive a typical tool, such as a slotted screwdriver 6. The radiator 3 is firmly fixed to the substrate 8 in a manner that the fitting plates 15 are fixed to the substrate 8 by soldering.

Next, with reference to FIGs.3 and 4 description is made on a way of separating or disassembling the above-mentioned radiator assembly from the substrate 8.

In case the radiator 3 fixed to the substrate 8 as shown in FIG.3 is separated from the substrate 8, the semiconductor device 1 is initially separated from the radiator 3 by removing the screw 4 with a typical tool, such as a Philip screwdriver 9 as shown in FIG.4.

In the next step, a slotted screwdriver 6 is inserted into the aperture 7, which is formed by attaching the fitting plate 15 having swelled portions 15a to the side wall 3d. And, the fitting plate 15 is pried from the side wall 3d by pushing the slotted screwdriver 6 in the aperture 7 so as to break the caulked joints 3b as shown in FIG.4.

Then, into the other aperture 7, which is arranged on the same side wall 3d (right side aperture in FIG.4), the slotted screwdriver 6 is also inserted and the other aperture 7 is pried open, thereby removing the fitting plate 15 from the side wall 3d of the radiator 3. As a result, the radiator 3 is separated from one fitting plate 15.

Separation of the radiator 3 from the other fitting plate 15 (which is hidden behind the radiator 3 in FIG.4) is carried out in the same way as the above-mentioned separating. Consequently, the aluminum radiator 3 is entirely removed from the substrate 8 for use as recycling resources.

Apart from the above-mentioned embodiments wherein the radiator 3 and the fitting plate 5 or 15 are coupled by the caulked joints, a modified embodiment may be such that the radiator and the fitting plate are coupled by optional mechanical coupling means, such as pressure welding, rivet joint.

Claims

1. A radiator assembly for substrate with printed circuit comprising:
 - a substrate (8) for mounting an electronic device;
 - a fitting plate (5) fixed to said substrate (8) by at least a welding joint; and
 - a radiator (3) for cooling an electronic device which is heat-conductively attached to said radiator (3) which is coupled to said fitting plate (5) by mechanical connecting means, said radiator (3) having at least a hollow (3c) forming at least an aperture (7) for receiving a pry tool (6) between said fitting plate (5) and said radiator (3).
2. An assembly in accordance with claim 1 wherein, said radiator (3) is coupled to said fitting plate (5) by caulked joints, and said fitting plate (5) is fixed to said substrate (8) by soldering.
3. A radiator assembly for a substrate comprising:
 - a substrate (8) for mounting an electronic device;
 - a radiator (3) for cooling said electronic device which is heat-conductively attached to said radiator (3); and
 - a fitting plate (15) which is fixed to said substrate (8) by at least a welding joint, said fitting plate being coupled to said radiator (3) by mechanical connecting means, said fitting plate (15) having swelled portions (15a) forming apertures (7) for receiving a pry tool (6) between said fitting plate (15) and said radiator (3).
4. An assembly in accordance with claim 3 wherein, said radiator (3) is coupled to said fitting plate (15) by caulked joints, and said fitting plate (15) is fixed to said substrate (8) by soldering.

Patentansprüche

1. Kühlergebilde für ein Substrat mit einer gedruckten Schaltung, umfassend:
 - ein Substrat (8) zum Anbringen einer elektronischen Vorrichtung;
 - eine Anschluß- bzw. Verbindungsplatte (5), die mittels wenigstens einer Schweißverbindung an dem Substrat (8) befestigt ist; und
 - einen Kühler (3) zum Kühlen einer elektronischen Vorrichtung, die wärmeleitend an dem Kühler (3) angebracht ist, der durch mechanische Verbindungsmittel mit der Anschluß- bzw. Verbindungsplatte (5) gekoppelt ist, wobei der Kühler (3) wenigstens einen Hohlteil (3c) hat, der wenigstens eine Öffnung (7) bildet zum Aufnehmen el-



tached to the radiator 3 at both side faces. The fitting plate 15 is slid and fitted into each-other-opposing two grooves 3a, 3a, which are formed vertical on edge portions of side wall 3d of the radiator 3 as shown in FIG.3. The fitting plate 15 is firmly fixed at the predetermined position of the side wall 3d by caulking at plural portions 3b, 3b, 3b, 3b of guide rails of the grooves 3a, 3a. The fitting plate 15 is formed to have two swelled portions 15a, 15a like two pockets. Two apertures 7, 7 are formed by attaching the fitting plate 15 to the side wall 3d of the radiator 3 because the fitting plate 15 has the swelled portions 15a. The apertures 7 are arranged close to the caulked joints 3b connecting between the fitting plate 15 and the side wall 3d of the radiator 3. The aperture 7 have a slotted shape so as to easily receive a typical tool, such as a slotted screwdriver 6. The radiator 3 is firmly fixed to the substrate 8 in a manner that the fitting plates 15 are fixed to the substrate 8 by soldering.

Next, with reference to FIGs.3 and 4 description is made on a way of separating or disassembling the above-mentioned radiator assembly from the substrate 8.

In case the radiator 3 fixed to the substrate 8 as shown in FIG.3 is separated from the substrate 8, the semiconductor device 1 is initially separated from the radiator 3 by removing the screw 4 with a typical tool, such as a Philip screwdriver 9 as shown in FIG.4.

In the next step, a slotted screwdriver 6 is inserted into the aperture 7, which is formed by attaching the fitting plate 15 having swelled portions 15a to the side wall 3d. And, the fitting plate 15 is pried from the side wall 3d by pushing the slotted screwdriver 6 in the aperture 7 so as to break the caulked joints 3b as shown in FIG.4.

Then, into the other aperture 7, which is arranged on the same side wall 3d (right side aperture in FIG.4), the slotted screwdriver 6 is also inserted and the other aperture 7 is pried open, thereby removing the fitting plate 15 from the side wall 3d of the radiator 3. As a result, the radiator 3 is separated from one fitting plate 15.

Separation of the radiator 3 from the other fitting plate 15 (which is hidden behind the radiator 3 in FIG.4) is carried out in the same way as the above-mentioned separating. Consequently, the aluminum radiator 3 is entirely removed from the substrate 8 for use as recycling resources.

Apart from the above-mentioned embodiments wherein the radiator 3 and the fitting plate 5 or 15 are coupled by the caulked joints, a modified embodiment may be such that the radiator and the fitting plate are coupled by optional mechanical coupling means, such as pressure welding, rivet joint.

Claims

1. A radiator assembly for substrate with printed circuit comprising:
 - a substrate (8) for mounting an electronic device;
 - a fitting plate (5) fixed to said substrate (8) by at least a welding joint; and
 - a radiator (3) for cooling an electronic device which is heat-conductively attached to said radiator (3) which is coupled to said fitting plate (5) by mechanical connecting means, said radiator (3) having at least a hollow (3c) forming at least an aperture (7) for receiving a pry tool (6) between said fitting plate (5) and said radiator (3).
2. An assembly in accordance with claim 1 wherein, said radiator (3) is coupled to said fitting plate (5) by caulked joints, and said fitting plate (5) is fixed to said substrate (8) by soldering.
3. A radiator assembly for a substrate comprising:
 - a substrate (8) for mounting an electronic device;
 - a radiator (3) for cooling said electronic device which is heat-conductively attached to said radiator (3); and
 - a fitting plate (15) which is fixed to said substrate (8) by at least a welding joint, said fitting plate being coupled to said radiator (3) by mechanical connecting means, said fitting plate (15) having swelled portions (15a) forming apertures (7) for receiving a pry tool (6) between said fitting plate (15) and said radiator (3).
4. An assembly in accordance with claim 3 wherein, said radiator (3) is coupled to said fitting plate (15) by caulked joints, and said fitting plate (15) is fixed to said substrate (8) by soldering.

Patentansprüche

1. Kühlergebilde für ein Substrat mit einer gedruckten Schaltung, umfassend:
 - ein Substrat (8) zum Anbringen einer elektronischen Vorrichtung;
 - eine Anschluß- bzw. Verbindungsplatte (5), die mittels wenigstens einer Schweißverbindung an dem Substrat (8) befestigt ist; und
 - einen Kühler (3) zum Kühlen einer elektronischen Vorrichtung, die wärmeleitend an dem Kühler (3) angebracht ist, der durch mechanische Verbindungsmittel mit der Anschluß- bzw. Verbindungsplatte (5) gekoppelt ist, wobei der Kühler (3) wenigstens einen Hohlteil (3c) hat, der wenigstens eine Öffnung (7) bildet zum Aufnehmen ei-



- nes Stemmwerkzeuges (6) zwischen der Anschluß- bzw. Verbindungsplatte (5) und dem Kühler (3).
2. Gebilde nach Anspruch 1, in welchem
 der Kühler (3) mit der Anschluß- bzw. Verbindungsplatte (5) durch Dichtnähte gekoppelt ist, und die Anschluß- bzw. Verbindungsplatte (5) an dem Substrat (8) durch Löten befestigt ist. 5
 3. Kühlergebilde für ein Substrat, umfassend:
 ein Substrat (8) zum Anbringen einer elektronischen Vorrichtung;
 einen Kühler (3) zum Kühlen der elektronischen Vorrichtung, die wärmeleitend an dem Kühler (3) angebracht ist; und 10
 eine Anschluß- bzw. Verbindungsplatte (15), die an dem Substrat (8) durch wenigstens eine Schweißverbindung befestigt ist und die mit dem Kühler (3) durch mechanische Verbindungsmittel gekoppelt ist, wobei die Anschluß- bzw. Verbindungsplatte (15) ausgebauchte bzw. aufgebauhte Teile (15a) hat, die Öffnungen (7) zum Aufnehmen eines Stemmwerkzeuges (6) zwischen der Anschluß- bzw. Verbindungsplatte (15) und dem Kühler (3) bilden. 15 20 25
 4. Gebilde nach Anspruch 3, in welchem
 der Kühler (3) mit der Anschluß- bzw. Verbindungsplatte (15) durch Dichtnähte gekoppelt ist, und die Anschluß- bzw. Verbindungsplatte (15) an dem Substrat (8) durch Löten befestigt ist. 30

Revendications

1. Assemblage de radiateur destiné à un support comportant un circuit imprimé comprenant :
 un support (8) destiné à monter un dispositif électronique, 40
 une plaque d'adaptation (5) fixée audit support (8) par au moins un joint de soudure, et
 un radiateur (3) destiné à refroidir un dispositif électronique, lequel est accolé de façon à conduire la chaleur, audit radiateur (3) qui est relié à ladite plaque d'adaptation (5) par un moyen de liaison mécanique, ledit radiateur (3) possédant au moins un évidement (3c) formant au moins une ouverture (7) destinée à recevoir un outil formant levier (6) entre ladite plaque d'adaptation (5) et ledit radiateur (3). 45 50
2. Assemblage selon la revendication 1 dans lequel, ledit radiateur (3) est relié à ladite plaque d'adaptation (5) à l'aide de joints matés et ladite plaque d'adaptation (5) est fixée audit support (8) par soudure. 55

3. Assemblage de radiateur destiné à un support comprenant :
 un support (8) destiné à monter un dispositif électronique,
 un radiateur (3) destiné à refroidir ledit dispositif électronique, lequel est accolé de façon à conduire la chaleur, audit radiateur (3), et
 une plaque d'adaptation (15) qui est fixée audit support (8) au moyen d'au moins un joint de soudure, ladite plaque d'adaptation étant reliée audit radiateur (3) à l'aide d'un moyen de liaison mécanique, ladite plaque d'adaptation (15) présentant des parties renflées (15a) formant des ouvertures (7) destinées à recevoir un outil formant levier (6) entre ladite plaque d'adaptation (15) et ledit radiateur (3).
4. Assemblage selon la revendication 3 dans lequel, ledit radiateur (3) est relié à ladite plaque d'adaptation (15) à l'aide de joints matés et ladite plaque d'adaptation (15) est fixée audit support (8) par soudure.