CLAIMS

1. A fastener, comprising:

a first clip member, comprising a first base portion and two first arm portions that extend upwardly from two sides of the first base portion;

a second clip member locked with the first clip member, comprising a second base portion and two second arm portions that extend upwardly from two sides of the second base portion; and

at least one hook portion extending from a distal end of one of the first and second arm portions,

wherein the first and second clip members are arranged horizontally along two different directions, and the second base portion is positioned on the first base portion, and

wherein each first arm portion is interlocked with at least one second arm portion by at least a pair of tab and aperture formed on adjacent sides of the first and second arm portions.

2. The fastener of any of claims 1, wherein the first base portion comprises a first through hole formed therein, and the second base portion comprises a second through hole formed therein and at least partially overlapped with the first through hole.

3. The fastener of claim 2, further comprising:

a fastening element positioned on the second base portion, wherein the fastening element comprises a screw hole exposed through the first and second through holes, or a male screw portion extends through the first and second through holes, and

at least one protrusion formed on an inner surface of one of the first and second arm portions and extending over a part of the fastening element to keep the fastening element within a main cavity formed by the second base portion and the first and second arm portions.

4. The fastener of claim 3, wherein the at least one protrusion is formed on the inner surface of at least one of the first arm portions.

5. The fastener of any of claims 3 and 4, wherein the fastening element further comprises a flange portion surrounding a lower part of a head portion, wherein the flange portion is sandwiched between the at least one protrusion and the second base portion.

6. The fastener of any of claims 3, 4, and 5, wherein the at least one protrusion is partially cut out from the one of the first and second arm portions, and bent towards the main cavity.

7. The fastener of any of the preceding claims, wherein the two first arm portions extend upwardly from two opposite sides of the first base portion, and the two second arm portions extend upwardly from two opposite sides of the second base portion.

8. The fastener of claim 2, wherein the first and second through holes are substantially coaxial, and the diameter of the first through hole is larger than the diameter of the second through hole.

9. The fastener of any of the preceding claims, wherein the hook portion comprises at least a groove or a ridge formed on a top surface thereof.

10. The fastener of any of the preceding claims, wherein at least one of the first and second arm portions comprises an opening.