

(19) World Intellectual Property Organization
International Bureau



G00002

(43) International Publication Date
4 April 2002 (04.04.2002)


PCT

(10) International Publication Number
WO 02/027968 A3

- (51) International Patent Classification⁷: **H04B 7/005**
- (21) International Application Number: PCT/US01/29876
- (22) International Filing Date:
21 September 2001 (21.09.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
09/670,292 25 September 2000 (25.09.2000) US
- (71) Applicant: **QUALCOMM INCORPORATED** [US/US];
5775 Morehouse Drive, San Diego, CA 92121-1714 (US).
- (72) Inventor: **SAIFUDDIN, Ahmed**; 8217 Jadecoast Road
#128, San Diego, CA 92126 (US).
- (74) Agents: **WADSWORTH, Philip, R.** et al.; Qualcomm Incorporated, 5775 Morehouse Drive, San Diego, CA 92121-1714 (US).
- (81) Designated States (*national*): AE, AG, AI, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR POWER CONTROL IN A WIRELESS COMMUNICATION SYSTEM



(57) Abstract: In a wireless communication system (10) a method for power control in a mobile unit (14, 16), wherein a variable size step is used to adjust the transmit power. The method compares a current power control signal to a previous one (52), and incrementally changing the step size for no change (64, 70). The adjusted step size is compared to maximum and minimum values (69, 74) to maintain a predetermined step size range. In one embodiment, a mobile unit (22) includes a memory storage device (32, 34) and a comparator (36) for storing the power control signals and comparing them.



162162

WO 02/027968 A3