PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : H01L 21/00 — A1

(11) International Publication Number: WO 00/59007

(43) International Publication Date: 5 October 2000 (05.10.00)

(21) International Application Number: PCT/US00/08176

(22) International Filing Date: 28 March 2000 (28.03.00)

(30) Priority Data:
09/281,595 30 March 1999 (30.03.99) US

(71) Applicant: LAM RESEARCH CORPORATION [US/US]; P0298.PCT, 4650 Cushing Parkway, Fremont, CA 94538–6516 (US).


(72) Inventor: LENZ, Eric, H.; 5930 Foligno Way, San Jose, CA 95138 (US).

(74) Agent: LEE, Michael; Beyer Weaver & Thomas, LLP, P.O. Box 130, Mountain View, CA 94042–0130 (US).

(81) Designated States: IL, JP, KR, SG, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: PERIMETER WAFER LIFTING



(57) Abstract

The invention relates to an apparatus for lifting a substrate form a surface of a chuck subsequent to a processing step. The apparatus includes a perimeter pin for lifting the substrate from the surface of the chuck to a first position wherein the substrate is disposed on the perimeter pin during lifting. The perimeter pin is configured to overcome a holding force at an interface of the substrate and the surface. Generally, the holding force is generated between the substrate and the surface during the processing step. The apparatus further includes a center pin for moving the substrate from the first position to a second position wherein the substrate is disposed on the center pin during moving. The second position is further away from the surface of the chuck than the first position.