

DESCRIPTION

MOUNTING PORT AND MOUNTING PORT OPENING/CLOSING METHOD

Technical Field

- 5 [0001] This invention relates to a mounting port for the mounting of articles, and a method for opening and closing the mounting port.

Background Art

- 10 [0002] A stocker is an apparatus that stores articles such as semiconductor wafers in a clean room, and internally includes a conveying apparatus and shelves. A worker delivers and receives articles via a mounting port. In order to prevent interference between the worker and the conveying apparatus, the opening on the conveying apparatus side of the mounting port is opened and closed by a shutter. However, when the shutter is slid in the horizontal direction, it enters an adjacent shelf's region, thus
15 creating a dead space.

- [0003] To address this, Patent Document 1 (JP 4185818B) proposes the opening and closing of the opening of the mounting port by guiding a sheet-like shutter with rollers. Guiding the sheet with rollers tends to raise dust, and since the sheet-like shutter bends easily, it requires space and has insufficient durability. A linear motion mechanism is
20 needed to guide the leading edge of the shutter, thus raising the cost and raising a large amount of dust.

Citation List

Patent Literature

- 25 [0004] Patent Literature 1: JP 4185818B

Summary of the Invention

Problems to be Solved by the Invention

[0005] An object of this invention is to provide a mounting port that includes a shutter that raises little dust and has a simple opening and closing mechanism, and a method of opening and closing the mounting port.

5

Means for Solving the Problem

[0006] One aspect of this invention is a mounting port via which an article is relayed between a worker and a conveying apparatus or a processing device in a clean room, the mounting port comprising:

- 10 an article mounting stand;
- an apparatus-side opening via which a conveying apparatus or a processing device transfers an article to and from the mounting stand;
- a passageway-side opening that faces a worker passageway;
- a shutter that is provided at a position for opening and closing the
- 15 apparatus-side opening and comprises an arc-shaped plate or a plate bent like an arc; and
- a swing mechanism that swings the shutter about a predetermined axis between a state in which the apparatus-side opening is opened and a state in which the apparatus-side opening is closed.

20 [0007] According to this invention, the opening is opened and closed by the shutter, which comprises an arc-shaped plate or a plate bent like an arc, swinging about the predetermined axis. Since the shutter is swung, a sliding portion and a linear motion mechanism are not needed, little dust is raised, and the cost is low. Furthermore, since the shutter is plate-shaped, it has a higher strength than a sheet-like shutter, and does not

25 bend easily. Note that the shutter may be a combination of multiple plates.

[0008] Preferably, the shutter comprises a pair of shutters,

 the predetermined axis comprises a pair of axes, one axis corresponding to one

shutter, and another axis corresponding to another shutter,

the swing mechanism comprises a driving axis provided at a position symmetrical with respect to the pair of shutters, a motor that rotates the driving axis, the pair of axes, a link mechanism that swings the pair of axes the same angle in opposite
 5 directions by rotation of the driving axis, and a pair of joining members that are attached to the pair of shutters and swing the pair of shutters about the pair of axes,

the pair of axes are provided at positions that are separated from each other and symmetrical with respect to the driving axis, and

the link mechanism is configured such that force applied to the joining
 10 members is not transmitted to the driving axis when the pair of shutters are closed.

[0009] Providing the pair of shutters makes it possible to reduce the amount of space needed to store the shutters in the closed state. Also, the pair of joining members can be swung the same angle in opposite directions by the driving axis provided at a position symmetrical with respect to the pair of shutters, the motor that rotates the
 15 driving axis, the pair of axes provided at positions that are separated from each other and symmetrical with respect to the driving axis, and the link mechanism that swings the pair of axes the same angle in opposite directions by rotation of the driving axis. When the pair of shutters are closed, force applied to the joining members is not transmitted to the driving axis, and therefore the motor does not need to be provided
 20 with a brake.

[0010] More preferably, the pair of shutters are a pair of left and right shutters, and the driving axis and the axes are vertical axes. According to this configuration, the shutters are stored in empty space to the left and right of the mounting port when in the open state.

25 [0011] Preferably, the link mechanism comprises a crank that is attached to the driving axis in a central portion in a lengthwise direction, and a pair of connection rods, ends of the pair of connection rods on one side are respectively rotatably attached to two ends of

the crank, and ends on another side are respectively rotatably attached to the pair of joining members at positions separated from the pair of axes, and the ends of the pair of connection rod on the one side are at respective dead center positions when the pair of shutters are closed. According to this configuration, the pair of shutters are reliably
5 opened and closed by four-bar linkage, and the shutters do not open even if force is inadvertently applied.

[0012] Particularly preferably, the swing mechanism is provided below the mounting port, and a partition that separates the swing mechanism and the mounting stand is provided. According to this configuration, dust raised by the swing mechanism is
10 blocked by the partition and prevented from reaching articles.

[0013] Preferably, the partition is shaped as a flat plate, and a groove that accommodates a side surface of the plate is provided in each of the pair of left and right shutters. According to this configuration, it is difficult for a finger or the like to become pinched in the gap between the side surface of the partition and the shutters.

15 [0014] Most preferably, above the mounting port, a pair of upper joining members that swing coaxially with the pair of axes are provided separately from the pair of joining members provided below the mounting port, and are respectively attached to upper portions of the pair of left and right shutters, and the pair of joining members provided below the mounting port and the pair of upper joining members support the pair of left
20 and right shutters in a manner of non-contact with other portions of the mounting port. According to this configuration, the shutters open and close without coming into contact with surrounding members, thus making it possible to reduce the raising of dust to a very small amount.

[0015] Also, another aspect of this invention is a method for opening and closing a
25 mounting port via which an article is relayed between a worker and a conveying apparatus or a processing device in a clean room,

the mounting port comprising:

an article mounting stand;

an apparatus-side opening that allows a conveying apparatus or a processing device to pass an article to and from the mounting stand;

a passageway-side opening that faces a worker passageway;

5 a shutter that is provided at a position for opening and closing the apparatus-side opening and comprises an arc-shaped plate or a plate bent like an arc; and

a swing mechanism that swings the shutter about a predetermined axis between a state in which the apparatus-side opening is opened and a state in which the apparatus-side opening is closed,

10 the apparatus-side opening being opened and closed by swinging the shutter about the predetermined axis.

Brief Description of Drawings

15 [0016] FIG. 1 is a partial cutout plan view of a mounting port according to an embodiment, in a state in which an upper plate has been removed.

FIG. 2 is a plan view showing a link mechanism for shutter opening and closing, in a state in which the shutters are closed.

FIG. 3 is a plan view showing the link mechanism for shutter opening and closing, in a state in which the shutters are open.

FIG. 4 is a side view of a relevant portion of the mounting port according to the embodiment, in a state in which the shutter on one side has been removed.

FIG. 5 is a plan view showing a variation of the shutters.

25 Description of Embodiment

[0017] The following describes a best mode for carrying out the present invention. The scope of this invention is based on the recitation of the claims, and is intended to be

determined in accordance with the understanding of a person skilled in the art with reference to the recitation of this description and well-known techniques in the field of this invention.

Embodiment

5 [0018] FIGS. 1 to 4 show a mounting port 2 of an embodiment. The mounting port 2 includes an apparatus-side opening 3 (hereinafter, simply "opening 3"). The mounting port 2 is used when conveying semiconductor wafers, reticles, flat panel display substrates, or the like in a clean room, and is provided in a stocker 4 that stores containers containing these articles, for example. Note that the containers will be
10 simply called articles in the following description. 6 indicates a shelf that has the mounting port 2 provided on a portion thereof. 8 indicates a conveying space in which a conveying apparatus 10 such as a stacker crane travels along a rail 9 to convey articles within the stocker 4. The mounting port 2 is a port used when articles are delivered to and received from the stocker 4. Articles are transferred to the mounting port 2
15 through an opening on a passageway 12 side either manually or by an automated guided vehicle or the like, and then conveyed to the front of the shelf 6 by the conveying apparatus 10. Conversely, articles are also transferred from the conveying apparatus 10 to the mounting port 2, and then transferred to the passageway 12 side either manually or by an automated guided vehicle or the like. 14 and 15 indicate vertical
20 supports of the stocker 4.

[0019] In order to avoid interference between the conveying apparatus 10 and people or the like, a pair of left and right plate-shaped shutters 16 and 17 are provided at the boundary between the mounting port 2 and the conveying space 8 of the conveying apparatus 10. The shutters 16 and 17 each comprise a single metal plate or the like,
25 are arc-shaped in a plan view, cannot be folded, and do not include a door roller or the like. Preferably, elastic portions 18 and 19 are provided at the portions where the shutters 16 and 17 come into contact with each other, so as to prevent the raising of dust

and the like due to the contact. The shutters 16 and 17 each swing in a predetermined range with an axis 30 serving as a vertical axis, and the left and right side surfaces of the mounting port 2 are covered by covers 20. When the shutters 16 and 17 open, they move inward of the covers 20, and the shutters 16 and 17 and the covers 20 do not come into contact at that time. The shutters 16 and 17 swing between the state in which the entrance to the mounting port 2 is open and the state in which the entrance is closed as in FIG. 1.

[0020] FIGS. 2 and 3 show a mechanism for opening and closing the shutters 16 and 17. Note that the upper plate has been removed in FIGS. 1 to 3. 22 indicates a driving axis that is located at a position symmetrical with respect to the shutters 16 and 17 and drives a crank 38. 24 and 25 indicate connection rods that swing arms 26 and 28, which are attached to the shutters 16 and 17, 90° for example about the pair of axes 30, 30 arranged at positions symmetrical with respect to the driving axis 22. The driving axis 22 is rotated in a range of approximately 180°, for example, by a motor 32, and the motor 32 does not include a brake. Also, the shutters 16 and 17 are each swingably supported from above the mounting port 2 as well, by an arm 62 and axes 64 (FIG. 4) that is coaxial with the corresponding axes 30, 30, and thus are suspended above the other elements of the mounting port 2. Axes 34 and 35 join the crank 38 and the connection rods 24 and 25, and axes 36 and 37 join the connection rods 24 and 25 and arms 26 and 28. The dashed-dotted lines in FIG. 2 indicate the swinging range (approximately 90°) of the axes 36 and 37. Furthermore, the axes 22, 30, and 34 to 37 comprise bearings or the like.

[0021] In the state in which the shutters 16 and 17 are closed as shown in FIG. 2, and also in the state in which they are open as shown in FIG. 3, the axes 34 and 35 are at dead center, and although the shutters 16 and 17 can be opened and closed by the motor 32, it is difficult for the crank 38 to be swung by the shutters 16 and 17. For this reason, the shutters 16 and 17 do not open or close inadvertently, and there is no need to

provide the motor 32 with a brake. Note that since it is important for the shutters 16 and 17 to not open inadvertently, it is sufficient that the axes 34 and 35 are at dead center when the shutters 16 and 17 are in the closed state as shown in FIG. 2, and these axes are not necessarily required to be at dead center in the state shown in FIG. 3.

5 [0022] In FIG. 1, 40 indicates an operation panel that is used for operation of the stocker 4 or communication with the stocker 4 by the worker or an automated guided vehicle. 42 indicates a magnetic sensor that detects the shutter 17, which comprises a metal plate for example, to confirm that the shutters 16 and 17 are closed. Note that if the shutters 16 and 17 comprise a plastic plate, a metal plate or metal plating may be
10 provided at the position to be detected by the magnetic sensor 42, or the shutters 16 and 17 may be detected by a reflective light projecting/receiving sensor instead of the magnetic sensor 42. Also, a ground controller (not shown) of the stocker 4 controls the opening and closing of the shutters 16 and 17. The shutters 16 and 17 are normally closed, and when it is not confirmed by the magnetic sensor 42 that the shutters 16 and
15 17 are closed, the entrance of the conveying apparatus 10 into the region facing the mounting port 2 is prohibited. When the conveying apparatus 10 arrives at the mounting port 2, the worker's attention is called using the operation panel 40 or the like, the shutters 16 and 17 are opened and closed, and articles are transferred.

[0023] FIG. 4 shows the mounting port 2 in a view from the side, in the state in which
20 the shutter 16 on one side has been removed. 50 indicates a lower plate that is the base portion of the mounting port 2, and 52 indicates an upper plate that is fixed to the lower plate 50 by a vertical support 53. A mounting stand 54 is provided on the upper plate 52, and an article 56 such as an FOUP is mounted thereon. A transfer space 57 is provided between the bottom surface of the mounting stand 54 and the upper plate 52 to
25 enable the movement of a scalar arm, a slide fork, or the like of the conveying apparatus 10 or the like. It is preferable to prevent fingers from being pinched in the gap between the upper plate 52 and the shutters 16 and 17. To achieve this, a groove 58 is

provided in the shutters 16 and 17, and the side surface of the leading edge of the upper plate 52 is accommodated in the grooves 58 as shown in the lower left of FIG. 4. 60 indicates a top plate of the mounting port 2 that is provided with the arms 62 at positions overlapping the arms 26 and 28 in a plan view, and the shutters 16 and 17 are supported thereto by axes 64 that are coaxial with the axes 30, 30. Note that the arms 62 and the axes 64 are provided as pairs of left and right members. The shutters 16 and 17 are supported by the arms 26, 28, 62, and the like, and are suspended above the mounting port 2 in other portions.

[0024] The following describes operations in this embodiment. The shutters 16 and 17 are normally closed, and due to operation of the operation panel 40 or communication with the operation panel 40 by a worker or an automated guided vehicle, an article 56 is transferred to or from the mounting stand 54. After the conveying apparatus 10 transfers the article 56 to or from the mounting stand 54, if it is not confirmed by the magnetic sensor 42 that the shutters 16 and 17 are closed, the conveying apparatus 10 is prevented from entering the region adjacent to the mounting port 2. A worker or an automated guided vehicle checks the transfer of an article on the operation panel 40, and the opening of the shutters 16 and 17 is prohibited until the transfer is completed. When the conveying apparatus 10 stops at a position adjacent to the mounting port, the shutters 16 and 17 are opened and closed, and the article 56 is transferred. Here, when the conveying apparatus 10 accesses the mounting port 2, the worker's attention is called using the operation panel 40 or the like, and access by the automated guided vehicle is prohibited.

[0025] The mechanism for opening and closing the shutters 16 and 17 is summarized as follows.

1) The opening 3 of the mounting port 2 is opened and closed by the pair of left and right plate-shaped shutters 16 and 17 swinging about the axes 30, 30.

2) The shutters 16 and 17 are hidden inward of the cover 20 when opened.

3) A driving axis 22 is located at a position that is bilaterally symmetric as viewed from the pair of shutters 16 and 17, and is rotated by the motor 32 that does not include a brake.

4) A link mechanism that employs the crank 38, the connection rods 24 and 25, and the like converts the rotation of the driving axis 22 into swinging of the arms 26 and 28 about the axes 30, 30 in a bilaterally symmetrical manner.

[0026] With respect to cleanliness in the mounting port 2, the mounting port 2 is configured as follows.

1) The shutters 16 and 17 are suspended above their surroundings and do not have sliding portions, and a linear motion mechanism for moving the shutters 16 and 17 is not provided. Also, there is no mechanism by which the shutters 16 and 17 are bended, folded, or the like. Accordingly, very little dust is raised in the opening and closing of the shutters 16 and 17.

2) The driving axis 22 and the like are arranged below the upper plate 52, and are separated from the space that houses the articles 56.

[0027] Safety is ensured as follows.

1) The conveying apparatus 10 does not enter the region adjacent to the mounting port 2 if the magnetic sensor 42 has not confirmed that the shutters 16 and 17 are closed.

2) The side surface of the upper plate 52 is accommodated in the grooves 58 in the shutters 16 and 17, thus making it difficult for a finger or the like to become pinched in the gap between the shutters 16 and 17 and the upper plate 52.

3) The worker or an automated guided vehicle checks the transfer of articles on the operation panel 40, and the opening of the shutters 16 and 17 is prohibited until the transfer has ended.

4) When the conveying apparatus 10 accesses the mounting port 2, the worker's attention is called using the operation panel 40 or the like, and access by the

automated guided vehicle is prohibited.

[0028] The mounting port 2 further has the following features.

1) The shutters 16 and 17 are stored on the left and right sides, and therefore the shutters 16 and 17 can be stored in the spaces on the sides of the mounting port 2.

5 2) The shutters 16 and 17 are not bent or the like, and therefore durability is high. For example, a sheet-like shutter has low strength.

[0029] Although the pair of shutters 16 and 17 that open to the left and right are described in the embodiment, there is no limitation to this. For example, a single shutter having the axis 30, with the center of the axis 30 being horizontal, may be
10 swung about a horizontal central axis. However, in this case, the space for storing the shutter increases in size. Also, a pair of upper and lower shutters, rather than a pair of left and right shutters, may be swung in a mutually linked manner. However, in this case as well, a large amount of dead space is needed above and below the mounting port 2. Note that the mounting port 2 may be the load port of a processing device instead of
15 the stocker 4. Furthermore, the mounting port 2 need only be accessible by a worker, and does not need to be accessible by an automated guided vehicle.

[0030] Since it is difficult to bend the shutters 16 and 17 into a perfect arc, FIG. 5 shows a simpler example. 72 and 73 indicate shutters that replace the shutters 16 and 17 and are bent at bending portions 75 and 76 so as to follow virtual arcs 70 and 71.

20

DESCRIPTION OF REFERENCE NUMERALS

[0031] 2 Mounting port

3 Opening

4 Stocker

25 6 Shelf

8 Conveying space

9 Rail

	10 Conveying apparatus
	12 Passageway
	14, 15 Vertical support
	16, 17 Shutter
5	18, 19 Elastic portion
	20 Cover
	22 Driving axis
	24, 25 Connection rod
	26, 28 Arm
10	30 Axis
	32 Motor
	34-37 Axis
	38 Crank
	40 Operation panel
15	42 Magnetic sensor
	50 Lower plate
	52 Upper plate
	53 Vertical support
	54 Mounting stand
20	56 Article
	57 Transfer space
	58 Groove
	60 Top plate
	62 Arm
25	64 Axis

CLAIMS

1. A mounting port via which an article is relayed between a worker and a conveying apparatus or a processing device in a clean room, the mounting port
5 comprising:

an article mounting stand;

an apparatus-side opening via which a conveying apparatus or a processing device transfers an article to and from the mounting stand;

a passageway-side opening that faces a worker passageway;

10 a shutter that is provided at a position for opening and closing the apparatus-side opening and comprises an arc-shaped plate or a plate bent like an arc; and

a swing mechanism that swings the shutter about a predetermined axis between a state in which the apparatus-side opening is opened and a state in which the
15 apparatus-side opening is closed.

2. The mounting port according to claim 1,

wherein the shutter comprises a pair of shutters,

the predetermined axis comprises a pair of axes, one axis corresponding to one
20 shutter, and another axis corresponding to another shutter,

the swing mechanism comprises a driving axis provided at a position symmetrical with respect to the pair of shutters, a motor that rotates the driving axis, the pair of axes, a link mechanism that swings the pair of axes the same angle in opposite directions by rotation of the driving axis, and a pair of joining members that are
25 attached to the pair of shutters and swing the pair of shutters about the pair of axes,

the pair of axes are provided at positions that are separated from each other and symmetrical with respect to the driving axis, and

the link mechanism is configured such that force applied to the joining members is not transmitted to the driving axis when the pair of shutters are closed.

3. The mounting port according to claim 2,

5 wherein the pair of shutters are a pair of left and right shutters, and the driving axis and the pair of axes are vertical axes.

4. The mounting port according to claim 3,

10 wherein the link mechanism comprises a crank that is attached to the driving axis in a central portion in a lengthwise direction, and a pair of connection rods,

ends of the pair of connection rods on one side are respectively rotatably attached to two ends of the crank, and ends on another side of the connection rods are respectively rotatably attached to the pair of joining members at positions separated from the pair of axes, and

15 the ends of the pair of connection rods on the one side are at respective dead center positions when the pair of shutters are closed.

5. The mounting port according to claim 4,

20 wherein the swing mechanism is provided in a lower part of the mounting port, and a partition that separates the swing mechanism and the mounting stand is further provided.

6. The mounting port according to claim 5,

25 wherein the partition is a flat plate, and a groove that accommodates a side surface of the flat plate is provided in each of the pair of left and right shutters.

7. The mounting port according to claim 6,

wherein in an upper part of the mounting port, a pair of upper joining members that swing coaxially with the pair of axes are provided separately from the pair of joining members provided in the lower part of the mounting port, and are respectively attached to upper portions of the pair of left and right shutters, and

5 the pair of joining members provided in the lower part of the mounting port and the pair of upper joining members support the pair of left and right shutters in a manner of non-contact with other portions of the mounting port.

8. A method for opening and closing a mounting port via which an article is
10 relayed between a worker and a conveying apparatus or a processing device in a clean room,

 the mounting port comprising:

 an article mounting stand;

 an apparatus-side opening that allows a conveying apparatus or a processing
15 device to pass an article to and from the mounting stand;

 a passageway-side opening that faces a worker passageway;

 a shutter that is provided at a position for opening and closing the
apparatus-side opening and comprises an arc-shaped plate or a plate bent like an arc;
and

20 a swing mechanism that swings the shutter about a predetermined axis between a state in which the apparatus-side opening is opened and a state in which the apparatus-side opening is closed,

 wherein the apparatus-side opening is opened and closed by swinging the shutter about the predetermined axis.