



(51) International Patent Classification:
B66B 3/02 (2006.01)

(21) International Application Number:
PCT/FI2009/000062

(22) International Filing Date:
25 June 2009 (25.06.2009)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20080460 12 August 2008 (12.08.2008) FI

(71) Applicant (for all designated States except US): **KONE CORPORATION** [FI/FI]; Kartanontie 1, FI-00330 Helsinki (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MERI, Timo** [FI/FI]; Valtakäyrä 7 as 5, FI-111 00 Riihimäki (FI). **LOUKAS, Tommi** [FI/FI]; Uramontie 39B, FI-111 20 Riihimäki (FI).

(74) Agent: **KONE CORPORATION**; Patent Department, P.O. Box 677, FI-05801 Hyvinkää (FI).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: ARRANGEMENT AND METHOD FOR DETERMINING THE POSITION OF AN ELEVATOR CAR




Fig. 1

(57) Abstract: The invention relates to an arrangement and a method for determining the position of an elevator car (1) in the elevator hoistway (2). The arrangement comprises a measuring apparatus (3) fitted in connection with the elevator car (1). The measuring apparatus is arranged to form an electromagnetic radio-frequency measuring signal (5), for determining the position of the elevator car. The arrangement also comprises a position identifier (4) fitted in a selected location in relation to the elevator hoistway (2). The position identifier is arranged to connect inductively to the aforementioned electromagnetic measuring signal (5), and also after it has connected to send a determined pulse pattern using the aforementioned measuring signal (5).