

Transmitted-receiver.

This Sheet Has Been Replaced



The invention relates to a transmitter-receiver for at least two frequency ranges, in which at least one antenna arrangement is provided for each frequency range.

Furthermore, the invention relates to a mobile radiotelephone including such a transmitter-receiver.

5 Transmitter-receivers for at least two different frequency ranges are used, for example, for cordless telephones or in the mobile radio domain. The various frequency ranges then relate to, for example, the transmission frequency band and reception frequency band. Fig. 1 shows a circuit diagram of a transmitter-receiver in a mobile radiotelephone. An antenna 1 is used then for transmitting and receiving data. To avoid a transmit signal ending
10 up in the receiver channel 2, the transmitter channel 3 and the receiver channel 2 are to be separated. For this purpose, a duplex filter 4 may be used which comprises two sharp-edged bandpass filters 5 and 6. A bandpass filter 5 is then tuned to the reception frequency band and the other filter 6 to the transmission frequency band. As a result, a transmit signal does reach antenna 1, because the filter 6 has little attenuation for the transmission frequency, but does
15 not reach the receiver channel 2, because the filter 5 blocks this frequency band. A received signal from the antenna 1 is only slightly attenuated by the bandpass filter 5 and thus reaches the receiver channel 2, whereas it is strongly attenuated by the filter 6. Consequently, the duplex filter 4 is to have very small transit losses and a very sharp-edged filter behavior. Furthermore, an active electronic switch 7 (for example, realized by means of PIN diodes)
20 may be used for separating the transmitter channel 3 and receiver channel 2 on the antenna 1, as is represented in Fig. 2. This type of changeover needs an additional control signal for the switch 7, which is to be generated in a costly manner. Furthermore, very strict requirements are made on the switches because very fast switching is to be realized. Furthermore, filters are to be provided which filter the respective frequency band for the transmitter channel 3 and
25 receiver channel 2.

European patent application EP 0 481 986 has disclosed a communication radiotelephone which contains the transmitter and the receiver in one and the same housing, having a first antenna connected to the transmitter and tuned to the transmitter, and a second antenna connected to the receiver and tuned to the receiver, while the two antennas are

9903976-0

1 6 AUG 1999



separated from each other. The communication radiotelephone comprises a housing accommodating a transmitter and a receiver. The communication radiotelephone can transmit and receive simultaneously. A first antenna is connected to the receiver and a second antenna to the transmitter, while the transmitter and the receiver operate in different frequencies. The
5 antennas tuned to the different frequencies are each connected to the receiver and transmitter, respectively via a filter. A separation of transmitter and receiver channel is then achieved in that the transmitting and receiving antennas have asymmetrical radiation characteristics and the position of the radiation characteristic is selected such that the antenna effect is always turned away from the transmitter and receiver. This, however, is highly disadvantageous in
10 devices for transmission systems transmitting and receiving in the same direction. Furthermore, in most cases corresponding radiation characteristics for transmission and reception in a certain direction are required and/or desired.

For this purpose, it is an object of the invention to provide a better transmitter-receiver having a simpler separation of different frequency ranges.

15 According to the invention, the object is achieved in that at least a dielectric resonator antenna (DRA) is provided for forming at least an antenna arrangement. Due to its physical properties a dielectric resonator antenna is operable only in a narrow frequency band around its resonant frequency. Therefore, an antenna arrangement formed by a dielectric resonator antenna has a very narrow frequency band, with which a very good separation of
20 different frequency ranges, for example, for transmission and reception, is achieved. By changing the geometry or other parameters of the DRA, the resonant frequency and the bandwidth can be adapted to the requirements of different transmission systems regarding the frequency ranges to be adhered to.

In a preferred embodiment of the invention, a first antenna is arranged for
25 reception in a first frequency range and a second antenna for transmission in a second frequency range. This embodiment is highly suitable for use in a transmission system having different frequency ranges for transmission and reception, such as, for example, GSM900, GSM1800, DECT and so on.

A further advantageous embodiment of the invention is provided when a first
30 antenna is arranged for reception (or transmission) in a frequency range in a first transmission system and a second antenna for reception (or transmission) in a frequency range in a second transmission system. With this arrangement, the transmitter-receiver may be operated simultaneously in different transmission systems. It is alternatively possible to use more than two antennas, so that more frequency ranges may be used. In addition, further combinations of



various antennas for different frequency ranges of various transmission systems in one transmitter-receiver are conceivable.

Furthermore, the object of the invention is achieved by a mobile radiotelephone including a transmitter-receiver, which includes at least a dielectric resonator antenna (DRA) for forming at least one antenna arrangement.

These and other aspects of the invention are apparent from and will be elucidated, by way of non-limiting example, with reference to the embodiments described hereinafter.

10

In the drawings:

Fig. 1 shows a circuit diagram of a transmitter-receiver with a duplex filter,
Fig. 2 shows a circuit diagram of a transmitter-receiver with an electronic switch,
Fig. 3 shows a circuit diagram of a transmitter-receiver according to the invention, and
15 Fig. 4 shows a dielectric resonator antenna to be used in a transmitter-receiver according to the invention.

Fig. 3 shows a transmitter-receiver that includes a receiver channel 2 with a
20 receiving antenna 8 and a transmitter channel 3 with a transmitting antenna 9. As receiving antenna 8 and transmitting antenna 9 are used dielectric resonator antennas (DRA) which distinguish themselves by a high degree of miniaturization and the possibility of surface mounting (SMD technique). Furthermore, a DRA, because of its physical properties, has a very narrow frequency band (only operable in a very narrow frequency band around the
25 resonant frequency). The dielectric resonator antenna comprises a dielectric body (usually ceramic) deposited on a metallized surface. However, also other antennas having such properties may be used, such as, for example, a microstrip antenna for which a conductive structure is deposited as a radiating element on a (mostly dielectric) substrate, while a conductive layer on the back of the substrate forms the reference potential. The transmitting
30 antenna 9 is tuned to the transmitter frequency and the receiving antenna 8 to the receiver frequency. Due to the narrow-band properties, no further filters are necessary for separating receiver channel 8 and transmitter channel 9. The respective frequency ranges may be tuned to by a special design of the radiating elements of the dielectric substrate (resonator) or the way



in which the signal is supplied. The signal is mostly supplied via a coaxial line or a microstrip line.

Clearly narrower bandwidths may be achieved with a transmitter-receiver having a receiving antenna 8 and a transmitting antenna 9 which may each be realized by a dielectric resonator antenna. For a transmitter-receiver to operate in different frequency ranges, it is especially important to have a limitation of each respective bandwidth. This avoids a disturbance of a channel by a signal in another channel (for another frequency range). Since the antennas 8 and 9 used in the transmitter-receiver according to the invention have a very narrow frequency band, additional filters may be omitted.

In Fig. 4 is represented a DRA 10 in its basic form to be regarded as an example. Besides the form of a parallelepiped, other forms are also possible, such as, for example, cylindrical or spherical geometry. Dielectric resonator antennas are resonant components that work only in a narrow band around one of their resonant frequencies. The resonant frequency of the DRA 10 depends on the dimensions of the DRA 10. In order to obtain the smallest possible dimensions, mostly the lowest resonance (TE_{111}^2 -mode) is used. The DRA 10 shown is realized by means of a parallelepiped having dimensions $40 \times 40 \times 7.6 \text{ mm}^3$ of a (Ba,Nd,Gd)TiO₃ ceramic. This material is suitable for high frequencies, has a dielectric constant of about $\epsilon_r = 85$, low dielectric losses of $\tan \delta = 4 \times 10^{-4}$ and a low dielectric temperature coefficient of $\tau_\epsilon = -30 \text{ ppm/}^\circ\text{C}$ (NPO characteristic). The operating frequency of the DRA 10 lies at 1 GHz in its lowest resonance (TE_{111}^2 - mode). For different dimensions the resonant frequency is shifted. Typical dimensions for a DRA 10 having an operating frequency of about 1.9 GHz (DECT) lie at about $20 \times 20 \times 6 \text{ mm}^3$.

Highly suitable is such a transmitter-receiver for mobile radio telephony in which different frequency ranges are used for transmission and reception (for example, according to GSM the frequency ranges 890-915 MHz and 935-960 MHz for transmission and reception, respectively). Furthermore, cordless telephones according to DECT, mobile radiotelephones for DCS1800 and PHS and devices for other transmission systems utilizing different frequency ranges in one device, may be fields of application. Also conceivable are combined devices operating in more than one transmission systems.

CLAIMS:

This Sheet Has Been Replaced

1. A transmitter-receiver for at least two frequency ranges, in which at least one antenna arrangement (8, 9) is provided for each frequency range, characterized in that at least a dielectric resonator antenna (DRA) is provided for forming at least an antenna arrangement (8, 9).
- 5 2. A transmitter-receiver as claimed in claim 1, characterized in that a first antenna (8) is provided for reception in a first frequency range and a second antenna (9) for transmission in a second frequency range.
- 10 3. A transmitter-receiver as claimed in claim 1, characterized in that a first antenna (8) is provided for reception in a frequency range in a first transmission system and a second antenna (9) for reception in a frequency range in a second transmission system.
- 15 4. A transmitter-receiver as claimed in claim 1, characterized in that a first antenna (8) is provided for transmission in a frequency range in a first transmission system and a second antenna (9) for transmission in a frequency range in a second transmission system.
- 20 5. A mobile radiotelephone including a transmitter-receiver for at least two frequency ranges in which at least one antenna arrangement (8, 9) is provided for each frequency range, characterized in that at least a dielectric resonator antenna (DRA) is provided for forming at least an antenna arrangement (8, 9).

