

Device for the cleaning of vessels

The present invention relates to a device for the cleaning
5 of vessels.

In particular, the invention is intended to clean the
submerged part of the hull and other parts of vessels that
have been treated with a non-toxic layer of paint based on
10 a surface-treated coating such as, for example, a composite
reinforced with glass flakes.

Traditionally, the hull and other components of a vessel
are treated with a biocide-containing toxic layer of paint.
15

Such layer of paint is to combat so-called biofouling.

It is known that on the hull of a vessel, in particular of
a sea-going vessel, more specifically on the part located
20 under water, shellfish, algae and other organisms grow,
such that the vessel experiences greater resistance while
moving through the water. Consequently, the consumption of
fuel increases.

25 Preferably, preventive action is taken and the slime layer
that is deposited on a new or cleaned hull and on which
said biofouling attaches, is cleaned at regular intervals.

A disadvantage of the known biocide-containing toxic layer
30 of paint is that such layers of paint easily wear off
and/or are damaged during cleaning. Consequently, it is

necessary for the layer of paint to be applied again after a number of cleanings.

Moreover, after a number of cleanings, the effect of the
5 layer of paint will decrease, such that more biofouling will occur when the vessel is operational again.

This biofouling causes the vessel to experience more resistance when moving through the water. Consequently, the
10 consumption of fuel increases.

Moreover, vessels treated with such layers of paint cannot be cleaned when the vessel is located in the water.

15 During the cleaning of such vessels with traditional layers of paint, many toxic substances are indeed released which are harmful for the environment and marine life.

Consequently, it is necessary that the cleaning of the hull
20 and other parts of the vessel takes place in a dry dock.

The disadvantage of this method is that it takes a lot of time, which means the vessel is unavailable for a long time.

25

Vessels treated with a surface-treated coating, such as a composite reinforced with glass flakes, experience said disadvantages to a much lesser extent, as the layer of paint is much more resistant and does not contain any toxic
30 substances that may be released during cleaning.

Typically, the cleaning of such vessels treated with a surface-treated layer of paint is done in the water by divers by means of machines with rotating brushes.

- 5 Although the cleaning of vessels with a surface-treated layer of paint can be done much faster and easier than in the case of vessels with a toxic traditional layer of paint, there are some disadvantages to using divers.
- 10 Visibility in the water may be limited, which may make it difficult to carry out the cleaning properly.

Moreover, the divers are sometimes exposed to strong currents under water, which can make cleaning dangerous.

- 15 In addition, a large number of professional divers are needed who are spread around the world in the ports, whereby the hiring of suitable divers can sometimes be a problem.

- 20 Even with this method the cleaning of a vessel takes one or more days, a period during which the vessel is not operationally available.

- 25 From the Belgian patents nos. 1.013.429, 1.014.204 en 1.015.235 of the same applicant, devices are known for the removal of the biofouling on a vessel's hull, said devices consisting of a cleaning element which is pressed against the hull of the vessel by means of a cable that runs
- 30 transversely under the hull of the vessel and whereby the cleaning element, by running the cable under the vessel, is moved across the hull from one side of the hull to the

other side of the hull, thus cleaning a strip of the width of the mat on the hull.

To run said cable under the vessel, this cable is attached
5 for example to two winches set up opposite from each other on either side on the deck of the vessel, whereby, for the cleaning of the hull, the cable is rolled up on one winch, while rolling off the other winch respectively.

10 Each of said winches is set up movably lengthways of the vessel to be able to clean the hull strip after strip.

However, said known devices do not always achieve the hoped for result, particularly in vessels with a flat bottom as
15 is usually the case in big sea-going vessels with a length of for example 400 metres or more but also in the case of relatively small vessels of for example 80 metres in length.

20 Such flat bottom can cover a considerable surface of for example 400 metres by 55 metres. It's clear that cleaning such surface by divers represents a considerable workload.

Another disadvantage concerns the bilge keels, these are
25 long plates that are placed lengthways in a perpendicular direction to the hull, at the location where the hull changes from the bottom to the side.

At the location of the bilge keels, the cleaning elements
30 cannot make any or only difficult contact with the bottom either, as they have to move over the bilge keels there.

This location also causes problems with the cable scraping along the bilge keels.

5 The purpose of the present invention is to provide a solution to at least one of said and other disadvantages.

To this end, the invention relates to a device for the cleaning of a submerged section of the hull of a vessel that has been treated with a non-toxic layer of paint based
10 on a surface-treated coating, characterised in that the device comprises a platform with a first cleaning module and with means to place and move the cleaning module against the side of the hull of the vessel and that the device is further provided with a launch platform with a
15 second cleaning module which can place the second cleaning module against the bottom of the hull, whereby the second cleaning module is connected via a first cable to the launch platform for the movement and control thereof.

20 This provides the advantage that with the help of such a device, the hull of a vessel can be cleaned quickly and on an industrial scale.

Moreover, the vessel does not have to be in a dry dock,
25 considering that the cleaning can be done under water. Moreover, no divers are needed.

By using the surface-treated coating, there will be practically no biofouling, this means that practically no
30 biofouling will be formed on the vessel's hull, which in turn results in the vessel experiencing less resistance. In

this way fuel can be saved and there will be less CO₂ emission.

Moreover, when cleaning a surface-treated coating no
5 biocides will be released and cause local pollution.

In addition, a surface-treated coating will not be damaged or partially removed by cleaning, such that no corrosion problems will occur.

10

The surface-treated coating will also require less maintenance.

Yet another advantage consists in that by using the launch
15 platform and the second cleaning module specifically for the bottom of the hull, it is possible to avoid a cleaning module or a cable having to pass over or along a bilge keel. In this way, the poor cleaning of the hull at the location of the bilge keels as well as the scraping of the
20 cable along the bilge keels can be avoided.

Moreover, the bilge keels themselves and the vessel's hull on the level of the bilge keels can also be cleaned by allowing both the first and the second cleaning module to
25 come up against the bilge keels.

Preferably, the first and second cleaning module comprise a frame with a number of roller brushes mounted therein, whereby the roller brushes are driven by a motor, whereby
30 the axles of the roller brushes extend horizontally and parallel to the hull of the vessel during operation.

Such cleaning module can be made in a big size, and a big cleaning surface will be obtained.

5 The roller brushes will suck themselves as it were against the hull of the vessel during operation under water as a result of the swirls in the water caused by the rotation of the roller brushes around their axles.

10 In a practical embodiment, the platform is a vessel or the like.

This has the advantage that the device can be placed in a port or the like, whereby vessels can sail along the platform, after which the two cleaning elements can be placed against the side and the bottom of the hull to clean the hull.

20 The vessel may be, for example, a workboat, pontoon or the like.

With the intention of better showing the characteristics of the invention, a few preferred embodiments of a device according to the invention for the cleaning of vessels are described hereinafter by way of an example, without any limiting nature, with reference to the accompanying figures, wherein:

figure 1 schematically shows a device according to the invention;

30 figure 2 on a larger scale and in more detail shows the section indicated in figure 1 by F2;

figure 3 shows a practical embodiment of a cleaning element.

Figure 1 schematically shows a sea-going vessel 1, the hull
5 2 of which is located in the water.

The hull 2 is provided with so-called bilge keels 3, which extend in a longitudinal direction of the vessel 1 on the location where the side 4 of the hull 2 changes into the
10 bottom 5 of the hull 2.

The bilge keels 3 are installed perpendicular to the hull 2.

15 The hull 2, or at least the submerged sections of the hull 2, are treated with a non-toxic layer of paint based on a surface-treated coating.

In this case this surface-treated coating comprises a
20 composite reinforced with glass flakes.

The advantage of such coating is that it is not only far more effective in preventing biofouling of the vessel's hull 2, but also that no biocides will be released when
25 cleaning the vessel's hull 2. Moreover, the coating will not be damaged or wear off, such that practically no maintenance or repairs are necessary to the coating itself.

Figure 1 also shows a device 6 for the cleaning of a
30 submerged section of the hull 2 of the vessel 1.

According to the invention, the device 6 comprises the following components:

- a platform 7 with a first cleaning module 8 and with means 9 to place and move the cleaning module 8 against the side 4 of the hull 2 of the vessel 1; and
- a launch platform 10 with a second cleaning module 11 which can place the second cleaning module 11 against the bottom 5 of the hull 2.

10

As shown in the figure, in this case there are two platforms 7 and two first cleaning modules 8 and two launch platforms 10 with two second cleaning modules 11. In other words, the device 6 is made symmetrically. This is not necessary for the invention.

15

The platform 7 in the example shown is made as a vessel, such as for example a floating pontoon or workboat. However, this is not necessarily the case. The platform 7 could also be on the quay.

20

Said means 9 to place and move the cleaning module 8 against the side 4 of the hull 2 can be realised in different ways. For the efficient operation of the device 6 it is sufficient if these means 9 can move the cleaning module 8 up and down against the hull 2 of the vessel 1.

25

The launch platform 10 can be made as a kind of cage, in which the necessary equipment is installed and to which or in which the second cleaning module 11 can be installed.

30

This launch platform 10 is intended to be submerged in the water. As will be clear from the description, this launch platform 10 can be considered as an underwater engine room, also called a 'submergable engine room'.

5

According to the invention the second cleaning module 11 is connected via a first cable 12 to the launch platform 10 for the movement and control thereof.

10

Figure 2 shows a section of the device 6 in more detail.

This figure shows that the platform 7 is provided with a control unit 13 to control the movement of the platform 7 and of the first cleaning module 8.

15

The launch platform 10 is connected to the platform 7, in particular to the control unit 13 of the platform 7, by a second cable 14 to control the launch platform 10.

20

It is clear that the launch platform 10 can also be controlled in other ways other than by the second cable 14 and the control unit 13.

25

It is also not excluded that the second cleaning module 11 is also controlled by the second cable 14.

However, in this case, the launch platform 10 is provided with a control unit 15 to control the second cleaning module 11.

30

The control is via said first cable 12. This cable 12 is what is called an "umbilical cable", a rigid, thick and not

very flexible cable 12 to send all the necessary control signals, electrical and hydraulic energy, etc. from the launch platform 10, in particular from the control unit 15, to the second cleaning module 11.

5

By working with the launch platform 10 for the second cleaning module 11, this first cable 12 can be kept much shorter than when the second cleaning module 11 were to be connected via the platform 7.

10

The first cable 12 will also be used to control the movement of the second cleaning module 11.

The launch platform 10 is also provided with propulsion means 16, such as for example propellers, rotors, thrusters or the like to move under water.

Furthermore, the launch platform 10 is provided with a stop 17 for the hull 2 of the vessel 1 in the form of one or more wheels, fender cushions or the like.

This will allow the launch platform 10 to come very close, up against the hull 2 of the vessel 1, without the possibility of damage, both to the vessel 1 and the launch platform 10.

As shown in figure 1, the two second cleaning modules 11 are connected to each other by means of a cable 18, said cable hereinafter referred to as the 'connecting cable 18'.

30

This connecting cable 18 can be a regular cable and does not have to be a so-called "umbilical cable". It will only

be used for the physical coupling of the second cleaning modules 11 to each other and not for control, energy transfer or the like.

- 5 This cable 18 will be used to be able to move both cleaning modules by pulling, this will be explained later.

Figure 3 shows a possible embodiment of a cleaning module 8, 11 in more detail.

10

- The cleaning module 8, 11 comprises a frame 19 with a number of roller brushes 20 mounted therein, whereby the roller brushes 20 are driven by a motor 21, whereby the axles 22 of the roller brushes 20 extend horizontally and
15 parallel with the hull 2 of the vessel 1 during operation.

The roller brushes 20 thus also extend parallel to each other and are placed in a sort of staggered set-up.

- 20 In this case there are three roller brushes 20, which can rotate around their axles 22. It is also possible there are only one, two, four, five or more roller brushes 20.

- The roller brushes 20 overlap slightly in a direction
25 perpendicular to the axles 22, such that a completely uninterrupted cleaning surface is obtained when the cleaning module 8, 11 is moved over the hull 2 of the vessel 1.

- 30 In this case the launch platforms 10 also contain one or several floats 23 or floating elements or the like which will generate an upthrust. Preferably, the upthrust of

these floats 23 is adjustable. This could be realised, for example, by making the floats 23 in the form of air cushions or the like, which can be filled with more or less air in order to regulate the upthrust of the floats 23.

5 The operation of the device 6 is very simple and as follows.

The platforms 7 and the launch platforms 10 first sail to a vessel 1 to be cleaned.

10

The platforms 7 position themselves on either side of the vessel 1 with the first cleaning modules 8 oriented to the side 4 of the hull 2.

15 The launch platforms 10 are placed on the level of the bottom 5 of the hull 2, by possibly raising or lowering them in the water such that they are at the right level, whereby the second cleaning modules 11 are located on the level of the bottom 5 of the hull 2. Said floats 23 can be
20 used for this.

The stops 17 will be up against the hull 2 or bilge keels 3.

25 Then the whole device 6 moves along the vessel 1, as shown in figure 1, whereby the first cleaning modules 8 make contact with the side 4 and the second cleaning modules 11 with the bottom 5.

30 It is of course also possible that the device 6 is set up at a certain location and that the vessel 1 sails to it.

The device 6 can then be put into operation. The roller brushes 20 of the cleaning modules 8, 11 are put into operation by switching on the motors 21.

5 The cleaning modules 20 will suck themselves, as it were, onto the hull 2 of the vessel 1.

The cleaning of the hull 2 can then be started: the first cleaning modules 8 are moved in an upward and downward movement against the side 4 by the platforms 7.

10

They will move up against the bilge keels 3, to clean the hull 2 at the level of the bilge keels 3 and the upward facing side of the bilge keels 3 themselves.

15 The second cleaning modules 11 are moved back and forth over the bottom by alternately rolling up and down or extending and retracting the first two cables 12, in such a way that the two second cleaning modules 11, by the operation of the connecting cable 18 between both second
20 cleaning modules 11, are moved synchronously back and forth over the bottom 5 of the hull 2.

The second cleaning modules 11 will also move up against the bilge keels 3 to thus clean the hull 2 on the level of
25 the bilge keels 3 and the downward facing side of the bilge keels 3 themselves.

After one upward and downward movement of the first cleaning modules 8 and one lateral back and forth movement
30 of the second cleaning modules 11 the biofouling will be removed.

Possibly a second movement of the cleaning modules 8, 11 can be executed.

The device is then moved to a following section of the hull 2 to be cleaned. Alternatively, the vessel 1 can also be
5 repositioned in relation to the device 6.

The cleaning modules 8, 11 are moved in a similar way as described above on the next section of the hull 2 to be cleaned.

10

It is also possible that the cleaning modules 8, 11 make a continuous upward and downward and back and forth movement, while the device 6 moves slowly along the vessel 1 or the vessel 1 moves slowly through it.

15

In this way, the hull 2 and bilge keels 3 can be cleaned quickly. To clean the front and the back of the vessel, divers can be used. These sections constitute only a small share of the total surface area of the vessel.

20

Although in the example shown above, the cleaning modules 8, 11 comprise roller brushes, it cannot be excluded that the first and second cleaning modules 8, 11 comprise a frame 19 with a number of sponges mounted therein. By the
25 upward and downward and back and forth movement of the cleaning modules 8, 11 against the vessel's hull 2, the sponges can be rubbed against the vessel's hull 2 to thus clean the hull 2.

30 The present invention is by no means limited to the embodiments described as an example and shown in the drawings, but a device according to the invention for the

cleaning of vessels can be realised in all kinds of forms and dimensions, without departing from the scope of the invention.

Claims.

-
- 1.- Device for the cleaning of a submerged section of the
5 hull (2) of a vessel (1) that is treated with a non-toxic
layer of paint based on a surface-treated coating,
characterised in that the device (6) comprises a platform
(7) with a first cleaning module (8) and with means (9) to
place and move the cleaning module (8) against the side (4)
10 of the hull (2) of the vessel (1) and that the device (6)
is further provided with a launch platform (10) with a
second cleaning module (11) which can place the second
cleaning module (11) against the bottom (5) of the hull
(2), whereby the second cleaning module (11) is connected
15 via a first cable (12) to the launch platform (10) for the
movement and control thereof, whereby the launch platform
(10) is connected to said platform (7) by a second cable
(14) for the control of the launch platform (10).
- 20 2.- Device according to any one of the previous claims,
characterised in that the launch platform (10) is provided
with a stop (17) for the hull (2) of the vessel (1) in the
form of one or several wheels, fender cushions or the like.
- 25 3.- Device according to any one of the previous claims,
characterised in that the first and second cleaning module
(8, 11) comprise a frame (19) with a number of roller
brushes (20) mounted therein, whereby the roller brushes
(20) are driven by a motor (21), whereby the axles (22) of
30 the roller brushes (20) extend horizontally and parallel
with the hull (2) of the vessel (1) during operation.

4.- Device according to claim 1 or 2, characterised in that the first and second cleaning module (8, 11) comprise a frame (19) with a number of sponges mounted therein.

5 5.- Device according to any one of the previous claims, characterised in that the platform (7) is a vessel or the like.

6.- Device according to any one of the previous claims,
10 characterised in that there are two platforms (7) and two first cleaning modules (8) and two launch platforms (10) with two second cleaning modules (11).

7.- Device according to claim 6, characterised in that the
15 two second cleaning modules (11) are connected to each other by means of a cable (18).

8.- Device according to claim 7, characterised in that the second cleaning modules (11) are moved over the bottom (5)
20 of the hull (2) of the vessel (1) by alternately rolling up and down or extending and retracting the first two cables (12), in such a way that the two second cleaning modules (11) are moved synchronously back and forth over the bottom (5) of the hull (2).

25

9.- Device according to any one of the previous claims, characterised in that the second cleaning module (11) is provided with one or several floats (23), floating elements or the like.

30

10.- Device according to any one of the previous claims, characterised in that the coating is a composite reinforced with glass flakes.