

Fastening device for a chair

Embodiments of the present invention concern a fastening bracket for a chair, such as a children's chair with a seat plate, wherein the seat plate has a vertical hole in the front edge. Embodiments of the invention are especially suitable for a chair having the possibility for vertical and horizontal adjustment of the seat plate. Further, embodiments of the invention concern a harness and seating rail set for the fastener bracket and the use of the fastening bracket and the set.

Background of the invention

It is well known that small children, that is children such as from the age when they may sit by themselves (about 6-7 month) until they master sitting safely in a children's chair without falling out (about 2 years), need harnesses securing them sitting safely in children's chairs.

Often, conventional harnesses are used, such as those accompanying a children's pram, a children's chair of which may be bought separately. In new children's chairs the harnesses are often anchored by straps on each side of the seat in integrated fastening means, such as eyes or similar. Such harnesses have the disadvantage that they require integrated fastening means in the chair and also hinder the child in turning the upper body to the side because the straps on each side of the harness must be relative short. This short length of the straps is to secure that the child sits safely in the chair, but this hinders and generally irritates the child.

In later years, a development has evolved in the direction of more countries and regions having their own safety requirements and regulations for equipment to be used for children, such as for children's chairs and harnesses. This must continuously be taken into account in the development of new children's chairs, but it may be difficult to adapt chairs which have been produced for a long time, before such safety regulations were put into force. It is especially difficult to perform such adaptation without making physical interventions in the chairs.

This is for example the case with the Tripp Trapp® children's chair which was developed as early as in 1972 and patented in 1976 and which still is a very popular children's chair in many countries.

The chair is designed to be adjusted in coherence with the growing body size of the child and therefore has a seat plate and a foot plate which may be moved into different height positions by gliding into tracks distributed upward along the length of the side pieces and being locked by tightening the distance between the side pieces. The sitting plate may further be adjusted in the depth position by the plate being pushed in and out (forward and backward) in relation to the back rest, and thereby providing the child using the chair, a correct seat length under the thighs.

It has proven difficult to adapt existing seats to new effective requirements, especially in order to retain the above-mentioned original functions of the chair. In order to achieve this, the fastening or fasteners for a children's harness should be able to follow the height position of the seat.

In addition to fastening a harness to such chairs, it may also be desirable to be able to mount a children's seating rail, which either may be used alone or simultaneously with the harness.

Embodiments of the present invention seek to provide a fastening means for this additional equipment so that also owners of older chairs may upgrade their chairs. As mentioned, embodiments of the present invention seek to avoid physical intervention in the chair, such as making holes in any of the parts or inserting screws that leave spoiling marks in the chair, which will be visible when there no longer is use for the children's equipment. Moreover, such adaptations involve a risk of the user making adaptations in the wrong manner, and that the safety is not kept intact. Embodiments of the invention seek to make the fastening of the children's equipment as intuitive and simple as possible, and upholding the safety at the same time.

NO 323899/ WO 2007/097637, Peter Opsvik AS, shows a fastening bracket for use in a seat plate with a vertical hole in a children's chair of the type mentioned above. The bracket comprises a fastening means with a slit for placing on the underside of the seat plate, and a lining clip with vertical locking pegs which are guided through the hole in the seat plate from the top side and which is locked on the top side of the seat plate by a flange which is larger than the hole. The locking pegs have horizontal holes wherein a locking pin is inserted for locking the fastening device to the lining clips on the underside of the seat plate. The fastening device may in addition comprise an edge slit protruding in front of the seat plate for insertion of a part of a children's seating rail.

In order to secure that the fastening of equipment as mentioned above is carried out in a correct manner, and that it is intuitive, embodiments of the present invention seek to limit the number of parts to reduce the possibility for such parts being installed wrongly. A few number of parts also reduces the possibility for individual parts to be lost during storage of the equipment, such as in-between periods when the equipment is not used, for later to be brought out when for example the next child is grown enough to sit in a children's chair. In such periods, there is also the chance that the original user guide disappears.

Faulty installation is often a consequence of the user not reading the user guide or not understanding the user guide, it may be that the language and/or the illustrations for installation are difficult to understand, or that the user guide has disappeared. Embodiments of the present invention seek to reduce the possibility of installing the equipment in a manner that seemingly may be perceived as correct for the consumer, or as a possible alternative installation manner, but which in use will not tolerate the loads that the equipment is meant to be exposed to.

Further, embodiments of the present invention seek to obtain a fastening device which is small, discrete and less bothersome for the user, both physically and ecstastically. At the same time, such a fastening device should not protrude outside of the outer edges of the chair both to hinder that it absorbs impact and is damaged if the chair for example is tipped over and to allow a cushion with a pocket in the frontal edge to be installed in the chair, wherein the pocket is thread over the entire front edge of the chair.

Description of the invention

Embodiments of the present invention disclose a fastening bracket for the fastening of children's equipment which solves the above mentioned problems. The bracket may be part of a harness set and/or seating rail set particularly adapted for use in a children's chair.

The bracket consists of one single fastening device with a bow, which is entered into the hole in the seat plate from the topside and which allows for a part of a children's harness to be thread through the bow and/or that a part of the children's seating rail to be inserted down into and fastened in the fastening device.

Embodiments of the present invention concern a fastening bracket, a harness set, as well as the use of this according to the appended disclosure and according to the aspects given below.

In one aspect, the invention provides for a fastening device for use in a children's chair with a seat plate, wherein the seat plate has a vertical through hole for the mounting of the fastening device, characterized in that the fastening device comprises: at least one cross piece connected to two side pieces which are joined by at least one cross bar and defining an opening, wherein the cross bar is positioned in a vertical distance from the cross piece when the fastening device is mounted; and at least two mainly vertical lining elements to be inserted into the hole, connected to the underside of the cross piece and/or side pieces in their upper ends, wherein the lining elements each comprise at least one locking hook in their lower ends which have a larger horizontal extent than the lining elements.

In another embodiment at least parts of the mentioned cross piece and the mentioned side pieces comprise a contact surface on the underside of the pieces to bear against the top side of the seat plate, preferably an open or closed continuous contact surface, even more preferably a contact surface stretching in a half circle around the outer sides of the lining elements.

In a further embodiment the fastening device allows for insertion of a part of a children's seating rail, preferably a crouch strap, through the opening when the fastening device is mounted in a seat plate, preferably an extremity with a snap flap which flips out on the underside of seat plate to which the fastening device is attached; and/or the fastening device allows a part of a children's harness, preferably a crouch strap, to freely run around the cross bar when the fastening device is mounted in a seat plate, preferably simultaneously with a part of a children's seating rail being fastened through the fastening device.

In one embodiment the locking hooks are directed partly towards each other, preferably about 45 degrees in relation to the length and/or transverse direction of the fastening device, and in another embodiment each lining element (14) comprises two locking hooks, preferably directed towards each other, more preferably about 45 degrees in relation to the length and/or transverse direction of the fastening device. In an alternative embodiment each lining element comprises flexible zones with reduced rigidity to allow torsion and/or bending of the locking hooks, such as wherein the reduced rigidity is achieved by countersinks present in the lining elements, and/or by

the complete or part of the lining elements comprising a more flexible material than the rest of the fastening device. In one embodiment the locking hooks are locked by inserting a part of a seating rail through the opening of the fastening device.

In a further embodiment the side pieces have an increasing height from the cross piece towards the cross bar, preferably that they are wedge formed.

In a second aspect, the invention provides for a harness set for a children's chair having a back rest and seat plate with a vertical hole in the front edge, characterized in that it comprises the fastening device according to any of the above and a children's harness comprising a crouch strap which may be anchored in the fastening device, and preferably a back strap running around at least one cross piece of the back rest in the children's chair it is fastened to.

In a third aspect, the invention provides for a seating rail set for a children's chair having a back rest and seat plate with a vertical hole in the front edge, characterized in that it comprises the fastening device according to any of the above and a children's seating rail with a crouch strap which may be anchored to the seat plate via an extremity which may be guided through the opening in the fastening device and the hole in the seat plate, the extremity preferably having a snap flap which flips out on the underside of the seat plate and the children's seating rail more preferably having end pieces which may be inserted into slits in the side pieces of the chair.

In a forth aspect, the invention provides for a combined harness and seating rail set comprising the sets above.

In a fifth aspect, the invention provides for the use of a fastening device according to any of the above, or a set according to any of the above, for mounting a harness and/or a seating rail in a children's chair wherein the seat plate has a vertical hole and wherein the chair has the possibility of vertical and horizontal adjustment of the seat plate.

The above aspects of the invention will in the following be described in greater detail by the help of the examples of embodiments and the appended figures, none of which are meant to limit the scope of the invention.

Short description of the drawings

Figure 1 shows a perspective view of a first embodiment of the fastening device seen from above.

5

Figure 2 shows a perspective view of the fastening in figure 1 seen from below.

Figure 3 shows a planar view of the fastening in figure 1 seen from above.

10

Figure 4 shows a planar view of the fastening in figure 1 seen from below.

Figure 5 shows a side view of the fastening in figure 1 seen from the rear.

Figure 6 shows a side view of the fastening in figure 1 seen from the (left) side.

15

Figure 7 shows a perspective drawing and a second embodiment of the fastening device seen from above.

Figure 8 shows a perspective cut-out of the fastening device in use in a chair with a fastened seating rail.

20

Detailed description

In the description to follow the following words and terms should be understood as follows:

25

By "front", "front side" or "foremost" is meant the horizontal direction which the face and chest of a child sitting in a chair in an ordinary manner is facing towards; and

30

By "behind", "rear" or "at the back of" is meant the opposite horizontal direction, that is the direction towards which the back of a child sitting in a chair in an ordinary manner is facing towards.

35

By "traverse" side or direction is meant the horizontal direction perpendicular to the symmetrical plane through the chair; and

By "length", "depth" or "length direction" is meant the horizontal direction in the symmetrical plane of the chair.

The terms "cross piece" and "side pieces" are not to be understood as linear straight or individual elements that necessarily are separate pieces joint together in clear joints, but rather as elements that have the same functions as the named pieces, and which may have a smooth or progressive junction between them.

In figure 1 fastening device 10 is shown in perspective from above, i.e. from the side of which the top side of the seat plate is directed towards and from the front side of the chair. The fastening device 10 has in this embodiment a flange in shape of a rounded rectangular or trapezoid shape with a front cross piece 1, two wedge-shaped side pieces 2 and a rear upper cross bar 3. From the flange, two parallel lining elements 4 protrude downward from the underside of the side pieces, having locking hooks 5 in their lower ends. The flange surrounds an opening 6 where one end of a crouch strap or a strap from a children's seating rail may be inserted.

The shape of the fastening device and flange, is not limited by the present embodiment of a rectangular or trapezoid shape, and may of course have any suitable form, such as an oval, circular, polygonal shape or any shape therein between, included any rounded form, which also applies to the cross piece and side pieces thereof.

In figure 2 the fastening device 10 is shown from below. As may be seen the front crosspiece 1 has a flat underside which makes up a part of a contact surface 7 which should bear against the top side of a seat plate. The contact surface 7 stretches from the front cross piece 1 and further out to the sides of the cross piece and on the underside of the side pieces 2, around the outside of the lining elements 4 wherein they are fastened to the side pieces 2. The contact surface 7 thus forms two half circles facing each other about the lining elements 4, wherein the half circles are joined by the front cross piece 1 and together form a stable flange when the fastening device is strapped down to the underside of the seat plate by the locking hooks 5. As may be seen in figure 2, the rear cross bar 3 is in a vertical higher position compared to the contact surface 7, so that a strap may run around the cross bar and through the opening 6, in order to fasten a children's harness to the seat plate.

In figure 3, the fastening device 19 is seen directly from above and the rounded trapezoidal form of the device of this embodiment as well as the opening 6 is especially

visible. As may be seen from this angle, the two locking hooks 5 partly protrude out into the opening 6, and these surfaces together with the rest of the horizontal top surface of the locking hooks 5, will after mounting through a hole in the seat plate, bear against the underside of the seat plate.

5

In figure 4 the fastening device 10 is seen directly from the underside. The locking hooks 5 will during mounting be twisted towards each other so that they may be guided through an oblong shaped hole in the seat plate, such as an oblong rounded rectangular hole, and will flip back into the position shown in the figure as the hooks exit on the
10 underside of the seat plate. The hole in the seat plate will in this embodiment typically have a form and extent which follows the transition between the contact surface 7 and the lining elements 4 as they appear in the figure.

In figure 5 the fastening device 10 is seen directly from behind as the upper cross piece
15 3 is totally visible and the front crosspiece emerges behind the side pieces 2. From this angle the vertical distance between the front 1 and rear 3 cross pieces appears clearly as well as the vertical opening 8 between the lower edge of the rear cross piece 3 and the upper surface of the seat plate (against the contact surface 7) when the device is attached to a seat plate. In this embodiment the horizontal opening 8 is the same as the
20 vertical opening 6 mentioned above, but this needs not be the case, for example if a third cross piece is introduced in parallel with the front cross piece, in the same vertical position, to join together the contact surface 7 on the rear side of the side pieces 2 and lining elements 4. Precisely because there is no such third cross piece in the present embodiment, it is possible to minimize the height of the rear cross piece 3 at the same
25 time as sufficient space is provided for guiding a harness part, such as a crotch strap of a children's harness, around the cross piece, without the fastening device being of hindrance for the user.

In figure 6, the fastening device is shown directly from the left side and as above, the
30 vertical positions of the elements are apparent. As may be seen, the contact surface 7 has a relative broad extent in relation to the hole, through which the lining elements 4 are to be guided through, wherein the hole typically will have a dimension close to that of the width of the base on the lining elements for a wobble free fastening. Further, it may be seen that the rear cross piece 3, in addition is positioned in a horizontal distance
35 behind the lining elements 4, which may receive a part of a seating rail piece part between each other, in front of the rear cross piece 3.

A flexible zone 9 in the lining elements 4 also appears in figures 5 and 6 on the same side as the locking hooks 5, but higher up on the elements. The flexible zone 9 in this embodiment, constitutes a countersink in the elements where the rigidity of the lining elements is reduced in order to allow torsion and/or bending of the elements as the locking hooks may be twisted and/or bent in towards each other in order to enter the oblong hole in the seat plate. The form and position of the flexible zone may vary depending on the desired flex resistance and flex direction and the zones may possibly be constituted of a different material in the lining elements and/or locking hooks, instead of a countersink, all according to what is desired to achieve.

10

From the figures 4-6 the extent of the locking hooks 5 both in the transverse and length direction is also apparent. In this embodiment, the hooks are pointed backwards towards each other in about 45 degrees in relation to the transverse and length directions, but this may vary according to the desired appearance and need for fastening. The shaping is in this embodiment adapted to allow the insertion of an extremity of a children's seating rail into the fastening device from the top side and down through the opening 6, which at its front side will bear against the front cross piece 1. The extremity of the children's seating rail preferably has a snap flap which by complete insertion in the hole of the seat plate and fastening device will flip out on the underside of the seat plate and lock it to the plate. The top side of the locking hooks 5 are horizontal and planar in order to bear against the underside of the seat plate.

20

The upper part of the extremity of the children's seating rail will have a contact surface against the topside of the seat plate or fastening device so that the seating rail does not move further down into the hole in the seat plate, such as a wider form than the extremity which is inserted into the hole in the seat plate between the lining elements 4. The extremity of the children's seating rail may preferably have a vertical extent equal to or longer than the lining elements with locking hooks and a thickness and width which fills the opening defined by the front cross piece 1, the side pieces 2 and the locking hooks 5, as best seen on figures 3 and 4. In this manner, the extremity of the children's seating rail also hinder that the locking hooks 5 may be twisted towards each other after the insertion of the extremity of the children's seating rail and in this manner lock the fastening device 10 to the seat plate. Further, such a shaping will result in the seating rail being well fastened in the seat plate and fastening device 10 and hinder wobble between the parts.

35

In figure 7 an alternative embodiment of the fastening device 20 is shown in perspective. In this embodiment each lining element 14 extend into two locking hooks 15 on each of the elements, one directed forward, and one directed backward, both in about 45 degrees from the length or transverse direction. In this case the lining elements 14 comprise flexible zones 19 both on the inside front side and rear side of the lining elements 14, as well as the inside opposing vertical sides, an must be pinched together in order to insert the hooks and lining elements through an oblong hole in a seat plate. Preferably, pincers are used for doing this in such a case. It should be noted that in this embodiment also, an extremity of a children's seating rail, possibly with a snap flap, may be inserted down between the lining elements 14 and the locking hooks 15 and lock the fastening device to the seat plate in that the locking hooks 15 are hindered in being twisted in towards the opening.

In figure 8 it is shown how a fastening device 10 is placed in a hole in a seat plate 41 in a children's chair 40. The fastening device 10 is adapted to the hole in the seat plate so that the flange with the contact surface 7 has a larger horizontal extent than the area of the opening of the hole and rests on the top side of the seat plate around at least parts of the edges of the hole. The inner opening 6 in the fastening device 10 thereby allows the extremity 32 of a crouch part 31 of the children's seating rail 30 to be guided through the opening 6 and simultaneously through the seat plate 41. A snap flap at the extremity 32 of the seating rail springs out on the underside of the seat plate 41 and attaches the seating rail to the seat plate.

In the example embodiment of figure 8, the fastening device is adapted to a seat plate in a Tripp Trapp® chair. The seating rail 30 is in this case adapted by end arms 33 on each side which fit into slits in the side pieces of the chair 40. By this fastening of the seating rail, the seating rail may easily be removed by pressing the snap flap 33 in the extremity and pressing the seating rail from the sides such that one end arm 33 is pressed out of the slit it is inserted. Thus, the chair may be used by an older child or an adult, without the fastening device, which is small and discrete, needing removal.

Hence, the invention also comprises a seating rail set for a children's chair comprising a seating rail with a crouch piece which may be anchored through the fastening device 10 or 20 according to the invention, preferably by end arms which may be slipped into slits on the inside faces of the side pieces of a children's chair.

Besides a children's seating rail which is fastened by the fastening device 10, a children's harness (not shown) may be fastened to the seat plate either alone or in addition, via the fastening device 10, in that a crouch strap may be thread under the rear cross bar 3 which is positioned above the seat surface of the seat plate and behind the extremity 31 of the children's seating rail 30. The children's harness may be used for further securing the child in the chair, especially against climbing out of the chair.

In the embodiments above, the fastening devices are adapted to a seat plate in a Tripp Trapp® chair. The harness should in such a case be further adapted in that it in addition to being fastened in the seat plate 41 has a back strap which passes around at least one lateral piece 42 or 43 of the back rest in the chair. With this fastening of the harness the child will obtain better freedom of movement compared to traditional children's harnesses. There will also be fewer straps which the child may soil or fasten his fingers into.

Hence, the invention also comprises a harness set for a children's chair comprising a harness with a crouch strap which may be anchored to the bracket fastening device 10 or 20 according to the invention, and at least one strap which runs around at least one lateral piece 42 and/or 43 of the back rest on the chair 40 it is attached to.

Further, the invention comprises a combined seating rail and harness set comprising a harness with a crouch strap and a seating rail with a crouch piece, which both may be fastened via the fastening device 10/20 of the invention to a seat plate in the children's chair.

The advantage with the fastening device and harness set/seating rail set according to the invention is thereby that it may be used on an existing chair, such as the Tripp Trapp® chair or other chairs, without making physical changes on any of the parts of the chair or using fastening means such as screws. The fastening device 10, 20 is locked firmly only by the use of a simple tool, such as pincers, possibly by strong hand force, and the fastening for both harness and/or seating rail follows the adjustments of the chair both vertically and horizontally, such as by height adjustment or depth adjustment of the seat plate, without hindering any of the functions of the chair.

The fastening device renders the detachable fastening of both a harness and a seating rail possible, either separately or together. This provides several practical solutions and makes the use of the chair adaptable to several different users, in a simple and flexible

manner. The fastening device may be left mounted in the seat plate without it being of inconvenience for other users or being damaged. As the fastening device only constitutes a small rounded elevation on the seat plate, in an area between the legs which is not weighed down by the user in a normal sitting position, neither the user will
5 be able to bruise himself on the device, nor will the fastening device be exposed to wear, and it will in addition not be aesthetically bothersome.

The fastening device 10, 20 and harness/seating rail set may be removed simply after use or moved to another corresponding chair when they are not needed any more.

10

The fastening device 10, 20 is preferably produced of a relative rigid material, such as metal, plastic or a composite material, but preferably plastic.

C l a i m s

1.

A fastening device for use in a children's chair (40) with a seat plate (41), wherein the
5 seat plate has a vertical through hole for the mounting of the fastening device,
characterized in that the fastening device comprises:

- at least one cross piece (1) connected to two side pieces (2) which are joined by
at least one cross bar (3) and defining an opening (6), wherein the cross bar (3)
is positioned in a vertical distance from the cross piece (1) when the fastening
10 device is mounted,
- at least two mainly vertical lining elements (4) to be inserted into the hole,
connected to the underside of the cross piece (1) and/or side pieces (2) in their
upper ends, wherein the lining elements (4) each comprise at least one locking
hook 5 in their lower ends which have a larger horizontal extent than the lining
15 elements.

2.

A fastening device according to claim 1, wherein at least parts of the mentioned cross
piece (1) and the mentioned side pieces (2) comprise a contact surface (7) on the
20 underside of the pieces to bear against the top side of the seat plate (41), preferably an
open or closed continuous contact surface, even more preferably a contact surface
stretching in a half circle around the outer sides of the lining elements (4).

3.

A fastening device according to claim 1 or 2, wherein the fastening device allows for
25 insertion of a part of a children's seating rail, preferably a crouch strap, through the
opening (6) when the fastening device is mounted in a seat plate, preferably an
extremity with a snap flap which flips out on the underside of seat plate to which the
fastening device is attached.

30

4.

A fastening device according to any of the preceding claims, wherein the fastening
device allows a part of a children's harness, preferably a crouch strap, to freely run
around the cross bar (3) when the fastening device is mounted in a seat plate, preferably
35 simultaneously with a part of a children's seating rail being fastened through the
fastening device.

5.

A fastening device according to any of the preceding claims, wherein the locking hooks (5) are directed partly towards each other, preferably about 45 degrees in relation to the length and/or transverse direction of the fastening device.

6.

A fastening device according to any of the preceding claims, wherein each lining element (14) comprises two locking hooks (15), preferably directed towards each other, more preferably about 45 degrees in relation to the length and/or transverse direction of the fastening device.

7.

A fastening device according to any of the preceding claims, wherein each lining element (4, 14) comprises flexible zones (9) with reduced rigidity to allow torsion and/or bending of the locking hooks (5,15).

8.

A fastening device according to claim 7, wherein the reduced rigidity is achieved by countersinks present in the lining elements (4, 14).

9.

A fastening device according to claims 7 or 8, wherein the reduced rigidity is achieved by the complete or part of the lining elements comprising a more flexible material than the rest of the fastening device.

10.

A fastening device according to any of the preceding claims, wherein the locking hooks (5) are locked by inserting a part of a seating rail through the opening (6) of the fastening device.

11.

A fastening device according to any of the preceding claims, wherein the side pieces (2) have an increasing height from the cross piece (1) towards the cross bar (3), preferably that they are wedge formed.

12.

A harness set for a children's chair (40) having a back rest and seat plate (41) with a vertical hole in the front edge,

- 5 *characterized in that* it comprises the fastening device (10) according to any of the claims 1 to 11 and a children's harness comprising a crouch strap which may be anchored in the fastening device, and preferably a back strap running around at least one cross piece (42) of the back rest in the children's chair (40) it is fastened to.

10 13.

A seating rail set for a children's chair (40) having a back rest and seat plate (41) with a vertical hole in the front edge,

- characterized in that* it comprises the fastening device (10) according to any of the claims 1 to 11 and a children's seating rail (30) with a crouch strap (31) which may be
15 anchored to the seat plate (41) via an extremity (32) which may be guided through the opening (6) in the fastening device (10) and the hole in the seat plate (41), the extremity preferably having a snap flap which flips out on the underside of the seat plate (41) and the children's seating rail more preferably having end pieces (33) which may be inserted into slits in the side pieces of the chair.

20

14.

A combined harness and seating rail set comprising the sets according to claims 12 and 13.

25 15.

The use of a fastening device according to any of the claims 1 to 11, or a set according to the claims 12 to 14, for mounting a harness and/or a seating rail in a children's chair wherein the seat plate has a vertical hole and wherein the chair has the possibility of vertical and horizontal adjustment of the seat plate.

30

35