

The present invention relates to a new continuous industrial manufacturing process for an aqueous solution of glyoxylic acid.

It has been known for a long time how to prepare aqueous
5 solutions of glyoxylic acid by nitric oxidation of aqueous
solutions of glyoxal (French Patent No.s 1,326,605,
2,372,141, 2,516,506, German Patent No.s 932,369, 933,987,
1,002,309, Japanese Patent No.s 73-103517, 76-29441, 76-
80821, 77-105121, 80-129240 and East German Patent No.
10 128,233).

All these processes are achieved using nitric acid, in
the optional presence either of a strong mineral acid, such
as hydrochloric acid (FR 2,516,506 and JP Kokai 73-103517),
or of a soluble cobalt salt (DD 128233), or finally of
15 molecular oxygen (JP Kokai 76-29441, 76-80821, 77-105121, 82-
55698, 80-129240) and they provide aqueous solutions of
glyoxylic acid containing, in addition to residual glyoxal
and nitric acid, relatively large quantities of nitrogen
oxides and oxalic acid which must be eliminated by subsequent
20 laborious treatments (cf. in particular French Patent No.s
2,297,830 and 2,552,426).

The presence of residual glyoxal and nitric acid is
particularly inconvenient, therefore their elimination must
be carried out in such a way as to obtain a residual molar
25 concentration of glyoxal of less than 2% relative to
glyoxylic acid and a molar concentration of nitric acid of
less than 0.05% relative to glyoxylic acid.

French Patent No. 2,516,506 teaches an oxidation process
for aqueous solutions of glyoxal in an aqueous solution of
30 glyoxylic acid using an oxidizing agent obtained from nitric
acid and a non-oxidizing strong acid present at a
concentration by weight of 6 to 40% in the reaction mixture.

The aqueous solutions of glyoxylic acid resulting from
this process have the advantage of presenting weak residual
35 concentrations of nitric acid. However, they do not respond
totally to the demands of the market due to their excessive
concentrations of glyoxal.

Now, the Applicant has discovered a new industrial

manufacturing process for an aqueous solution of glyoxylic acid obviating these disadvantages.

The process according to the present invention which consists of subjecting an aqueous solution of glyoxal to a
5 nitric oxidation in the presence of hydrochloric acid is characterized in that it is carried out continuously in a reaction mixture containing a concentration by weight of nitric acid of greater than 10% and of hydrochloric acid of between 5 and 6% using 0.80 ± 0.02 mole of nitric acid and
10 0.70 ± 0.05 mole of hydrochloric acid per mole of glyoxal used.

The process of the present invention allows the glyoxal to be converted virtually quantitatively into a mixture of glyoxylic and oxalic acids. The losses of glyoxal are very
15 slight, always less than 1% and the non-converted glyoxal is always less than 2%. As for the nitric acid, it is totally consumed, so well that the aqueous solutions of glyoxylic acid obtained always contain less than 0.1% by weight of residual nitric acid. The selectivity of the oxidation of
20 the glyoxal into glyoxylic acid is comprised between 75 and 80%.

The process according to the present invention is preferably carried out at a temperature between 30 and 80°C. In particular the operation is done at a pressure comprised
25 between 0.5 and 10 bars and advantageously at a pressure comprised between 1 and 5 bars.

The process according to the present invention can be effected for example in a series of reactors agitated in series, or better still, in an assembly constituted by one or
30 more agitated reactors followed by one or more piston reactors.

Advantageously, either three reactors agitated in series, or preferably one agitated reactor followed by two piston reactors are used. The supply is effected
35 continuously into the first reactor and advantageously the gases resulting from the process are washed with the incoming supply of the aqueous solution of glyoxal. On leaving the last reactor, the reaction mixture is cooled down to ambient

temperature, then the oxalic acid formed is eliminated by crystallization and the mother liquors containing the glyoxylic acid formed, the hydrochloric acid and traces of oxalic acid and nitric acid are subjected to two successive
5 electrodialyses which allow the extraction from the reaction medium, firstly of the hydrochloric acid which is recycled, then of the residual oxalic acid which is recycled in the reaction medium resulting from the last reactor.

The reaction medium leaving the second electrodialysis
10 machine is either used as it is, or concentrated under reduced pressure to the desired concentration of glyoxylic acid.

For the supply, commercially available aqueous solutions of glyoxal, of hydrochloric acid and of nitric acid,
15 optionally diluted with water, are preferably used. The oxidation according to the process of the invention is quick: usually it requires less than two hours and it is advantageously effected in successive reactors heated to identical temperatures or to higher and higher temperatures.

20 Preferably, the oxidation is started at 45°C, then completed at 55°C.

The aqueous solutions of glyoxylic acid are in particular currently used to access for example vanillin starting with guaicol or parahydroxymandelic acid starting
25 with phenol.

The following example illustrates the invention without however limiting it.

Example

An agitated reactor maintained at $45 \pm 1^\circ\text{C}$, followed by
30 two piston reactors in series, maintained at 55°C , are supplied continuously with:

- 29,020 g/h of an aqueous solution of glyoxal at 20% by weight, that is 100 moles/h of glyoxal,
- 13,322 g/h of hydrochloric acid at 20% by weight, that
35 is 73 moles/h of hydrogen chloride,
- 7,441 g/h of nitric acid at 69% by weight, that is 81.5 moles/h of nitric acid at 100%.

This reaction mixture remains in the agitated reactor

for 12 minutes, then for 35 minutes in the first piston reactor and finally for 45 minutes in the second piston reactor, then the reaction mixture is cooled down. The oxalic acid formed crystallizes and after elimination of the oxalic acid crystals by filtration, the reaction medium is subjected to two successive electrodialyses to eliminate the hydrochloric acid and then the residual oxalic acid. The hydrochloric acid isolated in the first electrodialysis machine is recycled to the start of the process and the aqueous solution of oxalic acid containing traces of hydrochloric acid and glyoxylic acid is recycled on leaving the second piston reactor.

At the exit of the second piston reactor, 47,391 g/h of an aqueous solution containing by weight 12.11% of glyoxylic acid, or 77.5 moles/h, 5.62% of hydrochloric acid, or 73 moles/h, 3.9% of oxalic acid, or 20.5 moles/h, 0.18% of glyoxal, or 1.5 mole/h, 0.04% of nitric acid, or 0.03 mole/h and finally 78.15% of water is obtained. At the same time, gases are released which, after washing with the aqueous solution of glyoxal of the beginning of the process, have an output of 2,390 g/h and which are constituted by 92.6% of nitrogen oxide, or 73.8 moles/h, 1.2% of nitrogen, or 1 mole/h, 4.1% of nitrous oxide, or 2.2 moles/h and 2.1% of carbon dioxide, or 1.1 mole/h.

The yield of glyoxylic acid is established at 77-78% relative to the glyoxal used, the yield of oxalic acid is established at 20-21% relative to the glyoxal and only 0.5% of the glyoxal is lost as carbon dioxide.

The conversion rate of the glyoxal is about 98.5%.

On leaving the second electrodialysis machine, the aqueous solution of glyoxylic acid containing minute traces of hydrochloric acid, oxalic acid and nitric acid is concentrated so as to bring its titer to 40% or 50% according to commercial demands.

The 69% nitric acid can be replaced by 55% nitric acid. To do this, it is sufficient to supply the reactor with an aqueous solution either of glyoxal, or of hydrochloric acid, or of these two products slightly more concentrated. Thus,

for example, if the reactor is supplied with 81.5 moles/h of 55% nitric acid, or 9,335.5 g/h, 27,126 g/h of a 21.4% aqueous solution of glyoxal, or 100 moles, are used.



CLAIMS

- 1) Manufacturing process for an aqueous solution of glyoxylic acid by nitric oxidation of an aqueous solution of glyoxal carried out in the presence of hydrochloric acid, characterized in that this oxidation is effected continuously using 0.80 ± 0.02 mole of nitric acid and 0.70 ± 0.05 mole of hydrochloric acid per mole of glyoxal in a reaction medium which has a concentration by weight comprised between 5 and 6% of hydrochloric acid and higher than 10% of nitric acid.
- 2) Process according to claim 1, characterized in that it is used at a temperature comprised between 30 and 80°C.
- 3) Process according to claim 1 or 2, characterized in that it is carried out at a pressure comprised between 0.5 and 10 bars.