

CONVEYOR OVEN

PRIORITY CLAIM

The present application claims priority under 35 U.S.C. § 119(e)(1) to non-provisional application number 13/399,840 filed on February 17, 2012, the contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Technical Field

The present invention relates to conveyor ovens in general, and in particular to a conveyor oven capable of providing continuous, precise cooking of a variety of foods that require different cook times and thermal profiles, while preventing heat loss.

2. Description of Related Art

A conveyor oven typically has a first opening through which uncooked food enters and a second opening at the opposite end of the oven through which cooked food exits. A stainless steel conveyor belt is commonly used to carry food items through a heated cavity between the first and second openings. The conveyor belt extends past both openings sufficiently to allow safe insertion and retrieval of food items. This arrangement allows food items to be placed on the conveyor belt on a continuous basis to achieve sequential steady-state cooking.

When food items offered by a commercial food service operation, such as a restaurant, are to be cooked at the same thermal profile for the same amount of time, a conveyor oven is particularly advantageous. The operators need only set the temperature,

1 the blower speeds and conveyor belt speed as necessary to cook the selected foods. Once
2 the above-mentioned three parameters are set, the oven may be operated continuously
3 without any further adjustments. With a conveyor oven, even a person unskilled in the art
4 of cooking is able to prepare high-quality cooked food products simply by placing them on
5 a conveyor belt of the conveyor oven. The ease of operation and high throughput make
6 conveyor ovens highly desirable in restaurants and other commercial food service settings.

7
8 However, conveyor ovens also have many disadvantages. For example, most
9 commercial food service operations offer a variety of different food items, such as pizza,
10 chicken, vegetables and pie, which require a wide range of cooking times and thermal
11 profiles. Even a single food order at a restaurant may include a variety of food items, and
12 different food items require different cooking times. Conveyor ovens are very efficient
13 when cooking similar food items, but not for cooking a variety of food items that require
14 vastly different cooking times and thermal profiles.

15
16 Consequently, it would be desirable to provide an improved conveyor oven.

SUMMARY OF THE INVENTION

In accordance with an aspect of the present invention, a conveyor oven includes a housing, a conveyor belt, a control panel, a first oven door, a second oven door, and a heat source. The housing includes a cavity, a first opening and a second opening. The conveyor belt extends through said first opening, said cavity, and said second opening. The control panel displays a plurality of cooking settings corresponding to different food items for selection by a user. The first oven door covers said first and opening to prevent heat within the cavity from escaping through the first opening during oven food cooking operation. The second oven door covers said second opening to prevent heat within said cavity from escaping through said second opening during oven food cooking operation. The heat source provides heat to the cavity for heating up any food item placed on a portion of the conveyor belt located within the cavity, wherein said control panel is configured to (1) receive said user's selection of a first cooking setting corresponding to a first food item placed on said conveyor belt and initiate a first cooking operation based on said first cooking setting when said first food item is transported into said cavity for cooking; and (2) receive said user's selection of a second cooking setting corresponding to a second food item placed on said conveyor belt and initiate a second cooking operation based on said second cooking setting when said second food item is transported into said cavity for cooking; and wherein said conveyor belt is configured to (1) receive said first food item outside said cavity; (2) transport said first food item into said cavity through said first opening; (3) move said first food item within said cavity in a to-and-fro fashion during said first cooking operation; (4) receive said second food item while said first food item is within said cavity; and (5) transport said first food item out of said cavity through said second opening after completion of said first cooking operation and transport said second food item into said cavity through said first opening.

All features and advantages of the present invention will become apparent in the following detailed written description.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention itself, as well as a preferred mode of use, further objects, and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 is a front view of a conveyor oven, in accordance with a preferred embodiment of the present invention;

Figure 2 is a cross-sectional view of the conveyor oven from Figure 1, in accordance with a preferred embodiment of the present invention;

Figure 3 is a diagram of a heating and airflow system within the conveyor oven from Figure 1, in accordance with a preferred embodiment of the present invention;

Figures 4a-4e illustrate a method of cooking food items separately in the conveyor oven from Figure 1, in accordance with a preferred embodiment of the present invention; and

Figures 5a-5d illustrate a method of cooking food continuously in the conveyor oven from Figure 1, in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT

Referring now to the drawings and in particular to Figures 1 and 2, there are depicted a front and cross-sectional view of a conveyor oven, in accordance with a preferred embodiment of the present invention. As shown, a conveyor oven 10 is defined by a housing 11 having a cavity 12. Housing 11, as well as cavity 12, has a first opening 18 and a second opening 19. Conveyor oven 10 includes a heating and airflow system (not shown) to supply heat to cavity 12 for heating up any food items that have been carried into cavity 12 from first opening 18 via a metal conveyor belt 20. Conveyor belt 20 has an upper surface 23 and a lower surface 24. Since upper surface 23 and lower surface 24 are part of conveyor belt 20, upper surface 23 and lower surface 24 are substantially identical at any given time. Conveyor oven 10 also includes a first door 16 for covering first opening 18, and a second door 17 for covering second opening 19, when appropriate.

Conveyor oven 10 also includes a control panel 15. Control panel 15 is preferably implemented with a touchscreen but it can also be implemented with a keypad and liquid crystal display (LCD). An operator can enter commands, such as mode of operations, cooking temperatures within cavity 12, cooking time, blower speed, etc., via control panel 15 to effectuate cooking controls on any food items placed within cavity 12. Control panel 15 is preferably associated with a non-volatile memory for storing various cooking instructions, such as cook times, cook temperatures and blower speeds, for different food items under the names or graphical representations of corresponding food items.

Housing 11 accommodates conveyor belt 20 having a food loading section 21 for receiving various uncooked food items and a food unloading section 22 for gathering various cooked food items once they have traveled through cavity 12. Any food item intended to be cooked can be initially placed on food loading section 21. Conveyor belt 20 is connected to a stepper motor (not shown) that controls the linear movement of conveyor belt 20 in and out of cavity 12. Since food loading section 21 and food

1 unloading section 22 are part of conveyor belt 20, the surfaces of food loading section 21
2 and food unloading section 22 are substantially identical at any given time.

3
4 First and second openings 18 and 19 can be covered by first and second
5 doors 16 and 17, respectively, during cooking and also when conveyor oven 10 is being
6 idle (*i.e.*, when there is no food located within cavity 12 and conveyor belt 20 is not
7 moving). The purpose of first and second doors 16, 17 is to prevent heat loss from cavity
8 12 via first and second openings 18, 19, respectively, at all times other than when food is
9 being transported in or out of cavity 12 on conveyor belt 20.

10
11 In addition, housing 11 also contains a top plenum 35 and a bottom plenum
12 38. Top plenum 35 is connected to a top nozzle plate 34. Bottom plenum 38 is connected
13 to a bottom nozzle plate 37. Top nozzle plate 34, top plenum 35, bottom nozzle plate 37
14 and bottom plenum 38 are part of the heating and airflow system for conveyor oven 10
15 such that heated air in top plenum 35 and bottom plenum 38 are in gaseous communication
16 with cavity 12 through top nozzle plate 34 and bottom nozzle plate 37, respectively. Top
17 nozzle plate 34 includes multiple conical shaped top nozzles 25, and bottom nozzle plate
18 37 includes multiple conical shaped bottom nozzles 26. Nozzles 25, 26 are configured to
19 direct pressurized hot airstreams towards any food items placed on the portion of conveyor
20 belt 20 located within cavity 12. Although air passes through top nozzle plate 34 and
21 bottom nozzle plate 37 into cavity 12, it is understood by those skilled in the art that top
22 plenum 35 or bottom plenum 38 could be in gaseous communication with cavity 12 via a
23 variety of air opening configurations such as tubes, rectangular openings and the like.
24 Moreover, air can enter cavity 12 through one or both of top plenum 35 or bottom plenum
25 38.

26
27 For additional heating, an optional infrared radiation heating element 36 can
28 be placed within cavity 12 somewhere between conveyor belt 20 and bottom nozzle plate
29 38 or between conveyor belt 20 and top nozzle plate 34 for supplying heat towards any

1 food items located within cavity 12. It is understood by those skilled in the art that other
2 heating means, such as microwave, steam or a combination thereof, can be used instead of
3 infrared radiation heating element 36.

4
5 Referring now to Figure 3, there is depicted a diagram of the heating and
6 airflow system within conveyor oven 10, in accordance with a preferred embodiment of the
7 present invention. Air within cavity 12 is initially pumped into a heater plenum 31 via an
8 intake opening 30. Heater plenum 31 includes a heater 39. After it has been sufficiently
9 heated by heater 39, the hot air is then directed to top plenum 35 via a top blower 32 and
10 to bottom plenum 38 via a bottom blower 33. The pressurized hot air formed within top
11 plenum 35 is subsequently directed to cavity 12 via multiple nozzles 25 located on top
12 nozzle plate 34 (from Figure 2). Similarly, pressurized hot air formed within bottom
13 plenum 38 is subsequently directed to cavity 12 via multiple nozzles 26 located on bottom
14 nozzle plate 37 (from Figure 2). Although heated air is shown to be sent to top air plenum
15 35 and bottom plenum 38 via separate blowers, it is understood by those skilled in the art
16 that heated air can be sent to both top plenum 35 and bottom plenum 38 via a single
17 blower.

18
19 Preferably, the diameter of the openings of nozzles 25, 26 may range from
20 $\frac{1}{4}$ " to $\frac{1}{2}$ ". Each of nozzles 25, 26 can provide a pressurized hot airstream of 1" diameter
21 coverage directed towards any food items placed on the portion of conveyor belt 20 located
22 approximately 4" from top nozzle plate 34 or bottom nozzle plate 37. After a food item
23 has been placed in the center of cavity 12 by conveyor belt 20, conveyor belt 20 can stop
24 moving, and pressurized hot airstreams can be directed towards the food item placed on
25 conveyor belt 20 to begin the cooking process. At this point, conveyor belt 20 may move
26 in a slight to-and-fro fashion (*i.e.*, from left to right and from right to left). For example,
27 conveyor belt 20 may vacillate between $\frac{1}{2}$ " left of the stopping point and $\frac{1}{2}$ " right of the
28 stopping point in order to increase the hot airstream coverage on the food item on conveyor
29 belt 20, and to avoid overheating of a food item at any spot located directly underneath one

1 of nozzles 25 or directly above one of nozzles 26. It will be appreciated by those skilled
2 in the art that the placement of nozzles 25 in top nozzle plate 34 and also the placement
3 of nozzles 26 in bottom nozzle plate 37 will be selected such that the slight to-and-fro
4 movement in conveyor belt 20 will be sufficient to travel the left-to-right distance between
5 individual nozzles in top nozzle plate 34 and bottom nozzle plate 37.

6
7 In a preferred embodiment of the present invention, conveyor oven 10 has
8 at least two modes of operation, namely, a burst mode and a continuous mode. Figures 4a-
9 4e show the burst mode of operation, and Figures 5a-5d show the continuous mode of
10 operation.

11
12 For the burst mode of operation, a first raw food item RF-1 is initially
13 placed on food loading section 21 (from Figure 2), as shown in Figure 4a. Various types
14 of food items, such as "16-inch pepperoni pizza," "12 chicken breasts," etc., are displayed
15 on control panel 15. A selection of a food item displayed on control panel 15 by a user
16 initiates the burst mode operation. Suffice to say, the food item selection from control
17 panel 15 should correspond with first raw food item RF-1. At this point, first oven door
18 16 opens and first raw food item RF-1 is then transported to cavity 12 via conveyor belt
19 20 (*i.e.*, with conveyor belt upper surface 23 moving from left to right, as depicted in
20 Figure 4b). Once first raw food item RF-1 has been situated within cavity 12, first oven
21 door 16 will be automatically lowered to cover first opening 18, as shown in Figure 4c, to
22 prevent heat loss from cavity 12 during the cooking of first raw food item RF-1.

23
24 During the cooking process, pressurized hot air is directed through top and
25 bottom nozzle plates 34, 37, through nozzles 25, 26, into cavity 12 for a period of time and
26 at blower speeds and cook temperatures that have been previously stored in control panel
27 15 to effectuate cooking of food items substantially similar to the item represented by the
28 food item selected. In Figure 4c, first raw food item RF-1 is shown to be positioned
29 centrally within openings 18 and 19. Once first raw food item RF-1 has been situated

1 within cavity 12, first raw food item RF-1 will remain in that general location for the
2 duration of the cook cycle so that the portion of first raw food item RF-1 that is beneath
3 one of nozzles 25 or above one of nozzles 26 will remain generally in that location for the
4 duration of the cook cycle.

5
6 In the meantime, a second raw food item RF-2 can be placed on food
7 loading section 21 (from Figure 2) as shown in Figure 4c and the corresponding food item
8 displayed on control panel 15 can be selected. Second raw food item RF-2 can be
9 substantially the same as first raw food item RF-1, which requires the same cook time and
10 blower speeds to be properly cooked, or second raw food item RF-2 can be completely
11 different from first raw food item RF-1, which requires completely different cook time and
12 blower speeds to be properly cooked. After first raw food item RF-1 has been fully
13 cooked, both first door 16 and second door 17 open, and the fully cooked food item (now
14 CF-1) is sent to food unloading section 22 (from Figure 2) via conveyor belt 20 (*i.e.*, with
15 conveyor belt upper surface 23 moving from left to right) and second raw food item RF-2
16 is transported from food loading section 21 to cavity 12, as depicted in Figure 4d.

17
18 Once second raw food item RF-2 has been situated within cavity 12, both
19 first and second doors 16, 17 will be automatically lowered to cover first and second
20 openings 18, 19, respectively, to prevent heat loss from cavity 12 during the cooking of
21 second raw food item RF-2, as shown in Figure 4e. At this point, first cooked food item
22 CF-1 can be removed from food unloading section 22, and food loading section 21 is ready
23 to receive a third raw food item RF-3.

24
25 The above-mentioned sequence can be performed repeatedly for different
26 types of food items. Since different cooking times can be entered by an operator, any of
27 the above-mentioned food items can be completely different from each other.

1 It will be readily apparent to those skilled in the art that when only one food
2 item needs to be cooked, only one of first and second doors 16, 17 will be raised or
3 lowered corresponding with the movement of the food item into or out of cavity 12.
4

5 If a user desires to cook multiple substantially similar cook items as quickly
6 as possible, the user may select the continuous mode of operation from control panel 15.
7 During the continuous mode of operation, conveyor belt 20 is running continuously in one
8 direction according to the preference of the operator. Initially, a first raw food item RF-1
9 is placed on food loading section 21 (from Figure 2), as shown in Figure 5a. During the
10 continuous mode of operation, first and second doors 16, 17 are lifted up completely the
11 entire time. For example, raw food items can be placed on food loading section 21 (from
12 Figure 2) and the cooked food items can be retrieved from food unloading section 22 (from
13 Figure 2) after they have been thoroughly cooked within cavity 12. In essence, the
14 continuous mode is similar to the standard operation method of conventional conveyor
15 ovens, as depicted in Figures 5b and 5c. Once the multiple substantially similar food items
16 have been cooked, the operator can make a selection from control panel 15 to place
17 conveyor oven 10 in idle, with both first and second doors 16, 17 in closed position, as
18 shown in Figure 5d.
19

20 As has been described, the present invention provides an improved conveyor
21 oven for continuously cooking a wide variety of food items while preventing heat loss in
22 order to improve energy efficiency.
23

24 While the invention has been particularly shown and described with reference
25 to a preferred embodiment, it will be understood by those skilled in the art that various
26 changes in form and detail may be made therein without departing from the spirit and scope
27 of the invention.

CLAIMS

What is claimed is:

1. An oven comprising;

a housing having a cavity, a first opening, and a second opening;

a conveyor belt extending through said first opening, said cavity, and said second opening;

a control panel to display a plurality of cooking settings corresponding to different food items for selection by a user;

a first oven door for covering said first opening, to prevent heat within said cavity from escaping through said first opening during oven food cooking operation;

a second oven door for covering said second opening to prevent heat within said cavity from escaping through said second opening during oven food cooking operation;

a heat source for providing heat to said cavity for heating up any food item placed on a portion of said conveyor belt located within said cavity, wherein said control panel is configured to (1) receive said user's selection of a first cooking setting corresponding to a first food item placed on said conveyor belt and initiate a first cooking operation based on said first cooking setting when said first food item is transported into said cavity for cooking; and (2) receive said user's selection of a second cooking setting corresponding to a second food item placed on said conveyor belt and initiate a second cooking operation based on said second cooking setting when said second food item is transported into said

cavity for cooking; and

wherein said conveyor belt is configured to (1) receive said first food item outside said cavity; (2) transport said first food item into said cavity through said first opening; (3) move said first food item within said cavity in a to-and-fro fashion during said first cooking operation; (4) receive said second food item while said first food item is within said cavity; and (5) transport said first food item out of said cavity through said second opening after completion of said first cooking operation and transport said second food item into said cavity through said first opening.

2. The oven of Claim 1, wherein said conveyor belt is capable of stopping during cooking operation.

3. The oven of Claim 1, wherein said conveyor belt moves in said to-and-fro fashion in order to increase hot airstream coverage on a food item placed on said conveyor belt during cooking operation.

4. The oven of Claim 1, wherein said oven includes an air intake for receiving air from said cavity.

5. The oven of Claim 4, wherein said oven includes a heater for heating air received from said air intake.

6. The oven of Claim 5, wherein said oven includes a blower for returning hot air to said cavity.

7. The oven of Claim 1, wherein said cavity includes a first plenum and a first nozzle plate having multiple nozzles.

8. The oven of Claim 7, wherein said cavity includes a second plenum and a second nozzle plate having multiple nozzles.
9. The oven of Claim 1, wherein said to-and-fro fashion includes said conveyor belt being vacillated between half inch (1.27cm) left of a stopping point and half inch (1.27cm) right of said stopping point.
10. The oven of Claim 1, further comprising a stepper motor to drive said conveyor belt.
11. The oven of Claim 1, wherein said control panel comprises a touch-screen, a key pad, or a liquid crystal display.
12. The oven of Claim 1, further comprising a non-volatile memory for storing said plurality of cooking settings for different food items.