

HEAT DISSIPATION DEVICE HAVING LATERAL-SPREADING HEAT DISSIPATING AND SHUNTING HEAT CONDUCTIVE STRUCTURE

5 BACKGROUND OF THE INVENTION

(a) Field of the Invention

The present invention provides a heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure, in which the central area of heat conductive interface of the heat dissipation
10 device (100) where a heat generating device (101) being disposed is installed with a close-loop shunting heat conductive structure, so the heat at the central area of the heat generating device (101) can be conducted to a distal heat dissipating segment (104) for being dissipated to the exterior, thereby through working with the heat dissipation operation of the heat dissipation structure at
15 the periphery of the heat generating device (101) and leaded to the distal heat dissipating segment (104), the temperature distribution at the central area and the peripheral area of the heat generating device (101) can be more even.

(b) Description of the Prior Art

A conventional semiconductor having heat loss, e.g. a light emitting
20 diode (LED), central process unit (CPU), memory, power semiconductor, rectifier, or power-type IC in which heat loss being generated, or an active heat generating unit, e.g. a heater, oven or cooking ware operated through electric power or thermal combustion, the heat source is often installed at the bottom central area of a heat dissipation device, and through a heat
25 conductive structure radially and outwardly extending and upwardly extending, the heat can be conducted to a distal heat dissipation structure thereby dissipating the heat to the exterior; because the lateral edge area of the heat generating unit is closer to the heat conductive structure radially and outwardly extending and upwardly extending, while the central area of the
30 heat generating unit is relatively farer, the temperature at the central area of

the heat generating unit is higher than the temperature at the peripheral area during operation, thereby causing an disadvantage of the temperature between the central area and the lateral edge of the heat generating unit being uneven.

5

SUMMARY OF THE INVENTION

The present invention provides a heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure, in which the top central area or the bottom central area of heat conductive interface of the heat dissipation device (100) where a heat generating device (101) being provided is installed with the heat generating device (101), the central area of heat conductive interface of the mentioned heat dissipation device (100) is installed with a close-loop shunting heat conductive structure, so the heat at the periphery of the heat generating device (101) can be conducted from the outer periphery to the distal heat dissipating segment (104) for being dissipated to the exterior, and the heat at the central area can be conducted through the close-loop shunting heat conductive structure (103) to the distal heat dissipating segment (104) for being dissipated to the exterior.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a cross sectional view illustrating the close-loop shunting heat conductive structure (103) being installed between the central area of the base structure (102) of the heat dissipation device (100) and the combining location (c) of the horizontally expanding and upwardly extending distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103), according to one embodiment of the present invention.

FIG. 2 is a cross sectional view illustrating two or more heat generating devices (101) being installed in the heat dissipation device (100) shown in FIG. 1, according to one embodiment of the present invention.

FIG. 3 is a cross sectional view illustrating the central airflow aperture (1022) and two or more heat generating devices (101) being installed in the

heat dissipation device (100) shown in FIG. 1, according to one embodiment of the present invention.

FIG. 4 is a cross sectional view illustrating two or more airflow apertures (1023) being formed at the periphery expanded from the central area of the base structure (102) of the heat dissipation device (100) shown in FIG. 1,
5 according to one embodiment of the present invention.

FIG. 5 is a schematic structural view illustrating the present invention being formed as a heat dissipation device having U-shaped structure (1000), wherein the close-loop shunting heat conductive structure (103) and/or the
10 distal heat dissipating segment (104) being formed with airflow apertures (1052), according to one embodiment of the present invention.

FIG. 6 is a top view of FIG. 5.

FIG. 7 is a lateral view of FIG. 5.

FIG. 8 is a schematic structural view illustrating the present invention being formed as a heat dissipation device having U-shaped structure (1000), wherein the close-loop shunting heat conductive structure (103) and/or the
15 distal heat dissipating segment (104) being formed with a radial grid heat dissipation space, according to one embodiment of the present invention.

FIG. 9 is a top view of FIG. 8.

20 FIG. 10 is a lateral view of FIG. 8.

FIG. 11 is a schematic structural view illustrating the present invention being formed as a heat dissipation device having tubular structure (2000), wherein the periphery of the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) and/or the heat
25 dissipation device having tubular structure (2000) being formed with airflow apertures (1052), according to one embodiment of the present invention.

FIG. 12 is a top view of FIG. 11.

FIG. 13 is a lateral view of FIG. 11.

FIG. 14 is a schematic structural view illustrating the present invention
30 being formed as a heat dissipation device having tubular structure (2000),

wherein the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) being formed with the radial grid heat dissipation space, according to one embodiment of the present invention.

FIG. 15 is a top view of FIG. 14.

5 FIG. 16 is a lateral view of FIG. 14.

FIG. 17 is a lateral view illustrating the present invention being applied in a LED lamp, according to the first embodiment of the present invention.

FIG. 18 is a top view of FIG. 17.

10 FIG. 19 is a lateral view illustrating the present invention being applied in a LED lamp, according to the second embodiment of the present invention.

FIG. 20 is a top view of FIG. 19.

FIG. 21 is a lateral view illustrating the present invention being applied in a LED lamp, according to the third embodiment of the present invention.

FIG. 22 is a top view of FIG. 21.

15 FIG. 23 is a lateral view illustrating the present invention being applied in a LED lamp, according to the fourth embodiment of the present invention.

FIG. 24 is a bottom view of FIG. 23.

FIG. 25 is a lateral view of the present invention being applied in a LED lamp, according to the fifth embodiment of the present invention.

20 FIG. 26 is a top view of FIG. 25 taken along A-A.

FIG. 27 is a lateral view of the present invention being applied in a LED lamp, according to the sixth embodiment of the present invention.

FIG. 28 is a top view of FIG. 27 taken along A-A.

25 FIG. 29 is a lateral view of the present invention being applied in a LED lamp, according to the seventh embodiment of the present invention.

FIG. 30 is a top view of FIG. 29 taken along A-A.

FIG. 31 is a lateral view of the present invention being applied in a LED lamp, according to the eighth embodiment of the present invention.

FIG. 32 is a top view of FIG. 31 taken along A-A.

30 FIG. 33 is a lateral view of the present invention being applied in a LED

lamp, according to the ninth embodiment of the present invention.

FIG. 34 is a cross sectional view of FIG. 33 taken along B-B.

FIG. 35 is a lateral view of the present invention being applied in a LED lamp, according to the tenth embodiment of the present invention.

5 FIG. 36 is a cross sectional view of FIG. 35 taken along B-B.

FIG. 37 is a lateral view of the present invention being applied in a LED lamp, according to the eleventh embodiment of the present invention.

FIG. 38 is a cross sectional view of FIG. 37 taken along B-B.

FIG. 39 is a lateral view of the present invention being applied in a LED
10 lamp, according to the twelfth embodiment of the present invention.

FIG. 40 is a cross sectional view of FIG. 39 taken along B-B.

DESCRIPTION OF MAIN COMPONENT SYMBOLS

- 100: Heat dissipation device
- 15 101: Heat generating device
- 102: Base structure
- 103: Close-loop shunting heat conductive structure
- 104: Distal heat dissipating segment
- 105: Inner heat dissipation surface
- 20 106: Outer heat dissipation surface
- 107: Radial airflow aperture
- 110: Annularly-arranged axial airflow aperture
- 111: Light emitting diode
- 112: Secondary optical device
- 25 113: Light pervious lamp cover
- 114: Fastening and electric conducting interface
- 115: Drive circuit device
- 116: Conductive wire
- 1000: Heat dissipation device having U-shaped structure
- 30 1022: Central airflow aperture
- 1023, 1052: Airflow aperture

2000: Heat dissipation device having tubular structure

a: Central location of the base structure (102) close to the heat generating device (101)

5 b: Outer location of the base structure (102) close to the heat generating device (101)

c: Combining location of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103)

d: Distal location of the distal heat dissipating segment (104)

e: Distal location of the close-loop shunting heat conductive structure (103)

10

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A conventional semiconductor having heat loss, e.g. a light emitting diode (LED), central process unit (CPU), memory, power semiconductor, rectifier, or power-type IC in which heat loss being generated, or an active
15 heat generating unit, e.g. a heater, oven or cooking ware operated through electric power or thermal combustion, the heat source is often installed at the bottom central area of a heat dissipation device, and through a heat conductive structure radially and outwardly extending and upwardly extending, the heat can be conducted to a distal heat dissipation structure
20 thereby dissipating the heat to the exterior; because the lateral edge area of the heat generating unit is closer to the heat conductive structure radially and outwardly extending and upwardly extending, while the central area of the heat generating unit is relatively farer, the temperature at the central area of the heat generating unit is higher than the temperature at the peripheral area
25 during operation, thereby causing an disadvantage of the temperature between the central area and the lateral edge of the heat generating unit being uneven.

The present invention provides a heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure, in which the top central area or the bottom central area of heat conductive
30 interface of the heat dissipation device (100) where a heat generating device

(101) being provided is installed with the heat generating device (101), the central area of heat conductive interface of the mentioned heat dissipation device (100) is installed with a close-loop shunting heat conductive structure, so the heat at the periphery of the heat generating device (101) can be
5 conducted from the outer periphery to the distal heat dissipating segment (104) for being dissipated to the exterior, and the heat at the central area can be conducted through the close-loop shunting heat conductive structure (103) to the distal heat dissipating segment (104) for being dissipated to the exterior;

FIG. 1 is a cross sectional view illustrating the close-loop shunting heat
10 conductive structure (103) being installed between the central area of the base structure (102) of the heat dissipation device (100) and the combining location (c) of the horizontally expanding and upwardly extending distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103), according to one embodiment of the present invention;

15 As shown in FIG. 1, it mainly consists of:

-- heat dissipation device (100): composed of a heat conductive material, e.g. aluminum, copper, alloy or ceramic material, formed in a U-shaped plate shape, circular cup-like shape or polygonal cup-like shape, or formed in a fork-like cup-shaped structure having upward heat dissipating fork at the
20 outer side, the center of the heat dissipation device (100) is installed with the heat generating device (101), and the close-loop shunting heat conductive structure (103) is installed between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining locations (c) of the distal heat dissipating segment (104) and the close-loop
25 shunting heat conductive structure (103), thereby reducing the temperature differentiation between the central location (a) of the base structure (102) close to the heat generating device (101) and the distal location (d) of the distal heat dissipating segment (104);

-- heat generating device (101): composed of one or more semiconductor
30 components which generating heat loss such as light emitting diodes (LED),

central processing unit (CPU), memory, power semiconductors, rectifier, or power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat, served for being combined with the base structure (102) or directly being heated by the external from the
5 base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device,
10 and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material, integrally formed with the heat dissipation device (100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central
15 location (a) of the base structure (102) close to the heat generating device (101) and the combining locations (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103).

FIG. 2 is a cross sectional view illustrating two or more heat generating devices (101) being installed in the heat dissipation device (100) shown in
20 FIG. 1, according to one embodiment of the present invention;

As shown in FIG. 2, it mainly consists of:

-- heat dissipation device (100): composed of a heat conductive material, e.g. aluminum, copper, alloy or ceramic material, formed in a U-shaped plate-like shape, circular cup-like shape or polygonal cup-like shape, or
25 formed in a fork-like cup-shaped structure having upward heat dissipating fork at the outer side, the center of the heat dissipation device (100) is installed with the heat generating device (101), and the close-loop shunting heat conductive structure (103) is installed between the central location (a) of the base structure (102) close to the heat generating device (101) and the
30 distal location (d) of the distal heat dissipating segment (104), thereby

reducing the temperature differentiation between the central location (a) of the base structure (102) close to the heat generating device (101) and the distal location (d) of the distal heat dissipating segment (104);

-- heat generating device (101): composed of two or more semiconductor components which generating heat loss such as light emitting diodes (LED), central processing unit (CPU), memory, power semiconductors, rectifier, or power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat, served for being combined with the base structure (102) or directly being heated by the external from the base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device, and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material, integrally formed with the heat dissipation device (100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103).

FIG. 3 is a cross sectional view illustrating the central airflow aperture (1022) and two or more heat generating device (101) being installed in the heat dissipation device (100) shown in FIG. 1, according to one embodiment of the present invention;

As shown in FIG. 3, it mainly consists of:

-- heat dissipation device (100): composed of a heat conductive material, e.g. aluminum, copper, alloy or ceramic material, formed in a U-shaped plate-like shape, circular cup-like shape or polygonal cup-like shape, or

formed in a fork-like cup-shaped structure having upward heat dissipating fork at the outer side, the heat dissipation device (100) is formed with the central airflow aperture (1022) and two or more heat generating devices (101) annularly arranged at the periphery of the central airflow aperture (1022), the
5 central airflow aperture (1022) is formed as a single aperture or plural aperture structure, the plural aperture structure include plural individual apertures or net-like apertures or grid-like apertures, the center of the heat dissipation device (100) is installed with the heat generating device (101), and the close-loop shunting heat conductive structure (103) is installed between
10 the central location (a) of the base structure (102) close to the heat generating device (101) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103), thereby reducing the temperature differentiation between the central location (a) of the base structure (102) close to the heat generating device (101) and
15 the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103);

-- heat generating device (101): composed of two or more semiconductor components which generating heat loss such as light emitting diodes (LED), central processing unit (CPU), memory, power semiconductors, rectifier, or
20 power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat, served for being combined with the base structure (102) or directly being heated by the external from the base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source
25 thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device, and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a
30 heat conductive material, integrally formed with the heat dissipation device

(100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central locations (a) of the base structure (102) close to the heat generating devices (101) at the periphery of the central airflow aperture (1022) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103).

FIG. 4 is a cross sectional view illustrating two or more airflow apertures (1023) being formed at the periphery expanded from the central area of the base structure (102) of the heat dissipation device (100) shown in FIG. 1, according to one embodiment of the present invention;

As shown in FIG. 4, it mainly consists of:

-- heat dissipation device (100): composed of a heat conductive material, e.g. aluminum, copper, alloy or ceramic material, formed in a U-shaped plate-like shape, circular cup-like shape or polygonal cup-like shape, or formed in a fork-like cup-shaped structure having upward heat dissipating fork at the outer side, two or more airflow apertures (1023) are formed at the periphery expanded from the central area of the base structure (102), which is installed with the heat generating device (101), of the heat dissipation device (100), the airflow apertures (1023) are formed as plural individual apertures or a structure having net-like apertures or grid-like aperture, the center of the heat dissipation device (100) is installed with the heat generating device (101), and the close-loop shunting heat conductive structure (103) is installed between the central location (a) of the base structure (102) close to the heat generating device (101) and the distal location (d) of the distal heat dissipating segment (104), thereby reducing the temperature differentiation between the central location (a) of the base structure (102) close to the heat generating device (101) and the distal location (d) of the distal heat dissipating segment (104);

-- heat generating device (101): composed of one or more semiconductor components which generating heat loss such as light emitting diodes (LED),

central processing unit (CPU), memory, power semiconductors, rectifier, or power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat, served for being combined with the base structure (102) or directly being heated by the external from the base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device, and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material, integrally formed with the heat dissipation device (100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103).

FIG. 5 is a schematic structural view illustrating the present invention being formed as a heat dissipation device having U-shaped structure (1000), wherein the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) being formed with airflow apertures (1052), according to one embodiment of the present invention;

FIG. 6 is a top view of FIG. 5;

FIG. 7 is a lateral view of FIG. 5;

As shown in FIG. 5, FIG. 6 and FIG. 7, the main configuration is that the heat dissipation device having U-shaped structure (1000) disclosed in FIG. 4 is adopted as a foundation, the characteristic is that the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) is further formed with the airflow apertures (1052), and the airflow apertures (1052) can be formed as plural individual apertures, or a structure having

net-like or grid-like apertures, the top edge of the distal heat dissipating segment (104) can be formed with a multiple-surface or annular or tooth-like crown or fork-like structure, and the surface thereof includes planar or grid-like shape or a structure with the heat dissipation fin.

5 FIG. 8 is a schematic structural view illustrating the present invention being formed as a heat dissipation device having U-shaped structure (1000), wherein the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) being formed with a radial grid heat dissipation space, according to one embodiment of the present invention;

10 FIG. 9 is a top view of FIG. 8;

FIG. 10 is a lateral view of FIG. 8;

As shown in FIG. 8, FIG. 9 and FIG. 10, the main configuration is that the heat dissipation device having U-shaped structure (1000) disclosed in FIG. 4 is adopted as a foundation, the characteristic is that the close-loop shunting
15 heat conductive structure (103) and/or the distal heat dissipating segment (104) is further formed with the radial grid heat dissipation space, the top edge of the distal heat dissipating segment (104) can be formed with a multiple-surface or annular or tooth-like crown or fork-like structure, and the surface thereof includes planar or grid-like shape or a structure with the heat
20 dissipation fin.

FIG. 11 is a schematic structural view illustrating the present invention being formed as a heat dissipation device having tubular structure (2000), wherein the periphery of the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) and/or the heat
25 dissipation device having tubular structure (2000) being formed with airflow apertures (1052), according to one embodiment of the present invention;

FIG. 12 is a top view of FIG. 11;

FIG. 13 is a lateral view of FIG. 11;

As shown in FIG. 11, FIG. 12 and FIG. 13, the main configuration is that
30 the heat dissipation device having tubular structure (2000) is adopted as a

foundation, wherein the heat dissipation device having tubular structure (2000) is composed of a heat conductive material and formed in a tubular shape, the top thereof is formed as an opened or sealed or semi-sealed structure, the bottom thereof is formed as a round plate-like structure, the periphery of the heat dissipation device having tubular structure (2000) is combined with the distal heat dissipating segment (104) composed of an annularly upwardly-extended structure formed in planar or grid-like shape or a surface with the heat dissipation fin, and radially-arranged airflow apertures (1052) are formed on the central area of the distal heat dissipating segment (104) facing the distal end of the distal heat dissipating segment (104), and/or the heat conductive structural surface formed on the close-loop shunting heat conductive structure (103) outwardly expanded towards the distal heat dissipating segment (104), and/or the heat conductive surface formed on the heat dissipation device having tubular structure (2000) outwardly expanded towards the periphery, and the bottom central area of the heat dissipation device having tubular structure (2000) is installed with the heat generating device (101).

FIG. 14 is a schematic structural view illustrating the present invention being formed as a heat dissipation device having tubular structure (2000), wherein the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) being formed with the radial grid heat dissipation space, according to one embodiment of the present invention;

FIG. 15 is a top view of FIG. 14;

FIG. 16 is a lateral view of FIG. 14;

As shown in FIG. 14, FIG. 15 and FIG. 16, the main configuration is that the heat dissipation device having tubular structure (2000) is adopted as a foundation, wherein the heat dissipation device having tubular structure (2000) is composed of a heat conductive material and formed in a tubular shape, the top thereof is formed as an opened or sealed or semi-sealed structure, the bottom thereof is formed as a round plate shaped heat dissipation device (100),

the periphery of the heat dissipation device having tubular structure (2000) is combined with the distal heat dissipating segment (104) composed of an annularly upwardly-extended structure formed in planar or grid-like shape or a surface with the heat dissipation fin, and radially-arranged airflow apertures (1052) are formed on the heat conductive structural surface formed on the close-loop shunting heat conductive structure (103) outwardly expanded towards the distal heat dissipating segment (104), and/or the heat conductive surface formed on the heat dissipation device having tubular structure (2000) outwardly expanded toward the periphery, and the bottom central area of the heat dissipation device having tubular structure (2000) is installed with the heat generating device (101).

FIG. 17 is a lateral view illustrating the present invention being applied in a LED lamp, according to the first embodiment of the present invention;

FIG. 18 is a top view of FIG. 17;

As shown in FIG. 17 and FIG. 18, the light emitting diodes (111) are annularly arranged at the periphery of the central airflow aperture (1022) at the light projection side of the heat dissipation device (100); wherein:

--heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an outer heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an inner heat dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the center of the light projection side is formed with a central airflow aperture (1022) allowing air to flow, the housing dimension at the other side of the heat dissipation

device (100) is gradually reduced thereby forming the distal heat dissipating segment (104) which is in a sealed or semi-sealed or opened state for being served as an interface structure connecting with a fastening and electric conducting interface (114);

5 --the housing of the heat dissipation device (100) close to the distal heat dissipating augment (104) is formed with one or more radial airflow apertures (107), and the radial airflow aperture (107) includes being composed of a grid aperture having pore or net-like structure;

10 --the center of the heat dissipation device (100) close to the light projection side is formed with the central airflow aperture (1022), the central airflow aperture (1022) is formed as a single aperture or plural aperture structure, the plural aperture structure include plural individual apertures or net-like apertures or grid-like apertures, and the periphery defined along the central airflow aperture (1022) is annularly installed with the light emitting
15 diodes (111);

20 -- the close-loop shunting heat conductive structure (103) is installed between the inner periphery of the central airflow aperture (1022) at the inner side of the heat dissipation device (100) close to the light projection side and the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111) close to the central airflow aperture (1022);

25 --close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive structure, installed between the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100) and the inner periphery of the central airflow aperture (1022), the constitution means includes being integrally formed with the heat dissipation device (100) through a die casting or metal casting or punching or forging or processing means, or individually manufactured for being mounted or laminated or
30 welded or riveted or locked between the inner heat dissipation surface (106)

defined at the mid portion of the radial housing of the heat dissipation device (100) and the inner periphery of the central airflow aperture (1022) for conducting heat, the structural configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique
5 conical surface having airflow apertures;

With the mentioned structure, when the light emitting diode (111) is electrically charged and generates heat loss, if the light projection side of the heat dissipation device (100) is downwardly arranged, the hot airflow inside the heat dissipation device (100) generates the hot ascent/cold descent effect,
10 the airflow is then introduced from the central airflow aperture (1022) of the light projection side, and discharged through the radial airflow apertures (107) close to the distal heat dissipating segment (104) thereby generating flowing air for discharging the heat inside the heat dissipation device (100); if the light projection side of the heat dissipation device (100) is upwardly arranged, the
15 air flowing direction is opposite;

--light emitting diode (111): composed of light emitting diode (111) or a light emitting diode module, arranged at the outer bottom periphery of the light projection side of the heat dissipation device (100), and served to project light according to the set direction;

20 --secondary optical device (112): composed of a structural device having functions of condensing, defusing, reflecting or refracting the optical energy of the light emitting diode (111) for projecting light to the exterior; the secondary optical device (112) can be optionally installed according to the actual needs;

25 --light pervious lamp cover (113): made of a light pervious material, provided for covering the light emitting diode (111) so as to protect the light emitting diode (111), allowing the optical energy of the light emitting diode (111) to be transferred through for being projected to the exterior; the light pervious lamp cover (113) can be optionally installed according to the actual
30 needs;

--fastening and electric conducting interface (114): one side thereof is combined with the distal heat dissipating segment (104) of the heat dissipation device (100), the other side is formed as a screw-in type, mount type or lock type lamp head or lamp seat, or an electric conductive interface structure composed of conductive wires or electric conductive terminals, served as a connection interface to the external electric power, and provided with an electric conductive member for being connected with the light emitting diode (111) through a drive circuit device (115) for conducting electric power;

--drive circuit device (115): composed of a solid-state electronic device and/or electromechanical device, provided for converting the electric power from the fastening and electric conducting interface (114) into the electric power for driving the light emitting diode (111), and provided for setting and controlling the voltage and current of the electric power used for driving the light emitting diode (111); the drive circuit device (115) can be optionally installed according to the actual needs;

--conductive wire (116): composed of a conductive member having insulation surface, provided for transferring the electric power of the drive circuit device (115) to the light emitting diode (111).

FIG. 19 is a lateral view illustrating the present invention being applied in a LED lamp, according to the second embodiment of the present invention;

FIG. 20 is a top view of FIG. 19;

As shown in FIG. 19 and FIG. 20, radial airflow apertures (107) are formed at the periphery of lower layer of the heat dissipation device (100) close to the light projection side, and the light emitting diodes (111) are arranged in the housing of the heat dissipation device (100) at the center of the light projection side; wherein:

--heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth

surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an outer heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure
5 having net-like or porous shape or having fins, thereby forming an inner heat dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the housing dimension at the other side of the heat dissipation device (100) is gradually
10 reduced thereby forming the distal heat dissipating segment (104) which is in a sealed or semi-sealed or opened state for being served as an interface structure connecting with a fastening and electric conducting interface (114);

--the housing of the heat dissipation device (100) close to the distal heat dissipating segment (104) is formed with one or more radial airflow apertures
15 (107) at the upper layer and formed with the radial airflow apertures (107) at the lower layer close to the light projection side, the radial airflow apertures (107) at the upper layer and the radial airflow apertures (107) close to the light projection side include being formed as plural individual apertures or a structure having net-like apertures or grid-like apertures;

20 --the center of the housing of the heat dissipation device (100) close to the light projection side is installed with the light emitting diodes (111);

-- the close-loop shunting heat conductive structure (103) is installed between the center at the inner of the housing of the heat dissipation device (100) close to the light projection side and the inner heat dissipation surface
25 (106) defined at the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111);

--close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive
30 structure, installed between the inner heat dissipation surface (106) defined at

the mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side, the constitution means includes being integrally formed with the heat dissipation device (100) through a die casting or metal casting or punching or forging or processing means, or individually manufactured for being mounted or laminated or welded or riveted or locked between the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side for conducting heat, the structural configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique conical surface having airflow apertures;

With the mentioned structure, when the light emitting diode (111) is electrically charged and generates heat loss, if the light projection side of the heat dissipation device (100) is downwardly arranged, the hot airflow inside the heat dissipation device (100) generates the hot ascent/cold descent effect, airflow is then introduced from the radial airflow apertures (107) at the lower side of the outer heat dissipation surface (105) close to the light projection side, and discharged through the radial airflow apertures (107) at the higher side close to the distal heat dissipating segment (104) thereby generating flowing air for discharging the heat inside the heat dissipation device (100); if the light projection side of the heat dissipation device (100) is upwardly arranged, the air flowing direction is opposite;

--light emitting diode (111): composed of light emitting diode (111) or a light emitting diode module, arranged at the center of outer bottom of the light projection side of the heat dissipation device (100), and served to project light according to the set direction;

and optionally installed with the secondary optical device (112), the light pervious lamp cover (113), the fastening and electric conducting interface (114), the drive circuit device (115), or the conductive wire (116).

FIG. 21 is a lateral view illustrating the present invention being applied in a LED lamp, according to the third embodiment of the present invention;

FIG. 22 is a top view of FIG. 21;

As shown in FIG. 21 and FIG. 22, annularly-arranged axial airflow apertures (110) are formed at the periphery of the light projection side of the heat dissipation device (100), and the light emitting diodes (111) are arranged at the center of the housing of the heat dissipation device (100) at the light projection side; wherein:

--heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an outer heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an inner heat dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the annularly-arranged axial airflow apertures (110) are formed at the periphery of the light projection side, and the housing dimension at the other side of the heat dissipation device (100) is gradually reduced thereby forming the distal heat dissipating segment (104) which is in a sealed or semi-sealed or opened state for being served as an interface structure connecting with a fastening and electric conducting interface (114);

--the housing of the heat dissipation device (100) close to the distal heat dissipating segment (104) is formed with one or more radial airflow apertures (107), the radial airflow apertures (107) include plural individual apertures or a structure having net-like apertures or grid-like apertures;

--the bottom side near the outer periphery of the light projection side at

the bottom of the housing of the heat dissipation device (100) are annularly formed with annularly-arranged axial airflow apertures (110), the annularly-arranged axial airflow apertures (110) include plural individual apertures or a structure having net-like apertures or grid-like apertures;

5 --the center of the housing of the heat dissipation device (100) close to the light projection side is installed with the light emitting diodes (111);

 -- the close-loop shunting heat conductive structure (103) is installed between the center at the inner of the housing of the heat dissipation device (100) close to the light projection side and the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111);

 -- close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive structure, installed between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side, the constitution means includes being integrally formed with the heat dissipation device (100) through a die casting or metal casting or punching or forging or processing means, or individually manufactured for being mounted or laminated or welded or riveted or locked between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side for conducting heat, the structural configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique conical surface having airflow apertures;

 With the mentioned structure, when the light emitting diode (111) is electrically charged and generates heat loss, if the light projection side of the heat dissipation device (100) is downwardly arranged, the hot airflow inside

the heat dissipation device (100) generates the hot ascent/cold descent effect, airflow is then introduced from the annularly-arranged axial airflow apertures (110) formed at the periphery of the light projection side, and discharged through the radial airflow apertures (107) close to the distal heat dissipating segment (104) thereby generating flowing air for discharging the heat inside the heat dissipation device (100); if the light projection side of the heat dissipation device (100) is upwardly arranged, the air flowing direction is opposite;

-- light emitting diode (111): composed of light emitting diode (111) or a light emitting diode module, arranged at the center of outer bottom of the light projection side of the heat dissipation device (100), and arranged in a circular and downward-facing state and served to project light according to the set direction;

and optionally installed with the secondary optical device (112), the light pervious lamp cover (113), the fastening and electric conducting interface (114), the drive circuit device (115), or the conductive wire (116).

FIG. 23 is a lateral view illustrating the present invention being applied in a LED lamp, according to the fourth embodiment of the present invention;

FIG. 24 is a bottom view of FIG. 23;

As shown in FIG. 23 and FIG. 24, the annularly-arranged axial airflow apertures (110) are annularly formed at the periphery of the light projection side of the heat dissipation device (100) and the central airflow aperture (1022) is formed at the center of the light project side, the light emitting diodes (111) are arranged between the central airflow aperture (1022) and the annually-arranged axial airflow apertures (110) at the light projection side of the heat dissipation device (100); wherein:

--heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having

net-like or porous shape or having fins, thereby forming an outer heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an inner heat
5 dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the center of the light projection side is formed with the central airflow aperture (1022) allowing air to flow thereby forming axial apertures and the
10 annularly-arranged axial airflow apertures (110) which are annularly arranged, the housing dimension at the other side of the heat dissipation device (100) is gradually reduced thereby forming the distal heat dissipating segment (104) which is in a sealed or semi-sealed or opened state for being served as an interface structure connecting with a fastening and electric conducting
15 interface (114);

--the housing of the heat dissipation device (100) close to the distal heat dissipating segment (104) is formed with one or more radial airflow apertures (107), the radial airflow apertures (107) include plural individual apertures or net-like apertures or grid-like apertures;

20 --the light emitting diodes (111) are annularly arranged between the central airflow aperture (1022) close to the light projection side of the heat dissipation device (100) and the annularly-arranged axial airflow apertures (110); wherein the central airflow aperture (1022) includes single aperture or plural aperture structure, the plural aperture structure include plural individual
25 apertures or net-like apertures or grid-like apertures, the annularly-arranged axial airflow apertures (110) include plural individual apertures or a structure having net-like apertures or grid-like apertures;

-- the close-loop shunting heat conductive structure (103) is installed between the inner periphery of the central airflow aperture (1022) at the inner
30 side of the housing of the heat dissipation device (100) close to the light

projection side and the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111) adjacent to the central airflow aperture (1022);

5 --close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive structure, installed between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation device (100) and the inner periphery of the central airflow aperture (1022), the constitution
10 means includes being integrally formed with the heat dissipation device (100) through a die casting or metal casting or punching or forging or processing means, or individually manufactured for being mounted or laminated or welded or riveted or locked between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation
15 device (100) and the inner periphery of the central airflow aperture (1022) for conducting heat, the structural configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique conical surface having airflow apertures;

With the mentioned structure, when the light emitting diode (111) is
20 electrically charged and generates heat loss, if the light projection side of the heat dissipation device (100) is downwardly arranged, the hot airflow inside the heat dissipation device (100) generates the hot ascent/cold descent effect, airflow is then introduced from the central airflow aperture (1022) and the annularly-arranged axial airflow apertures (110) of the light projection side,
25 and discharged through the radial airflow apertures (107) close to the distal heat dissipating segment (104) thereby generating flowing air for discharging the heat inside the heat dissipation device (100); if the light projection side of the heat dissipation device (100) is upwardly arranged, the air flowing direction is opposite;

30 --light emitting diode (111): composed of light emitting diode (111) or a

light emitting diode module, arranged between the outer periphery of the central airflow aperture (1022) and the annularly-arranged axial airflow apertures (110) of the light projection side of the heat dissipation device (100), and between the annularly-arranged axial airflow apertures (110) and the outer periphery of the heat dissipation device (100), downward-facing arranged in ring shape in two or more rings, and served to project light according to the set direction;

and optionally installed with the secondary optical device (112), the light pervious lamp cover (113), the fastening and electric conducting interface (114), the drive circuit device (115), or the conductive wire (116): composed of a conductive member having insulation surface, provided for transferring the electric power of the drive circuit device (115) to the light emitting diode (111).

According to heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure of the present invention, the structural members and the structural characteristics can be selected from the followings with respect to the actual application, including:

--the heat dissipation device (100), the heat dissipation device having U-shaped structure (1000), or the heat dissipation device having tubular structure (2000) is installed with a part or all of the central airflow aperture (1022), the annularly-arranged axial airflow aperture (110), the radial airflow aperture (107), the airflow aperture (1023) and the airflow aperture (1052), and the installed quantity of each type of the airflow apertures.

According to the heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure of the present invention, the housing contour of the heat dissipation device (100) includes:

- (1) formed as a hollow cup-shaped member having smaller top and larger bottom (as shown from FIG. 17 to FIG. 24); or
- (2) formed as a hollow cup-shaped member having larger top and

smaller bottom (as shown from FIG. 25 to FIG. 32); or

(3) formed as a hollow cup-shaped member being parallel or substantially-parallel (as shown from FIG. 33 to FIG. 40).

According to the heat dissipation device having lateral-spreading heat
5 dissipating and shunting heat conductive structure of the present invention,
the geometric shape of the housing of the heat dissipation device (100) can be
formed as the following geometric shapes according to the actual applications,
wherein the hollow housing cross section of the heat dissipation device (100)
includes:

10 (1) formed as a hollow tubular structure with round or round-like shape;
or

(2) formed as a hollow tubular structure having polygonal shape with
three or more sides or polygonal-like shape.

CLAIMS

1. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure, in which the top central area or the bottom central area of heat conductive interface of the heat dissipation device (100) where a heat generating device (101) being provided is installed with be heat generating device (101), the central area of heat conductive interface of the mentioned heat dissipation device (100) is installed with a close-loop shunting heat conductive structure, so the heat at the periphery of the heat generating device (101) can be conducted from the outer periphery to the distal heat dissipating segment (104) for being dissipated to the exterior, and the heat at the central area can be conducted through the close-loop shunting heat conductive structure (103) to the distal heat dissipating segment (104) for being dissipated to the exterior;
the mentioned heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure includes the close-loop shunting heat conductive structure (103) is installed between the central area of the base structure (102) of the heat dissipation device (100) and the combining location (c) of the outwardly expanding distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103);
it mainly consists of:
 - heat dissipation device (100): composed of a heat conductive material, e.g. aluminum, copper, alloy or ceramic material, formed in a plate-like shape, or disc-like shape or polygonal shape, the base structure (102) at the center is installed with the heat generating device (101);
 - heat generating device (101): composed of one or more semiconductor components which generating heat loss such as light emitting diodes (LED), central processing unit (CPU), memory, power semiconductors, rectifier, or power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat, served for being combined with the base structure (102) or directly being

heated by the external from the base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device, and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material, integrally formed with the heat dissipation device (100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103);

the mentioned heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure further includes the heat generating device (101) is installed in the base structure (102) at one or more bottom lateral sides of the heat dissipation device (100), and a close-loop shunting heat conductive structure (103) in one or more loops is installed between one or more sides of the base structure (102) away from the distal heat dissipating segment (104) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103).

2. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, wherein the close-loop shunting heat conductive structure (103) is installed between the central area of the base structure (102) of the heat dissipation device (100) and the combining location (c) of the horizontally expanding and upwardly extending distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103); it mainly consists of:

-- heat dissipation device (100): composed of a heat conductive material,

e.g. aluminum, copper, alloy or ceramic material, formed in a U-shaped plate shape, circular cup-like shape or polygonal cup-like shape, or formed in a fork-like cup-shaped structure having upward heat dissipating fork at the outer side, the center of the heat dissipation device (100) is installed with the heat generating device (101), and the close-loop shunting heat conductive structure (103) is installed between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining locations (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103), thereby reducing the temperature differentiation between the central location (a) of the base structure (102) close to the heat generating device (101) and the distal location (d) of the distal heat dissipating segment (104);

-- heat generating device (101): composed of two or more semiconductor components which generating heat loss such as light emitting diodes (LED), central processing unit (CPU), memory, power semiconductors, rectifier, or power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat, served for being combined with the base structure (102) or directly being heated by the external from the base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device, and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material, integrally formed with the heat dissipation device (100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining locations (c) of the distal heat dissipating

segment (104) and the close-loop shunting heat conductive structure (103).

3. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, wherein includes the structure that the heat dissipation device (100) is formed with the central airflow aperture (1022); it mainly consists of:

5 -- heat dissipation device (100): composed of a heat conductive material, e.g. aluminum, copper, alloy or ceramic material, formed in a U-shaped plate-like shape, circular cup-like shape or polygonal cup-like shape, or formed in a fork-like cup-shaped structure having upward heat dissipating fork at the outer side, the heat dissipation device (100) is formed with the central airflow aperture (1022) and one or more heat generating devices (101) are installed at the periphery of the central airflow aperture (1022), the central airflow aperture (1022) is formed as a single aperture or plural aperture structure, the plural aperture structure include plural individual apertures or net-like apertures or grid-like apertures, the center of the heat dissipation device (100) is installed with the heat generating device (101), and the close-loop shunting heat conductive structure (103) is installed between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103), thereby reducing the temperature differentiation between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103);

15 -- heat generating device (101): composed of two or more semiconductor components which generating heat loss such as light emitting diodes (LED), central processing unit (CPU), memory, power semiconductors, rectifier, or power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat,

20

25

30

served for being combined with the base structure (102) or directly being heated by the external from the base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device, and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material, integrally formed with the heat dissipation device (100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central locations (a) of the base structure (102) close to the heat generating devices (101) at the periphery of the central airflow aperture (1022) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103).

4. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, wherein two or more airflow apertures (1023) are formed at the periphery expanded from the central area of the base structure (102) of the heat dissipation device (100); it mainly consists of:

-- heat dissipation device (100): composed of a heat conductive material, e.g. aluminum, copper, alloy or ceramic material, formed in a U-shaped plate-like shape, circular cup-like shape or polygonal cup-like shape, or formed in a fork-like cup-shaped structure having upward heat dissipating fork at the outer side, two or more airflow apertures (1023) are formed at the periphery expanded from the central area of the base structure (102), which is installed with the heat generating device (101), of the heat dissipation device (100), the airflow apertures (1023) are formed as plural individual apertures or a structure having net-like apertures or grid-like aperture, the center of the heat dissipation device (100) is installed with the

heat generating device (101), and the close-loop shunting heat conductive structure (103) is installed between the central location (a) of the base structure (102) close to the heat generating device (101) and the distal location (d) of the distal heat dissipating segment (104), thereby reducing the temperature differentiation between the central location (a) of the base structure (102) close to the heat generating device (101) and the distal location (d) of the distal heat dissipating segment (104);

-- heat generating device (101): composed of one or more semiconductor components which generating heat loss such as light emitting diodes (LED), central processing unit (CPU), memory, power semiconductors, rectifier, or power IC, and etc., or composed of an electrically-charged heating member or a heat conductive material receiving external heat, served for being combined with the base structure (102) or directly being heated by the external from the base structure (102), or served as the active heat generating device such as the electrical or combustion-heated heater, oven or cookware, the heat source thereof is usually disposed at the central bottom of the heat dissipation device, and the heat is transmitted through the heat conductive structure radially extended outward and upward to the distal end of the heat dissipating device, and then dissipated outwardly;

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material, integrally formed with the heat dissipation device (100), or composed of the same or different material with respect to the heat dissipation device (100), and combined or welded between the central location (a) of the base structure (102) close to the heat generating device (101) and the combining location (c) of the distal heat dissipating segment (104) and the close-loop shunting heat conductive structure (103).

5. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, which includes a heat dissipation device having U-shaped structure (1000), wherein the close-loop shunting heat conductive structure (103) and/or the distal heat

dissipating segment (104) are formed with airflow apertures (1052); the main configuration is that the heat dissipation device having U-shaped structure (1000) is adopted as a foundation, the characteristic is that the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) is further formed with the airflow apertures (1052), and the airflow apertures (1052) can be formed as plural individual apertures, or a structure having net-like or grid-like apertures, the top edge of the distal heat dissipating segment (104) can be formed with a multiple-surface or annular or tooth-like crown or fork-like structure, and the surface thereof includes planar or grid-like shape or a structure with the heat dissipation fin.

6. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, which includes a heat dissipation device having U-shaped structure (1000), wherein the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) are formed with a radial grid heat dissipation space; the main configuration is that the heat dissipation device having U-shaped structure (1000) is adopted as a foundation, and the characteristic is that the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) is further formed with the radial grid heat dissipation space, the top edge of the distal heat dissipating segment (104) can be formed with a multiple-surface or annular or tooth-like crown or fork-like structure, and the surface thereof includes planar or grid-like shape or a structure with the heat dissipation fin.

7. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, which includes a heat dissipation device having tubular structure (2000), wherein the periphery of the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) and/or the heat dissipation device having tubular structure (2000) are formed with airflow apertures (1052);

the main configuration is that the heat dissipation device having tubular structure (2000) is adopted as a foundation, wherein the heat dissipation device having tubular structure (2000) is composed of a heat conductive material and formed in a tubular shape, the top thereof is formed as an
5 opened or sealed or semi-sealed structure, the bottom thereof is formed as a round plate-like structure, the periphery of the heat dissipation device having tubular structure (2000) is combined with the distal heat dissipating segment (104) composed of an annularly upwardly-extended structure formed in planar or grid-like shape or a surface with the heat dissipation fin,
10 and radially-arranged airflow apertures (1052) are formed on the central area of the distal heat dissipating segment (104) facing the distal end of the distal heat dissipating segment (104), and/or the heat conductive structural surface formed on the close-loop shunting heat conductive structure (103) outwardly expanded towards the distal heat dissipating segment (104),
15 and/or the heat conductive surface formed on the heat dissipation device having tubular structure (2000) outwardly expanded towards the periphery, and the bottom central area of the heat dissipation device having tubular structure (2000) is installed with the heat generating device (101).

8. A heat dissipation device having lateral-spreading heat dissipating and
20 shunting heat conductive structure as claimed in claim 1, which includes a heat dissipation device having tubular structure (2000), wherein the close-loop shunting heat conductive structure (103) and/or the distal heat dissipating segment (104) are formed with the radial grid heat dissipation space; the main configuration is that the heat dissipation device having
25 tubular structure (2000) is adopted as a foundation, wherein the heat dissipation device having tubular structure (2000) is composed of a heat conductive material and formed in a tubular shape, the top thereof is formed as an opened or sealed or semi-sealed structure, the bottom thereof is formed as a round plate shaped heat dissipation device (100), the
30 periphery of the heat dissipation device having tubular structure (2000) is

combined with the distal heat dissipating segment (104) composed of an annularly upwardly-extended structure formed in planar or grid-like shape or a surface with the heat dissipation fin, and radially-arranged airflow apertures (1052) are formed on the heat conductive structural surface formed on the close-loop shunting heat conductive structure (103) outwardly expanded towards the distal heat dissipating segment (104), and/or the heat conductive surface formed on the heat dissipation device having tubular structure (2000) outwardly expanded toward the periphery, and the bottom central area of the heat dissipation device having tubular structure (2000) is installed with the heat generating device (101).

9. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, which is applied in a LED lamp, including the light emitting diodes (111) being annularly arranged at the periphery of the central airflow aperture (1022) at the light projection side of the heat dissipation device (100); wherein:

--heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an outer heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an inner heat dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the center of the light projection side is formed with a central airflow aperture (1022) allowing air to flow, the housing dimension at the other side of the heat dissipation device (100) is gradually reduced thereby forming the distal heat dissipating segment (104) which is in a sealed or

semi-sealed or opened state for being served as an interface structure connecting with a fastening and electric conducting interface (114);

--the housing of the heat dissipation device (100) close to the distal heat dissipating augment (104) is formed with one or more radial airflow apertures (107), and the radial airflow aperture (107) includes being composed of a grid aperture having pore or net-like structure;

--the center of the heat dissipation device (100) close to the light projection side is formed with the central airflow aperture (1022), the central airflow aperture (1022) is formed as a single aperture or plural aperture structure, the plural aperture structure include plural individual apertures or net-like apertures or grid-like apertures, and the periphery defined along the central airflow aperture (1022) is annularly installed with the light emitting diodes (111);

-- the close-loop shunting heat conductive structure (103) is installed between the inner periphery of the central airflow aperture (1022) at the inner side of the heat dissipation device (100) close to the light projection side and the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111) close to the central airflow aperture (1022);

--close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive structure, installed between the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100) and the inner periphery of the central airflow aperture (1022), the constitution means includes being integrally formed with the heat dissipation device (100) through a die casting or metal casting or punching or forging or processing means, or individually manufactured for being mounted or laminated or welded or riveted or locked between the inner heat dissipation surface (106) defined at the mid portion of the radial housing

of the heat dissipation device (100) and the inner periphery of the central airflow aperture (1022) for conducting heat, the structural configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique conical surface having airflow apertures;

5 --light emitting diode (111): composed of light emitting diode (111) or a light emitting diode module, arranged at the outer bottom periphery of the light projection side of the heat dissipation device (100), and served to project light according to the set direction;

--secondary optical device (112): composed of a structural device having
10 functions of condensing, defusing, reflecting or refracting the optical energy of the light emitting diode (111) for projecting light to the exterior; the secondary optical device (112) can be optionally installed according to the actual needs;

--light pervious lamp cover (113): made of a light pervious material,
15 provided for covering the light emitting diode (111) so as to protect the light emitting diode (111), allowing the optical energy of the light emitting diode (111) to be transferred through for being projected to the exterior; the light pervious lamp cover (113) can be optionally installed according to the actual needs;

20 --fastening and electric conducting interface (114): one side thereof is combined with the distal heat dissipating segment (104) of the heat dissipation device (100), the other side is formed as a screw-in type, mount type or lock type lamp head or lamp seat, or an electric conductive interface structure composed of conductive wires or electric conductive
25 terminals, served as a connection interface to the external electric power, and provided with an electric conductive member for being connected with the light emitting diode (111) through a drive circuit device (115) for conducting electric power;

--drive circuit device (115): composed of a solid-state electronic device
30 and/or electromechanical device, provided for converting the electric

power from the fastening and electric conducting interface (114) into the electric power for driving the light emitting diode (111), and provided for setting and controlling the voltage and current of the electric power used for driving the light emitting diode (111); the drive circuit device (115) can
5 be optionally installed according to the actual needs;
-- conductive wire (116): composed of a conductive member having insulation surface, provided for transferring the electric power of the drive circuit device (115) to the light emitting diode (111).

10. A heat dissipation device having lateral-spreading heat dissipating and
10 shunting heat conductive structure as claimed in claim 1, which is applied in a LED lamp, including radial airflow apertures (107) being formed at the periphery of lower layer of the heat dissipation device (100) close to the light projection side, and the light emitting diodes (111) being arranged in the housing of the heat dissipation device (100) at the center of the light
15 projection side; wherein:
-- heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure
20 having net-like or porous shape or having fins, thereby forming an outer heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming
25 an inner heat dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the housing dimension at the other side of the heat dissipation device (100) is gradually reduced thereby forming the distal heat dissipating segment
30 as an interface structure connecting with a fastening and electric

conducting interface (114);

-- the housing of the heat dissipation device (100) close to the distal heat dissipating segment (104) is formed with one or more radial airflow apertures (107) at the upper layer and formed with the radial airflow apertures (107) at the lower layer close to the light projection side, the radial airflow apertures (107) at the upper layer and the radial airflow apertures (107) close to the light projection side include being formed as plural individual apertures or a structure having net-like apertures or grid-like apertures;

-- the center of the housing of the heat dissipation device (100) close to the light projection side is installed with the light emitting diodes (111);

-- the close-loop shunting heat conductive structure (103) is installed between the center at the inner of the housing of the heat dissipation device (100) close to the light projection side and the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111);

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive structure, installed between the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side, the constitution means includes being integrally formed with the heat dissipation device (100) through a die casting or metal casting or punching or forging or processing means, or individually manufactured for being mounted or laminated or welded or riveted or locked between the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side for conducting heat, the structural

configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique conical surface having airflow apertures;

-- light emitting diode (111): composed of light emitting diode (111) or a light emitting diode module, arranged at the center of outer bottom of the light projection side of the heat dissipation device (100), and served to project light according to the set direction;

and optionally installed with the secondary optical device (112), the light pervious lamp cover (113), the fastening and electric conducting interface (114), the drive circuit device (115), or the conductive wire (116).

11. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, which is applied in a LED lamp, including annularly-arranged axial airflow apertures (110) being formed at the periphery of the light projection side of the heat dissipation device (100), and the light emitting diodes (111) being arranged at the center of the housing of the heat dissipation device (100) at the light projection side; wherein:

-- heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an outer heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an inner heat dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the annularly-arranged axial airflow apertures (110) are formed at the periphery of the light projection side, and the housing dimension at the

other side of the heat dissipation device (100) is gradually reduced thereby forming the distal heat dissipating segment (104) which is in a sealed or semi-sealed or opened state for being served as an interface structure connecting with a fastening and electric conducting interface (114);

5 -- the housing of the heat dissipation device (100) close to the distal heat dissipating segment (104) is formed with one or more radial airflow apertures (107), the radial airflow apertures (107) include plural individual apertures or a structure having net-like apertures or grid-like apertures;

-- the bottom side near the outer periphery of the light projection side at the bottom of the housing of the heat dissipation device (100) are annularly formed with annularly-arranged axial airflow apertures (110), the annularly-arranged axial airflow apertures (110) include plural individual apertures or a structure having net-like apertures or grid-like apertures;

10 -- the center of the housing of the heat dissipation device (100) close to the light projection side is installed with the light emitting diodes (111);

-- the close-loop shunting heat conductive structure (103) is installed between the center at the inner of the housing of the heat dissipation device (100) close to the light projection side and the inner heat dissipation surface (106) defined at the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111);

20 -- close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive structure, installed between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side, the constitution means includes being integrally formed with the heat dissipation device (100) through a

25 die casting or metal casting or punching or forging or processing means, or

30

individually manufactured for being mounted or laminated or welded or riveted or locked between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation device (100) and the center at the inner of the housing of the heat dissipation device (100) close to the light projection side for conducting heat, the structural configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique conical surface having airflow apertures;

-- light emitting diode (111): composed of light emitting diode (111) or a light emitting diode module, arranged at the center of outer bottom of the light projection side of the heat dissipation device (100), and arranged in a circular and downward-facing state and served to project light according to the set direction;

and optionally installed with the secondary optical device (112), the light pervious lamp cover (113), the fastening and electric conducting interface (114), the drive circuit device (115), or the conductive wire (116).

12. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, which is applied in a LED lamp, including the annularly-arranged axial airflow apertures (110) being annularly formed at the periphery of the light projection side of the heat dissipation device (100) and the central airflow aperture (1022) being formed at the center of the light project side, the light emitting diodes (111) being arranged between the central airflow aperture (1022) and the annually-arranged axial airflow apertures (110) at the light projection side of the heat dissipation device (100); wherein:

-- heat dissipation device (100): composed of a material having great heat conductivity, integrally formed or assembled by pieces for forming as a hollow member, the radial outer surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an outer

heat dissipation surface (105); the radial inner surface is formed as a plane and smooth surface, rib-like surface, grid-like surface, or formed with a structure having net-like or porous shape or having fins, thereby forming an inner heat dissipation surface (106); the housing dimension at one side of the heat dissipation device (100) is gradually enlarged towards the bottom side, and the outer bottom side is defined as a light projection side, the center of the light projection side is formed with the central airflow aperture (1022) allowing air to flow thereby forming axial apertures and the annularly-arranged axial airflow apertures (110) which are annularly arranged, the housing dimension at the other side of the heat dissipation device (100) is gradually reduced thereby forming the distal heat dissipating segment (104) which is in a sealed or semi-sealed or opened state for being served as an interface structure connecting with a fastening and electric conducting interface (114);

-- the housing of the heat dissipation device (100) close to the distal heat dissipating segment (104) is formed with one or more radial airflow apertures (107), the radial airflow apertures (107) include plural individual apertures or net-like apertures or grid-like apertures;

-- the light emitting diodes (111) are annularly arranged between the central airflow aperture (1022) close to the light projection side of the heat dissipation device (100) and the annularly-arranged axial airflow apertures (110); wherein the central airflow aperture (1022) includes single aperture or plural aperture structure, the plural aperture structure include plural individual apertures or net-like apertures or grid-like apertures, the annularly-arranged axial airflow apertures (110) include plural individual apertures or a structure having net-like apertures or grid-like apertures;

-- the close-loop shunting heat conductive structure (103) is installed between the inner periphery of the central airflow aperture (1022) at the inner side of the housing of the heat dissipation device (100) close to the light projection side and the inner heat dissipation surface (106) defined at

the mid portion of the radial housing of the heat dissipation device (100), thereby conducting the heat from the light emitting diodes (111) adjacent to the central airflow aperture (1022);

-- close-loop shunting heat conductive structure (103): composed of a heat conductive material and formed as an individual heat conductive structure, installed between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation device (100) and the inner periphery of the central airflow aperture (1022), the constitution means includes being integrally formed with the heat dissipation device (100) through a die casting or metal casting or punching or forging or processing means, or individually manufactured for being mounted or laminated or welded or riveted or locked between the inner heat dissipation surface (106) defined at the inner mid portion of the radial housing of the heat dissipation device (100) and the inner periphery of the central airflow aperture (1022) for conducting heat, the structural configuration includes being formed as a strip-shaped radial structure, or an oblique conical surface, or an oblique conical surface having airflow apertures;

-- light emitting diode (111): composed of light emitting diode (111) or a light emitting diode module, arranged between the outer periphery of the central airflow aperture (1022) and the annularly-arranged axial airflow apertures (110) of the light projection side of the heat dissipation device (100), and between the annularly-arranged axial airflow apertures (110) and the outer periphery of the heat dissipation device (100), downward-facing arranged in ring shape in two or more rings, and served to project light according to the set direction;

and optionally installed with the secondary optical device (112), the light pervious lamp cover (113), the fastening and electric conducting interface (114), the drive circuit device (115), or the conductive wire (116).

13. A heat dissipation device having lateral-spreading heat dissipating and

shunting heat conductive structure as claimed in claim 1, wherein the structural members and the structural characteristics can be selected from the followings with respect to the actual application, including:

-- the heat dissipation device (100), the heat dissipation device having U-shaped structure (1000), or the heat dissipation device having tubular structure (2000) is installed with a part or all of the central airflow aperture (1022), the annularly-arranged axial airflow aperture (110), the radial airflow aperture (107), the airflow aperture (1023) and the airflow aperture (1052), and the installed quantity of each type of the airflow apertures.

10 14. A heat dissipation device having lateral-spreading heat dissipating and shunting heat conductive structure as claimed in claim 1, wherein the housing contour of the heat dissipation device (100) includes:

(a) formed as a hollow cup-shaped member having smaller top and larger bottom; or

15 (b) formed as a hollow cup-shaped member having larger top and smaller bottom; or

(c) formed as a hollow cup-shaped member being parallel or substantially-parallel;

20 the hollow housing cross section of the heat dissipation device (100) includes:

(a) formed as a hollow tubular structure with round or round-like shape; or

(b) formed as a hollow tubular structure having polygonal shape with three or more sides or polygonal-like shape.

25