



METHOD AND APPARATUS FOR TWIST LOCK MANIPULATION

Field of the Invention

The invention relates to the handling of freight through the use of intermodal
5 devices such as containers, flat racks and similar devices applicable for use with
engagement devices such as twist-locks.

In particular, the invention relates to methods and devices for the engagement
and disengagement of twist-locks from said intermodal devices.

10 Background

Twist-locks are used for securing shipping containers to ships and to each other.
Twist-locks are mounted on the bottom and top of shipping containers and thereby
multiple containers can be joined in a vertical stack. When shipping containers have
been lifted off the ship by a crane the twist-locks must be removed before the containers
15 are taken to another location. Furthermore, when the containers are loaded onto a
vessel, twist-locks must be fitted at the wharf to secure containers on board the vessel.
Typically, securing or removing twist-locks is via manual handling of the twist-locks
below a shipping container held approximately 1 to 1.8 metres above the ground by the
crane.

20 This operation is dangerous as the stevedore must manually handle the twist-
locks which are quite heavy and work under or adjacent suspended loads in a high
traffic area. It is also inefficient as it can take one to three minutes to fit the twist-locks,
thereby slowing the crane cycle time. It is also labour cost intensive since two men are
often allocated to undertake such a task.



Methods and devices to alleviate this labour intensive task have been proposed including that disclosed in PCT/AU2005/001258, the contents of which are incorporated herein by reference.

5 An issue with such devices is the removal and storage of the twist-lock devices having been disengaged from the container. Whilst the device of PCT/AU2005/001258 reduces the bottleneck of the process by speeding the removal of the twist-locks, a further bottleneck may be created by the removal of the twist-locks from the device and subsequent storage. Whilst alternatives have been proposed to achieve this, a simpler
10 and cheaper option would provide further advantage to the process.

Summary of the Invention

In a first aspect, the invention provides a manipulation device for either securing a twist-lock to a shipping container or releasing it therefrom or both, the device
15 comprising engagement means operative to engage and rotate at least a portion of the twist-lock so as to secure the twist lock in the shipping container or to release it therefrom; a support member disposed above the engagement means, the support member being arranged to receive and support a mid region of the twist-lock whilst allowing a lower portion of the supported twist-lock to project below the member to be
20 engagable with the engagement means; said support member being in the form of a plate incorporating at least one aperture allowing the lower portion of the supported twist-lock to project below the plate; wherein said support member is selectively movable out of alignment with an axis of rotation of the twist-lock.

In a second aspect, the invention provides a storage bin for storing twist lock devices, comprising said storage bin having a housing, a floor and an internal assembly, said floor and assembly within said housing; said internal assembly for biasing the floor of said bin upwards using a resilient biasing assembly; said resilient biasing assembly
5 capable of applying sufficient force to overcome the weight of a pre-determined number of twist lock devices wherein a number in excess of said pre-determined number being of a force to overcome said force and consequently leading to a lowering of the floor.

In a third aspect, the invention provides a storage rack assembly for storing twist lock devices comprising a plurality of elongate racks for receiving twist lock devices in
10 sliding engagement; a drive arrangement to which said plurality of racks are mounted; said drive arrangement capable of moving said racks to discreet positions, said positions including at least one position whereupon twist lock devices may be received by at least one rack and an unloading position where at least one rack may unload twist lock devices.

15 Accordingly, by shifting the position of support member so as to be out of alignment with the axis of rotation of the engagement means a twist-lock supported by the support means may be placed in a more favourable position to facilitate removal than would otherwise be the case.

In a preferred embodiment, moving the twist-lock from out of alignment with
20 the axis of rotation may be achieved through rotation of the support member about an axis parallel to but not colinear with the axis of rotation of the engagement means.

In an alternative embodiment, the support member may be selectively rotatable about an axis not parallel to the axis of rotation of the engagement means. In a more preferred embodiment, the support member may be selectively rotatable about an axis at

right angle to the axis of rotation of the engagement means. In this case, the support member may be pivoted about said axis so as to move the plane defined by the support member so as to be inclined.

In a more preferred embodiment, moving said plane may cause the twist-lock to shift through gravity so as to self disengaged from said support member. Said self disengagement may be through sliding or falling from the support member through inclination of the plane defined by the support member.

In a preferred embodiment, movement of the support member may be through biasing by an actuator, said actuator may be hydraulic/electric or pneumatic.

In a more preferred embodiment, the actuator may be a rotation actuator so as to rotate the support member out of alignment with the axis of the rotation of the engagement member. Alternatively, the actuator may be a linear actuator such that the actuator biases the support member so as to pivot the support member and, consequently inclining the plane defined by the support member.

In a preferred embodiment, the support member may be movable in a direction of the axis of rotation of the engagement means. Alternatively, the engagement means may be movable relative to the support member in the direction of the axis of rotation. In a further preferred embodiment, both the support member and the engagement means may be movable in the direction of axis of rotation.

In a preferred embodiment, the manipulation device may comprise a frame incorporating both the engagement means and the support member such that the frame is movable in the direction of axis of rotation.

In a preferred embodiment, the frame may be arranged to be within a housing such that the frame is movable relative to the housing in the direction of axis of rotation.

Brief Description of Drawings

It will be convenient to further describe the present invention with respect to the accompanying drawings that illustrate possible arrangements of the invention. Other
5 arrangements of the invention are possible and, consequently the particularly of the accompanying drawings is not to be understood as superseding the generality of that preceding description of the invention.

Figures 1A to 1C are isometric views of a manipulation device according to one
10 embodiment of the present invention;

Figure 2 is a cross-sectional elevation view of a storage bin according to one embodiment of the present invention;

Figure 3 is an isometric view of a rack according to one embodiment of the present invention, and;

15 Figure 4 is an isometric view of a support platform according to one embodiment of the present invention.

Description of Preferred Embodiment

Intermodal devices, such as shipping containers are characterised by their ability to be engaged by standardised connections for the purpose of engaging said containers
20 to lift or for securing multiple containers in place.

One example of said standardised connection is a twist-lock which acts to engage two containers lying one on top of the other. The twist-lock is placed intermediate the containers engaging both so as to hold both together.

The invention relates to a manipulation device 5 for engaging and disengaging said twist-locks from a container with Figures 1A to C showing various views of said device 5.

5 The manipulation device 5 comprises an assembly 55, 60 mounted to a frame 50. The assembly 55, 60 has an upper section 60 engaged with the lower section 55 with the engagement being through hinges 35. With the lower section 55 engaged with the frame 50, the upper section 60 is free to pivot about the hinges 35 relative to the lower section 55. To control this pivotal movement there is mounted between the upper
10 and lower section 55, 60, a hydraulic ram 40 such that on extension of the ram 40, the upper section 60 selectively pivots relative to the lower section 55.

 The upper section 60 includes a support member 15 being a plate having a slot 25 into which the twist-lock 10 is inserted. The slot 25 and plate 15 are arranged such
15 that the twist-lock 10 sits on the plate 15 with the upper portion of the twist-lock 10 extending above the plate 15 and the lower portion extending below the plate 15.

 Mounted to the lower section 55 is an engagement member 20 comprising a U-shaped bracket which is shaped to receive and engage the lower portion of the twist-
20 lock 10 as it extends below the plate 15. Further, the engagement member 20 is mounted to a motor 30 capable of selectively rotating the engagement member 20 about an axis colinear with the vertical axis of the engagement member.

The twist-lock, on insertion into the manipulation device 5, is supported by the plate 15 and engaged by the engagement member 20, whereupon the lower portion of the twist-lock is rotated by the motor 30. This rotation is sufficient to either engage the upper portion of the twist-lock with a container or alternatively to disengage the upper
5 portion of the twist-lock from a container. In the case of the twist-lock 10 being disengaged from a container, on removal from the container, the twist-lock is then free to be removed from the manipulation device 5.

The steps to disengage the twist-lock from the manipulation device 5 commence
10 with the engagement member 20 disengaging from the twist-lock. This is achieved by activating the actuator 45 to lower the engagement member 20. The actuator 45 has sufficient stroke on the ram to move the engagement member 20 clear of the twist-lock whilst supported by the plate 15. Next, the pivoting actuator 40 is extended biasing the upper section 60 which consequently rotates about the hinges 35 tilting the upper
15 section 60 and, consequently the plate 15. As the slot 25, in which the twist-lock 10 is positioned, permits free sliding movement of the twist-lock 10, the twist-lock is then free to slide out of engagement from the upper section 60, by gravity. The twist-lock 10 may fall into a containment area such as the storage bin 70 shown in Figure 2 or, alternatively, to slide into engagement with the rack 100 shown in Figure 3. In a still
20 further embodiment, the twist-lock 10 may be more easily removed from the manipulation device 5 given the free sliding nature of the twist-lock 10 with the upper section 60 in the inclined position.

Figure 2 shows a purpose-built storage bin 70 according to one embodiment of the present invention. The storage bin 70 is adapted to receive the twist-locks 10 that are disengaged from the manipulation device 5. Said twist-locks fall within the space 95 defined by the outer shell 75 of the bin and the movable floor 80. The movable floor 80 is supported by a scissor lift arrangement 90 which is biased by a resilient assembly such a hydraulic ram or spring arrangement such that the number of twist-locks within the cavity 95 define the position of the movable floor 80 relative to the other shell 75. Said movable floor 80 is operable up or down 85 according to the position of the scissor lift 90 which in turn, because of the resilient assembly, is subject to the number of twist-lock within the cavity 95.

The resilient assembly is such that when a single layer, or less, of twist-locks are located within the cavity 95, the movable floor 80 is at its highest position. As subsequent twist-locks are added, the floor 80 will progressively move down as the outer shell 75 progressively fills. The movable floor 80 is intended to provide the available twist-locks within the cavity 95 at a convenient height so that, irrespective of the number of twist-locks within the bin 70, there will always be twist-locks available adjacent the top of the bin 70 for convenient access by those requiring said twist-locks.

Figure 3 shows an alternative, or a complementary, storage system for said twist-locks. Here a rack 100 mounted to a chain drive 110 includes a frame 105 into which can slot a finite number of twist-locks 115. Whilst this rack 100 cannot contain a comparable number of twist-locks to the bin 70, it does maintain the twist-locks 115 in a pre-determined orientation such that a user can more easily mount said twist-locks or

alternatively permit the automation of the positioning of the twist-locks ready for engagement within the manipulation device 5. Further, multiple rows of the frames 105 may be mounted to the chain drive 110 such that a larger number of twist-locks are available within the same rack system 100.

5

Figure 4 shows a platform 125 onto which a container (not shown) may be placed. In this embodiment the support platform 125 is sized to receive two 20 foot containers end to end or alternatively a single 40 foot container. The support platform 125 in this embodiment is configurable between the 20 foot and 40 foot containers, as
10 can be seen by the placement of manipulation devices 5, and corresponding storage bins 70, intermediate the extreme ends of said support platform 125. Accordingly there are further manipulation devices and corresponding bins placed at the corners of the support platform 125 to correspond with the connection points of either the extreme ends of a 40 foot container or ends of, end to end, 20 foot containers placed upon the
15 support platform. Further, each manipulation device 5 includes a bin 70 into which twist-locks may be placed after removable from the respective manipulation devices 5 or, alternatively, conveniently placed so as to permit a user to withdraw a twist-lock from the bin 70 and place it within the manipulation device ready for engagement with a container placed on said support platform 125.

20

THE CLAIMS:

1. A manipulation device for either securing a twist-lock to a shipping container or releasing it therefrom or both, the device comprising engagement means operative to engage and rotate at least a portion of the twist-lock so as to secure the twist lock in the shipping container or to release it therefrom;

a support member disposed above the engagement means, the support member being arranged to receive and support a mid region of the twist-lock whilst allowing a lower portion of the supported twist-lock to project below the member to be engagable with the engagement means;

said support member being in the form of a plate incorporating at least one aperture allowing the lower portion of the supported twist-lock to project below the plate;

wherein said support member is selectively movable out of alignment with an axis of rotation of the twist-lock.
2. A manipulation device according to claim 1, wherein the support member is arranged such that the selective movement of the support member causes the twist lock to disengage from said device.
3. A manipulation device according to claim 1 or 2, wherein said support member is selectively pivotable.
4. A manipulation device according to claim 3, wherein said support member is selectively pivotable about a pivoting axis perpendicular to the axis of rotation.

5. A manipulation device according to claim 3, wherein said support member is selectively pivotable about a pivotting axis parallel to the axis of rotation.
6. A manipulation device according to any one of the preceding claims, further including an actuator arranged to selectively bias the support member in a pivotal motion.
7. A manipulation device according to claim 6, wherein said actuator includes any one of: a hydraulic, electric or pneumatic ram.
8. A manipulation device according to any one of claims 1 to 7, wherein the support member is movable in the direction of the axis of rotation of the engagement means.
9. A manipulation device according to any one of claims 1 to 7, wherein the engagement means is movable relative to the support member in the direction of the axis of rotation of the engagement means.
10. A manipulation device according to any one of claims 1 to 7, wherein both the engagement means and the support member are movable in the direction of the axis of rotation of the engagement means.
11. A manipulation device according to any one of the preceding claims, further comprising a frame incorporating the engagement means and the support member, wherein in use, the frame is movable in the direction of the axis of rotation of the engagement means.

12. A manipulation device according to claim 11, further comprising a housing wherein the frame is disposed within the housing and movable relative to the housing in the direction of the axis of rotation of the engagement means.

5

13. A manipulation device according to claim 12, further comprising a height adjustment assembly operative to move the frame relative to the housing in the direction of the axis of rotation of the engagement means.

10

14. A manipulation device according to claim 13, wherein the height adjustment means is one or more hydraulic piston cylinder assemblies.

15

15. A manipulation device according to any one of the preceding claims, wherein the support member is interchangeable with at least one other support member of different shape to accommodate different types of twist-locks.

20

16. A manipulation device according to any one of the preceding claims, wherein the engagement means is interchangeable with at least one other engagement means of different shape to accommodate different types of twist-locks.

17. A manipulation device according to any one of claims 1 to 15, wherein the engagement means is able to be reconfigured to accommodate different types of twist-locks.

18. A manipulation device according to claim 17, wherein the engagement means comprises a plurality of elements that are movable between a retracted and extended position and wherein a recess operative to receive the twist-lock is formed on retracting selected areas of the elements.

5

19. A manipulation device according to claim 18, wherein the engagement means comprises a base plate and side plates, wherein at least one of the base plates or the side plates are extendable to vary the size or shape of a recess for receiving a twist-lock.

10

20. A manipulation device according to any one of claims 1 to 18, wherein the engagement means is in the form of jaws which are operable to grip the twist-lock disposed in the manipulation device.

15

21. A manipulation device according to any one of the preceding claims, further comprising an actuator operative to release a locking mechanism disposed on the twist-lock.

22. A storage bin for storing twist lock devices, comprising

20

said storage bin having a housing, a floor and an internal assembly, said floor and assembly within said housing;

said internal assembly for biasing the floor of said bin upwards using a resilient biasing assembly;

25

said resilient biasing assembly capable of applying sufficient force to overcome the weight of a pre-determined number of twist lock devices wherein a number

in excess of said pre-determined number being of a force to overcome said force and consequently leading to a lowering of the floor.

23. A system for removing and storing twist lock devices, comprising

- 5 a manipulation device according to any one of claims 1 to 21;
- a storage bin according to claim 22, said bin located adjacent to said manipulation device such that a twist lock removed by said manipulation device is capable of falling into said storage bin on activation of said manipulation device.

10

24. A storage rack assembly for storing twist lock devices comprising

- a plurality of elongate racks for receiving twist lock devices in sliding engagement;
- a drive arrangement to which said plurality of racks are mounted;
- 15 said drive arrangement capable of moving said racks to discreet positions, said positions including at least one position whereupon twist lock devices may be received by at least one rack and an unloading position where at least one rack may unload twist lock devices.

- 20 25. The storage rack assembly according to claim 24, wherein said drive arrangement includes a chain drive.