28 November 2002

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 :
H01L 21/00

A1

(11) International Publication Number: WO 99/63584

(43) International Publication Date: 9 December 1999 (09.12.99)

(21) International Application Number: PCT/US99/11554

(22) International Filing Date: 26 May 1999 (26.05.99)

(30) Priority Data:
10/150137 29 May 1998 (29.05.98) JP

(71) Applicant *(for all designated States except US)*: E.I. DU PONT DE NEMOURS AND COMPANY [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).

(72) Inventors; and
(75) Inventors/Applicants *(for US only)*: NAKAGAWA, Shinichi [JP/JP], Maruta Heights II 205, 631-15, Imaizumi-cho, Utsunomiya-shi, Tochigi 321-0962 (JP). SAKAI, Shuji [JP/JP]; 2-9-5-207, Tsunashima-nishi Kohoku-ku, Yokohama, Kanagawa (JP).

(74) Agent: BELOPOLSKY, Inna, Y.; E.I. du Pont de Nemours and Company, Legal Patent Records Center, 1007 Market Street, Wilmington, DE 19898 (US).


(81) Designated States: CA, CN, SG, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published
With international search report.
Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: RESIN MOLDED ARTICLE FOR CHAMBER LINER

(57) Abstract

A resin molded article for fitting to an inside wall of a liner in a chamber of a dry etching apparatus used in semiconductor manufacture is disclosed. The resin molded article is a seamless annular molded article having a heat resistance temperature of at least 100 °C, a tensile elongation at break of at least 0.3 %, a flexural modulus of at least 10,000 kg/cm^2, an outside diameter from 0 to 0.3 % larger than the inside diameter of the liner, and a wall thickness of not more than 2 mm.



162162

G00002