

WHAT IS CLAIMED IS:

1. A wearable device, adapted to be worn on at least one of a torso and limbs of a user or a combination thereof, the wearable device comprising:

a wearable body, having at least two fixing parts adapted to be fixed on at least two adjacent
5 movable joints of the user, such that the wearable body fits on at least one of the torso, the limbs, or the combination thereof, wherein the wearable body forms a positioning region between the at least two fixing parts, and that a part of at least one of the torso, the limbs, or the combination thereof located between the at least two adjacent movable joints is within a range of the positioning region; and

10 at least one positioning unit, located in the positioning region of the wearable body to correspond to a specific position of the user, wherein the positioning unit is fitted to a body shape of the user along with the wearable body, the positioning unit is a physical coordinate grid or a virtual coordinate grid shown, configured or virtually indicated on the positioning region, and the positioning unit is only arranged in a range of the positioning region which is defined among the
15 at least two fixing parts.

2. The wearable device according to claim 1, wherein the fixing part has a thickened structure corresponding to a periphery of a convex part of the movable joint.

3. The wearable device according to claim 1, wherein the fixing part has an opening corresponding to a convex part of the movable joint.

20 4. The wearable device according to claim 1, wherein the fixing part has a thickened structure corresponding to a recess of the movable joint.

5. The wearable device according to claim 1, wherein the fixing part has a strap structure tied to two opposite sides of the movable joint.

25 6. The wearable device according to claim 1, wherein the fixing part has a strap structure and a thickened structure, the strap structure is tied next to the movable joint, and the thickened

structure corresponds to a bone bulge of the user.

7. The wearable device according to claim 1, wherein a material of the wearable body in the positioning region has elasticity.