

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 October 2001 (18.10.2001)


PCT

(10) International Publication Number
WO 01/78437 A1

- (51) International Patent Classification⁷: **H04Q 7/38**,
H04L 12/56, H04Q 7/22
- (21) International Application Number: PCT/FI01/00353
- (22) International Filing Date: 10 April 2001 (10.04.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
20000855 10 April 2000 (10.04.2000) FI
- (71) Applicant (for all designated States except US): **NOKIA MOBILE PHONES LTD.** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **SARKKINEN, Sinikka** [FI/FI]; Kisällinkuja 5, FIN-36200 Kangasala
- (FI) **MIKOLA, Juha** [FI/FI]; Meritullinkatu 15 C 31, FIN-00170 Helsinki (FI).
- (74) Agent: **BERGGREN OY AB**; P.O. Box 16, FIN-00101 Helsinki (FI).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND ARRANGEMENT FOR MAINTAINING SYNCHRONIZATION IN ASSOCIATION WITH RESET-
TING A COMMUNICATION CONNECTION



(57) Abstract: A method and an arrangement are disclosed for resetting a communication connection between a first communication device and a second communication device in a cellular radio system. Firstly, there is detected (201, 404, 501, 604) the need for resetting the communication connection. There is transmitted (202, 408, 408', 502, 607, 219, 519) from the first communication device to the second communication device a first piece of information (203, 210, 503, 510) indicating the need for resetting the communication connection. A resetting procedure (205, 422, 505, 512, 621) is performed at the second communication device, and there is transmitted (206, 213, 424, 506, 513, 623, 623') from the second communication device to the first communication device a second piece of information (207, 214, 507, 514) indicating the completion of the resetting procedure with respect to the second communication device. There is also inserted (408, 408', 623, 623') into a certain piece of information (203, 210, 507, 514) transmitted between the first communication device and the second communication device an indication of an effective number of certain resetting operations associated with a certain detected need for resetting the communication connection.

WO 01/78437 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.