

SPECIFICATION

This Sheet Has Been Replaced



HEADER COVER

Field of the Invention

5 The present invention relates to a cover for use
in automatically mounting electric connectors to the
surface of a printed-circuit board with the aid of a
vacuum-suction nozzle and more particularly, to a cover for
securing to an electric connector comprising a housing and
pin-like terminals projecting from the upper surface of the
10 housing.

Background of the Invention

As is well known, a soldering reflow vessel is
often used in automatically mounting electric connectors to
printed-circuit boards. Specifically, an electric
15 connector is secured by a vacuum-suction nozzle, and the
electric connector is adjusted in position and brought to
a selected position in a printed-circuit board by the
vacuum-suction nozzle. The electric connector is then
released from the vacuum-suction nozzle by stopping
20 application of negative pressure thereto. Then, gas is
released inside the soldering reflow vessel, or infrared
rays are radiated therein until the solder applied to
selected conductors in the printed-circuit board has been
melted, thereby soldering the solder tails of the electric
25 connector to the selected conductors in the printed-circuit
board.

As for the electric connector, if it has a flat
top surface, such top surface is convenient for securement
by a vacuum-suction nozzle as described above. Many
30 electric connectors, however, have pin-like terminals

REPLACED SHEETS	SG
☒ Description : paged ...1... to paged ...7.....	
☒ Claim(s) : paged ...8... to paged ...12.....	
☒ Drawing(s) : paged ...1/5... to paged ...5/5.....	
☒ Abstract : paged ...1/1... to paged ...-.....	
DATE OF RECEIPT	



projecting from their top surface, thus preventing the direct use of vacuum-suction nozzles.

Summary of the Invention

5 One object of the present invention is to provide a cover for use in automatically mounting electric connectors to the surface of a printed-circuit board with the aid of a vacuum-suction nozzle regardless of the configuration of the top surface of the electric connectors.

10 To attain this object, a fitting cover according to the present invention comprises a top plate to which the end of a vacuum-suction nozzle can be applied, and opposite hooks integrally connected to the opposite ends of said top plate. These hooks catch the opposite side walls of the
15 connector housing. The attaching of the fitting cover to the electric connector provides a smooth, flat surface to the electric connector convenient to the suctioning-and-holding of the electric connector by a vacuum-suction nozzle, regardless of irregular contours on the top surface
20 of the electric connector. Thus, existing vacuum-suction nozzles can be used to hold different electric connectors without modification.

According to one aspect of the present invention, a fitting cover may have hooks with an engagement
25 projection integrally connected thereto to fit in the engagement recess of each of the opposite side walls of the connector housing. This arrangement facilitates the reliable holding and release of electric connectors from their associated covers.

30 According to another aspect of the present invention, the rear side of the top plate of the fitting cover is designed to be brought in contact with the tips of

the pin-like terminal of the electric connector when the engagement projection of each hook of the cover fits in the engagement recess of each of the opposite side walls of the connector housing. The pin-like terminals of equal height are pushed against the lower side of the top plate of the fitting cover, thereby permitting the electric connector to be held in horizontal position, perpendicular to the longitudinal axis of the vacuum suction nozzle. This facilitates controlling the position of the electric connector handled by the vacuum suction nozzle. The pressure caused by the vacuum suction nozzle is distributed equally to all pin-like terminals, and therefore, there is no fear of deformation of selected pin-like terminals, which may be caused in case of pin-like terminals of unequal heights.

According to still another aspect of the present invention, the width l of the top plate of the cover is selected to be smaller than the tip-to-tip lateral distance L of opposite solder tails of the electric connector. This arrangement permits the complete exposure of all solder tails of the electric connector to infrared rays for soldering without being concealed behind the fitted cover.

Other objects and advantages of the present invention will be apparent from the following description of a fitting cover according to a preferred embodiment of the present invention, which is shown in accompanying drawings:



Brief Description of the Drawings

Fig. 1 is a perspective view of an electric connector and fitting cover according to the present invention prior to attaching of the fitting cover to the electric connector;

Fig. 2 is a front view of the integral combination of the electric connector and the fitting cover;

Fig. 3 is a side view, partly in section, of the integral combination of the electric connector and the fitting cover;

Fig. 4 is an enlarged view, showing how the fitting cover is engaged with the electric connector;

Fig. 5 is a perspective view of the integral combination of the electric connector and the fitting cover;

Fig. 6 shows the manner in which a vacuum-suction nozzle is initially suctioning and holding an electric connector while in packaging utilized for shipping of the connector;

Fig. 7 shows the manner in which the electric connector having an associated fitting cover attached thereto is aligned in lateral position by a pair of opposite positioning arms; and

Fig. 8 shows the manner in which the electric connector and fitting cover combination is aligned in longitudinal position by another pair of opposite positioning arms.



Detailed Description of the Preferred Embodiment

As seen from drawings and in particular Fig. 1, an electric connector 4 comprises a housing 1 and pin-like terminals 3 project from the upper surface 2 of the housing 1. The electric connector 4 is to be mounted to a printed-circuit board (not shown) with the aid of a vacuum-suction nozzle 5. A cover 6 is used in automatically mounting such electric connector 4 to the printed-circuit board. The cover comprises a top plate 7, to which the end 16 of a vacuum-suction nozzle 5 can be applied, and opposite arms 9 integrally connected to the opposite ends of the top plate 7 which latch the opposite side walls 8 of the connector housing 1. Each arm 9 has an engagement projection or hook 11 to fit in the engagement recess 10 of each side wall 8 of the connector housing 1 in order to latch the cover 6 to connector 4.

As best seen from Fig. 2, the underside 13 of the top plate 7 of the fitting cover 6 is designed to be brought into contact with the tips 14 of the pin-like terminals 3 of the electric connector 4 when the cover 6 is positioned on connector 4 and engagement projection 11 fits in the engagement recess 10 of each of the opposite side walls 8 of the connector housing 1.

As best seen from Fig. 3, the width or lateral dimension 1 of the ceiling plate 7 of the cover 6 is selected to be smaller than the tip-to-tip lateral distance L of opposite solder tails 12 of the electric connector 4.

In use, the cover 6 is fitted on the electric connector 4 with the underside of the cover 6 pushed against the pin-like projections 14 of the electric connector 4 and with the opposite hooks 9 of the cover 6 caught by the recesses 10 of the opposite sides of the



electric connector 4. A printed-circuit board on which the electric connector is to be placed will be parallel to the top surface of the cover 6, which is fitted on the electric connector 4 as just described. As described earlier, the width or lateral dimension 1 of the top plate of the cover is smaller than the tip-to-tip lateral distance L of opposite solder tails 12 of the electric connector 4.

An integral combination of electric connector and cover is attracted to the vacuum suction nozzle 5 by applying negative pressure to the cover 6. Specifically, the end 16 of the vacuum nozzle 5 is put in contact with the top plate 7 of the cover 6 and negative pressure is applied to the ceiling plate 7 of the cover 6, thereby causing the connector and cover combination to be held by the vacuum suction nozzle 5. Then, as seen from Figs. 7 and 8, the connector-and-cover combination is adjusted in position to reduce lateral and longitudinal deviations, if any, relative to the center of the connector 4 with the aid of two pairs of positioning arms 15.

The connector and cover combination is brought to a selected position on the printed-circuit board where the electric connector 4 is placed. Then, application of negative pressure to the top 7 of the cover 6 is stopped, thereby releasing the connector.

The printed-circuit board having the electric connector 4 placed thereon is brought to a reflow vessel in which, for instance, infrared rays are radiated to melt the solder applied to selected conductors of the printed-circuit board. Gas may be used in place of infrared rays for soldering in the reflow vessel. Thus, the solder tails 12 of the electric connector 4 are soldered to the selected conductors of the printed-circuit board. After attaching



the electric connector 4 to the printed circuit board, the cover 6 is removed from the electric connector 4.

5 As may be understood from the above, a fitting cover may be easily attached to an electric connector having pin-like terminals projecting from its upper surface with its opposite hooks caught in the recesses of the opposite sides of the electric connector, thus covering the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector
10 will provide a smooth, flat surface to the connector and cover combination, thereby facilitating the use of a vacuum-suction nozzle to hold the electrical connector regardless of an irregular contour on the top surface of the electrical connector.

15 It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and
20 the invention is not to be limited to the details given herein.

CLAIMS

1. In an electrical connector assembly (4) for mounting to a mounting surface of an electrical apparatus through the engagement of a vacuum-suction nozzle (5), said
5 assembly including a header having an insulative housing (1) with a first surface adapted to be positioned adjacent said mounting surface, a second surface (2) opposite said first surface and a pair of opposed sidewalls (8) generally perpendicular to said first surface, said housing further
10 including a plurality of conductive terminals (3) mounted therein, each terminal having a tail portion (12) for interconnection to circuitry of the electrical apparatus and a free end (14) extending upward beyond said second surface of the housing, characterized in that:

15 a cover (6) is positioned on said header to overlie a central region of said housing, said cover having a generally planar, smooth top surface (7) for engagement by the vacuum-suction nozzle and a pair of cantilevered arms (9) depending downward for engaging
20 said sidewalls; and

complementary releasable retention means (10,11) on said sidewalls of the housing and said cantilevered arms for releasably securing said cover to said header.

25 2. The electrical connector assembly of claim 1 each said cantilevered arm includes a hook adjacent an end thereof with an engagement projection (11) extending therefrom that fits into an engagement recess (10) in one of said sidewalls to releasably secure said cover to said
30 header.



3. The electrical connector assembly of claim 1 wherein said cover has a lower surface (13) facing said second surface (12) of the housing, and said housing, said terminals, and said cover are dimensioned so that said lower surface of said cover engages the free ends of said terminals when said cover is secured to said header.

4. The electrical connector assembly of claim 2 wherein said cover has a lower surface (13) facing said second surface (12) of the housing, and said housing, said terminals, and said cover are dimensioned so that said lower surface of said cover engages the free ends of said terminals when said cover is secured to said header and said engagement projections extend into their respective engagement recesses.

5. The electrical connector assembly of claim 1 wherein the tail portions of said terminals are configured for mounting to the mounting surface, an end of each said tail portion extends beyond the perimeter of the housing, the header has a width (L) in a first direction equal to the distance between the ends of aligned terminals positioned on opposite sides of said housing, and the width of the header in said first direction is greater than the width (l) of said cover in said first direction.

6. The electrical connector assembly of claim 3 wherein the tail portions of said terminals are configured for mounting to the mounting surface, an end of each said tail portion extends beyond the perimeter of the housing, the header has a width (L) in a first direction equal to the distance between the ends of aligned terminals positioned on opposite sides of said housing, and the width



of the header in said first direction is greater than the width (1) of said cover in said first direction.

5 7. A method of positioning an electrical connector assembly (4) on a mounting surface of an electrical apparatus through the engagement of a vacuum-suction nozzle (5) including the steps of providing an electrical connector assembly including a header having an insulative housing (1) with a first surface adapted to be positioned adjacent said mounting surface, a second surface
10 (2) opposite said first surface and a pair of opposed sidewalls (8) generally perpendicular to said first surface, said housing further including a plurality of conductive terminals (3) mounted therein, each terminal having a tail portion (12) for interconnection to circuitry
15 of the electrical apparatus and a free end (14) extending upward beyond said second surface of the housing;

characterized in that:

 positioning a cover (6) on said header to overlie a central region of said housing, said cover having a
20 generally planar, smooth top surface (7) for engagement by the vacuum-suction nozzle and a pair of cantilevered arms (9) depending downward for engaging said sidewalls and complementary releasable retention means (10,11) on said sidewalls of the housing and
25 said cantilevered arms for releasably securing said cover to said header;

 engaging said smooth top surface of said cover with the vacuum-suction nozzle;

 positioning said electrical connector assembly on
30 said mounting surface;

 soldering said tail portions of said terminals to said electrical apparatus; and



removing said cover from said assembly to expose said free ends of said terminals.

7. A method of positioning an electrical connector assembly (4) on a mounting surface of an electrical apparatus through the engagement of a vacuum-suction nozzle (5) including the steps of providing an electrical connector assembly including a header having an insulative housing (1) with a first surface adapted to be positioned adjacent said mounting surface, a second surface (2) opposite said first surface and a pair of opposed sidewalls (8) generally perpendicular to said first surface, said housing further including a plurality of conductive terminals (3) mounted therein, each terminal having a tail portion (12) for interconnection to circuitry of the electrical apparatus and a free end (14) extending upward beyond said second surface of the housing;

characterized in that

providing said header having a cover (6) thereon to overlie a central region of said housing (1), said cover (6) having a generally planar, smooth top surface (7) for engagement by the vacuum-suction nozzle (5);

engaging said smooth top surface (7) of said cover (6) with the vacuum-suction nozzle (5);

positioning said electrical connector assembly (4) on said mounting surface;

soldering said tail portions (12) of said terminals (3) to said electrical apparatus; and

removing said cover (6) from said assembly (4) to expose said free ends (14) of said terminals (3).

8. The method of claim 7 further including the step of aligning said connector assembly (4) on said vacuum-suction nozzle (5) by engaging said



connector assembly (4) with alignment means (9, 15) prior to said positioning step.

9. The method of claim 8 wherein said aligning step includes engaging said connector assembly (4) on first opposite sides (8) of the assembly (4) and then engaging said connector assembly on second opposite sides (at 12) of the assembly.

**ABSTRACT****HEADER COVER**

Disclosed is a cover (6) for use in automatically mounting electric connectors (4) to a printed-circuit board with the aid of a vacuum-suction nozzle (5). The cover comprises a top plate (7) to which the vacuum-suction nozzle can be applied, and opposite hooks (11) integrally connected to the opposite ends of the top plate which catch the opposite side walls (8) of the connector housing. The fitting cover may be easily attached to an electric connector having pin-like terminals (3) projecting from its upper surface to cover the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector will provide a smooth, flat surface to the connector-and-cover combination, thereby facilitating the use of the vacuum suction nozzle to hold electrical connectors regardless of the contour of their upper surface.



FIG. 1





FIG. 2



This Sheet Has Been Replaced



FIG. 3





FIG. 4



This Sheet Has Been Replaced



FIG. 5




FIG. 6

This Sheet Has Been Replaced





FIG. 7



This Sheet Has Been Replaced





FIG. 8



3-1001000

-1-

REPLACED SHEETS		SG
☒	Description	: paged ...1... to paged ...1.....
☒	Claim(s)	: paged ...1... to paged ...12.....
☒	Drawing(s)	: paged ...1/2... to paged ...3/4.....
☒	Abstract	: paged ...13... to paged ...-.....
DATE OF RECEIPT		

SPECIFICATIONHEADER COVER

REPLACEMENT SHEETS		SG
☒	Description	: paged ...1... to paged ...12.....
☒	Claim(s)	: paged ...1... to paged ...12.....
☒	Drawing(s)	: paged ...1/2... to paged ...3/4.....
☒	Abstract	: paged ...13... to paged ...-.....
DATE OF RECEIPT ...11/11.....		

Field of the Invention

The present invention relates to a cover for use in automatically mounting electric connectors to the surface of a printed-circuit board with the aid of a vacuum-suction nozzle and more particularly, to a cover for securing to an electric connector comprising a housing and pin-like terminals projecting from the upper surface of the housing.

Background of the Invention

As is well known, a soldering reflow vessel is often used in automatically mounting electric connectors to printed-circuit boards. Specifically, an electric connector is secured by a vacuum-suction nozzle, and the electric connector is adjusted in position and brought to a selected position in a printed-circuit board by the vacuum-suction nozzle. The electric connector is then released from the vacuum-suction nozzle by stopping application of negative pressure thereto. Then, gas is released inside the soldering reflow vessel, or infrared rays are radiated therein until the solder applied to selected conductors in the printed-circuit board has been melted, thereby soldering the solder tails of the electric connector to the selected conductors in the printed-circuit board.

As for the electric connector, if it has a flat top surface, such top surface is convenient for securement by a vacuum-suction nozzle as described above. Many electric connectors, however, have pin-like terminals

This Sheet Has Been Replaced



projecting from their top surface, thus preventing the direct use of vacuum-suction nozzles.

Summary of the Invention


One object of the present invention is to provide a cover for use in automatically mounting electric connectors to the surface of a printed-circuit board with the aid of a vacuum-suction nozzle regardless of the configuration of the top surface of the electric connectors.

To attain this object, a fitting cover according to the present invention comprises a top plate to which the end of a vacuum-suction nozzle can be applied, and opposite hooks integrally connected to the opposite ends of said top plate. These hooks catch the opposite side walls of the connector housing. The attaching of the fitting cover to the electric connector provides a smooth, flat surface to the electric connector convenient to the suctioning-and-holding of the electric connector by a vacuum-suction nozzle, regardless of irregular contours on the top surface of the electric connector. Thus, existing vacuum-suction nozzles can be used to hold different electric connectors without modification.

According to one aspect of the present invention, a fitting cover may have hooks with an engagement projection integrally connected thereto to fit in the engagement recess of each of the opposite side walls of the connector housing. This arrangement facilitates the reliable holding and release of electric connectors from their associated covers.

According to another aspect of the present invention, the rear side of the top plate of the fitting cover is designed to be brought in contact with the tips of

This Sheet Has Been Replaced



the pin-like terminal of the electric connector when the engagement projection of each hook of the cover fits in the engagement recess of each of the opposite side walls of the connector housing. The pin-like terminals of equal height are pushed against the lower side of the top plate of the fitting cover, thereby permitting the electric connector to be held in horizontal position, perpendicular to the longitudinal axis of the vacuum suction nozzle. This facilitates controlling the position of the electric connector handled by the vacuum suction nozzle. The pressure caused by the vacuum suction nozzle is distributed equally to all pin-like terminals, and therefore, there is no fear of deformation of selected pin-like terminals, which may be caused in case of pin-like terminals of unequal heights.

According to still another aspect of the present invention, the width l of the top plate of the cover is selected to be smaller than the tip-to-tip lateral distance L of opposite solder tails of the electric connector. This arrangement permits the complete exposure of all solder tails of the electric connector to infrared rays for soldering without being concealed behind the fitted cover.

Other objects and advantages of the present invention will be apparent from the following description of a fitting cover according to a preferred embodiment of the present invention, which is shown in accompanying drawings:

This Sheet Has Been Replaced



REPLACEMENT SHEET

16 AUG 1996

Brief Description of the Drawings

Fig. 1 is a perspective view of an electric connector and fitting cover according to the present invention prior to attaching of the fitting cover to the electric connector;

Fig. 2 is a front view of the integral combination of the electric connector and the fitting cover;

Fig. 3 is a side view, partly in section, of the integral combination of the electric connector and the fitting cover;

Fig. 4 is an enlarged view, showing how the fitting cover is engaged with the electric connector;


Fig. 5 is a perspective view of the integral combination of the electric connector and the fitting cover;

Fig. 6 shows the manner in which a vacuum-suction nozzle is initially suctioning and holding an electric connector while in packaging utilized for shipping of the connector;

Fig. 7 shows the manner in which the electric connector having an associated fitting cover attached thereto is aligned in lateral position by a pair of opposite positioning arms; and

Fig. 8 shows the manner in which the electric connector and fitting cover combination is aligned in longitudinal position by another pair of opposite positioning arms.

This Sheet Has Been Replaced



Detailed Description of the Preferred Embodiment


As seen from drawings and in particular Fig. 1, an electric connector 4 comprises a housing 1 and pin-like terminals 3 project from the upper surface 2 of the housing 1. The electric connector 4 is to be mounted to a printed-circuit board (not shown) with the aid of a vacuum-suction nozzle 5. A cover 6 is used in automatically mounting such electric connector 4 to the printed-circuit board. The cover comprises a top plate 7, to which the end 16 of a vacuum-suction nozzle 5 can be applied, and opposite arms 9 integrally connected to the opposite ends of the top plate 7 which latch the opposite side walls 8 of the connector housing 1. Each arm 9 has an engagement projection or hook 11 to fit in the engagement recess 10 of each side wall 8 of the connector housing 1 in order to latch the cover 6 to connector 4.

As best seen from Fig. 2, the underside 13 of the top plate 7 of the fitting cover 6 is designed to be brought into contact with the tips 14 of the pin-like terminals 3 of the electric connector 4 when the cover 6 is positioned on connector 4 and engagement projection 11 fits in the engagement recess 10 of each of the opposite side walls 8 of the connector housing 1.

As best seen from Fig. 3, the width or lateral dimension 1 of the ceiling plate 7 of the cover 6 is selected to be smaller than the tip-to-tip lateral distance L of opposite solder tails 12 of the electric connector 4.

In use, the cover 6 is fitted on the electric connector 4 with the underside of the cover 6 pushed against the pin-like projections 14 of the electric connector 4 and with the opposite hooks 9 of the cover 6 caught by the recesses 10 of the opposite sides of the

This Sheet Has Been Replaced




electric connector 4. A printed-circuit board on which the electric connector is to be placed will be parallel to the top surface of the cover 6, which is fitted on the electric connector 4 as just described. As described earlier, the width or lateral dimension 1 of the top plate of the cover is smaller than the tip-to-tip lateral distance L of opposite solder tails 12 of the electric connector 4.

An integral combination of electric connector and cover is attracted to the vacuum suction nozzle 5 by applying negative pressure to the cover 6. Specifically, the end 16 of the vacuum nozzle 5 is put in contact with the top plate 7 of the cover 6 and negative pressure is applied to the ceiling plate 7 of the cover 6, thereby causing the connector and cover combination to be held by the vacuum suction nozzle 5. Then, as seen from Figs. 7 and 8, the connector-and-cover combination is adjusted in position to reduce lateral and longitudinal deviations, if any, relative to the center of the connector 4 with the aid of two pairs of positioning arms 15.

The connector and cover combination is brought to a selected position on the printed-circuit board where the electric connector 4 is placed. Then, application of negative pressure to the top 7 of the cover 6 is stopped, thereby releasing the connector.

The printed-circuit board having the electric connector 4 placed thereon is brought to a reflow vessel in which, for instance, infrared rays are radiated to melt the solder applied to selected conductors of the printed-circuit board. Gas may be used in place of infrared rays for soldering in the reflow vessel. Thus, the solder tails 12 of the electric connector 4 are soldered to the selected conductors of the printed-circuit board. After attaching

This Sheet Has Been Replaced




the electric connector 4 to the printed circuit board, the cover 6 is removed from the electric connector 4.

As may be understood from the above, a fitting cover may be easily attached to an electric connector having pin-like terminals projecting from its upper surface with its opposite hooks caught in the recesses of the opposite sides of the electric connector, thus covering the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector will provide a smooth, flat surface to the connector and cover combination, thereby facilitating the use of a vacuum-suction nozzle to hold the electrical connector regardless of an irregular contour on the top surface of the electrical connector.

It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.

This Sheet Has Been Replaced



CLAIMS




1. In an electrical connector assembly (4) for mounting to a mounting surface of an electrical apparatus through the engagement of a vacuum-suction nozzle (5), said assembly including a header having an insulative housing (1) with a first surface adapted to be positioned adjacent said mounting surface, a second surface (2) opposite said first surface and a pair of opposed sidewalls (8) generally perpendicular to said first surface, said housing further including a plurality of conductive terminals (3) mounted therein, each terminal having a tail portion (12) for interconnection to circuitry of the electrical apparatus and a free end (14) extending upward beyond said second surface of the housing, characterized in that:

a cover (6) is positioned on said header to overlie a central region of said housing, said cover having a generally planar, smooth top surface (7) for engagement by the vacuum-suction nozzle and a pair of cantilevered arms (9) depending downward for engaging said sidewalls; and

complementary releasable retention means (10,11) on said sidewalls of the housing and said cantilevered arms for releasably securing said cover to said header.

2. The electrical connector assembly of claim 1 each said cantilevered arm includes a hook adjacent an end thereof with an engagement projection (11) extending therefrom that fits into an engagement recess (10) in one of said sidewalls to releasably secure said cover to said header.

This Sheet Has Been Replaced






3. The electrical connector assembly of claim 1 wherein said cover has a lower surface (13) facing said second surface (12) of the housing, and said housing, said terminals, and said cover are dimensioned so that said lower surface of said cover engages the free ends of said terminals when said cover is secured to said header.

4. The electrical connector assembly of claim 2 wherein said cover has a lower surface (13) facing said second surface (12) of the housing, and said housing, said terminals, and said cover are dimensioned so that said lower surface of said cover engages the free ends of said terminals when said cover is secured to said header and said engagement projections extend into their respective engagement recesses.

5. The electrical connector assembly of claim 1 wherein the tail portions of said terminals are configured for mounting to the mounting surface, an end of each said tail portion extends beyond the perimeter of the housing, the header has a width (L) in a first direction equal to the distance between the ends of aligned terminals positioned on opposite sides of said housing, and the width of the header in said first direction is greater than the width (1) of said cover in said first direction.

6. The electrical connector assembly of claim 3 wherein the tail portions of said terminals are configured for mounting to the mounting surface, an end of each said tail portion extends beyond the perimeter of the housing, the header has a width (L) in a first direction equal to the distance between the ends of aligned terminals positioned on opposite sides of said housing, and the width

This Sheet Has Been Replaced





of the header in said first direction is greater than the width (1) of said cover in said first direction.

7. A method of positioning an electrical connector assembly (4) on a mounting surface of an electrical apparatus through the engagement of a vacuum-suction nozzle (5) including the steps of providing an electrical connector assembly including a header having an insulative housing (1) with a first surface adapted to be positioned adjacent said mounting surface, a second surface (2) opposite said first surface and a pair of opposed sidewalls (8) generally perpendicular to said first surface, said housing further including a plurality of conductive terminals (3) mounted therein, each terminal having a tail portion (12) for interconnection to circuitry of the electrical apparatus and a free end (14) extending upward beyond said second surface of the housing;

characterized in that:


positioning a cover (6) on said header to overlie a central region of said housing, said cover having a generally planar, smooth top surface (7) for engagement by the vacuum-suction nozzle and a pair of cantilevered arms (9) depending downward for engaging said sidewalls and complementary releasable retention means (10,11) on said sidewalls of the housing and said cantilevered arms for releasably securing said cover to said header;

engaging said smooth top surface of said cover with the vacuum-suction nozzle;

positioning said electrical connector assembly on said mounting surface;

soldering said tail portions of said terminals to said electrical apparatus; and

This Sheet Has Been Replaced





removing said cover from said assembly to expose said free ends of said terminals.

7. A method of positioning an electrical connector assembly (4) on a mounting surface of an electrical apparatus through the engagement of a vacuum-suction nozzle (5) including the steps of providing an electrical connector assembly including a header having an insulative housing (1) with a first surface adapted to be positioned adjacent said mounting surface, a second surface (2) opposite said first surface and a pair of opposed sidewalls (8) generally perpendicular to said first surface, said housing further including a plurality of conductive terminals (3) mounted therein, each terminal having a tail portion (12) for interconnection to circuitry of the electrical apparatus and a free end (14) extending upward beyond said second surface of the housing;

characterized in that

providing said header having a cover (6) thereon to overlies a central region of said housing (1), said cover (6) having a generally planar, smooth top surface (7) for engagement by the vacuum-suction nozzle (5);

engaging said smooth top surface (7) of said cover (6) with the vacuum-suction nozzle (5);

positioning said electrical connector assembly (4) on said mounting surface;

soldering said tail portions (12) of said terminals (3) to said electrical apparatus; and

removing said cover (6) from said assembly (4) to expose said free ends (14) of said terminals (3).

8. The method of claim 7 further including the step of aligning said connector assembly (4) on said vacuum-suction nozzle (5) by engaging said

This Sheet Has Been Replaced



REPLACEMENT SHEET


16 AUG 1996



connector assembly (4) with alignment means (9, 15) prior to said positioning step.

9. The method of claim 8 wherein said aligning step includes engaging said connector assembly (4) on first opposite sides (8) of the assembly (4) and then engaging said connector assembly on second opposite sides (at 12) of the assembly.

This Sheet Has Been Replaced



ABSTRACT**HEADER COVER**

Disclosed is a cover (6) for use in automatically mounting electric connectors (4) to a printed-circuit board with the aid of a vacuum-suction nozzle (5). The cover comprises a top plate (7) to which the vacuum-suction nozzle can be applied, and opposite hooks (11) integrally connected to the opposite ends of the top plate which catch the opposite side walls (8) of the connector housing. The fitting cover may be easily attached to an electric connector having pin-like terminals (3) projecting from its upper surface to cover the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector will provide a smooth, flat surface to the connector-and-cover combination, thereby facilitating the use of the vacuum suction nozzle to hold electrical connectors regardless of the contour of their upper surface.

FIGURE 1

This Sheet Has Been Replaced




FIG. 1






FIG. 2



This Sheet Has Been Replaced



FIG. 3







FIG. 4



This Sheet Has Been Replaced



FIG. 5



This Sheet Has Been Replaced




FIG. 6





FIG. 7




This Sheet Has Been Replaced



REPLACEMENT SHEET

16 AUG 1996



This Sheet Has Been Replaced



REPLACEMENT SHEET

16 AUG 1996

REPLACED SHEETS		SG
☒	Description	: paged to paged
☒	Claim(s)	: paged to paged
☐	Drawing(s)	: paged to paged
☒	Abstract	: paged to paged
DATE OF RECEIPT		

1
HEADER COVER

REPLACEMENT SHEETS		SG
☒	Description	: paged to paged
☒	Claim(s)	: paged to paged
☒	Drawing(s)	: paged to paged
☒	Abstract	: paged to paged
DATE OF RECEIPT 20/6/97		

Description

The present invention relates to an electrical connector assembly according to the preamble of claim 1 and to a method of positioning an electrical connector assembly on a mounting surface of an electrical apparatus.

As is well known, a soldering reflow vessel is often used in automatically mounting electric connectors to printed-circuit boards. Specifically, an electric connector is secured by a vacuum-suction nozzle, and the electric connector is adjusted in position and brought to a selected position in a printed-circuit board by the vacuum-suction nozzle. The electric connector is then released from the vacuum-suction nozzle by stopping application of negative pressure thereto. Then, gas is released inside the soldering reflow vessel, or infrared rays are radiated therein until the solder applied to selected conductors in the printed-circuit board has been melted, thereby soldering the solder tails of the electric connector to the selected conductors in the printed-circuit board.

If the electric connector has a flat top surface, such top surface is convenient for securement by a vacuum-suction nozzle as described above and shown in US-A-5,003,692.

Many electric connectors, however, have pin-like terminals projecting from their top surface, thus preventing the direct use of vacuum-suction nozzles.

The problem to be solved by the present invention is to position an electrical connector on a mounting surface of an electrical apparatus regardless of the configuration of the top surface of the electrical connector.

The invention is defined in claims 1 and 5.

REPLACEMENT SHEET
20 JUN 1997

A fitting cover according to the present invention comprises a top plate to which the end of a vacuum-suction nozzle can be applied, and opposite hooks integrally connected to the opposite ends of said top plate. These hooks catch the opposite side walls of the connector housing. The attaching of the fitting cover to the electric connector provides a smooth, flat surface to the electric connector convenient to the suctioning-and-holding of the electric connector by a vacuum-suction nozzle, regardless of irregular contours on the top surface of the electric connector. Thus, existing vacuum-suction nozzles can be used to hold different electric connectors without modification.

According to one aspect of the present invention, the fitting cover may have hooks with an engagement projection integrally connected thereto to fit in the engagement recess of each of the opposite side walls of the connector housing. This arrangement facilitates the reliable holding and release of electric connectors from their associated covers.

According to another aspect of the present invention, the rear side of the top plate of the fitting cover is designed to be brought in contact with the tips of the pin-like terminal of the electric connector when the engagement projection of each hook of the cover fits in the engagement recess of each of the opposite side walls of the connector housing. The pin-like terminals of equal height are pushed against the lower side of the top plate of the fitting cover, thereby permitting the electric connector to be held in horizontal position, perpendicular to the longitudinal axis of the vacuum suction nozzle. This facilitates controlling the position of the electric connector handled by the vacuum suction nozzle. The pressure caused by the vacuum suction nozzle is distributed equally to all pin-like terminals, and therefore, there is no fear of deformation of selected pin-like terminals, which may be caused in case of pin-like terminals of unequal heights.

REPLACEMENT SHEET

20 JUN 1997

According to still another aspect of the present invention, the width l of the top plate of the dover is selected to be smaller than the tip-to-tip lateral distance L of opposite solder tails of the electric connector. This arrangement permits the complete exposure of all solder tails of the electric connector to infrared rays for soldering without being concealed behind the fitted cover.

Other objects and advantages of the present invention will be apparent from the following description of a fitting cover according to a preferred embodiment of the present invention, which is shown in accompanying drawings:

Brief Description of the Drawings

Fig. 1 is a perspective view of an electric connector and fitting cover according to the present invention prior to attaching of the fitting cover to the electric connector;

Fig. 2 is a front view of the integral combination of the electric connector and the fitting cover;

Fig. 3 is a side view, partly in section, of the integral combination of the electric connector and the fitting cover;

Fig. 4 is an enlarged view, showing how the fitting cover is engaged with the electric connector;

Fig. 5 is a perspective view of the integral combination of the electric connector and the fitting cover;

Fig. 6 shows the manner in which a vacuum-suction nozzle is initially suctioning and holding an electric connector while in packaging utilized for shipping of the connector;

Fig. 7 shows the manner in which the electric connector having an associated fitting cover attached thereto is aligned in lateral position by a pair of opposite positioning arms; and

REPLACEMENT SHEET

20 JUN 1997

Fig. 8 shows the manner in which the electric connector and fitting cover combination is aligned in longitudinal position by another pair of opposite positioning arms.


Detailed Description of the Preferred Embodiment

As seen from drawings and in particular Fig. 1, an electric connector 4 comprises a housing 1 and pin-like terminals 3 project from the upper surface 2 of the housing 1. The electric connector 4 is to be mounted to a printed-circuit board (not shown) with the aid of a vacuum-suction nozzle 5. A cover 6 is used in automatically mounting such electric connector 4 to the printed-circuit board. The cover comprises a top plate 7, to which the end 16 of a vacuum-suction nozzle 5 can be applied, and opposite arms 9 integrally connected to the opposite ends of the top plate 7 which latch the opposite side walls 8 of the connector housing 1. Each arm 9 has an engagement projection or hook 11 to fit in the engagement recess 10 of each side wall 8 of the connector housing 1 in order to latch the cover 6 to connector 4.

As best seen from Fig. 2, the underside 13 of the top plate 7 of the fitting cover 6 is designed to be brought into contact with the tips 14 of the pin-like terminals 3 of the electric connector 4 when the cover 6 is positioned on connector 4 and engagement projection 11 fits in the engagement recess 10 of each of the opposite side walls 8 of the connector housing 1.

As best seen from Fig. 3, the width or lateral dimension I of the ceiling plate 7 of the cover 6 is selected to be smaller than the tip-to-tip lateral distance L of opposite solder tails 12 of the electric connector 4.

In use, the cover 6 is fitted on the electric connector 4 with the underside of the cover 6 pushed against the pin-like projections 14 of the electric connector 4 and



with the opposite hooks 9 of the cover 6 caught by the recesses 10 of the opposite sides of the electric connector 4. A printed-circuit board on which the electric connector is to be placed will be parallel to the top surface of the cover 6, which is fitted on the electric connector 4 as just described. As described earlier, the width or lateral dimension l of the top plate of the cover is smaller than the tip-to-tip lateral distance L of opposite solder tails 12 of the electric connector 4.

An integral combination of electric connector and cover is attracted to the vacuum suction nozzle 5 by applying negative pressure to the cover 6. Specifically, the end 16 of the vacuum nozzle 5 is put in contact with the top plate 7 of the cover 6 and negative pressure is applied to the ceiling plate 7 of the cover 6, thereby causing the connector and cover combination to be held by the vacuum suction nozzle 5. Then, as seen from Figs. 7 and 8, the connector-and-cover combination is adjusted in position to reduce lateral and longitudinal deviations, if any, relative to the center of the connector 4 with the aid of two pairs of positioning arms 15.

The connector and cover combination is brought to a selected position on the printed-circuit board where the electric connector 4 is placed. Then, application of negative pressure to the top 7 of the cover 6 is stopped, thereby releasing the connector.

The printed-circuit board having the electric connector 4 placed thereon is brought to a reflow vessel in which, for instance, infrared rays are radiated to melt the solder applied to selected conductors of the printed-circuit board. Gas may be used in place of infrared rays for soldering in the reflow vessel. Thus, the solder tails 12 of the electric connector 4 are soldered to the selected conductors of the printed-circuit board. After attaching the electric connector 4 to the printed circuit board, the cover 6 is removed from the electric connector 4.

REPLACEMENT SHEET

20 JUN 1997

As may be understood from the above, a fitting cover may be easily attached to an electric connector having pin-like terminals projecting from its upper surface with its opposite hooks caught in the recesses of the opposite sides of the electric connector, thus covering the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector will provide a smooth, flat surface to the connector and cover combination, thereby facilitating the use of a vacuum-suction nozzle to hold the electrical connector regardless of an irregular contour on the top surface of the electrical connector.

Claims

1. An electrical connector assembly adapted for being positioned on a mounting surface of an electrical apparatus by a vacuum-suction nozzle (5),

said connector assembly comprising a connector (4) which includes an insulative housing (1) having
 a first surface which is to be positioned adjacent said mounting surface of said electrical apparatus,
 a second surface (2) opposite of said first surface, and
 side walls including a pair of opposed sidewalls (8) generally perpendicular to said first surface,
 a plurality of terminals (3) mounted in said housing (1), each terminal having
 a tail portion (12) for interconnection to said electrical apparatus, and
 a free end (14) extending from said second surface (2) in direction to said vacuum-suction nozzle (5),

REPLACEMENT SHEET

20 JUN 1997


This Sheet Has Been Replaced



characterized in that said connector assembly further comprises
 a cover (6) which includes
 a generally planar, smooth top surface (7) adapted to be engaged by said vacuum-suction nozzle (5), and a pair of cantilevered arms (9) adapted to engage said pair of sidewalls (8), and
 in that said sidewalls (8) and said arms (9) are provided with
 releasable retention means (10, 11) which are complementary to one another for releasably securing said cover (6) to said housing (1).

The connector assembly according to claim 1 wherein said retention means (10, 11) include a hook or projection (11) on each of said arms (9) and each a recess (10) in said sidewalls (8).

3. The connector assembly according to claims 1 or 2 wherein said arms (9) are of such length that the lower surface (13) of said cover (6) engages the free ends (14) of said terminals (3) when the cover (6) is secured to said housing (1).
4. The connector assembly according to one of claims 1 to 3 wherein said tail portions (12) extend beyond the perimeter of the housing (1) to a width (L) which is greater than the width (1) of the cover (6) in the same direction.
5. A positioning method for an electric connector assembly of claim 1 on a mounting surface of an electric apparatus, comprising the steps of positioning the cover (6) onto said connector (4) so as to overlie a central region thereof and form said connector assembly,




This Sheet Has Been Replaced



engaging the retention means (11) of the cover (6) into the retention means (10) of the connector housing (1),
engaging the top surface (7) of the cover (6) with a vacuum-suction nozzle (5),
positioning said connector assembly on said mounting surface,
soldering said tail portion (12) of said terminals (3) to said electrical apparatus and
removing said cover (6) from said connector (4) to expose said free ends (14) of said terminals (3).

6. The method of claim 5
wherein said connector (4) is engaged and aligned by alignment means (9, 15) prior to said positioning step.
7. The method of claim 6
wherein said aligning step includes engaging said connector (4) on first opposite sides (8) thereof and then engaging said connector (4) on its second opposite sides (at 12).

This Sheet Has Been Replaced





ABSTRACT**HEADER COVER**

Disclosed is a cover (6) for use in automatically mounting electric connectors (4) to a printed-circuit board with the aid of a vacuum-suction nozzle (5). The cover comprises a top plate (7) to which the vacuum-suction nozzle can be applied, and opposite hooks (11) integrally connected to the opposite ends of the top plate which catch the opposite side walls (8) of the connector housing. The fitting cover may be easily attached to an electric connector having pin-like terminals (3) projecting from its upper surface to cover the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector will provide a smooth, flat surface to the connector-and-cover combination, thereby facilitating the use of the vacuum suction nozzle to hold electrical connectors regardless of the contour of their upper surface.

FIGURE 1

This Sheet Has Been Replaced



1

FIG. 1




FIG. 2





FIG. 3




FIG. 4






FIG. 5



REPLACEMENT SHEET

20 JUN 1997

FIG. 6




FIG. 7






FIG. 8



As may be understood from the above, a fitting cover may be easily attached to an electric connector having pin-like terminals projecting from its upper surface with its opposite hooks caught in the recesses of the opposite sides of the electric connector, thus covering the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector will provide a smooth, flat surface to the connector and cover combination, thereby facilitating the use of a vacuum-suction nozzle to hold the electrical connector regardless of an irregular contour on the top surface of the electrical connector.

REPLACEMENT SHEETS		SG
☒	Description : paged .6.. to paged .7..	
☒	Claim(s) : paged .7.. to paged .1..	
☐	Drawing(s) : paged to paged	
☒	Abstract : paged .10.. to paged .11..	
DATE OF RECEIPT		5/1/11

Claims



1. An electrical connector assembly adapted for being positioned on a mounting surface of an electrical apparatus by a vacuum-suction nozzle (5),

said connector assembly comprising a connector (4) which includes an insulative housing (1) having

a first surface which is to be positioned adjacent said mounting surface of said electrical apparatus,

a second surface (2) opposite of said first surface, and

side walls including a pair of opposed sidewalls (8) generally perpendicular to said first surface, a plurality of terminals (3) mounted in said housing (1), each terminal having

a tail portion (12) for interconnection to said electrical apparatus, and

a free end (14) extending from said second surface (2) in direction to said vacuum-suction nozzle (5),


characterized in that said connector assembly further comprises

a cover (6) which includes

a generally planar, smooth top surface (7) adapted to be engaged by said vacuum-suction nozzle (5), and a pair of cantilevered arms (9) adapted to engage said pair of sidewalls (8), and

in that said sidewalls (8) and said arms (9) are provided with

releasable retention means (10, 11) which are complementary to one another for releasably securing said cover (6) to said housing (1).






2. The connector assembly according to claim 1
wherein said retention means (10, 11) include a hook or projection (11) on each of said arms (9) and each a recess (10) in said sidewalls (8).
3. The connector assembly according to claims 1 or 2
wherein said arms (9) are of such length that the lower surface (13) of said cover (6) engages the free ends (14) of said terminals (3) when the cover (6) is secured to said housing (1).
4. The connector assembly according to one of claims 1 to 3
wherein said tail portions (12) extend beyond the perimeter of the housing (1) to a width (L) which is greater than the width (1) of the cover (6) in the same direction.
5. A positioning method for an electric connector assembly of claim 1 on a mounting surface of an electric apparatus, comprising the steps of positioning the cover (6) onto said connector (4) so as to overlie a central region thereof and form said connector assembly,
engaging the retention means (11) of the cover (6) into the retention means (10) of the connector housing (1),
engaging the top surface (7) of the cover (6) with a vacuum-suction nozzle (5),
positioning said connector assembly on said mounting surface,
soldering said tail portion (12) of said terminals (3) to said electrical apparatus and
removing said cover (6) from said connector (4) to expose said free ends (14) of said terminals (3).

REPLACEMENT SHEET

05 AUG 1999



6. The method of claim 5
wherein said connector (4) is engaged and aligned
by alignment means (9, 15) prior to said positioning
step.
7. The method of claim 6
wherein said aligning step includes engaging said
connector (4) on first opposite sides (8) thereof and
then engaging said connector (4) on its second
opposite sides (at 12).



ABSTRACT**HEADER COVER**

Disclosed is a cover (6) for use in automatically mounting electric connectors (4) to a printed-circuit board with the aid of a vacuum-suction nozzle (5). The cover comprises a top plate (7) to which the vacuum-suction nozzle can be applied, and opposite hooks (11) integrally connected to the opposite ends of the top plate which catch the opposite side walls (8) of the connector housing. The fitting cover may be easily attached to an electric connector having pin-like terminals (3) projecting from its upper surface to cover the pin-like terminals of the electric connector. The attaching of the fitting cover to the electric connector will provide a smooth, flat surface to the connector-and-cover combination, thereby facilitating the use of the vacuum suction nozzle to hold electrical connectors regardless of the contour of their upper surface.

FIGURE 1

