



(51) International Patent Classification:

A61M 39/04 (2006.01) A61M 39/10 (2006.01)
A61M 39/16 (2006.01) A61M 25/00 (2006.01)
A61M 39/26 (2006.01)

(21) International Application Number:

PCT/US2015/025799

(22) International Filing Date:

14 April 2015 (14.04.2015)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

14/260,078 23 April 2014 (23.04.2014) US

(71) Applicant: **BECTON, DICKINSON AND COMPANY**
[US/US]; 1 Becton Drive, Mail Code 110, Franklin Lakes,
New Jersey 07417-1880 (US).

(72) Inventors: **LIN, Janice**; 2530 Qume Drive, San Jose, Cali-
fornia 95131 (US). **LIU, Huibin**; 9300 Redwood Road
#25-12, West Jordan, Utah 84088 (US). **BIHLMAIER,**
Bryan Fred; 5240 North Canyon Road, Provo, Utah
84604 (US).

(74) Agents: **HIGHET, David W.** et al.; Becton, Dickinson
And Company, 1 Becton Drive, Mail Code 110, Franklin
Lakes, New Jersey 07417-1880 (US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: PORTED CATHETER OR FEMALE LUER FITTING WITH ANTIMICROBIAL SEPTUM




FIG. 5A

(57) Abstract: Ports, such as the ports of ported catheters or of female luer fittings, can be configured to include an antimicrobial septum for disinfecting devices that are attached to the ports. The antimicrobial septum can be positioned within the lumen of the port. The lumen can include an annular recess for securing the antimicrobial septum in place during use. The antimicrobial septum can include an antimicrobial lubricant which transfers onto a device, such as a male luer, as the device passes through the septum thereby killing any microbes that may be present on the surfaces of the device. The antimicrobial septum can be configured in various shapes including a continuous disk shape, a ring shape, or an elongated ring or tube shape.



Declarations under Rule 4.17:

— *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

Published:

— *with international search report (Art. 21(3))*

(88) Date of publication of the international search report:

17 December 2015