

Device for inserting a transponder

The invention relates to a device for inserting a transponder into a slot of an object, according to the preamble of claim 1, to the use of such a device, according to claims 11 and 12, and to a
5 panel for formwork, equipped with such a device, according to claim 13.

The problem arises for various objects, in particular objects which are rented and which cannot be clearly identified because they do not have serial numbers, of easily identifying them - for example, to find out whether an identical rented object has been returned, or has
10 been replaced prior to the return. Being able to detect such objects digitally, store their information in databases, and catalog them based on location are also desirable features.

Such objects can be equipped with optical codes to accomplish this. However, this is impossible in many sectors, or is associated with major disadvantages - for example, in the
15 construction sector for the process of identifying scaffolding or formwork. These components are subject to considerable mechanical stress and are cleaned with high-pressure cleaners. Optical identifiers are therefore not strong enough for these components.

As such, the use of electronic identifiers in the form of RFID transponders is known from the
20 prior art. For example, WO 2008/098755 A1 describes a formwork element having a formwork skin and having an outer frame made of metal, on which a recess is provided in which a transponder is arranged and retained.

DE 20 2010 005 092 U1 discloses an object having a recess and a transponder in this recess,
25 the recess being formed by a container which is made of metal or plastics material.

DE 10 2010 038 474 A1 discloses a formwork element having a formwork frame and formwork skin, wherein an RFID transponder is attached to the back of the formwork skin.

DE 103 576 95 A1 discloses a slot antenna for a transponder, and US 2006/0232412 A1
30 discloses an RFID chip and a slot antenna.

WO 2014/048954 discloses a transportable device, in particular a formwork, which is equipped with a transponder which is arranged in a recess made of metal, the bottom of the recess being provided with a slot.

- 5 DE 10 2006 029 249 A1 discloses a device for inserting a transponder into a slot of an object, the device having approximately the length and width of the slot and having an insert part which receives the transponder.

- 10 DE 20 2008 001 549 U1 relates to an RFID transponder having a housing, a coupling loop which is electrically connected to an RFID chip arranged in the housing, and an antenna which has a slot and is arranged on the outside of the housing. In this case, the housing with the chip is placed on an object from the outside.

- 15 US 2006/0 232 412 A1 also deals with a reading system and a method for identifying goods with the aid of transponders, with particular reference being made to scaffolding material.

- For the devices mentioned, the insertion of the transponder into the slot is difficult. Especially when the object to be marked has a cavity behind the slot, the transponder, the tag or the chip having the transponder can often fall through the slot into this cavity and disappear. It sometimes takes several attempts to fix a chip securely in the slot - for example, by gluing or soldering. Such a fixation also does not withstand the hard, continuous stress on objects that are used in the construction sector. In many cases, the glued or soldered chip comes off when the object is cleaned.
- 20

- 25 The problem therefore exists of designing a device for inserting a transponder into a slot of an object in such a way that the transponder to be used can be reliably positioned at the correct location of the slot.

- This problem is addressed by the features of claim 1. Advantageous embodiments, and also the use of such a device and a method for inserting such a device into the slot of an object are the subject matter of the dependent claims.
- 30

An embodiment of the invention is described below with reference to the accompanying drawings, wherein:

Figure 1: shows a first embodiment of the device - in particular

- a) a view of the device from the front;
- b) a view of the device in a) from the right;
- 5 c) a view of the device in a) and b) from the side;
- d) a view of the device in a) - c) in perspective;
- e) a device according to a) - d) inserted into a slot of an object;
- f) a section of e) taken along the line A - A with the transponder inserted;
- g) the detail X from f);
- 10 h) a perspective view of the device inserted into a slot of an object;

Figure 2: shows a second embodiment of the device - in particular

- a) a view of the device from the front;
- b) a view of the device in a) from the right;
- 15 c) a view of the device in a) and b) from the side;
- d) a view of the device in a) - c) in perspective;
- e) a device according to a) - d) inserted into a slot of an object;
- f) a section of e) taken along the line A - A with the transponder inserted;
- g) the detail X from f);
- 20 h) a perspective view of the device inserted into a slot of an object;

Figure 3: shows a third embodiment of the device - in particular

- a) a view of the device from the front;
- b) a view of the device in a) from the right;
- 25 c) a view of the device in a) and b) from the side;
- d) a view of the device in a) - c) in perspective;
- e) a device according to a) - d) inserted into a slot of an object;
- f) a section of e) taken along the line A - A with the transponder inserted;
- g) the detail X from f);
- 30 h) a perspective view of the device inserted into a slot of an object;

Figure 4: shows a fourth embodiment of the device - in particular

- a) a view of the device from the front;
- b) a view of the device in a) from the right;

- c) a view of the device in a) and b) from the side;
- d) a view of the device in a) - c) in perspective;
- d') the detail Y from d);
- e) a device according to a) - d) inserted into a slot of an object;
- 5 e') a section from e) taken along lone B - B;
- f) a section of e) taken along the line A - A with the transponder inserted;
- g) the detail X from f);
- h) a perspective view of the device inserted into a slot of an object;

10 **Figure 5:** shows a fifth embodiment of the invention - in particular

- a) a view of the device from the front;
- b) a view of the device in a) from the right;
- c) a view of the device in a) and b) from the side;
- d) a view of the device in a) - c) in perspective;
- 15 e) the detail X from c);
- f) an illustration from a perspective rotated by approximately 90° with respect to d);

Figure 6: shows the embodiment according to Figure 5, wherein Figures a) to f) correspond
20 to the illustrations from Figure 5, but with a transponder inserted;

Figure 7: shows a protective cover for the fifth embodiment of the invention according to
Figures 5 and 6 - in particular

- a) a view of the protective cover from the front;
- 25 b) a view of the protective cover in a) from the right;
- c) a view of the protective cover in a) and b) from the side;
- d) a view of the protective cover in a) - c) in perspective;
- e) the detail X from c);
- f) a further perspective view of the protective cover rotated by approximately
30 90° with respect to the illustration d);

Figure 8: shows the fifth embodiment of the invention according to Figures 5 to 7 with the
protective cover placed on the device - in particular

- a) a view of the device from the front;

- b) a view of the device in a) from the right;
- c) a view of the device in a) and b) from the side;
- d) a view of the device in a) - c) in perspective;
- e) the detail X from c);
- 5 f) an illustration from a perspective rotated by approximately 90° with respect to d);

Figure 1 shows, in Figures a) - d), a first embodiment of a device according to the invention, and in Figures e) - h) the use of this device within a slot 2 of an object 3 with a transponder 1
10 inserted.

In this description, the term transponder is used not only for the actual transponder chip, but also for the component that contains the transponder. This is usually a larger component in which the transponder is potted, screwed, glued or installed in some other way. The
15 component referred to as the transponder thus has a certain mechanical resistance and can also be resistant to external influences such as heat, pressure, liquids, etc.

The device is an insert part 4 made of plastics material, for example made of polyvinyl chloride or another plastics material or a mixture of several plastics materials, which is
20 produced by injection-molding and which is substantially hard, but bendable and flexible. The insert part 4 is elongated in form and has a base 8. At one end 5 of the insert part 4, there is a receptacle 6 for a transponder. The receptacle 6 for the transponder is designed as a resilient web 7 for clamping the transponder 1 when it is inserted. On both sides of the insert part 4 there are hook-shaped stops 9, which are formed by the material being bent by 90° starting
25 from the base 8 of the insert part, and then being bent again by 90° in the opposite direction, roughly producing a Z-shape when viewed from the side (see Figure 1c)). The dimensions of the insert part 4 are chosen such that the length of the base 8 corresponds approximately to the length of the slot 2 within the object 3 in which the insert part 4 is to be inserted. In this way, the hook-shaped stops 9 overlap the ends of the slot 2 on the outside thereof when the insert
30 part 4 is inserted into the slot 2, as shown in sub-figure f).

As sub-figure g) shows, the transponder 1 is arranged near the inner side of the slot 2 - that is to say, facing away from the surface of the object 3, when the insert part 4 is inserted in the

slot 2. This has the advantage of better transmission power, which has been confirmed by experiments.

The insert part 4 inserted into the slot 2 of the object 3 in this manner is firmly seated inside the slot 2, without the risk of slipping through into the inner cavity of the object 3, because it is held at the ends of the slot 2 by the hook-shaped stops 9. The transponder 1 is again firmly seated within the receptacle 6 because it is clamped by the resilient web 7.

After the insertion of the insert part 4 into the slot 2 of the object 3 - i.e., after the insert part 4 has assumed the position shown in the sub-figures e) - h), the slot 2 is potted with a potting compound which is known per se, wherein the potting compound is applied inside the slot 2 and in its edge regions, and the insert part 4 is at least mostly, and optionally completely, covered.

The potting compound can be an adhesive or another one-component or two-component potting compound (binder / hardener system) known from the prior art.

The device according to the invention achieves the advantage that the transponder 1, when inserted into the slot 2 of the object 3, can no longer fall through and get lost in the inner cavity of the object 3, and it is also securely positioned at a fixed location in the region of the slot 2. As already described, tests have shown that the optimal position for the transponder 1 is at the end of the slot 2 and in the region of the inner side of the slot 2. In this way, optimal activity and transmission power of the transponder 1 are achieved.

Alternative embodiments can be seen in Figures 2 - 4. The same components are designated with the same reference numerals. Likewise, the sub-figures a) - h) correspond in all of the Figures 1 - 4.

In the following, only the differences from the embodiment described with reference to Figure 1 will be discussed in the description of the further embodiments.

In the embodiment according to Figure 2, instead of the hook-shaped stops 9 arranged on both sides, the insert part 4 has a claw 10 at only one end, wherein the width of the claw 10 is such that it approximately corresponds to the thickness of the material of the object 3 in the region

of the slot 2. The transponder 1 is clamped on the insert part 4 in a similar receptacle 6 with a resilient web 7.

The attachment of the insert part 4 to the object 3 is shown in the sub-figures e) - h). First, the transponder 1 is inserted into the receptacle 6 and the insert part 4 is then inserted into the slot 2 of the object 3, wherein the claw 10 engages over the end of the slot, thereby producing a secure holder. The other end of the insert part 4 remains free in the region of the underside of the slot 2.

This is followed by potting with a potting compound as described in relation to the embodiment according to Figure 1.

The embodiment according to Figure 3 differs from the embodiments according to Figures 1 and 2 in that, instead of the hook-shaped stops 9 or the claw 10, at least two - in the embodiment shown, four - lateral hooks 11 projecting upwards from the base 8 of the insert part 4 are provided. Two hooks are arranged in the region of one end of the insert part 4 and two are arranged in the region of the other end; however, both are not quite at the end of the insert part 4, and are rather at a distance from the ends of the insert part 4. They project upwards and then laterally from the base 8 of the insert part 4. In the embodiment shown, the two hooks 11 shown on the left are located on the resilient web 7 of the receptacle 6.

In the inserted state, the lateral hooks 11 overlap the slot 2 inside the object 3, as shown in Figure 3 h), and in this way fix the insert part 4 inside the slot 2. This is then followed by potting with a suitable potting compound, the slot 2 being completely sealed.

In the further embodiment shown in Figure 4, instead of the hook-shaped stops 9, claw 10 or lateral hooks 11 shown in the embodiments according to Figures 1 - 3, there is a total of four inclined surfaces 12 projecting from the base 8 in the region of the ends of the insert part 4, but at a distance from the ends rather than entirely at the ends, which, starting from the edges of the base 8, project slightly laterally outwards beyond the base 8 of the insert part 4 - either by an oblique arrangement or by a corrugation or gradation. The insert part 4 is thus somewhat wider in the region of the inclined surfaces 12 than in the region of the base 8. Since the base 8 has exactly the width of the slot 2 of the object 3, the inclined surfaces 12 are wider than the slot 2; this results in a clamping connection between the insert part 4 and the

slot 2 when the insert part 4 is pressed into the slot 2, as shown in Figure 4 h) and Figure 4 e'). The resilient and slightly outwardly directed inclined surfaces 12 produce the clamping effect. In this embodiment, the insert part 4 disappears completely inside the slot 2. In a last step, the slot 2 is also potted with a potting compound.

5

In a further embodiment, which is not shown, the transponder can be arranged as a single piece inside the device - for example, potted, molded, or incorporated in another way therein and encapsulated by the device. The device thus forms a one-piece unit with the transponder.

10 As described above, the slot can be introduced into the object by cutting, lasering, or shaping using standard material-removing or machining processes, such as by sawing, milling, lasering, cutting, etc. The slot can be introduced before or after the surface treatment of the component - that is, before or after painting, galvanizing or powder-coating.

15 In a further, alternative embodiment, the slot can be provided with an undercut in order to facilitate the flowing of the potting compound, and thus better fixing of the device within the slot, since the potting compound flows around the device. The slot preferably has a molded edge configuration which is matched to the edge configuration of the device, in order to achieve a better connection of the device to the slot - for example, a latching or meshing.

20

The embodiment according to Figure 5 differs from the embodiments according to Figures 1 to 4 in that there is no insertion of the insert part into the slot of the object; rather, the insert part 4 is attached from behind to the object (accessible from the rear), wherein the resilient web 7 and optionally further positioning aids 15 on the base 8 of the insert part 4 are inserted
25 into the slot of the object. The attachment of the insert part 4 inside the slot of the object is not done mechanically, but rather by large-area gluing, which is possible in this embodiment because the base 8 of the insert part 4 is made much wider than the slot - i.e. comes to lie behind the slot - such that the entire region of the very wide base 8 rests on the back side of the object and can be glued thereto. Figures 5a, b, d and f show this very clearly. It can be
30 seen that the base 8 of the insert part 4 is substantially wider than the previously described embodiments, and clearly exceeds the width of the resilient web 7 and also of the positioning aids 15 which engage in the slot of the object.

As in the other embodiments, a receptacle 6 for a transponder 1 is formed at one end 5 of the insert part 4 by a resilient web 7, which extends from the base 8 of the insert part 4 in a hook shape, wherein the gap between the web 7 and the base 8 in this case as well is undersized with respect to the thickness of the transponder 1.

5

The inserted transponder 1 can be seen in Figure 6. As particularly shown in Figures 6a, 6c, 6d and 6e, this projects in the direction of the slot of the object beyond the resilient web 7 and almost completely fills the space between the resilient web 7 and the left positioning aid 15. The transponder 1 in this case has an elongated shape and, when it is installed later, is inserted completely into the slot of the object.

10

The protective cover 16 shown in Figure 7 is provided to shield the transponder 1, which is essentially unprotected in the slot of the object, against external influences such as strikes, impacts, weather conditions, etc. All sub-figures in Figure 7 show the protective cover 16. This has a slightly protruding elongated positioning aid 17 which engages in the slot of the object during later assembly, and thus allows the protective cover 16 to be positioned more easily. Otherwise, the dimensions of the protective cover are similar to those of the insert part 4, but somewhat narrower.

15

The installed combination of the insert part 4 and protective cover 16 is shown in Figure 8. Here, the insert part 4 with the transponder 1 is located in a slot (not shown) of an object, wherein the transponder 1, which is located in the receptacle 6 between the base 8 and the resilient web 7 of the insert part 4, is protected by the protective cover 16 attached over it. It can be clearly seen how the positioning aid 17 of the protective cover 16 engages in the slot (not shown here) of the object and thus ensures a simple positioning of the protective cover 16 over the slot and, in particular, over the transponder 1 to be protected.

20

25

Claims

1. A device for inserting a transponder (1) into a slot (2) of an object (3), the device
5 being designed as an insert part (4) which has approximately the length and width of
the slot (2) and which can be connected to the slot (2), and which has a receptacle (6)
for the transponder (1), **characterized in that** the receptacle (6) is arranged on the end
(5) of the insert part (4) facing an end of the slot (2), and has a resilient web (7) for
clamping the transponder (1), when inserted, between a base (8) of the insert part 4
10 and the resilient web (7), wherein the space between the web (7) and the base (8) is
undersized with respect to the thickness of the transponder (1).
2. The device according to claim 1, **characterized in that** it is designed as an injection-
molded part or as a part made of plastics material in 3D printing.
- 15 3. The device according to any one of the preceding claims, **characterized in that** the
base (8) is located in the region of the inner side of the slot (2) when the device is in
the inserted state.
- 20 4. The device according to any one of the preceding claims, **characterized in that** it has
hook-shaped stops (9) on both sides, which overlap the ends of the slot (2) on the
outside thereof when the device is in the inserted state.
5. The device according to any one of the claims 1 - 3, **characterized in that** it has a
25 claw (10) at one end which can be inserted into the end of the slot (2).
6. The device according to any one of the claims 1 - 3, **characterized in that** it has at
least two lateral hooks (11) which project upwards from its base (8) and engage
laterally around the slot (2) when the device is in the inserted state.
- 30 7. The device according to claim 6, **characterized in that** at least one hook (11) is
arranged in the region of the receptacle (6) for the transponder (1).
8. The device according to any one of the claims 1 - 3, **characterized in that** it has at
35 least two lateral inclined surfaces (12) which project upwards from its base (8) and
which, when the device is in the inserted state, push against and clamp against the
inner side surfaces of the slot (2).

9. The device according to any one of the preceding claims, **characterized in that** the receptacle (6) has a screw, rivet, hook-and-loop, adhesive or clamp connection for the transponder (1).
- 5 10. The device according to any one of the preceding claims, **characterized in that** the transponder (1) forms a one-piece component together with the device.
- 10 11. The use of a device according to any one of the preceding claims, **characterized in that** the object (3) is a component of a scaffold or formwork.
12. The use according to claim 11, **characterized in that** the scaffold or the formwork consists of metal at least in the region of the slot (2).
- 15 13. A component for formwork or scaffolding, **characterized** in that it has a device according to any one of the claims 1 to 10.