

METHOD AND DEVICE FOR REALIZING INTELLIGENT CONSTANT-SPEED AND ENERGY-SAVING DRIVING

[0001] The present application claims the priority to Chinese Patent Application No. 201811440774.0, titled "METHOD AND DEVICE FOR REALIZING INTELLIGENT CONSTANT-SPEED AND ENERGY-SAVING DRIVING ", filed with the China National Intellectual Property Administration, on November 29, 2018, which is incorporated herein by reference in its entirety.

FIELD

[0002] The present application relates to the technical field of rail transportations, and in particular to a method and a device for realizing intelligent constant-speed and energy-saving driving.

BACKGROUND

[0003] The constant-speed function of the existing electrical multiple units project is mainly classified into two types: one is a constant-speed operation mode, that is, when the electrical multiple units meet a constant-speed condition, the driver sets a target speed, and then relevant control functions are completed by a vehicle-mounted CCU (Central Control Unit). The constant-speed operation mode cannot automatically adjust the target speed according to speed limits of different operation sections, and all adjustments of the speed are manually completed by the driver.

[0004] The other is an automatic train operation mode, that is, an ATO mode. Although automatic adjustments of the target speed can be realized in this mode according to speed limits of different operation sections, an additional ATO host and related sensors need to be provided on the train, which has a high manufacturing cost. In the meantime, during the implementation of this mode, since a certain given speed value is automatically tracked in this mode according to a route situation and a signal situation in front of the train, if speed deviation occurs, the train will be hauled/braked immediately to correct the speed deviation, which results in that route conditions cannot be reasonably utilized, and the energy

consumption of the train is increased.

[0005] For example, in a case that the given speed value is 250km/h, the speed of the train is corrected in real time by traction/braking to keep the train at the speed of 250km/h. In a case that there is a downhill ahead, the train still travels at the speed of 250km/h, which results in that the train cannot effectively utilize the potential energy when going downhill to reduce the energy consumption.

SUMMARY

[0006] In order to solve the above technical problem, a method and a device for realizing intelligent constant-speed and energy-saving driving are provided according to embodiments of the present application. The technical solutions are as follows.

[0007] A method for realizing intelligent constant-speed and energy-saving driving is applied to a central control unit, which includes:

obtaining control information of a train when the train enters an intelligent constant-speed mode, wherein the control information includes route information and train information; and

generating an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train, and controlling operation of the train according to the automatic driving and energy-saving control strategy.

[0008] Preferably, the generating an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train includes:

generating a first automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a gentle route, wherein the first automatic driving and energy-saving control strategy is to control the speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the route, and to reduce the speed of the train from the first speed to a second speed through an idle running condition in remainder of the route, and to reduce the speed of the train from the second speed to zero by braking deceleration, wherein the first

speed is less than a speed limit threshold, and the given speed is a speed when the train enters the intelligent constant-speed mode; and

generating a second automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a complex route, wherein the complex route includes an uphill route and/or a downhill route, and in a case that the complex route includes the uphill route, the second automatic driving and energy-saving control strategy is to start speeding up the train by using the maximum-power traction within a preset distance before the train enters the uphill route; and in a case that the complex route includes the downhill route, the second automatic driving and energy-saving control strategy is to control the speed of the train to drop by using the idle running condition within a preset distance before the train enters the downhill route.

[0009] Preferably, the reducing the speed of the train from the second speed to zero by braking deceleration includes:

reducing the speed of the train from the second speed to zero by means of electric braking.

[0010] Preferably, the controlling the speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the route includes:

planning a speed-time curve of the train according to the control information;

calculating resistance of the gentle route in real time to obtain a calculation result of the route resistance;

calculating a real-time output power according to the speed-time curve and the calculation result of the route resistance;

performing a matching calculation for power units according to the real-time output power to obtain a calculation result of power-matching; and

obtaining a power-switching instruction based on the calculation result of power-matching to control the power units to be turned on or off according to the calculation result of power-matching, wherein activation or shutdown of the power units allows the speed of the train to rise from the given speed to the first speed.

[0011] Preferably, the method further includes:

determining whether the train meets a condition for entering the intelligent constant-speed mode;

determining whether an instruction of entering the intelligent constant-speed mode is received, if the condition for entering the intelligent constant-speed mode is met; and

5 performing the obtaining control information of the train, if the instruction of entering the intelligent constant-speed mode is received.

[0012] A device for realizing intelligent constant-speed and energy-saving driving is applied to a central control unit, which includes:

10 an obtaining unit, configured to obtain control information of a train when the train enters an intelligent constant-speed mode, wherein the control information includes route information and train information; and

15 a processing unit, configured to generate an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train, and to control operation of the train according to the automatic driving and energy-saving control strategy.

[0013] Preferably, the processing unit is specifically configured to:

20 generate a first automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a gentle route, wherein the first automatic driving and energy-saving control strategy is to control the speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the route, and to reduce the speed of the train from the first speed to a second speed through an idle running condition in remainder of the route, and to reduce the speed of the train from the second speed to zero by braking deceleration, wherein the first speed is less than a speed limit threshold, and the given speed is a speed when the train enters the intelligent constant-speed mode; and

30 generate a second automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a complex route, wherein the complex route includes an uphill route and/or a downhill route, and in a case that the complex route includes the uphill route, the second automatic driving and energy-saving control strategy is to start speeding up the train by using the maximum-power traction within a

preset distance before the train enters the uphill route; and in a case that the complex route includes the downhill route, the second automatic driving and energy-saving control strategy is to control the speed of the train to drop by using the idle running condition within a preset distance before the train enters the downhill route.

5 **[0014]** Preferably, the reducing the speed of the train from the second speed to zero by braking deceleration in the processing unit includes:

reducing the speed of the train from the second speed to zero by means of electric braking.

[0015] Preferably, the processing unit is specifically configured to:

10 plan a speed-time curve of the train according to the control information;

calculate resistance of the gentle route in real time to obtain a calculation result of the route resistance;

calculate a real-time output power according to the speed-time curve and the calculation result of the route resistance;

15 perform a matching calculation for power units according to the real-time output power to obtain a calculation result of power-matching; and

obtain a power-switching instruction based on the calculation result of power-matching to control the power units to be turned on or off according to the calculation result of power-matching, wherein activation or shutdown of the power units
20 allows the speed of the train to rise from the given speed to the first speed.

[0016] Preferably, the device further includes:

a first determining unit, configured to determine whether the train meets a condition for entering the intelligent constant-speed mode; and

a second determining unit, configured to determine whether an instruction of entering
25 the intelligent constant-speed mode is received, if the condition for entering the intelligent constant-speed mode is met, wherein the obtaining control information of the train in the obtaining unit is performed, if the instruction of entering the intelligent constant-speed mode is received.

[0017] According to the technical solutions provided by the embodiments of the present

application, when the train enters the intelligent constant-speed operation mode, the control information of the trains is obtained, and an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train is generated, thereby controlling operation of the train according to the automatic driving and energy-saving control strategy. Since the automatic driving and energy-saving control strategy is generated according to the route information, the embodiments of the present application can reduce the energy consumption of the train, compared with the constant-speed operation in the conventional technology.

10 BRIEF DESCRIPTION OF THE DRAWINGS

[0018] Figure 1 is a schematic flowchart of a method for realizing intelligent constant-speed and energy-saving driving according to an embodiment of the present application;

[0019] Figure 2 is another schematic flowchart of the method for realizing intelligent constant-speed and energy-saving driving according to an embodiment of the present application; and

[0020] Figure 3 is a schematic structural diagram of a device for realizing intelligent constant-speed and energy-saving driving according to an embodiment of the present application.

20 DETAILED DESCRIPTION OF EMBODIMENTS

[0021] The technical solutions according to the embodiments of the present application will be described clearly and completely as follows in conjunction with the drawings in the embodiments of the present application. It is apparent that the described embodiments are only a part of the embodiments according to the present application, rather than all the embodiments. Based on the embodiments of the present application, all other embodiments, made by those skilled in the art without any creative efforts, fall into the scope of the present application.

[0022] Referring to Figure 1, Figure 1 is a schematic flowchart of a method for realizing intelligent constant-speed and energy-saving driving according to an embodiment of the present application, the method is applied to a central control unit, and the method includes:

[0023] Step S101, obtaining control information of a train when the train enters an intelligent constant-speed mode.

The control information includes route information and train information.

In practical applications, the control information may be information of timetables, running maps, train speed, ramps, curves, stations, roads, bridges, tunnels, speed limit, train length, unit mass, load, auxiliary power, traction\braking force characteristics, resistance characteristics, and so on.

Preferably, before step S101, the method further includes:

determining whether the train meets a condition for entering the intelligent constant-speed mode;

determining whether an instruction of entering the intelligent constant-speed mode is received, if the condition for entering the intelligent constant-speed mode is met; and

performing the obtaining control information of the train, if the instruction of entering the intelligent constant-speed mode is received.

In the embodiments of the present application, if the train meets the condition for entering the intelligent constant-speed mode, the driver may trigger a specific button to enter the mode.

[0024] Step S102, generating an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train, and controlling operation of the train according to the automatic driving and energy-saving control strategy.

The step of generating an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train includes:

generating a first automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a gentle route, wherein the first automatic driving and energy-saving control strategy is to control the speed of the train to rise from a given speed to a first speed by using maximum-power traction

at a starting portion of the route, and to reduce the speed of the train from the first speed to a second speed through an idle running condition in remainder of the route, and to reduce the speed of the train from the second speed to zero by braking deceleration, wherein the first speed is less than a speed limit threshold, and the given speed is a speed when the train enters the intelligent constant-speed mode; and

generating a second automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a complex route, wherein the complex route includes an uphill route and/or a downhill route, and in a case that the complex route includes the uphill route, the second automatic driving and energy-saving control strategy is to start speeding up the train by using the maximum-power traction within a preset distance before the train enters the uphill route; and in a case that the complex route includes the downhill route, the second automatic driving and energy-saving control strategy is to control the speed of the train to drop by using the idle running condition within a preset distance before the train enters the downhill route.

[0025] In the present embodiment, the CCU controls the train to enter the intelligent constant-speed mode. If the forward route is uphill, the train is accelerated in advance by the maximum-power traction, or if the forward route is downhill, the train is decelerated in advance by the idle running condition. Since the train is decelerated before going downhill, the potential energy of the train when going downhill is converted into the kinetic energy of the train, so that the train is speeded up on the basis of the first speed, thereby reducing the energy consumption of the train while ensuring the running time of the train. In addition, speeding up the train in advance on the basis of the given speed before going uphill also reduces the energy consumption of the train, compared with speeding up the train after going uphill. Finally, if the train is running on a gentle route, the train is accelerated only at the starting portion of the route, and then is driven by the idle running condition until the train is decelerated at a tail end of the route, which reduces the energy consumption of the train, compared with that the train keeps travelling at a constant speed in the conventional technology.

[0026] In another embodiment of the present application, the speed of the train is reduced from the second speed to zero by braking deceleration. Specifically, the speed of the train may

be decelerated from the second speed to zero by means of electric braking. The electric braking can convert the kinetic energy of the train into electric energy, so that the electric braking can also reduce the energy consumption of the train, compared with air braking.

[0027] In another embodiment of the present application, the controlling the speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the route, as show in Figure 2, includes:

Step S201, planning a speed-time curve of the train according to the control information;

Step S102, calculating resistance of the gentle route in real time to obtain a calculation result of the route resistance;

Step S203, calculating a real-time output power according to the speed-time curve and the calculation result of the route resistance;

Step S204, performing a matching calculation for power units according to the real-time output power to obtain a calculation result of power-matching; and

Step S205, obtaining a power-switching instruction based on the calculation result of power-matching to control the power units to be turned on or off according to the calculation result of power-matching, wherein activation or shutdown of the power units allows the speed of the train to rise from the given speed to the first speed.

[0028] In another embodiment of the present application, the step of generating an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train may include:

using maximum-power traction to ensure that the train is accelerated quickly, if the speed of the train needs to rise; and

using the idle running condition, if the speed of the train needs to decrease; or using maximum-power braking, if the idle running condition cannot meet deceleration requirements of the train.

[0029] According to the technical solutions provided by the embodiments of the present application, when the train enters the intelligent constant-speed operation mode, the control information of the trains is obtained, and an automatic driving and energy-saving control

strategy according to the control information on the basis of meeting a running time of normal operation of the train is generated, thereby controlling operation of the train according to the automatic driving and energy-saving control strategy. Since the automatic driving and energy-saving control strategy is generated according to the route information, the
5 embodiments of the present application can reduce the energy consumption of the train, compared with the constant-speed operation in the conventional technology.

[0030] Referring to Figure 3, Figure 3 is a schematic structural diagram of a device for realizing intelligent constant-speed and energy-saving driving according to an embodiment of the present application. Working process of each module in the schematic structural diagram
10 refers to the execution process of the method in the embodiment corresponding to Figure 1. The device includes:

an obtaining unit 310, configured to obtain control information of a train when the train enters an intelligent constant-speed operation mode, wherein the control information includes route information and train information; and

15 a processing unit 320, configured to generate an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train, and to control operation of the train according to the automatic driving and energy-saving control strategy.

[0031] According to the technical solutions provided by the embodiments of the present
20 application, when the train enters the intelligent constant-speed operation mode, the control information of the trains is obtained, and an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train is generated, thereby controlling operation of the train according to the automatic driving and energy-saving control strategy. Since the automatic driving and
25 energy-saving control strategy is generated according to the route information, the embodiments of the present application can reduce the energy consumption of the train, compared with the constant-speed operation in the conventional technology.

[0032] In another embodiment of the present application, it is preferred that the processing unit is specifically configured to:

30 generate a first automatic driving and energy-saving control strategy, if the route

information indicates that the train is running on a gentle route, wherein the first automatic driving and energy-saving control strategy is to control the speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the route, and to reduce the speed of the train from the first speed to a second speed through an idle running condition in remainder of the route, and to reduce the speed of the train from the second speed to zero by braking deceleration, wherein the first speed is less than a speed limit threshold, and the given speed is a speed when the train enters the intelligent constant-speed mode; and

generate a second automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a complex route, wherein the complex route includes an uphill route and/or a downhill route, and in a case that the complex route includes the uphill route, the second automatic driving and energy-saving control strategy is to start speeding up the train by using the maximum-power traction within a preset distance before the train enters the uphill route; and in a case that the complex route includes the downhill route, the second automatic driving and energy-saving control strategy is to control the speed of the train to drop by using the idle running condition within a preset distance before the train enters the downhill route.

[0033] In another embodiment of the present application, it is preferred that the reducing the speed of the train from the second speed to zero by braking deceleration in the processing unit includes:

reducing the speed of the train from the second speed to zero by means of electric braking.

[0034] In another embodiment of the present application, it is preferred that the processing unit is specifically configured to:

plan a speed-time curve of the train according to the control information;

calculate resistance of the gentle route in real time to obtain a calculation result of the route resistance;

calculate a real-time output power according to the speed-time curve and the calculation result of the route resistance;

perform a matching calculation for power units according to the real-time output

power to obtain a calculation result of power-matching; and

obtain a power-switching instruction based on the calculation result of power-matching to control the power units to be turned on or off according to the calculation result of power-matching, wherein activation or shutdown of the power units allows the speed of the train to rise from the given speed to the first speed.

[0035] In another embodiment of the present application, it is preferred that the device further includes:

a first determining unit, configured to determine whether the train meets a condition for entering the intelligent constant-speed mode; and

a second determining unit, configured to determine whether an instruction of entering the intelligent constant-speed mode is received, if the condition for entering the intelligent constant-speed mode is met, wherein the obtaining control information of the train in the obtaining unit is performed, if the instruction of entering the intelligent constant-speed mode is received.

[0036] In the specification, claims, and accompanying drawings of the present application, the terms "first", "second", "third", "fourth", and the like (if existing) are intended to distinguish between similar objects rather than describe a specific order. It should be understood that, data used in this way can be interchanged in an appropriate case, so that the embodiments of the present application that are described herein, for example, can be implemented in a sequence other than those sequences illustrated or described herein. In addition, the terms "include" and "have" and any variations thereof are intended to cover non-exclusive inclusions. For example, a process, a method, a system, a product or a device that includes a series of steps or units is not limited to those clearly listed steps or units, and may instead include other steps or units not explicitly listed or inherent to the process, method, product or device.

[0037] Since the device or system embodiment corresponds to the method embodiment, reference may be made to the method embodiment for the relevant parts. The device or system embodiment described above is merely illustrative. The units described as separate components may be or not be separated physically. The components shown as units may be or not be physical units, i.e., the units may be located at a same place or may be distributed onto

multiple network units. A part or all of the modules may be selected based on actual needs to implement the solution according to the embodiment. Those skilled in the art may understand and implement the present application without creative work.

[0038] In the embodiments according to the present application, it should be understood that the disclosed system, device and method may be implemented in other ways without departing from the spirit and scope of the present application. The present embodiments are only exemplary examples and should not be construed as a limitation, and the specific contents given should not limit the purpose of the present application. For example, the units or sub-units are merely divided according to a logic function, and the units may be divided in other way in practice. For example, multiple units or sub-units may be combined. Moreover, the units or parts may be combined or integrated into another system, or some features may be omitted or not performed.

[0039] In addition, the described system, device, and method, as well as schematic diagrams of different embodiments, can be combined or integrated with other systems, modules, technologies, or methods without departing from the scope of the present application. In addition, the coupling, direct coupling or communication connection between components which are shown or discussed may be indirect coupling or communication connection via some interfaces, devices or units, which may be electrical, mechanical, or in other form.

[0040] Only specific embodiments of the present application are described above, it should be pointed out that various improvements and modifications can be made by those skilled in the art without departing from the principle of the present application, and these improvements and modifications should fall within the protection scope of the present application.

CLAIMS

1. A method for realizing intelligent constant-speed and energy-saving driving, wherein the method is applied to a central control unit, and comprises:

5 obtaining control information of a train when the train enters an intelligent constant-speed mode, wherein the control information comprises route information and train information; and

generating an automatic driving and energy-saving control strategy according to the control information while meeting a running time of normal operation of the train, and
10 controlling operation of the train according to the automatic driving and energy-saving control strategy.

2. The method according to claim 1, wherein the generating an automatic driving and energy-saving control strategy according to the control information while meeting a running
15 time of normal operation of the train comprises:

generating a first automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a gentle route, wherein the first automatic driving and energy-saving control strategy is to control a speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the
20 route, and to reduce the speed of the train from the first speed to a second speed through an idle running condition in remainder of the route, and to reduce the speed of the train from the second speed to zero by braking deceleration, wherein the first speed is less than a speed limit threshold, and the given speed is a speed when the train enters the intelligent constant-speed mode; and

25 generating a second automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a complex route, wherein the complex route comprises an uphill route and/or a downhill route, and in a case that the complex route comprises the uphill route, the second automatic driving and energy-saving control strategy is to start speeding up the train by using the maximum-power traction within a preset distance
30 before the train enters the uphill route; and in a case that the complex route comprises the

downhill route, the second automatic driving and energy-saving control strategy is to control the speed of the train to drop by using the idle running condition within a preset distance before the train enters the downhill route.

5 3. The method according to claim 2, wherein the reducing the speed of the train from the second speed to zero by braking deceleration comprises:

reducing the speed of the train from the second speed to zero by means of electric braking.

10 4. The method according to claim 2, wherein the controlling the speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the route comprises:

planning a speed-time curve of the train according to the control information;

15 calculating resistance of the gentle route in real time to obtain a calculation result of the route resistance;

calculating a real-time output power according to the speed-time curve and the calculation result of the route resistance;

performing a matching calculation for power units according to the real-time output power to obtain a calculation result of power-matching; and

20 obtaining a power-switching instruction based on the calculation result of power-matching to control the power units to be turned on or off according to the calculation result of power-matching, wherein activation or shutdown of the power units allows the speed of the train to rise from the given speed to the first speed.

25 5. The method according to claim 1, further comprising:

determining whether the train meets a condition for entering the intelligent constant-speed mode;

determining whether an instruction of entering the intelligent constant-speed mode is

received, if the condition for entering the intelligent constant-speed mode is met; and

performing the obtaining control information of the train, if the instruction of entering the intelligent constant-speed mode is received.

5 6. A device for realizing intelligent constant-speed and energy-saving driving, wherein the device is applied to a central control unit, and comprises:

an obtaining unit, configured to obtain control information of a train when the train enters an intelligent constant-speed mode, wherein the control information comprises route information and train information; and

10 a processing unit, configured to generate an automatic driving and energy-saving control strategy according to the control information on the basis of meeting a running time of normal operation of the train, and to control operation of the train according to the automatic driving and energy-saving control strategy.

15 7. The device according to claim 6, wherein the processing unit is configured to:

generate a first automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a gentle route, wherein the first automatic driving and energy-saving control strategy is to control a speed of the train to rise from a given speed to a first speed by using maximum-power traction at a starting portion of the route, and to reduce the speed of the train from the first speed to a second speed through an idle running condition in remainder of the route, and to reduce the speed of the train from the second speed to zero by braking deceleration, wherein the first speed is less than a speed limit threshold, and the given speed is a speed when the train enters the intelligent constant-speed mode; and

25 generate a second automatic driving and energy-saving control strategy, if the route information indicates that the train is running on a complex route, wherein the complex route comprises an uphill route and/or a downhill route, and in a case that the complex route comprises the uphill route, the second automatic driving and energy-saving control strategy is to start speeding up the train by using the maximum-power traction within a preset distance before the train enters the uphill route; and in a case that the complex route comprises the

30

downhill route, the second automatic driving and energy-saving control strategy is to control the speed of the train to drop by using the idle running condition within a preset distance before the train enters the downhill route.

5 8. The device according to claim 7, wherein the reducing the speed of the train from the second speed to zero by braking deceleration in the processing unit comprises:

reducing the speed of the train from the second speed to zero by means of electric braking.

10 9. The device according to claim 7, wherein the processing unit is configured to:

plan a speed-time curve of the train according to the control information;

calculate resistance of the gentle route in real time to obtain a calculation result of the route resistance;

15 calculate a real-time output power according to the speed-time curve and the calculation result of the route resistance;

perform a matching calculation for power units according to the real-time output power to obtain a calculation result of power-matching; and

20 obtain a power-switching instruction based on the calculation result of power-matching to control the power units to be turned on or off according to the calculation result of power-matching, wherein activation or shutdown of the power units allows the speed of the train to rise from the given speed to the first speed.

10. The device according to claim 6, further comprising:

25 a first determining unit, configured to determine whether the train meets a condition for entering the intelligent constant-speed mode; and

a second determining unit, configured to determine whether an instruction of entering the intelligent constant-speed mode is received, if the condition for entering the intelligent constant-speed mode is met, wherein the obtaining control information of the train in the

obtaining unit is performed, if the instruction of entering the intelligent constant-speed mode is received.