

Description

The present invention relates to a slim-type polarized electromagnetic relay for use in a communication system or the like.

EP 0 277 833 (A2) discloses relays comprising a base block having a supporting stud protruding from the center of a recess portion of said base block, an armature block having a pair of armatures, a coupling member for coupling said armatures so as to be parallel with each other, and at least one permanent magnet, between said armatures, said coupling member having a hole at the center thereof, said armature block being rotatably supported on said base block by insertion of said stud of said base block into said hole of said armature block; and an electromagnetic block having an approximately U-shaped core including a magnetic pole leg at each end thereof, a winding wound on said core, and terminals connected to said winding, said magnetic pole legs of said electromagnetic block being inserted between said armatures and fixed to said base block, to thereby sandwich said armature block between said base block and said electromagnetic block.

There are two kinds of electromagnetic relays: a slim-type and a flat-type. The slim type requires a less occupied area rather than a smaller height, while the flat-type requires a smaller height rather than a less occupied area.

In the prior art, however, the two kinds of electromagnetic relays are constructed with individual parts specialized to each kind, and as a result, the expense of manufacturing the two kinds of electromagnetic relays is high, and thus the manufacturing cost is increased.

Therefore, an object of the present invention is to reduce the manufacturing cost of electromagnetic relays.

A relay according to the present invention is characterized in that a fitting groove is provided adjacent each end of the base block, the magnetic pole legs of the electromagnetic block are inserted into the fitting grooves, and the armature block has approximately the same width as said electromagnetic block. That is, the slim-type electromagnetic relay according to the present invention has a large number of components commonly used in a flat-type electromagnetic relay.

The present invention will be more clearly understood from the description as set forth below, with reference to the accompanying drawings, wherein:

Fig. 1 is an exploded, perspective view illustrating a prior art flat-type polarized electromagnetic relay,

Fig. 2 is a perspective view of an assembled state of the relay of Fig. 1;

Fig. 3 is an exploded, perspective view illustrating an embodiment of the slim-type polarized

electromagnetic relay according to the present invention; and

Fig. 4 is a perspective view of an assembled state of the relay of Fig. 3.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Before the description of an embodiment of the present invention, a prior art flat-type electromagnetic relay will be explained with reference to Figs. 1 and 2.

In Fig. 1, which is an exploded, perspective view, reference A designates a base block, B an armature block, and C an electromagnet block.

The base block A includes a base 1 made of synthetic resin provided with a recess 2, and a stud 3 for supporting the armature block B is protruded from a center of the recess 2 of the base 1. Also, movable contact springs 4a and 4b, and stationary contact springs 5a, 5b, 5c, and 5d, which oppose the ends of the movable contact springs 4a and 4b, are inserted into the base 1 by molding. Further, reference numerals 6 designate terminals connected to the movable contact springs 4a, 4b, the stationary contact springs 5a, 5b, 5c, and 5d, and winding terminals 13a, 13b, 13c, and 13d. Also, reference numerals 7a, 7b, 7c, and 7d designate winding terminal coupling portions for the winding terminals 13a, 13b, 13c, and 13d, respectively.

The armature block B includes a pair of parallel armatures 8a and 8b, and a coupling member 9, including a permanent magnet, for coupling the armatures 8a and 8b to each other.

The electromagnet block C includes an approximately U-shaped core 10 on which a winding 11 is wound, and collars 12a and 12b on which the winding terminals 13a through 13d are mounted.

The armature block B is mounted on the base block A by inserting the stud 3 thereof into a hole 9a of the coupling member 9 of the armature block B. Then, the electromagnet block C is mounted on the armature block B, so that the core 10 is interposed between the armatures 8a and 8b, whereby an assembled state of the relay of Fig. 1 is obtained as illustrated in Fig. 2. Note that reference numerals 14a and 14b designate cards for coupling the movable contact springs 4a and 4b to the armatures 8a and 8b, respectively.

The above-mentioned flat-type electromagnetic relay of Figs. 1 and 2 is not suitable for a slim-type relay, and further, a prior art slim-type electromagnetic relay is constructed by different parts of such a flat-type electromagnetic relay as shown in Figs. 1 and 2 (see: U.S. Patent No. 4,843,360 and EP-A-0 277 833), thus increasing the manufacturing cost.

In the present invention, most of the parts of the flat-type electromagnetic relay of Figs. 1 and 2 are

used.

In Fig. 3, which is an exploded, perspective view of the slim-type electromagnetic relay according to the present invention, a base block A' is similar to the base block A of Fig. 1, but a base 1' is slimmer than the base 1 of Fig. 1. Also, fitting grooves 15a and 15b are provided at both ends of the base 1', to allow magnetic pole legs 18a and 18b to be inserted therein.

An armature block B' is similar to the armature block B of Fig. 1, except that protrusions 16a, 16b, 16c, and 16d are provided on four ends of the coupling member 9. This coupling member 9 is made by molding to keep armatures 8a and 8b in parallel with each other. Also, reference numerals 17a and 17b designate permanent magnets.

An electromagnet block C' is also similar to the electromagnet block C of Fig. 1, except that the magnetic pole legs 18a and 18b of the U-shaped core 10 are longer than those of Fig. 1 (not shown), and can reach the fitting grooves 15a and 15b of the base block A'.

The blocks A', B', and C' of Fig. 3 are assembled to obtain a state as illustrated in Fig. 4. That is, the armature block B' is mounted on the base block A' by inserting the stud 3 thereof into the hole 9a of the coupling member 9. Also, the protrusions 16a through 16d of the coupling member 9 are associated by the cards 14a and 14b with the central upper portions of the movable contact springs 4a and 4b. Further, the electromagnet block C' is placed above the armature block B' and the base block A', by inserting the magnetic pole legs 18a and 18b into the fitting grooves 15a and 15b of the base block A', and as a result, the faces of the magnetic pole legs 18a and 18b oppose the faces of the armatures 8a and 8b. Also, the winding terminals 13a through 13d, which are made, for example, by an insert-molding into the collars 12a and 12b, are adhered by a spot-welding to the winding terminal coupling portions 7a, 7b, 7c, and 7d of the base block A'. Thus, the armature block B' is sandwiched by the base block A' and the electromagnet block C', as illustrated in Fig. 4.

The operation of the relay of Figs. 3 and 4 will be explained below.

When the winding 11 is not excited, a magnetic circuit is formed by only the permanent magnets 17a and 17b. That is, a magnetic flux generated from the permanent magnets 17a and 17b is absorbed by one end of the armature 8a and one end of the armature 8b which are in contact with the faces of the magnetic pole legs 18a and 18b. As a result, the movable contact spring 4a is in contact with one of the stationary contact springs 5a and 5c, while the movable contact spring 4b is in contact with one of the stationary contact springs 5b and 5d. This state is maintained until the winding 11 is excited.

Next, when the winding 11 is excited by supplying a current thereto, to generate a magnetic flux oppo-

site to the magnetic flux in the core 10 by the permanent magnets 17a and 17b, the faces of the magnetic pole legs 18a and 18b and the armatures 8a and 8b repulse and attract each other, so that the armatures 8a and 8b are rotated at the stud 3. As a result, the closed contacts, where the movable contact springs 4a and 4b are in contact with the stationary contact springs such as 5a and 5b, are opened, and the opened contacts, where the movable contact springs 4a and 4b are in contact with the stationary contact springs such as 5c and 5d, are closed, thus carrying out a switching operation. Thereafter, when the excitation of the winding 11 is released, the switched state of the relay is maintained by the magnetic flux of the permanent magnet 17a and 17b in the case of a latch type. Note, in the case of a non-latch type, the relay is returned, by the return force of the movable contact springs 4a and 4b and by nonmagnetic plates located on a face to be in contact with the magnetic pole faces of the armatures 8a and 8b, to a state before the winding 11 is excited.

Also, in the latch type, when the winding 11 is again excited in the reverse direction, the relay returns to its original state. Here, two cases exist: a case wherein the winding 11 is excited in both the positive and negative directions, and a case wherein the winding 11 is split into two portions which are excited in the positive direction and in the negative direction, respectively.

As explained above, according to the present invention, since the electromagnet block C' is arranged above the armature block B', the width of the relay can be remarkably reduced to obtain a super slim type, compared with the case where the electromagnet block C is arranged between the pair of armatures.

Also, since the armatures, the movable contact springs, the stationary contact springs, and the cards of the flat-type electromagnetic relay of Figs. 1 and 2 can be commonly used, the slim type relay according to the present invention can be economically manufactured. Further, since the pair of armatures are molded by synthetic resin to form the armature block, and the axis hole of the armature block is supported by the stud at the center of the base block, the relationship of the position of the pair of armatures can be precisely arranged.

Claims

1. A relay comprising:
 - a base block (A') having a supporting stud (3) protruding from the center of a recess portion (2) of said base block,
 - an armature block (B') having a pair of armatures (8a, 8b), a coupling member (9) for coupling said armatures so as to be parallel with each



used.

In Fig. 3, which is an exploded, perspective view of the slim-type electromagnetic relay according to the present invention, a base block A' is similar to the base block A of Fig. 1, but a base 1' is slimmer than the base 1 of Fig. 1. Also, fitting grooves 15a and 15b are provided at both ends of the base 1', to allow magnetic pole legs 18a and 18b to be inserted therein.

An armature block B' is similar to the armature block B of Fig. 1, except that protrusions 16a, 16b, 16c, and 16d are provided on four ends of the coupling member 9. This coupling member 9 is made by molding to keep armatures 8a and 8b in parallel with each other. Also, reference numerals 17a and 17b designate permanent magnets.

An electromagnet block C' is also similar to the electromagnet block C of Fig. 1, except that the magnetic pole legs 18a and 18b of the U-shaped core 10 are longer than those of Fig. 1 (not shown), and can reach the fitting grooves 15a and 15b of the base block A'.

The blocks A', B', and C' of Fig. 3 are assembled to obtain a state as illustrated in Fig. 4. That is, the armature block B' is mounted on the base block A' by inserting the stud 3 thereof into the hole 9a of the coupling member 9. Also, the protrusions 16a through 16d of the coupling member 9 are associated by the cards 14a and 14b with the central upper portions of the movable contact springs 4a and 4b. Further, the electromagnet block C' is placed above the armature block B' and the base block A', by inserting the magnetic pole legs 18a and 18b into the fitting grooves 15a and 15b of the base block A', and as a result, the faces of the magnetic pole legs 18a and 18b oppose the faces of the armatures 8a and 8b. Also, the winding terminals 13a through 13d, which are made, for example, by an insert-molding into the collars 12a and 12b, are adhered by a spot-welding to the winding terminal coupling portions 7a, 7b, 7c, and 7d of the base block A'. Thus, the armature block B' is sandwiched by the base block A' and the electromagnet block C', as illustrated in Fig. 4.

The operation of the relay of Figs. 3 and 4 will be explained below.

When the winding 11 is not excited, a magnetic circuit is formed by only the permanent magnets 17a and 17b. That is, a magnetic flux generated from the permanent magnets 17a and 17b is absorbed by one end of the armature 8a and one end of the armature 8b which are in contact with the faces of the magnetic pole legs 18a and 18b. As a result, the movable contact spring 4a is in contact with one of the stationary contact springs 5a and 5c, while the movable contact spring 4b is in contact with one of the stationary contact springs 5b and 5d. This state is maintained until the winding 11 is excited.

Next, when the winding 11 is excited by supplying a current thereto, to generate a magnetic flux oppo-

site to the magnetic flux in the core 10 by the permanent magnets 17a and 17b, the faces of the magnetic pole legs 18a and 18b and the armatures 8a and 8b repulse and attract each other, so that the armatures 8a and 8b are rotated at the stud 3. As a result, the closed contacts, where the movable contact springs 4a and 4b are in contact with the stationary contact springs such as 5a and 5b, are opened, and the opened contacts, where the movable contact springs 4a and 4b are in contact with the stationary contact springs such as 5c and 5d, are closed, thus carrying out a switching operation. Thereafter, when the excitation of the winding 11 is released, the switched state of the relay is maintained by the magnetic flux of the permanent magnet 17a and 17b in the case of a latch type. Note, in the case of a non-latch type, the relay is returned, by the return force of the movable contact springs 4a and 4b and by nonmagnetic plates located on a face to be in contact with the magnetic pole faces of the armatures 8a and 8b, to a state before the winding 11 is excited.

Also, in the latch type, when the winding 11 is again excited in the reverse direction, the relay returns to its original state. Here, two cases exist: a case wherein the winding 11 is excited in both the positive and negative directions, and a case wherein the winding 11 is split into two portions which are excited in the positive direction and in the negative direction, respectively.

As explained above, according to the present invention, since the electromagnet block C' is arranged above the armature block B', the width of the relay can be remarkably reduced to obtain a super slim type, compared with the case where the electromagnet block C is arranged between the pair of armatures.

Also, since the armatures, the movable contact springs, the stationary contact springs, and the cards of the flat-type electromagnetic relay of Figs. 1 and 2 can be commonly used, the slim type relay according to the present invention can be economically manufactured. Further, since the pair of armatures are molded by synthetic resin to form the armature block, and the axis hole of the armature block is supported by the stud at the center of the base block, the relationship of the position of the pair of armatures can be precisely arranged.

Claims

1. A relay comprising:

a base block (A') having a supporting stud (3) protruding from the center of a recess portion (2) of said base block,

an armature block (B') having a pair of armatures (8a, 8b), a coupling member (9) for coupling said armatures so as to be parallel with each



other, and at least one permanent magnet (17a, 17b), between said armatures, said coupling member having a hole (9a) at the center thereof, said armature block being rotatably supported on said base block by insertion of said stud of said base block into said hole of said armature block (B'); and

an electromagnetic block (C') having an approximately U-shaped core (10) including a magnetic pole leg (18a, 18b) at each end thereof, a winding (11) wound on said core, and terminals connected to said winding, said magnetic pole legs of said electromagnetic block being inserted between said armatures and fixed to said base block, to thereby sandwich said armature block between said base block and said electromagnetic block,

characterized in that a fitting groove (15a, 15b) is provided adjacent each end of the base block (A'), the magnetic pole legs (18a, 18b) of the electromagnetic block (C') are inserted into the fitting grooves (15a, 15b), and the armature block (B') has approximately the same width as said electromagnetic block (C').

2. A relay as set forth in claim 1, wherein said coupling member (9) is made by molding said armatures (8a, 8b) to keep them parallel with each other.
3. A relay as set forth in claim 1 or 2, wherein said base block further includes:
 - a pair of movable contact springs (4a, 4b);
 - a pair of cards (14a, 14b) for coupling said movable contact springs to said armatures; and
 - at least two stationary contact springs (5a, 5b,...) at opposite ends of said movable contact springs.

Patentansprüche

1. Relais, enthaltend:

einen Basisblock (A') mit einem Stützzapfen (3), der vom Zentrum eines Ausnehmungsbeereiches (2) des Basisblocks vorsteht,

einen Ankerblock (B') mit einem Paar von Ankern (8a, 8b), einem Kopplungsbauteil (9) zum Koppeln der Anker derart, daß sie parallel zueinander sind, und wenigstens einem Permanentmagneten (17a, 17b) zwischen den Ankern, wobei das Kopplungsbauteil in seinem Zentrum ein Loch (9a) hat und der Ankerblock durch Einsetzen des Zapfens des Basisblocks in das Loch des Ankerblocks (B') drehbar auf dem Basisblock gehalten ist; und

einen Elektromagnetblock (C') mit einem etwa U-förmigen Kern (10), der an jedem seiner

Enden einen Magnetpolschenkel (18a, 18b) enthält, einer auf den Kern gewickelten Wicklung (11) und mit der Wicklung verbundenen Anschlüssen, wobei die Magnetpolschenkel des Elektromagnetblocks zwischen die Anker eingesetzt und an dem Basisblock befestigt sind, um auf diese Weise den Ankerblock sandwichartig zwischen dem Basisblock und dem Elektromagnetblock aufzunehmen,

dadurch gekennzeichnet, daß neben jedem Ende des Basisblocks (A') eine Passnut (15a, 15b) vorgesehen ist, die Magnetpolschenkel (18a, 18b) des Elektromagnetblocks (C') in die Passnuten (15a, 15b) eingesetzt sind, und der Ankerblock (B') etwa die gleiche Breite wie der Elektromagnetblock (C') hat.

2. Relais nach Anspruch 1, wobei das Kopplungsbauteil (9) durch Formen der Anker (8a, 8b) hergestellt ist, um die Anker parallel zueinander zu halten.
3. Relais nach Anspruch 1 oder 2, wobei der Basisblock weiter enthält:
 - ein Paar bewegliche Kontaktfedern (4a, 4b);
 - ein Paar von Platten (14a, 14b) zum Koppeln der beweglichen Kontaktfedern an die Anker; und
 - wenigstens zwei stationäre Kontaktfedern (5a, 5b,...) an entgegengesetzten Enden der beweglichen Kontaktfedern.

Revendications

1. Relais comportant:

un bloc de base (A') présentant un tenon support (3) qui fait saillie depuis le centre d'une portion évidée (2) dudit bloc de base, un bloc d'armature (B') présentant une paire d'armatures (8, 8b), un élément de couplage (9) pour coupler lesdites armatures de façon à ce qu'elles soient parallèles l'une à l'autre, et au moins un aimant permanent (17a, 17b) entre lesdites armatures, ledit élément de couplage présentant un trou (9a) en son centre, ledit bloc d'armature étant supporté, avec liberté de rotation, sur ledit bloc de base par insertion dudit tenon dudit bloc de base dans ledit trou dudit bloc d'armature (B'); et

un bloc électromagnétique (C') présentant un noyau (10), approximativement en forme de U, incluant, à chacune de ses extrémités, une branche polaire magnétique (18a, 18b), un bobinage (11) bobiné sur ledit noyau, et des bornes reliées audit bobinage, lesdites branches polaires magnétiques dudit bloc électromagnétique étant insérées entre lesdites armatures et fixées



audit bloc de base, de façon à prendre en sandwich ledit bloc d'armature entre ledit bloc de base et ledit bloc électromagnétique,

caractérisé par le fait qu'une rainure de montage (15a, 15b) est prévue près de chaque extrémité du bloc de base (A'), que les branches polaires magnétiques (18a, 18b) du bloc électromagnétique (C') sont insérées dans les rainures de montage (15a, 15b) et que le bloc d'armature (B') a approximativement la même largeur que ledit bloc électromagnétique (C').

2. Relais comme exposé dans la revendication 1, dans lequel ledit élément de couplage (9) est prévu lors du moulage desdites armatures (8a, 8b) pour les maintenir parallèles l'une à l'autre.
3. Relais comme exposé dans la revendication 1 ou 2, dans lequel ledit bloc de base comporte en outre:
 - une paire de ressorts (4a, 4b) formant contacts mobiles;
 - une paire de cartes (14a, 14b) pour coupler lesdits ressorts formant contacts mobiles auxdites armatures; et
 - au moins deux ressorts (5a; 5, ...) formant contacts fixes aux extrémités opposées desdits ressorts formant contacts mobiles.

5

10

15

20

25

30

35

40

45

50

55

5