



AIR CONDITIONER

BACKGROUND OF THE INVENTION

The present invention relates to an air conditioner for exchanging heat with a refrigerant so as to adjust a room temperature to a designated temperature and for shifting a designated temperature to a predetermined temperature under a predetermined condition in such a case that a user is sleeping.

An air conditioner has a compressor for compressing a refrigerant and executes a refrigerating cycle for exchanging heat with the refrigerant so as to execute a control operation for approaching the room temperature to the designated temperature.

A conventional air conditioner performs the following control operation for approaching the room temperature to the designated temperature. The air conditioner performs a fussy operation corresponding to the difference Δt between the designated temperature and the room temperature and the variation thereof and calculates an increase/decrease amount of the frequency for controlling an AC motor of a compressor. Corresponding to the increase/decrease amount, the air conditioner increases or decreases the operation power of the AC motor so as to asymptotically approach the

This Sheet Has Been Replaced



room temperature to the designated temperature. In addition, the air conditioner compensates the real operation power corresponding to various factors such as the current consumption, the temperature of the compressor, and outer temperature at that time.

However, when the air conditioner performs the control operation while the user is sleeping, due to the fact that the body temperature of the user decreases, it cannot provide the user for a comfortable sleeping environment. In other words, the user designates a temperature while he is awaking, not a temperature while he is sleeping. When the body temperature of the user decreases while he is sleeping, he feels too cold in a cooling mode and too hot in a heating mode.

To solve such a problem, when a conventional air conditioner determines that the room temperature accords with the designated temperature, it increases the designated temperature to a predetermined temperature in the cooling mode and decreases the designated temperature to the predetermined temperature in the heating mode so as to handle a temperature change during sleeping.

It takes a long time until the room temperature reaches a designated temperature. Thus, the room temperature does not easily accord with the designated temperature. Consequently, it is very difficult to

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

determine whether the room temperature accords with the desired temperature. When the room temperature approaches a predetermined range of the desired temperature, the air conditioner determines that the room temperature accords with the desired temperature and performs the above-described temperature shift control.

However, when the amount of the load of the air conditioner is balanced with the operation power, the air conditioner tries to converge to the balanced state. In other words, the air conditioner stably operates in the condition that the room temperature does not accord with the designated temperature. In this case, the air conditioner does not perform the above-described temperature shift control. Thus, the air conditioner cannot provide the user for a temperature corresponding to his decreased body temperature.

SUMMARY OF THE INVENTION

The present invention is made from the above-described point of view. An object of the present invention is to properly perform the temperature shift control in the stable operation state for improving sleeping comfortableness and to properly perform designated temperature shift control for energy saving.

The present invention is an air conditioner for varying an air conditioning power and for approaching a



room temperature to a designated temperature, comprising a determining means for determining whether or not the conditioning power that is operating approaches a predetermined range of the air conditioning power required for maintaining the desired temperature and for outputting a corresponding signal, and a compensating means for compensating the desired temperature corresponding to the signal that is output from the determining means.

According to the present invention, when the air conditioner performs an operation for approaching the room temperature to the desired temperature, the air conditioning power necessary for the control operation gradually approaches the air conditioning power for maintaining the desired temperature. In this case, when the air conditioning power at the present time approaches a predetermined range of the air conditioning power for maintaining the desired temperature, the desired temperature is compensated. Thus, a situation of which a proper desired temperature becomes an improper temperature due to a variation of the body temperature of the user can be prevented. In addition, when the control operation becomes stable in the condition that the room temperature does not accord with the desired temperature, if it is determined that the air conditioning power during the control operation approaches the air conditioning power for



maintaining the desired temperature, the desired temperature is compensated. Thus, even if the control operation becomes stable, since the desired temperature is properly compensated, the air conditioner can provide the user for a comfortable sleep environment.

These and other objects, features and advantages of the present invention will become more apparent in light of the following detailed description of a best mode embodiment thereof, as illustrated in the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram showing an air conditioner according to an embodiment of the present invention;

Fig. 2 is a side view showing an inner construction of an indoor unit of the air conditioner according to the embodiment of the present invention;

Fig. 3 is a schematic diagram showing a refrigerant circuit of the air conditioner according to the embodiment of the present invention;

Fig. 4 is an electric circuit diagram of the indoor unit of the air conditioner according to the embodiment of the present invention;

Fig. 5 is an electric circuit diagram of an outdoor unit of the air conditioner according to the embodiment of the present invention;



Fig. 6 is a flow chart showing a temperature shift control of the air conditioner corresponding to the embodiment of the present invention;

Fig. 7 is a graph showing a time change of a room temperature t in a heating mode; and

Fig. 8 is a graph showing a time change of a room temperature t in a cooling mode

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

Next, with reference to the accompanying drawings, an embodiment of the present invention will be described.

Fig. 1 shows an air conditioner according to the embodiment of the present invention. The air conditioner comprises an indoor unit 10, an outdoor unit 12, and a remote controller 14. The indoor unit 10 and the outdoor unit 12 each have a refrigerant circulating path for circulating a refrigerant. The remote controller 14 sends operation signals as infrared rays to the air conditioner so as to remotely control it.

The remote controller 14 has various operation keys (switches) for turning on/off the power, selecting cooling/heating modes, designating temperature, designating timer, and so forth. With the operation keys, corresponding operation signals are output to the air conditioner. The remote controller 14 has air amount designating keys. With the air amount designating keys,

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

7

the user can select the air amount from "WEAK", "MEDIUM", and "STRONG".

In this embodiment, an air conditioner that has the three levels of air amount will be exemplified. However, the above-described three levels of air amount are fundamental in the embodiment. Thus, the embodiment can be applied for other constructions of which the air amount is varied in several levels (including for example "breeze", "high power", etc.), the air amount is gradually varied rather than in the fixed levels.

In addition, the remote controller 14 according to the embodiment has a "sleep mode" designating key. With the "sleep mode" designating key, a program for controlling air amount, temperature, and so forth for a comfortable sleeping environment is executed.

In the sleep mode, due to the fact that the body temperature of the user who is sleeping is lower than the body temperature of the user who is awaking, a function for shifting the room temperature to a lower temperature than the designated temperature in the cooling mode and to a higher temperature than the designated temperature in the heating mode is provided.

In this embodiment, as a means for sending operation signals of the remote controller 14 to the indoor unit 10, radio waves such as infrared rays are used. The indoor



unit 10 has an optical sensor 76B that receives the infrared rays. The optical sensor 76B will be described later.

When an operation signal sent from the remote controller 14 is received by the optical sensor 76B of the indoor unit 10, the air conditioner controls the room temperature, humidity, and so forth corresponding to the code of the received operation signal. It should be noted that the remote controller 14 can be connected to the indoor unit with a signal line.


As shown in Fig. 2, the indoor unit 10 is covered by a casing 202. The casing 202 is detachably secured to the upper and lower edges of a mounting base 200. A cross flow fan 204 is disposed at a center portion of the casing 202. The cross flow fan 204 is driven by a drive force of a fan motor 70E (that will be described later). The cross flow fan 204 sucks air in the room from a sucking opening 206 through various filters 208 and a heat exchanger 16 and supplies the resultant air to the room through an air path 210. The air path 210 has a horizontal fan 212 and horizontal flaps 214 so as to adjust the direction of the air supplied to the room.

A drain pan 216 is integrally disposed at the casing 202 corresponding to the lower portion of the heat exchanger 16.



Fig. 3 shows a refrigerant circuit of the air conditioner controlled by a control unit according to the embodiment of the present invention. In Fig. 3, reference numeral 26 is a compressor. Reference numeral 27 is a four-way valve. Reference numeral 28 is an outdoor heat exchanger disposed in the outdoor unit 12. Reference numeral 30 is a capillary tube. Reference numeral 16 is an indoor heat exchanger disposed in the indoor unit 10. Reference numeral 24 is an accumulator. These elements are circularly connected by a refrigerant pipe so as to construct a refrigerant cycle.

In the air conditioner, when the four-way valve 27 is placed in the state denoted by a solid line shown in Fig. 3, the refrigerant supplied from the compressor 26 flows in the direction of an arrow denoted by a solid line. Thus, the refrigerant is compressed in the outdoor heat exchanger 28. The refrigerant is evaporated by the indoor heat exchanger 16. Consequently, the room is cooled. On the other hand, when the four-way valve 27 is placed in the state denoted by a dotted line shown in Fig. 3, the refrigerant supplied from the compressor 26 flows in the direction of an arrow denoted by a dotted line. The refrigerant is compressed by the indoor heat exchanger 16. The refrigerant is evaporated by the outdoor heat exchanger 28. Consequently, the room is heated.



Reference numeral 112A is a fan motor that constructs an outdoor air supplying device. Reference numeral 70E is a fan motor that constructs an indoor air supplying device along with the cross flow fan 204. The fan motor 112A and the fan motor 70E cause air to be supplied to the outdoor heat exchanger 28 and the indoor heat exchanger 16, respectively.

Fig. 4 shows an electric circuit of the indoor unit 10. The electric circuit has a power supply board 70 and a control board 72. The power supply board 70 has a drive circuit 70A, a motor power supply circuit 70B, a control circuit power supply circuit 70C, and a serial circuit power supply circuit 70D. The drive circuit 70A is connected to the fan motor 70E that controls the air amount supplied to the room. The motor power supply circuit 70B generates the power for driving various motors. The control circuit power supply circuit 70C generates power for the control circuit. The serial circuit power supply circuit 70D generates the power for the serial circuit.

The control board 72 has a serial circuit 72A, a drive circuit 72B, and a microcomputer 72C. The serial circuit 72A is connected to the serial circuit power supply circuit 70D. The drive circuit 72B drives a motor. The microcomputer 72C functions as a control circuit. The drive circuit 72B is connected to an up/down flap motor



74A, left/right flap motors 74B and 74C, and a floor sensor motor 74D. The up/down flap motor 74A vertically moves a flap. The floor sensor motor 74D rotates a floor sensor that detects the temperature of the entire surface of the floor.

The microcomputer 72C is connected to a display LED, an optical sensor 76B, and a receiving circuit 76A. The display LED is disposed on the display board 76 and displays an operation mode and so forth. The receiving circuit 76a receives an operation signal as infrared rays through the optical sensor 76B from the remote controller 14.

In addition, the microcomputer 72C is connected to an area LED and a floor sensor. The area LED is disposed on a sensor board 78 and displays the temperature detecting area of the floor.

The remote controller 14 causes the air conditioner to drive the flap motors 74A, 74B, and 74C and change the flap angles and so forth, thereby selecting each mode of heating mode, cooling mode, dry mode, automatic operating mode, sleep mode, and so forth and changing the designated temperature, and changing the air supplying amount.

Moreover, the microcomputer 72C is connected to a room temperature sensor 80A, a heat exchanger temperature sensor 80B, and a humidity sensor 80C. The room temperature



sensor 80A detects the room temperature. The heat exchanger temperature sensor 80B detects the temperature of the refrigerant coil of the indoor heat exchanger 16. The humidity sensor 80C detects the humidity of the room. Furthermore, the microcomputer 72C is connected to a self diagnosis LED, an operation selection switch, and a self diagnosis switch that are disposed on the switch board 82. The operation selection switch selects one of the heating mode, the cooling mode, the dry mode, and the automatic operation mode.

Display LEDs corresponding to the "heating mode" , "cooling mode", "dry mode", "automatic operation mode", and "sleep mode" are disposed on the display board 76 and light corresponding to the operation modes.

Fig. 5 shows an electric circuit of the outdoor unit 12. This electric circuit has a rectifier circuit 100 and a control board 102. Terminals (1) to (3) of the electric circuit of the outdoor unit 12 are connected to the electric circuit of the indoor unit 10 shown in Fig. 4.

The control board 102 has a serial circuit 102A, noise filters 102B, 102C, and 120D, a switching power supply circuit 102E, and a microcomputer 102F. The serial circuit 102A is connected to the serial circuit power supply circuit 70D of the indoor unit 10. The noise filters 102B, 102C, and 120D remove noise. The switching power supply



circuit 102E generates a power for switching the inverter 104. The microcomputer 102F functions as a control circuit.

The switching power supply circuit 102E is connected to the inverter 104. The inverter 104 is connected to the compressor 26, which compresses the refrigerant.

The microcomputer 102F is connected to an outer air temperature thermistor 110A, a coil temperature thermistor 110B, and a compressor temperature thermistor 110C. The outer air temperature thermistor 110A is an outer temperature sensor that detects the temperature of the outer air. The coil temperature thermistor 110B is a coil temperature sensor that detects the temperature of the refrigerant coil of the outdoor heat exchanger 28. The compressor temperature thermistor 110C is a temperature sensor that detects the temperature of the compressor 26.

The noise filter 102B is connected to a fan motor 112A and a fan motor condenser 112B. The fan motor 112A supplies air to the outdoor heat exchanger 28. In parallel with the fan motor 112A and the fan motor condenser 112B, the four-way valve 27, which changes the flow direction of the refrigerant supplied from the compressor 26, is connected to the noise filter 102B.

Next, the operation of the embodiment of the present invention will be described. Firstly, the normal operation



will be described.

When the remote controller 14 is operated in the operation stop state and an operation signal is received by the receiving circuit 76A, the code of the received operation signal is analyzed.

It is determined whether or not the analyzed result is a power on command or a timer designating command. In the power off state, some operation signals of for example temperature designating command and air amount designating command are canceled. Thus, when such operation signals are input, they are not accepted and the receiving circuit 7 is kept in the receiving state.

When a timer designating command is detected, the user of the remote controller 14 can designate the timer so that the air conditioner will operate at a predetermined time (for example, two hours later). Thus, the remote controller 14 outputs a corresponding operation signal to the air conditioner and thereby the timer (on time) is designated in the air conditioner. Thus, the air conditioner will automatically operate two hours later.

When a power on command is detected, the air conditioner starts in the designated mode of the last operation.

Thereafter, when an operation signal is received from the remote controller 14, the code of the received



operation signal is analyzed and it is determined whether or not the analyzed result is a power off command, an air amount designating (changing) command, a temperature designating (changing) command, or a timer designating (changing) command. Corresponding to the determined result, an item corresponding to the analyzed result is selected. Thus, the operation of the air conditioner is stopped or the designated operation mode is executed.

When the sleep mode is used, a desired temperature is designated with the temperature designating keys of the remote controller 14 and then the sleep mode switch button is pressed. With this key operation sequence, the remote controller 14 generates an operation signal. When the operation signal is received by the receiving circuit 76A, the operation signal is analyzed and it is determined that the operation signal represents the sleep mode and the designated temperature (desired temperature).

When the desired temperature and the sleep mode are designated, the fan motor 70, the compressor 26, and so forth are controlled so that the air amount and the temperature are changed for a good sleeping environment.

Next, with reference to a flow chart of Fig. 6, the temperature control of the air conditioner according to the embodiment of the present invention will be described.

At step 300, a flag for causing a designated



temperature (desired temperature) shift control to be executed once is initialized. In other words, "0" is stored in a flag register fr.

At step 302, the designated temperature t_0 at present time is stored to the register. At step 304, the room temperature t is detected by the room temperature sensor 80A.

At step 306, the absolute value $|t - t_0|$ of the room temperature and the designated temperature t_0 is obtained. The absolute value $|t - t_0|$ is denoted by Δt and stored in the register.

At step 308, the indoor unit 10 performs a fussy operation corresponding to Δt and the variation of Δt so as to calculate an increase/decrease amount ΔF of a frequency F for controlling the AC motor of the compressor 26.

It can be said that the frequency F for controlling the AC motor represents the operation power of the air conditioner. Thus, hereinafter, the operation power of the air conditioner in the case that the AC motor of the compressor is controlled corresponding to the frequency F is denoted by an operation power F .

At step 310, the increase/decrease amount ΔF of the operation power F calculated by the indoor unit 10 is sent to the outdoor unit 12 through a signal line.

At step 312, the outdoor unit 12 increases or



decreases the operation power F at the time (namely, the frequency F of the AC motor) corresponding to the increase/decrease amount ΔF of the received operation power. The resultant operation power is denoted by F' . In other words, when ΔF is large, the operation power F is increased with a large amplitude. When ΔF is small, the operation power F is decreased with a small amplitude. Thus, the room temperature is effectively approached to the designated temperature. At this point, when an increase signal of the frequency F is received while the compressor 26 is being operated with the maximum power, the maximum power (maximum frequency) F is maintained.

The real operation power F' is compensated by the microcomputer 102F of the outdoor unit 12 corresponding to various factors such as the current consumption of the air conditioner at the present time, the temperature of the compressor 26, and the temperature of outer air. Thus, the real operation power F' is not always changed for ΔF , which is calculated by the indoor unit 10. In addition, the operation power F' tends to converge to an operation power that is balanced with the load of the air conditioner.

At step 314, it is determined whether or not the sleep mode has been selected. When the determined result is NO, the flow advances to step 322. At step 322, "0" is stored in the flag register fr. Thus, even if the sleep mode is



selected after it is cleared, the temperature shift (compensation) control is performed. Thereafter, the flow returns to step 302. At step 302, the above-described process is repeated.

On the other hand, when the determined result at step 314 is YES (namely, the sleep mode has been selected), the flow advances to the next step 316.

At step 316, the operation power F' obtained by the microcomputer 102F of the outdoor unit 12 is sent from the outdoor unit 12 to the indoor unit 10 through a signal line.

At step 318, the microcomputer 72C of the indoor unit 10 compares the received operation power F' with the operation power F stored before a predetermined time and calculates the increase/decrease amount $\Delta F'$ of the real operation power.

When $\Delta F'$ is a large positive value, the load of the air conditioner has been increased (namely, a window or a door has been opened or the room temperature exceeds the designated temperature). Thus, at this point, a large operation power is required. On the other hand, when $\Delta F'$ is a large negative value, the load of the air conditioner has been decreases (namely, the designated temperature has been changed). Thus, the required operation power becomes small. When the absolute value of $\Delta F'$ is small, the



magnitude of the load is balanced with the operation power F (namely, the designated temperature t_0 almost accords with the room temperature t).

At step 320, it is determined whether or not the absolute value $|\Delta F'|$ of $\Delta F'$ is a positive constant T or less. The constant T is designated in the range from 2 Hz to 5 Hz corresponding to the maximum operation power and so forth. When the determined result is NO (namely, $|\Delta F'|$ is larger than T), the flow advances to step 322. At step 322, "0" is stored in the flag register fr . Thereafter, the flow returns to step 302. At step 302, the above-described process is repeated. Thus, even if the sleep mode is selected after it is cleared, the temperature shift control can be executed. When the determined result is YES (namely, $|\Delta F'|$ is T or less), the flow advances to step 324.

At step 324, it is determined whether or not the content of the flag register fr is "1". When the determined result is YES, the flow returns to step 302. At step 302, the above-described process is repeated. When the determined result is NO, the flow advances to the next step 326. At step 326, "1" is stored in the flag register fr . Thus, since the temperature shift control is not executed, the designated temperature is not abnormally changed. It should be noted that for one to two hours



after the start of the air conditioner, the content of the flag register fr is kept to "0" so that the temperature shift control is performed after an elapse of the designated time period.

At step 328, it is determined whether the cooling mode or the heating mode has been selected. When the determined result is the cooling mode, the flow advances to step 330. When the determined result is the heating mode, the flow advances to step 332.

At step 330, the value of the designated temperature t_0 stored in the designated temperature register is read. The value of which 2°C is added to t_0 is stored in the designated temperature register. Thereafter, the flow returns to step 302. At step 302, the temperature control is performed corresponding to the designated temperature increased by 2°C . Of course, since the value of the flag register fr is "1", the designated temperature shift control is not performed. Unless the sleep mode is cleared, the changed designated temperature is maintained. Thus, the room temperature is not abnormally changed.

It should be noted that an automatic temperature restoring function can be provided so that the initially designated temperature is restored when the sleep mode is cleared after the temperature shift control is performed.

At step 332, the value of the designated temperature



t0 stores in the designated temperature resistor is read. The value of which 2 °C is subtracted from t0 is stored in the designated temperature register. Thereafter, the flow returns to step 302. At step 302, the temperature control is performed for the designated temperature decreased by 2 °C. Likewise, while the designated temperature is maintained, the temperature control is performed.

In the embodiment, as the temperature shift amount, 2 °C was used. However, the temperature shift amount should be designated corresponding to a temperature decrease of the user who is sleeping. Thus, the temperature shift amount may be other than 2 °C. Alternatively, the temperature shift amount may be selected by the user. As another alternative method, the temperature shift amount may be a function of the room temperature or a function of the designated temperature, not a constant thereof. As a further other alternative method, the temperature shift amount in the heating mode may be a function that is different from a function of the temperature shift amount in the cooling mode. Thus, the temperature shift amount can be selected corresponding to each application.

Figs. 7 and 8 are graphs showing time changes of the room temperature t in the case that the above-described operation power control is performed.

Fig. 7 is a graph showing a time change of the room



temperature t in the case that the room temperature t is approached to the designated temperature t_0 in the heating mode. In Fig. 7, a solid line 400 is a curve that represents a time change of the room temperature t in the case that the temperature shift control is performed corresponding to the embodiment. A dashed line 402 is a curve that represents a time change of the room temperature t in the case that the conventional temperature shift control is performed.

On the solid line 400, after the start of the operation, the room temperature t increases from the initial room temperature t_s and asymptotically approaches a straight line 404 that represents the designated temperature t_0 . In this case, the variation width $\Delta F'$ of the real operation power gradually decreases. When the solid line 400 reaches a small circle 408, it is determined that $\Delta F'$ is T (for example, 3 Hz) or less. Thereafter, the designated temperature t_0 is shifted to $t_0 - 2^\circ\text{C}$. Thus, the solid line 400 asymptotically approaches a straight line 406. Consequently, the room temperature t is maintained at the designated temperature $t_0 - 2^\circ\text{C}$.

On the dashed line 402, after the start of the operation, the room temperature t increases from the initial room temperature t_s as with the solid line 400. However, when the room temperature t almost accords with



the designated temperature t_0 , the designated temperature is shifted to $t_0 - 2\text{ }^{\circ}\text{C}$. Thus, the dashed line 402 parts from the solid line 400. Thereafter, the dashed line 402 asymptotically approaches the straight line 406. Thus, the room temperature t is maintained at the designated temperature $t_0 - 2\text{ }^{\circ}\text{C}$.

Fig. 8 is a graph showing a time change of the room temperature in the case that the room temperature t is approached to the designated temperature t_0 in the cooling mode. In Fig. 6, a solid line 420 is a curve that represents a time change of the room temperature t in the case that the temperature shift control is performed corresponding to the embodiment. A dashed line 422 is a curve that represents a time change of the room temperature t in the case that the conventional temperature shift control is performed.

On the solid line 420, after the start of the operation, the room temperature t decreases from the initial room temperature t_s . Thereafter, the solid line asymptotically approaches a straight line 424 that represents the designated temperature t_0 . In this case, the variation width $\Delta F'$ of the real operation power gradually decreases. When the solid line 420 reaches a small circle 430, it is determined that $\Delta F'$ is T (for example, 3 Hz) or less. At this point, the frequency for



maintaining the designated temperature is designated.

Thus, the designated temperature is maintained.

Thereafter, since the designated temperature t_0 is shifted to $t_0 + 2^\circ\text{C}$. Thus, the solid line 420 asymptotically approaches a straight line 406. The room temperature t is maintained at the designated temperature $t_0 + 2^\circ\text{C}$.

When the designated temperature shift control is performed twice, the following control is performed. When the room temperature t approaches the shifted designated temperature $t + 2^\circ\text{C}$, the variation width $\Delta F'$ of the operation power decreases. When the solid line 420 reaches a small circle 432, it is determined that $\Delta F'$ is T (for example, 3 Hz) or less once again. Thereafter, the designated temperature $t_0 + 2^\circ\text{C}$ is shifted to $t_0 + 3^\circ\text{C}$ once again. Thus, the control operation for the designated temperature $t_0 + 3^\circ\text{C}$ is performed.

On the dashed line 422, after the start of the operation, the room temperature t decreases from the initial room temperature t_s as with the solid line 420. However, when the room temperature t almost accords with the designated temperature t_0 , the designated temperature is shifted to $t_0 + 2^\circ\text{C}$. Thus, the dashed line 422 parts from the solid line 420 and asymptotically approaches a straight line 426 that represents the designated temperature $t_0 + 2^\circ\text{C}$. Thus, the room temperature t is



maintained at the designated temperature $t_0 + 2\text{ }^{\circ}\text{C}$.

As described above, according to the embodiment, when the variation width $\Delta F'$ of the frequency for controlling the AC motor converges to a predetermined range, it is determined that the power of the air conditioner that is operating approaches the predetermined range of the power for maintaining the designated temperature. Thereafter, the temperature shift control is performed. Thus, even if the body temperature of the user decreases due to sleeping or the like, the air conditioner can provide the user for a comfortable sleeping environment.

Consider that case that the power of the air conditioner converges to an operation power of which the load of the air conditioner is balanced with the operation power at a temperature that is different from the designated temperature (desired temperature) and thereby the operation of the air conditioner becomes stable. The conventional air conditioner performs the temperature shift control corresponding to the difference between the designated temperature and the room temperature, it cannot detect a match of the room temperature and the designated temperature. Thus, the air conditioner may not occasionally change the designated temperature. However, according to the embodiment of the present invention, even if the operation of the air conditioner becomes stable,



since the air conditioner can detect a decrease of the variation width of the operation power, it can determine an occurrence of the stable state of the operation and thereby properly perform the designated temperature shift control.

The present invention is not limited to the above-described embodiment. For example, in the above-described embodiment, as a means for representing the power of the air conditioning, the frequency for controlling the AC motor was used. However, another means can be used as long as it accurately represents the power of the air conditioner. For example, by controlling the voltage applied to a DC motor, the power of the air conditioner (the number of rotations of the DC motor) can be controlled.

In addition, as a means for determining whether or not the power of the air conditioner that is operating approaches a predetermined range necessary for maintaining a designated temperature, another method using other than $\Delta F'$ can be used. For example, a method for estimating a power K_0 for maintaining the predetermined temperature and for comparing K_0 with a present power K of the air conditioner can be used. In other words, any method can be used as long as it is determined whether or not the power of the air conditioner becomes stable at a temperature near the predetermined temperature and whether or not the power



of the air conditioner approaches the predetermined range.

According to the embodiment of the present invention, the temperature shift control was performed in the sleep mode. However, the temperature shift control can be performed in another mode as long as it prevents the designated temperature from becoming improper due to for example a change of the body temperature of the user. In addition, the number of times of the temperature shift control can be three or more, not limited to one and two.

As described above, according to the air conditioner of the present invention, when the sleep mode or the like is selected, the variation of the rotations for controlling the motor of the compressor is detected. When the variation converges to the predetermined range, the designated (desired temperature) is shifted (compensated) to the predetermined temperature. Thus, the air conditioner of the present invention can provide a user for a comfortable sleeping temperature environment although the body temperature of the user decreases. In addition, even if the load of the air conditioner is balanced with the operation power at a temperature that is different from the designated temperature and thereby the operation becomes stable, since the stable state can be determined, the same effect can be accomplished. Moreover, since the temperature shift control is occasionally performed before

the room temperature reaches the designated temperature, the present invention contributes to energy saving.

Although the present invention has been shown and described with respect to a best mode embodiment thereof, it should be understood by those skilled in the art that the foregoing and various other changes, omissions, and additions in the form and detail thereof may be made therein without departing from the spirit and scope of the present invention.



What is claimed is:

1. An air conditioner for varying an air conditioning power and for approaching a room temperature to a designated temperature, comprising:

determining means for determining whether or not the conditioning power that is operating approaches a predetermined range of the air conditioning power required for maintaining the desired temperature and for outputting a corresponding signal; and

compensating means for compensating the desired temperature corresponding to the signal that is output from said determining means.

2. The air conditioner as set forth in claim 1, further comprising:

a switch,

wherein said compensating means functions when said switch is enable.

3. The air conditioner as set forth in claim 2, wherein said compensating means is adapted for compensably decreasing the desired temperature when the operation of said air conditioner is in a mode for heating the room.

4. The air conditioner as set forth in claim 2, wherein said compensating means is adapted for compensably increasing the desired temperature when the





operation of said air conditioner is in a mode for cooling the room.

5. The air conditioner as set forth in claim 2, wherein said compensating means is adapted for compensably decreasing the desired temperature when the operation of said air conditioner is in a mode for heating the room, and

wherein said compensating means is adapted for compensably increasing the desired temperature when the operation of said air conditioner is in a mode for cooling the room.

6. The air conditioner as set forth in claim 5, wherein said compensating means is adapted for compensating the desired temperature corresponding to a change of the body temperature of a user who is sleeping in the room.

7. The air conditioner as set forth in claim 6, wherein said compensating means is adapted for compensating the desired temperature a plurality of times.

8. An air conditioner for air conditioning a room with a refrigerating cycle using a compressor, a condenser, an expansion device, and an evaporator, comprising:

a room temperature designating device for designating a desired temperature of the room;

a control mechanism for controlling the power of the





compressor corresponding to the difference between the desired temperature designated by said designating device and the temperature of the room;

determining means for determining whether or not the power controlled by said control mechanism approaches a predetermined range of the power necessary for maintaining the desired temperature and for outputting a corresponding signal; and

compensating means for compensating the desired temperature corresponding to the signal that is output from said determining means.

9. The air conditioner as set forth in claim 8, further comprising:

a switch,

wherein said compensating means functions when said switch is enable.

10. The air conditioner as set forth in claim 9, wherein said compensating means is adapted for compensably decreasing the desired temperature when the operation of said air conditioner is in a mode for heating the room.

11. The air conditioner as set forth in claim 9, wherein said compensating means is adapted for compensably increasing the desired temperature when the operation of said air conditioner is in a mode for cooling





the room.

12. The air conditioner as set forth in claim 9,
wherein said compensating means is adapted for
compensably decreasing the desired temperature when the
operation of said air conditioner is in a mode for heating
the room, and

wherein said compensating means is adapted for
compensably increasing the desired temperature when the
operation of said air conditioner is in a mode for cooling
the room.

13. The air conditioner as set forth in claim 12,
wherein said compensating means is adapted for
compensating the desired temperature corresponding to a
change of the body temperature of a user who is sleeping in
the room.

14. The air conditioner as set forth in claim 13,
wherein said compensating means is adapted for
compensating the desired temperature a plurality of times.

