

RIMP
copy

DESCRIPTION

RADIANT-ENERGY CLINICAL THERMOMETER

Technical Field

This invention relates to a radiant-energy clinical
5 thermometer for measuring body temperature by measuring
the amount of energy radiated from the human body,
especially radiant energy (heat rays) in the infrared
region. More particularly, the invention relates to a
radiant-energy clinical thermometer suitable for sensing
10 heat rays from the external ear of the human body.

Background Art

A radiant-energy clinical thermometer is equipped
with a probe projecting outwardly from a portion of a
case body. The tip of the probe is open and a radiant-
15 temperature sensor (a thermopile, for example) is
provided within the opened tip. When the tip of the
probe is inserted slightly into the orifice of the ear,
heat rays emitted from the external ear impinge upon the
radiant-temperature sensor. The temperature sensor is
20 connected to a temperature measuring circuit provided
within the case body. The measuring circuit determines
the body temperature based upon the output of the
temperature sensor. The radiant-energy clinical
thermometer is capable of measuring body temperature in
25 a short period of time in a basically contactless manner
(the temperature sensor at least does not contact the
human body).

The radiant-energy clinical thermometer has a

measurement starting switch, which is provided on the case body. The switch is operated manually. Closing the measurement starting switch starts the operation of the temperature measuring circuit.

- 5 The timing at which the measurement starting switch is closed differs from one operation to the next depending upon the operator. There are individuals who close the switch immediately upon inserting the tip of the probe into the ear orifice, and there are
- 10 individuals who operate the switch upon passage of a short period of time following insertion of the probe.

- The radiant-temperature sensor is readily influenced by a slight change in the state of the external ear, and the measured temperature fluctuates
- 15 with the passage of time upon insertion of the probe into the ear orifice. Accordingly, measuring body temperature under identical conditions at all times is desirable.

- When the timing at which the measurement starting
- 20 switch is operated differs depending upon the individual and depending upon time as mentioned above, a variance appears in the value of measured body temperature. Measures for making the measurement starting time the same on all occasions are desired.

- 25 An object of the present invention is to provide a radiant-energy clinical thermometer in which the timing for starting measurement of body temperature is capable of being fixed at all times.



Disclosure of the Invention

A radiant-energy clinical thermometer according to the present invention comprises a support member having a portion projecting outwardly from a case body, a
5 radiant-temperature sensor attached to a tip of the outwardly projecting portion of the support member, a cylindrical probe held by the support member in a freely extendible and retractable manner and having an open tip, a biasing mechanism for biasing the cylindrical
10 probe outwardly and holding the tip of the cylindrical probe at a position at which it covers the periphery of the temperature sensor, and switch means for sensing that the cylindrical probe has been retracted against a
15 biasing force of the biasing mechanism and generating a trigger signal that starts measurement of body temperature.

When the radiant-energy clinical thermometer is not used, the cylindrical probe is in the outwardly extended state so that the periphery of the radiant-temperature
20 sensor attached to the tip of the support member is covered by the cylindrical probe. As a result, the temperature sensor is protected.

When the cylindrical probe is inserted into the orifice of the ear in order to measure body temperature,
25 the cylindrical probe is retracted against the biasing force of the biasing mechanism. The radiant-temperature sensor is situated near the opening in the tip of the retracted cylindrical probe. The fact that the

cylindrical probe has been retracted is sensed by the switch means, which proceeds to generate the trigger signal for starting the measurement of body temperature.

As a result, a body-temperature measuring circuit

5 provided within the case body starts operating and determines the body temperature based upon the output of the temperature sensor. The body temperature determined is displayed on a display device provided on the case body.

10 Thus, when the cylindrical probe is inserted into or contacted with the part of the body measured, such as the orifice of the ear, the switch means automatically generates the trigger signal at this time to start the measurement of body temperature. Accordingly, the
15 conditions of body-temperature measurement are regularized at all times irrespective of the individual and irrespective of time. As a consequence, the occurrence of a variance in measured values and the occurrence of errors may be prevented in advance.

20 When the cylindrical probe is separated from the part being measured, it is extended outwardly by the biasing force of the biasing mechanism so as to return to the state in which the temperature sensor is protected. The switch means opens to conclude
25 measurement.

Preferably, a cover conforming to the human ear is attached to the tip portion of the cylindrical probe in a detachable manner.

By attaching the cover to the tip portion of the cylindrical probe, it is possible to prevent external wounds that are easily produced when the tip of the cylindrical probe is inserted into the ear orifice. By
5 changing the cover for each individual measured, the transmission of disease can be prevented even when the radiant-energy clinical thermometer is shared.

Covers having a variety of sizes and shapes are prepared in advance in conformity with sizes and shapes
10 of ear orifices.

In an embodiment of the present invention, a locking mechanism is further provided for preventing the cylindrical probe from retracting from the position at which it covers the periphery of the temperature sensor.
15 Preferably, the locking mechanism includes a locking lever operated from outside the case body.

When the radiant-energy clinical thermometer is not used, the cylindrical probe is retained in the projected state by the locking mechanism, thereby protecting the
20 temperature sensor at all times and making it possible to prevent a situation in which measured in started by inadvertent closure of the switch means. This is very useful when the radiant-energy clinical thermometer is transported or handled in a disorderly manner.

25 When the cover is removably attached to the cylindrical probe, and particularly when it is fitted on the probe, movement of the cylindrical probe is inhibited. As a result, it is easy to attach and detach

the cover and prevent the switch from being closed.

In another embodiment of the present invention, a mechanism is further provided for pushing out the cover along the cylindrical probe in order to detach the cover
5 attached to the tip of the cylindrical probe in a freely detachable manner. Preferably, the pushing mechanism includes a slider operated from outside the case body.

It is so arranged that the cover attached to the tip of the cylindrical probe is capable of being easily
10 detached by the pushing mechanism.

Brief Description of the Drawings

The drawings illustrate an embodiment of the present invention, in which:

Fig. 1 is a longitudinal sectional view
15 illustrating the entirety of a radiant-energy clinical thermometer;

Fig. 2 is an enlarged longitudinal sectional view of a portion of the radiant-energy clinical thermometer and illustrates the thermometer when not in use;

20 Fig. 3 is an enlarged longitudinal sectional view of a portion of the radiant-energy clinical thermometer and illustrates the thermometer when in use;

Fig. 4 is an enlarged transverse sectional view of a portion of the radiant-energy clinical thermometer and
25 illustrates the thermometer when not in use;

Fig. 5 is an enlarged transverse sectional view of a portion of the radiant-energy clinical thermometer and illustrates the thermometer when in use; and

Fig. 6 is an enlarged transverse sectional view of a portion of the radiant-energy clinical thermometer and illustrates a cover of the thermometer in the detached state.

5 Best Mode for Carrying Out the Invention

Fig. 1 illustrates the overall configuration of a radiant-energy clinical thermometer.

A case body 1 extends downwardly at an incline so as to be easily grasped by the hand. A body-temperature
10 measuring circuit (not shown) is incorporated within the case body 1. A display unit, such as a liquid-crystal display unit 15, for displaying a measured temperature is attached to one side of the case body 1 so that the temperature displayed on the display unit 15 can be
15 observed from the outside.

The upper portion of the case body 1 is integrally formed to include a supporting frame 11 to which a supporting cylinder 2 is secured horizontally. A portion of the supporting cylinder 2 projects outwardly
20 from the supporting frame 11.

A radiant-temperature sensor 3 is secured to the distal end face of the supporting cylinder 2. The radiant-temperature sensor 3 is constituted by a thermopile, for example, and is connected to the body-
25 temperature measuring circuit through lead wires disposed within the supporting cylinder 2.

A cylindrical probe 4 is fitted over the supporting cylinder 2 and is free to slide in the longitudinal

direction thereof. A switch, such as a microswitch 5, is secured to the supporting frame 11.

The foregoing will be described in greater detail with reference to Figs. 2 and 3.

5 The base portion of the cylindrical probe 4 is formed to have a comparatively large inner diameter, and a gap is provided between inner peripheral surface of the cylindrical probe 4 and the outer peripheral surface of the supporting cylinder 2. A coil spring 42 is
10 disposed within the gap. One end of the coil spring 42 abuts against the supporting frame 11, and the other end of the spring abuts against the inner wall surface of the cylindrical probe 4. The cylindrical probe 4 is biased by the coil spring 42 in a direction that thrusts
15 the distal end of the probe outwardly.

 The base end of the cylindrical probe 4 is formed to have a flange 41. The supporting frame 11 is formed to have a stopper 12 that engages with the flange 41. The extended position of the cylindrical probe 4 biased
20 outwardly by the coil spring 42 is decided by the flange 41 coming into contact with the stopper 12. When the cylindrical probe 4 is in the extended position, as shown in Fig. 2, its tip projects outwardly from the supporting cylinder 2 and the temperature sensor 3
25 secured to the tip of the supporting cylinder 2 assumes a state in which the periphery thereof is completely covered by the cylindrical probe 4. The tip of the cylindrical probe 4 is open.

Part of the supporting frame 11 is cut away and a lever 51 of the microswitch 5 secured to the supporting frame 11 penetrates into the interior of the supporting frame 11 from the portion that has been cut away. When
5 the cylindrical probe 4 is in the extended position, the base end of the cylindrical probe 4 is not in contact with the lever 51. The switch 5 is held in the off state at this time.

When the cylindrical probe 4 is caused to retract against the biasing force of the spring 42 by an externally
10 applied force, as shown in Fig. 3, the lever 51 of the switch 5 is pushed by the flange 41 so that the switch 5 is closed. An ON signal from the switch 5 is applied to the temperature measuring circuit as the trigger signal for starting measurement. The retracted position of the
15 cylindrical probe 4 is decided by the flange 41 coming into contact with a portion of the supporting frame 11. In this embodiment, the periphery of the temperature sensor 3 is substantially protected by the tip portion of the cylindrical probe 4 even when the cylindrical probe
20 4 is in the retracted position.

The outer peripheral surface of the tip of cylindrical probe 4 is formed so that the probe becomes incrementally more slender toward the tip. An annular groove is formed in the outer peripheral surface of the tip portion.

25 A cover 9 is attached to the tip of the cylindrical probe 4 in a freely detachable manner. The cover 9 is formed from a material that is as flexible as possible, and so as to free of corners, so that the orifice of an

ear will not be hurt when the tip of the cylindrical probe 4 is inserted slightly into the ear orifice in order to measure body temperature. An annular projection formed on the inner peripheral surface of the cover 9 fits into the annular groove formed in the tip of the cylindrical probe 4.

The cover 9 is prepared beforehand in a number of types having different sizes and shapes in conformity with sizes and shapes of ear orifices. Preferably, the cover 9 is changed for each individual whose body temperature is to be measured, and a cover suited to the individual is used. This is useful also in preventing the transmission of disease.

A cover pushing member 7 is fitted onto the periphery of the cylindrical probe 4 so as to be free to move in the longitudinal direction thereof. A slider 71 for being pushed by a finger is integrally formed on the pushing member 7. A coil spring 72 is provided between a portion of the case body 1 and a portion of the pushing member 7 to bias the pushing member 7 at its retracted position. The retracted position of the pushing member 7 is decided by a portion of the pushing member 7 coming into contact with a portion of the case body 1. By pushing the slider 71 against the biasing force of the spring 72, the pushing member 7 is moved along the outer periphery of the cylindrical probe 4 to remove the cover 9 that has been attached to tip of the cylindrical probe 4.

As shown in Figs. 4 through 6, a locking lever 6 is mounted at its midpoint to the case body 1 by means of a shaft 63 so as to be free to rock back and forth.

As illustrated in Fig. 4, the locking lever 6 is
5 biased by a spring (not shown) in such a manner that an operating portion 61 thereof projects slightly from the case body 1 while an acting portion 62 of the lever penetrates into the interior of the supporting case 11. In this state the tip of the acting portion 62 of
10 locking lever 6 is in abutting contact with the flange 41 of the cylindrical probe 4 so that the cylindrical probe 4 is locked in the extended position. In other words, even if the tip of the cylindrical probe 4 is pressed in an effort to cause its retraction, the flange
15 41 abuts against the acting portion 62 so that the cylindrical probe 4 will not move.

When the operating portion 61 of the locking lever 6 is pressed into the case body 1 by a finger or the like, as shown in Fig. 5, the acting portion 62 is moved
20 outward so that it is disengaged from the flange 41 of the cylindrical probe 4. In this state, the cylindrical probe 4 is capable of being retracted by an external force against the biasing force of the spring 42.

When the radiant-energy clinical thermometer having
25 this construction is not being used, the cylindrical probe 4 is outwardly extended by the biasing force of the spring 42, as illustrated in Figs. 2 and 4. The acting portion 62 of the locking lever 6 engages the

flange 41 so that the cylindrical probe 4 is held in the extended position. As a result, the cylindrical probe 4 will not retract, and the switch 5 will not close, when the thermometer is carried about or even if the thermometer is handled carelessly. Since the cylindrical probe 4 is in the extended position, the temperature sensor 3 attached to the distal end face of the supporting cylinder 2 is protected by the cylindrical probe 4 so that there is almost no danger of contamination or of adverse thermal effects. Since the flange 41 of the cylindrical probe 4 is spaced away from the lever 51 of the switch 5, the switch 5 is held in the off state.

In order to measure body temperature, the operating portion 61 of the locking lever 6 is pressed. Since the acting portion 62 moves in the outward direction, its locking action is eliminated so that the cylindrical probe 4 attains a state in which it is capable of being extended or retracted. With the operating portion 61 of the locking lever 6 being held in the pressed state, the tip of the cylindrical probe 4 to which the cover 9 has been attached is inserted slightly into the orifice of an ear and is pressed gently toward the orifice, whereupon the cylindrical probe 4 is retracted against the biasing force of the spring 42, as illustrated in Fig. 3. As a result, the temperature sensor 3 is situated in the proximity of the opening in the tip of the cylindrical probe 4, and a state is attained in

which thermal radiation from the external ear is capable of being sensed. Further, since the flange 41 of the retracted cylindrical probe 4 presses the lever 51 of the switch 5, the switch 5 is closed. The trigger
5 signal generated by the switch 5 is applied to the body-temperature measuring circuit to start the operation for measuring body temperature. The temperature sensor 3 accurately senses the heat rays emitted from within the orifice of the ear, and the body temperature is decided
10 by the body-temperature measuring circuit based upon the output of the temperature sensor 3. The body temperature determined is displayed on the display unit 15.

Thus, by causing the cylindrical probe to retract
15 by pressing it against the body part whose body temperature is to be measured, the switch 5 is closed to automatically start the measurement of body temperature. As a result, a situation in which the timing at which body temperature is measured differs from person to
20 person and from one time to another is avoided, thus making it possible to measure body temperature under identical conditions at all times.

When measurement of body temperature is concluded, the cylindrical probe 4 need only be separated from the
25 orifice of the ear. The cylindrical probe 4 is extended and returns to its original position owing to the force of the spring 42. When the operating portion 61 of the lever 6 is released, the lever 6 also returns to its

original position so that the cylindrical probe 4 is locked.

The cover 9 attached to the tip of the cylindrical probe 4 is capable of being freely attached and detached. Accordingly, the cover best suited to the person undergoing temperature measurement may be selected and attached to the cylindrical probe 4. In order to remove the cover 9 from the cylindrical probe 4, the slider 71 need only be pressed to push off the cover 9 by the pushing member 7. When the optimum cover 9 is attached to the cylindrical probe 4, the cylindrical probe 4 will not move, even if it is pushed, since the acting portion 62 of the locking lever 6 is in abutting contact with the flange 41, as mentioned above. Thus the cover 9 may be attached in a reliable manner and the switch 5 will not be closed inadvertently at this time.

Though the microswitch 5 is illustrated in the foregoing embodiment, it goes without saying that a switch such as a proximity switch or photoelectric switch can also be used.

Industrial Applicability

The present invention relates to improvements in a radiant-energy clinical thermometer, which is a clinical thermometer of a new type. Clinical thermometers fall within the purview of the medical-instruments industry and are utilized in this field.

WHAT IS CLAIMED IS:

1. A radiant-energy clinical thermometer comprising:
a support member having a portion projecting
outwardly from a case body;
5 a radiant-temperature sensor attached to a tip of
the outwardly projecting portion of said support member;
a cylindrical probe held by said support member in
a freely extendible and retractable manner and having an
open tip;
10 a biasing mechanism for biasing said cylindrical
probe outwardly and holding the tip of said cylindrical
probe at a position at which it covers the periphery of
said temperature sensor; and
switch means for sensing that said cylindrical
15 probe has been retracted against a biasing force of said
biasing mechanism and generating a trigger signal that
starts measurement of body temperature.
2. A radiant-energy clinical thermometer according to
claim 1, further comprising a locking mechanism for
20 preventing said cylindrical probe from retracting from
the position at which it covers the periphery of said
temperature sensor.
3. A radiant-energy clinical thermometer according to
claim 2, wherein said locking mechanism includes a
25 locking lever operated from outside the case body.
4. A radiant-energy clinical thermometer according to
claim 1, wherein a cover suited to the ear of a human
being is capable of being attached to the tip of said



cylindrical probe.

5. A radiant-energy clinical thermometer according to claim 1, further comprising a mechanism for pushing out said cover along said cylindrical probe in order to
- 5 detach the cover attached to the tip of said cylindrical probe in a freely detachable manner.

6. A radiant-energy clinical thermometer according to claim 5, wherein said pushing mechanism includes a slider operated from outside the case body.

