SYSTEM FOR EARLY DETECTION OF DECODING ERRORS

Field

Claim of Priority under 35 U.S.C. §119

[0001] The present Application for Patent claims priority to Provisional Application No. 60/721,824 entitled "METHOD FOR EARLY DETECTION OF DECODE FAILURES" filed September 28, 2005, and assigned to the assignee hereof and hereby expressly incorporated by reference herein.

Background

[0002] The present Application for Patent relates generally to communication systems, and more particularly, to a system for early detection of decoding errors for use in a communication system.

[0003] In typical wireless delivery systems, content is delivered to portable devices over a multicast transmission channel. The content is in the form of data packets that are coded to overcome packet loss that may occur as packets are transmitted over the transmission channel. An encoder at a transmitter takes the original data packets and produces code packets that are transmitted to one or more devices. Because of noise or other degrading transmission effects, a subset of the code packets is received at any particular device. The received code packets are decoded to recover the original data packets.

[0004] The success of the decoding process depends on the number of received code packets. In general, if the number of data packets is "k", the number of received code packets should be at least $k(1 + \varepsilon)$ where epsilon (ε) is a communication overhead factor, (e.g., 10% of k). Choosing a higher value of ε lowers the probability of decoding failure, but may increase decoding time and/or battery consumption at the device.

[0005] Conventional systems typically fix the value of ε to achieve selected decoding performance assuming a worst case transmission environment. However, it is generally uncommon for the transmission channel to perform according to the worst case assumptions. As a result, many unnecessary packets are received by a receiving device. For example, assuming the worst case transmission environment results in fixing the value of ε to be very large. This causes many additional and unnecessary

packets to be received for the purpose of decoding the data. This places a large burden on the resources of the receiving device because it requires additional power, CPU time, memory, and file system resources to receive and process the unnecessary packets.

[0006] Therefore, it would be desirable to have a system that operates to adjust the number of received packets based on the quality of the transmission channel to obtain selected decoder performance. The system should also operate to perform early error detection so that the number of received packets can be adjusted to produce selected decoder performance without having to wait for the results of the decoding process.

SUMMARY

[0007] In one or more embodiments, a decoding system is provided that operates to adjust the number of received packets based on the quality of the transmission channel to obtain selected decoder performance. In one embodiment, the system adjusts the number of received packets based on one or more trigger events. For example, one trigger event is associated with the failure of the decoding process. One or more other trigger events are associated with the early detection of errors so that the number of received packets can be adjusted to achieve selected decoder performance without having to wait for the results of the decoding process. The system is especially suited for use in wireless communication systems to allow data to be received/recovered by a portable device while minimizing the impact on device resources such as power consumption, memory, CPU time, and files accesses, etc.

[0008] In one embodiment, a method is provided for detecting a decode failure. The method comprises receiving an initial amount of code packets, detecting a trigger event that indicates a decode failure associated with the initial amount of code packets, and receiving one or more additional code packets.

[0009] In one embodiment, apparatus is provided for detecting a decode failure. The apparatus comprises receiving logic configured to receive an initial amount of code packets, and to receive one or more additional code packets when a trigger event is detected, and processing logic configured to detect the trigger event, wherein the trigger event indicates a decode failure associated with the initial amount of code packets.

[0010] In one embodiment, apparatus is provided for detecting a decode failure. The apparatus comprises means for receiving an initial amount of code packets, means

for detecting a trigger event that indicates a decode failure associated with the initial amount of code packets, and means for receiving one or more additional code packets.

[0011] In one embodiment, a computer-readable media is provided that comprises instructions, which when executed by at least one processor, operate to detect a decode failure. The computer-readable media comprises instructions for receiving an initial amount of code packets, instructions for detecting a trigger event that indicates a decode failure associated with the initial amount of code packets, and instructions for receiving one or more additional code packets.

[0012] In one embodiment, at least one processor is provided that is configured to perform a method for detecting a decode failure. The method comprises receiving an initial amount of code packets, detecting a trigger event that indicates a decode failure associated with the initial amount of code packets, and receiving one or more additional code packets.

[0013] Other aspects of the embodiments will become apparent after review of the hereinafter set forth Brief Description of the Drawings, Detailed Description, and the Claims.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The foregoing aspects of the embodiments described herein will become more readily apparent by reference to the following detailed description when taken in conjunction with the accompanying drawings wherein:

[0015] **FIG. 1** shows a communication path that comprises one embodiment of a decoding system;

[0016] **FIG. 2** shows a graph that illustrates a relationship between decoding failure probability and epsilon;

[0017] **FIG. 3** shows one embodiment of a decoder for use in embodiments of a decoding system;

[0018] **FIG. 4** shows one embodiment of a tree structure for use in embodiments of a decoding system;

[0019] **FIG. 5** shows one embodiment of a method for use in embodiments of a decoding system; and

[0020] **FIG. 6** shows one embodiment of a decoder for use in embodiments of a decoding system.

DESCRIPTION

[0021] The following description describes one or more embodiments of a decoding system. The decoding system operates to adjust the number of received packets based on the quality of a transmission channel to obtain selected decoder performance. The system is especially well suited for use in portable devices having limited resources, but may be used with any type of device. The system may also be used in devices operating in any type of network environment, including but not limited to, communication networks, public networks, such as the Internet, private networks, such as virtual private networks (VPN), local area networks, wide area networks, long haul networks, or any other type of data or communication network.

[0022] **FIG. 1** shows a communication path **100** that comprises one embodiment of a decoding system. For example, the communication path **100** may be used to deliver content to one or more portable devices. The communication path **100** comprises an encoder **102**, a transmission channel **104** and a decoder **106**.

[0023] In one embodiment, the encoder **102** performs message coding on data packets to be transmitted over the transmission channel **104**. The message coding is performed because the transmission channel **104** may be a lossy channel (or erasure channel) that causes transmitted packets to be lost. The message coding provides redundancy that allows lost data packets to be recovered. In one embodiment, message coding is performed using an encoding technology referred to as Low Density Generator Matrix (LDGM) technology. However, other types of message coding may be utilized in other embodiments.

[0024] In one embodiment, the encoder **102** receives data packets D (shown at **108**) and encodes them to produce code packets C. The code packets C comprise two types of packets. The first type of code packet comprises a packet header and data from a selected data packet. The second type of code packet comprises a packet header and data from one or more data packets that have been combined using any known combination algorithm, such as an exclusive "OR" algorithm. The packet header for the second type of code packet identifies which data packets have been combined and the type of combining algorithm used.

[0025] The code packets C are transmitted over the transmission channel **104** to one or more receiving devices. For example, the transmission of the code packets occurs

during a contact window having a selected duration. A subset of the code packets C' is received by a decoder **106** located at one of the receiving devices. The decoder **106** operates to process the received code packets C' to recover the original data packets D (shown at **110**).

[0026] The decoding process depends on the number of received code packets C'. In general, if the number of data packets D transmitted is equal to "k", the number of received code packets (C') should be at least $k(1 + \varepsilon)$. Choosing a higher value of ε lowers the probability of decoding failure, but may result in unnecessary packets being received and increased decoding time and/or power consumption at the decoder **106**.

[0027] In one embodiment, the decoding system operates to adjust the number of received code packets C' based on one or more trigger events. During operation, the decoder **106** is initialized with an initial minimum value for ε. The decoder then attempts to receive $k(1 + \varepsilon)$ code packets during a contact window in which a broadcast occurs. During or after the reception of the code packets one or more trigger events may occur. For example, trigger events may occur if the quality of the transmission channel is very poor. If a trigger event occurs, the system increases the number of code packets C' it receives to decode the data. Thus, the system operates to adjust the number of received code packets C' based on the quality of the transmission channel. A detailed description of the various trigger events is provided in another section of this document.

[0028] In one embodiment, the decoder **106** receives $k(1 + \varepsilon)$ code packets. The code packets are then decoded to recover the original data D. A decode error trigger event occurs if the decode process fails. For example, the decoding process may fail because too many code packets were lost in transmission as a result of the poor quality of the transmission environment. In this case, the value of ε is increased and the decoder **106** operates to receive more code packets during the contact window. As a result, the decoding system adjusts the decoder **106** to receive enough code packets C' to obtain selected decoding performance. This provides very efficient operation of the decoder **106** because a small initial value for ε may be used. If the transmission channel provides adequate performance, it is not necessary to increase ε so that large numbers of unnecessary code packets C' need not be received. Thus, the decoding system operates to conserves devices resources, such as power consumption, CPU processing time, memory, and file accesses, etc.

[0029] In one embodiment, the decoding system operates to perform one or more of the following functions.

1. Set an initial value for ε.
2. Receive a selected amount of code packets C' as determined by ε.
3. Decode the received code packets C'.
4. Determine if a decode error trigger event has occurred.
4. If a decode error trigger has occurred, increase the value of ε and receive additional code packets C'.
5. Decode the data from all received code packets C'.

[0030] In another embodiment, the decoder **106** attempts to receive $k(1 + \varepsilon)$ code packets during a contact window in which a broadcast occurs. As code packets C' are received, information about the amount of correctly received code packets is maintained. The information is stored at the decoder **106** and used to determine one or more trigger events that indicate how successful code packets are being received. For example, in one embodiment, the information is used to determine a receive ratio that indicates how many good packets are received as compared to the total number of packets. In one embodiment, this information is maintained in a tree structure that requires a selected amount of memory to maintain. A first type of early error detection trigger event is determined if the receive ratio falls below a selected threshold. Another type of early error detection error trigger event is determined if the memory required for the tree structure exceeds a selected threshold. When an early error detection trigger events occur, the value of ε is increased such that all remaining code packets in the contact window are received by the decoder. The decoder then processes all the received code packets to recover the original data.

[0031] In one embodiment, the decoding system operates to perform one or more of the following functions.

1. Set an initial value for ε.
2. Begin receiving code packets C'.
3. Determine if an early error detection trigger event has occurred.
4. If an early error detection trigger event has occurred, increase ε to receive all code packets C' remaining in the contact window.
5. Decode the data from the all the received code packets C'.

[0032] Thus, the decoding system operates to efficiently adjust the number of receive code packets based on the quality of the transmission channel. As a result, decoding system operates to minimize the number of unnecessary code packets received when the transmission channel is providing selected performance.

[0033] **FIG. 2** shows a graph **200** that illustrates "decoding failure probability" versus ε. As the graph **200** illustrates, the probability of decode failure is around 0.01 for a value of ε of approximately 0.2. The probability of decode failure is reduced to around 10^{-6} for a value of ε of approximately 0.5. In one or more embodiments of a decoding system, small initial values of ε may be used to achieve the same or better decoding performance as that of conventional systems using larger values of ε. As a result, fewer unnecessary code packets are received and therefore less resources of the decoding device are required.

[0034] **FIG. 3** shows one embodiment of a decoder **300** for use in embodiments of a decoding system. For example, the decoder **300** is suitable for use as the decoder **106** shown in **FIG. 1**. The decoder **300** comprises processing logic **302** and transceiver logic **304** that are coupled to an internal data bus **306**. The decoder **300** also comprises data storage **308**, code storage **310** and LDGM logic **312**, which are also coupled to the data bus **306**.

[0035] In one or more embodiments, the processing logic **302** comprises a CPU, processor, gate array, hardware logic, memory elements, virtual machine, software, and/or any combination of hardware and software. Thus, the processing logic **202** generally comprises logic to execute machine-readable instructions and to control or communicate with one or more other functional elements of the decoder **300** via the internal data bus **306**.

[0036] The transceiver logic **304** comprises hardware logic and/or software that operate to allow the decoder **300** to transmit and receive data and/or other information with remote devices or systems using communication channel **314**. For example, in one embodiment, the communication channel **314** comprises any suitable type of communication channel **314** to allow the decoder **300** to communicate with a data network. For example, in one embodiment, the transceiver logic **304** operates to receive code packets from a remote server through the communication channel **314**. The decoder **300** then operates to process the received code packets to recover the original data that was transmitted from the remote server.

[0037] The data storage **308** comprises any suitable memory device operable to store data. For example, the data storage **308** may comprise RAM, Flash memory, EEPROM, hard disk, and/or any other type of storage device. In one embodiment, the data storage **308** operates to store data that is decoded from code packets received by the transceiver logic **304**.

[0038] The code storage **310** comprises any suitable memory device operable to store code packet information. For example, the code storage **308** may comprise RAM, Flash memory, EEPROM, hard disk, and/or any other type of storage device. In one embodiment, the code storage **310** operates to store code information that is included in code packets received by the transceiver logic **304**. For example, in one embodiment, the code information comprises information associated with the second type of code packet as described above.

[0039] The LDGM logic **312** comprises a CPU, processor, gate array, hardware logic, memory elements, virtual machine, software, and/or any combination of hardware and software. Thus, the LDGM logic **202** generally comprises logic to execute machine-readable instructions and to control or communicate with one or more other functional elements of the decoder **300** via the internal data bus **306**.

[0040] In one embodiment, the processing logic **302** comprises rate logic **316** which operates to determine a ratio for received code packets. For example, the ratio describes the number of good code packets received as compared to the total code packets. Thus, if one hundred code packets are transmitted and only ninety code packets are successfully received, the rate logic **316** determines the ratio to be **90/100** or **90%**. If the ratio falls below a selected rate threshold, then the rate logic **316** generates a first type of early error detection trigger event **318**. In one embodiment, the rate threshold is transmitted to the rate logic **316** from a remote server, and in another embodiment, the rate threshold is pre-stored in the rate logic **316** during device manufacture.

[0041] In one embodiment, the LDGM logic **312** comprises tree logic **320** configured to process received code packets to generate a tree structure or database that describes the relationships between received/recovered code packets. In one embodiment, the generated tree structure is stored in a memory at the LDGM logic **312**. A more detailed description of the tree structure is provided in another section of this document. In one embodiment, the tree logic **320** operates to generate a second type of early error detection trigger event **322** when the memory required for the tree structure

exceeds a selected memory threshold. In one embodiment, the memory threshold is transmitted to the tree logic **320** from a remote server, and in another embodiment, the rate threshold is pre-stored in the tree logic **320** during device manufacture.

[0042] In one embodiment, the processing logic **302** comprises decoder logic **324** which operates to decode received code packets to detect decode failures. For example, the decoder **300** receives $k(1 + \varepsilon)$ code packets through the transceiver logic **304** and decodes those packets to determine the original data. If any selectable type or amount of decode errors are detected, the decode logic **324** operates to output a decode error trigger event **326**, which indicates that a decode error has occurred.

[0043] During operation of one or more embodiments, an initial value for ε is downloaded from a remote server through the transceiver logic **304**. In another embodiment, the initial value of ε is pre-stored at the decoder during manufacture.

[0044] In one embodiment, the decoder **300** operates to adjust the number of received code packets as a result of a decode error trigger event by performing one or more of the following functions.

1. An initial value of ε is set.
2. A total of $k(1 + \varepsilon)$ code packets are received and stored in the code storage **310** and the data storage **308**.
3. The received code packets are decoded by the decoding logic **324**.
4. A decode error trigger event **326** is generated if there is a decoder failure based on any pre-selected decode criteria.
5. The processing logic **302** detects the decode error trigger event **326** and increments the value of ε.
6. The increased value of ε is used by the transceiver logic **304** to collect additional code packets.
7. The decode logic **324** then decodes the data from all received code packets.
8. For the next data session, the value of ε is reset to its initial value.

[0045] In one embodiment, the decoder **300** operates to adjust the number of received code packets as a result of an early error detection trigger event by performing one or more of the following functions.

1. An initial value of ε is set.
2. Code packets are received
3. The tree logic **320** operates to construct a tree of the received code packets.

4. If the ratio of received to transmitted code packets falls below a selected rate threshold an early error detection trigger event is generated by the rate logic **316**.

5. If the amount of memory required for the tree structure exceeds a selected memory threshold an early error detection trigger event is generated by the tree logic **320**.

6. If an early error detection event is generated, the value of ε is increased to allow some or all additional code packets transmitted in the contact window to be received.

7. All the received code packets are decoded by the decode logic **324**.

8. For the next data session, the value of ε is reset to its initial value.

[0046] In one embodiment, the decoder **300** comprises one or more program instructions ("program instructions") stored on a computer-readable media, which when executed by at least one processor, for instance, the processing logic **302**, provides the functions described herein. For example, the program instructions may be loaded into the decoder **300** from a computer-readable media, such as a floppy disk, CDROM, memory card, FLASH memory device, RAM, ROM, or any other type of memory device or computer-readable medium that interfaces to the decoder **300**. In another embodiment, the instructions may be downloaded into the decoder **300** from an external device or network resource that interfaces to the decoder **300** through the transceiver logic **304**. The program instructions, when executed by the processing logic **302**, provide embodiments of a decoding system as described herein.

[0047] As a result, embodiments of the decoding system operate to process received code packets to recover data transmitted over a lossy transmission channel. The system operates to adjust the amount of code packets that are received based on one or more trigger events. Thus, embodiments of the decoding system operate to minimize the amount of unnecessary packets received so that device resources may be efficiently utilized.

[0048] **FIG. 4** shows one embodiment of a tree structure **400** for use in embodiments of a decoding system. In one embodiment, the tree structure **400** is generated and maintained at the LDGM logic **312**. The tree structure **400** comprises data **402** and combined data **404** that are obtained from received code packets. For example, the combined data **404** is provided in the second type of code packet described above. The tree structure **400** also comprises edge structures **406** that describe the relationship between the data **402** and the combined data **404**.

[0049] During operation of the decoding system, code packets are received by the transceiver logic **304** and the data and combined data they contain are stored in the data storage **308** and code storage **310**, respectively. The LDGM logic **312** processes information in the data storage **308** and the code storage **310** to construct the tree structure **400** so that it is possible to keep track of how many packets have been successfully received and which packets need to be recovered. Thus, the tree structure **400** provides a performance indicator in that it is possible to determine how many packets have been lost and how many packets have been successfully received.

[0050] In one embodiment, as the tree structure **400** is generated, portions of the tree structure **400** are added and portions of the tree structure are pruned. For example, once data is successfully recovered, edge structures are pruned, as shown by **408** and indicated by dashed lines. As additional packets are received and some packets lost, additional edge structures are added, as shown at **410** and indicated with solid lines. The ongoing addition and pruning of the tree structure **400** results in a certain amount of storage being allocated to store the tree structure 400. The amount of storage that is allocated for the tree structure 400 is an indicator that describes the number of packets that are lost in transmission.

[0051] Thus, the tree structure **400** provides several indicators pertaining to the operation of the decoding system. For example, the tree structure 400 indicates which packets have been successfully recovered and which have not. The tree structure 400 also indicates the number of lost packets. For example, a large tree structure indicates that a large number of packets have not been successfully received.

Trigger Events

[0052] In one or more embodiments, the decoding system operates to adjust the number of received code packets based on one or more trigger events. Two types of trigger events are described herein, although more types are possible within the scope of the embodiments. One type of trigger event is an early error detection trigger event. An early error detection trigger event occurs before or during the decoding process to indicate that the decoding of the received packets will be unsuccessful. The early error detection trigger event occurs before the decoding is completed so that it is possible to stop the decoding process to take corrective action, thereby conserving device resources and processing time.

[0053] Another type of trigger event is a decoding failure trigger event. The decoding failure trigger event occurs once the decoding process is complete and it indicates that there has been a decoding failure.

[0054] The following provides a detailed description of various trigger events. It should be noted that the system is not limited to using only the trigger events described below and that other trigger events may be defined and utilized within the scope of the embodiments.

Early Error Detection Trigger Events

[0055] The following is a description of two types of early error detection trigger events. These events are detected before the completion of the decoding process so that the decoding system can take corrective action without having to wait for the result of the decoding process.

Memory Utilization Trigger Event

[0056] In one embodiment, the decoding system operates to detect a memory utilization trigger event. For example, if a tree structure maintained by the tree logic **320** exceeds a selected memory threshold then the memory utilization trigger event is generated.

Receive Ratio Trigger Event

[0057] In one embodiment, the decoding system operates to detect a receive ratio trigger event. For example, if the rate logic **316** determines that the rate of successfully received packets falls below a selected threshold, then the received ratio trigger event is generated.

Decoding Failure Trigger Event

[0058] The following is a description of a decoding failure trigger event. This event is detected at the completion of the decoding process so that the decoding system can take corrective action with respect to the next receiving session.

Decoding Failure Trigger Event

[0059] The decoding failure trigger event is generated if the decoding process for a selected session of received code packets fails. For example, the decoder **300** operates to receive $k(1+\varepsilon)$ code packets transmitted within a selected contact window. If there is a failure in decoding the received code packets then the decoding failure trigger event is generated. A decoding failure may be defined by any desired decoding criteria. In one embodiment, the decoding logic **324** operates to decode the received code packets and generate the decoding failure trigger event **326** if a decoding failure is detected.

[0060] **FIG. 5** shows one embodiment of a method **500** for use in embodiments of a decoding system. For clarity, the method **500** is described herein with reference to the

decoder **300** shown in **FIG. 3**. For example, in one embodiment, the processing logic **302** executes machine-readable instructions to perform the functions described below.

[0061] At block **502**, a value of ε is initialized to a minimum value for the decoding system. For example, in one embodiment, the value of ε is downloaded to the decoder **300** from a remote server through the transceiver logic **304** and stored at the processing logic **302**. In one embodiment, the initial value of ε is approximately 0.1.

[0062] At block **504**, one or more code packets are received. For example, the code packets may be transmitted to the decoder **300** over a multicast transmission channel within a selected contact window and received by the transceiver logic **304**. As the code packets are received, the information they contained is stored in the data storage **308** and the code storage **310** as necessary. Additionally, the LDGM logic **312** constructs a tree structure as shown in **FIG. 4**.

[0063] At block **506**, a test is performed to determine if all desired code packets have been received. For example, the decoder **300** attempts to receive k(1+ ε) code packets. If all the code packets have been received the method proceeds to block **514**. If all the code packets have not been received the method proceeds to block **508**.

[0064] At block **508**, a test is performed to determine if an early error detection trigger event has occurred. For example, in one embodiment, the rate logic **316** and the tree logic **320** operate to determine if early error detection trigger events **318**, **322** have occurred. If an early error detection event has not occurred, the method proceeds back to block **504** where more code packets are received. If an early error detection event has occurred, the method proceeds to block **510**.

[0065] At block **510**, all or a selectable portion of the remaining code packets in the contact window are received. For example, the processing logic **302** is aware of the duration of a contact window in which code packets are being transmitted. The processing logic **302** operates to control the transceiver **304** to receive code packets for the remaining part of the contact window so that the decoder **300** may receive any more code packets that are transmitted. In one embodiment, the value of ε is increased to include all remaining code packets.

[0066] At block **512**, the received code packets are decoded. For example, the processing logic **302** decodes all the code packets received to recover as much of the transmitted data as possible. The recovered data is stored in the data storage **308**. The method then ends at block **524**.

[0067] At block **514**, the received k(1+ ε) code packets are decoded. For example, the processing logic **302** decodes the k(1+ ε) code packets to recover as much of the transmitted data as possible.

[0068] At block **516**, a test is performed to determine if a decode error trigger event has occurred. For example, a decode error trigger event **326** occurs if the decode logic **324** detects a failure (as described above) in decoding the received code packets. If the decode process was successful, the method ends at block **524**. If a decoding error is detected, the decode error trigger event is detected, the method proceeds to block **518**.

[0069] At block **518**, the value of ε is increased. For example, in one embodiment, the processing logic **302** increases the value of ε by any selected amount.

[0070] At block **520**, a test is performed to determine if more packets are available to be received. For example, code packets are transmitted over the duration of a contact window. The test determines if the contact window is still open so that more packets may be received. In one embodiment, the processing logic **302** determines if the contact window is still open. If the contact window has closed so that there are no more packets to receive, the method ends at block **524**. If the contact window is still open so that there are more packets to receive, the method proceeds to block **522**.

[0071] At block **522**, additional code packets are received. In one embodiment, the processing logic **302** controls the transceiver logic **304** to receive more code packets. As the packets are being received, the information they contain is stored in the data storage **308** and the code storage **310** as necessary. The method then proceeds to block **514** where all the received code packets are decoded.

[0072] Thus, the method **500** operates to provide one embodiment of a decoding system for use in a device. It should be noted that the method **500** represents just one implementation and that other implementations are possible within the scope of the embodiments.

[0073] **FIG. 6** shows one embodiment of a decoder **600** for use in embodiments of a decoding system. The decoder **600** comprises a means **602** for receiving an initial amount of code packets. For example, in one embodiment, the means **602** comprises the processing logic **302** controlling the transceiver logic **304** to receive k(1+ ε) code packets.

[0074] The decoder **600** also comprises means **612** for detecting a trigger event. The means **612** comprises means **604** for detecting a decode error, means **606** for

detecting a memory threshold error, and means **608** for detecting a receiving ratio error. For example, in one embodiment, the means **604** comprises the decode logic **324**, the means **606** comprises the tree logic **320**, and the means **608** comprises the rate logic **316**.

[0075] The decoder **600** also comprises means **610** for receiving additional code packets. For example, in one embodiment, the means **610** comprises the processing logic **302** controlling the transceiver logic **304** to receive additional code packets within the duration of a contact window. Thus, the decoder **600** provides one embodiment of a decoding system.

[0076] The various illustrative logics, logical blocks, modules, and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

[0077] The steps of a method or algorithm described in connection with the embodiments disclosed herein may be embodied directly in hardware, in a software module executed by a processor, or in a combination of the two. A software module may reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, a hard disk, a removable disk, a CD-ROM, or any other form of storage medium known in the art. An exemplary storage medium is coupled to the processor, such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an ASIC. The ASIC may reside in a user terminal. In the alternative, the processor and the storage medium may reside as discrete components in a user terminal.

[0078] The description of the disclosed embodiments is provided to enable any person skilled in the art to make or use the present invention. Various modifications to these embodiments may be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other embodiments, e.g., in an instant messaging service or any general wireless data communication applications, without departing from the spirit or scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown herein but is to be accorded the widest scope consistent with the principles and novel features disclosed herein. The word "exemplary" is used exclusively herein to mean "serving as an example, instance, or illustration." Any embodiment described herein as "exemplary" is not necessarily to be construed as preferred or advantageous over other embodiments

[0079] Accordingly, while one or more embodiments of a decoding system have been illustrated and described herein, it will be appreciated that various changes can be made to the embodiments without departing from their spirit or essential characteristics. Therefore, the disclosures and descriptions herein are intended to be illustrative, but not limiting, of the scope of the invention, which is set forth in the following claims.

CLAIMS

WHAT IS CLAIMED IS:

1. A method for detecting a decode failure, the method comprising:

receiving an initial amount of code packets;

detecting a trigger event that indicates a decode failure associated with the initial amount of code packets; and

receiving one or more additional code packets, based on the trigger event.

2. The method of claim 1, further comprising decoding the initial amount of code packets and the one or more additional code packets to obtain transmitted data.

3. The method of claim 1, further comprising increasing an ε parameter to determine an amount of the one or more additional code packets.

4. The method of claim 3, further comprising resetting the ε parameter to an initial value for a subsequent receiving session.

5. The method of claim 1, further comprising generating the trigger event based on a memory utilization threshold.

6. The method of claim 5, wherein said receiving comprises receiving the one or more additional code packets within the duration of a contact window.

7. The method of claim 1, further comprising generating the trigger event based on a receive ratio indicator.

8. The method of claim 7, wherein said receiving comprises receiving the one or more additional code packets within the duration of a contact window.

9. Apparatus for detecting a decode failure, the apparatus comprising:

receiving logic configured to receive an initial amount of code packets, and to receive one or more additional code packets when a trigger event is detected; and

processing logic configured to detect the trigger event, wherein the trigger event indicates a decode failure associated with the initial amount of code packets.

10. The apparatus of claim 9, further comprising decode logic configured to decode the initial amount of code packets and the one or more additional code packets to obtain transmitted data.

11. The apparatus of claim 9, further comprising decoding the initial amount of code packets to generate the trigger event.

12. The apparatus of claim 9, further comprising logic configured to increase an ε parameter to determine an amount of the one or more additional code packets.

13. The apparatus of claim 12, further comprising logic configured to reset the ε parameter to an initial value for a subsequent receiving session.

14. The apparatus of claim 9, further comprising logic configured to generate the trigger event based on a memory utilization threshold.

15. The apparatus of claim 14, wherein said receiving logic comprises logic configured to receive the one or more additional code packets within the duration of a contact window.

16. The apparatus of claim 9, further comprising logic configured to generate the trigger event based on a receive ratio indicator.

17. The apparatus of claim 16, wherein said receiving logic comprises logic configured to receive the one or more additional code packets within the duration of a contact window.

18. Apparatus for detecting a decode failure, the apparatus comprising:
means for receiving an initial amount of code packets;
means for detecting a trigger event that indicates a decode failure associated with the initial amount of code packets; and
means for receiving one or more additional code packets, based on the trigger event.

19. The apparatus of claim 18, further comprising means for decoding the initial amount of code packets and the one or more additional code packets to obtain transmitted data.

20. The apparatus of claim 18, further comprising means for increasing an ε parameter to determine an amount of the one or more additional code packets.

21. The apparatus of claim 20, further comprising means for resetting the ε parameter to an initial value for a subsequent receiving session.

22. The apparatus of claim 18, further comprising means for generating the trigger event based on a memory utilization threshold.

23. The apparatus of claim 22, wherein said means for receiving comprises means for receiving the one or more additional code packets within the duration of a contact window.

24. The apparatus of claim 18, further comprising means for generating the trigger event based on a receive ratio indicator.

25. The apparatus of claim 24, wherein said means for receiving comprises means for receiving the one or more additional code packets over the duration of a contact window.

26. A computer-readable media comprising instructions, which when executed by at least one processor, operate to detect a decode failure, the computer-readable media comprising:

instructions for receiving an initial amount of code packets;

instructions for detecting a trigger event that indicates a decode failure associated with the initial amount of code packets; and

instructions for receiving one or more additional code packets, based on the trigger event.

27. The computer-readable media of claim 26, further comprising instructions for decoding the initial amount of code packets and the one or more additional code packets to obtain transmitted data.

28. The computer-readable media of claim 26, further comprising instructions for increasing an ε parameter to determine an amount of the one or more additional code packets.

29. The computer-readable media of claim 28, further comprising instructions for resetting the ε parameter to an initial value for a subsequent receiving session.

30. The computer-readable media of claim 26, further comprising instructions for generating the trigger event based on a memory utilization threshold.

31. The computer-readable media of claim 30, wherein said instructions for receiving comprise instructions for receiving the one or more additional code packets within the duration of a contact window.

32. The computer-readable media of claim 26, further comprising instructions for generating the trigger event based on a receive ratio indicator.

33. The computer-readable media of claim 32, wherein said instructions for receiving comprise instructions for receiving the one or more additional code packets over the duration of a contact window.

34. At least one processor configured to perform a method for detecting a decode failure, the method comprising:

receiving an initial amount of code packets;

detecting a trigger event that indicates a decode failure associated with the initial amount of code packets; and

receiving one or more additional code packets, based on the trigger event.

35. The method of claim 34, further comprising decoding the initial amount of code packets and the one or more additional code packets to obtain transmitted data.

36. The method of claim 34, further comprising increasing an ε parameter to determine an amount of the one or more additional code packets.

37. The method of claim 36, further comprising resetting the ε parameter to an initial value for a subsequent receiving session.

38. The method of claim 34, further comprising generating the trigger event based on a memory utilization threshold.

39. The method of claim 38, wherein said receiving comprises receiving the one or more additional code packets within the duration of a contact window.

40. The method of claim 34, further comprising generating the trigger event based on a receive ratio indicator.

41. The method of claim 40, wherein said receiving comprises receiving the one or more additional code packets within the duration of a contact window.