

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/095738 A2

- (51) International Patent Classification⁷: **E05B**
- (21) International Application Number:
PCT/IL2005/000348
- (22) International Filing Date: 28 March 2005 (28.03.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0407196.5 30 March 2004 (30.03.2004) GB
- (71) Applicant (for all designated States except US): **MUL-T-LOCK TECHNOLOGIES LTD.** [IL/IL]; PO Box 637, 81104 Yavne (IL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **MARKBREIT,**

Dani [IL/IL]; 181 Jerusalem Street, 58001 Azur (IL).
BEN-AHARON, Efi [IL/IL]; 16 Zichron Yaakov Street, 49728 Petach Tikva (IL).


(74) Agent: **KLEIN, David**; Beit HaRo'fim, 18 Menuha VeNa-hala Street, Room 27, 76209 Rehovot (IL).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: KEY COMBINATION ELEMENT IN KEY BLANK AND KEY



(57) Abstract: A key blank including a generally elongate shaft portion defining first and second generally flat oppositely directed side surfaces, joined by edge surfaces, at least one of the first and second side surfaces cuttable to form key cuts that define a key combination surface, and at least one key combination element movably disposed in the elongate shaft portion and adapted for touching a lock combination element disposed in a cylinder lock plug, wherein the at least one key combination element has inherent energy for applying an urging force against the lock combination element. A key formed from the key blank and lock therefore are also disclosed.

WO 2005/095738 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*