



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B22F 3/00	A1	(11) International Publication Number: WO 99/15292 (43) International Publication Date: 1 April 1999 (01.04.99)
(21) International Application Number: PCT/US98/16491 (22) International Filing Date: 7 August 1998 (07.08.98) (30) Priority Data: 60/055,227 8 August 1997 (08.08.97) US 60/065,571 14 November 1997 (14.11.97) US (71) Applicants: ABB LUMMUS GLOBAL, INC. [US/US]; 1515 Broad Street, Bloomfield, NJ 07003 (US). AUBURN UNIVERSITY [US/US]; 309 Samford Hill, Auburn, AL 36849-5176 (US). (72) Inventors: OVERBEEK, Rudolf, A.; 32 Lexington Court, Chatham Township, NJ 07928 (US). KHONSARI, Ali, M.; 34 Red Maple Avenue, Bloomfield, NJ 07003 (US). CHANG, Yung-Feng; 25 Hickory Place E-10, Chatham, NJ 07928 (US). MURRELL, Lawrence, L.; 1229 McDonough Street, South Plainfield, NJ 07008 (US). TATARCHUK, Bruce, J.; 4901 Sand Hill Road, Auburn, AL 36830 (US). MEFFERT, Michael, W.; 1355 Commerce Drive #706, Auburn, AL 36830 (US). (74) Agents: FOURNIER, Arthur, E., Jr. et al.; ABB Worldwide Boiler Business Area, Patent Services, 2000 Day Hill Road, Windsor, CT 06095-0500 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: PRODUCTION OF COMPOSITE POROUS FIBRE STRUCTURES		
(57) Abstract A porous composite product comprised of a network of fibers is produced by forming an unsintered preformed network of fibers and a gasifiable structure forming agent, followed by gasification of the structure forming agent prior to sintering of the fibers at appropriate junction points. The preferred structure forming agent is a cellulosic material.		