

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B23C 5/22, 5/00, 5/28	A1	(11) International Publication Number: WO 97/10915 (43) International Publication Date: 27 March 1997 (27.03.97)
(21) International Application Number: PCT/IL96/00111 (22) International Filing Date: 17 September 1996 (17.09.96) (30) Priority Data: 115338 18 September 1995 (18.09.95) IL (71) Applicant (for all designated States except US): ISCAR LTD. (IL/IL); P.O. Box 11, 24959 Migdal Tefen (IL). (72) Inventors; and (75) Inventors/Applicants (for US only): SATRAN, Amir (IL/IL); 6 Moran Street, 24960 Kfar Vradim (IL). MARGULIS, Rafael (IL/IL); 14/20 Jasmin Street, 21940 Karmiel (IL). (74) Agent: KAY, Simon; Reinhold Cohn and Partners, P.O. Box 4060, 61040 Tel-Aviv (IL).	(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>With amended claims.</i>	

(54) Title: **MILLING CUTTING INSERT AND MILLING TOOLHOLDER THEREFOR**

(57) Abstract

A milling cutting insert (1) including a substantially prismatic body portion (2) having an upper surface (3), a lower surface (4) and at least two pairs of adjacent side surfaces (5, 7, 8, 9); a pair of spaced apart co-planar abutment surfaces (5A, 5B, 7A, 7B) formed along a first side of a first of the pairs of side surfaces and at least one planar abutment surface (8A, 8B) formed along a second side of the first pair of side surfaces; and a cutting corner (10A, 10B) defined between the side surfaces of a second pair of side surfaces and including a front cutting edge (17) protruding outwardly with respect to a first side (5, 7) of the other pair of side surfaces opposite the first side of the first pair of side surfaces, the front cutting edge being parallel to the spaced apart co-planar abutment surfaces.

