

5

**FLATBREAD MACHINE WITH AN AUTOMATIC FLATBREAD
PREPARATION METHOD BASED ON DOUGH CAPSULES AND A
PACKAGING SYSTEM**

10

[0001] Flatbreads are being produced by millions every day. In most cases, flatbreads are prepared whenever they are needed. But the traditional preparation of homemade fresh flatbreads is till today extremely laborious. In order to prepare fresh dough for flatbreads with the right consistency and flavor, it takes a lot of time, it requires know-how and some experience. Although the existing domestic machines or more industrialized machines for small enterprises, as restaurants, try to simplify this work, the preparation of homemade flatbread is still very laborious. Nowadays machines which are able to produce tortillas at a fully automated process are very costly, big and have to be monitored by humans. Therefore they are not very likely to be installed in any household. These are some reasons why many consumers or small enterprises buy industrially manufactured flatbreads which are often made in relatively large quantities. Those flatbreads which are widely available, suffer in quality to some extent by mass production and the natural decrease in freshness because of shelf time or the use of preservatives.

25

[0002] In the course of mixing the dough flour, water and other ingredients there are many factors that may influence the consistency and texture of the dough. For example the temperature of the water may affect the consistency and its taste. The preparation process is very complicated to achieve by persons without enough experience, know-how or time.

30

[0003] While patents such as the U.S. Pat. 5,366,744 from Drummond et al. describe a method for making packaged leavened dough suitable for extended refrigerated storage, this method does not provide an automatic separation of the dough from the tray. The consumer must remove the dough product from the tray at the time of baking and place the dough product into a baking sheet or other appropriate baking utensil.

[0004] At present, there are only pre-baked flatbreads available on the market. These are flatbreads which were baked for a part-time of the entire baking process and then packaged into plastic packaging. Before eating, those pre-baked flatbreads are finished and fully baked either in a stove or in a microwave device. However, the taste of such flatbreads never reach the richness and freshness of handmade and instantly made flatbreads.

[0005] It is therefore an objective of the present invention to provide a new method and apparatus for the fully automatic and instant preparation and baking of flatbreads of all kinds and sorts. The invention also comprises a means for the intermediate packaging and storage of dough portions for distribution and for storage in such an apparatus so the apparatus is able to deliver fresh made flatbreads at any time and instantly.

[0006] The invention provides a method for a fully automatic preparation of flatbreads such as tortilla, naan, ruti, piadina, etc. with a flatbread machine for use at home or in enterprises that can bake and deliver fresh made flatbreads at any time - just at the push of a button. The innovation includes dough portions packed in capsules that include a system that enables the dough to be suitable for extended refrigerated and unrefrigerated storage.

[0007] In the figures, various aspects of the method, the packaging of the dough portions and apparatus for processing the dough portions and its baking and delivery are shown by way of examples.

Shown is in:

- 5
Figure 1: The working principle of the method and apparatus by way of a schematic view of an apparatus;
- Figure 2: The working principle of the method and apparatus by way of a schematic view of another apparatus;
- 10
Figure 3: A capsule containing a portion of dough for one single flatbread;
- Figure 4: The two halves of a capsule containing a portion of dough for one single flatbread;
- 15
Figure 5: The two halves of another type of a capsule containing a portion of dough for one single flatbread;
- Figure 6: The opening and emptying of a capsule containing a portion of dough for one single flatbread;
- 20
Figure 7: The moment when the dough portion is falling out of the capsule;
- Figure 8: One single cylindrical capsule with its cover;
- 25
Figure 9: A row of cylindrical capsules closed on their bottom side;
- Figure 10: The pouring out of single dough portions out of capsules of a moving row of capsules;
- 30
Figure 11: Another way of isolating single dough portions out of capsules of a moving row of another type of capsules;
- Figure 12: The flattening of a dough portion within the apparatus;

- Figure 13: The baking of a dough portion squeezed in between two hot plates;
- 5 Figure 14: The flattening of a dough portion by a rolling pin within the apparatus;
- Figure 15: The flattening of a dough portion by pressing shells within the apparatus;
- 10 Figure 16: The delivering of a baked flat bread after completing of the baking process, by turning the baking plate;
- Figure 17: The delivering of a baked flat bread after completing of the baking process, by moving the two-parts of the baking plate apart;
- 15 Figure 18: A sophisticated flat bread machine in a view open on one side;
- Figure 19: The flat bread machine according to figure 18 in a view open on the opposite side;
- 20 Figure 20: Another flat bread machine in a view open on one side, functioning with another method for opening the dough capsules;
- Figure 21: A dough capsule in the shape of a cup with its top sealed by a foil;
- 25 Figure 22: A collapsible dough capsule in the shape of a cup with predetermined folding lines;
- Figure 23: The collapsible dough capsule according to figure 22 in the collapsed state;
- 30 Figure 24: A dough capsule in the shape of a cup with its top sealed by a foil, and with an upper edge forming a surrounding grove;

- Figure 25: A dough capsule in the shape of a cup with its top sealed by a foil, and with an upper edge forming a surrounding groove and with predetermined folding lines;
- 5
- Figure 26: A circular disc shaped foil piece with a weakening line, for sealing a cup-shaped dough capsule;
- Figure 27: A circular disc shaped foil piece with several weakening lines across the foil piece, for sealing a cup-shaped dough capsule;
- 10
- Figure 28: A circular disc shaped foil piece with crossing weakening lines, for sealing a cup-shaped dough capsule;
- Figure 29: A ball shaped dough capsule consisting of two hollow hemispheres;
- 15
- Figure 30: A ball shaped dough encapsulated in an evaporizable foil;
- Figure 31: A flat bread dough encapsulated in an evaporizable foil;
- 20
- Figure 32: A flat bread dough packaged and encapsulated in foil material;
- Figure 33: Flat bread dough capsules piled up and packed in a stack;
- 25
- Figure 34: Flat bread dough capsules arranged in a blister packaging;
- Figure 35: Flat bread dough capsules arranged in a row in a cardboard box;
- Figure 36: A flat bread dough capsule before inserting it into the machine by a pokayoke-system;
- 30
- Figure 37: A flat bread dough capsule conveying system for feeding the flat

bread machine;

Figure 38: A flat bread dough capsule conveyer carousel for feeding the flat bread machine;

5

Figure 39: A flat bread dough capsule stack for feeding the flat bread machine;

Figure 40: A flat bread dough capsule opening system for tearing the sealing foil off the capsule;

10

Figure 41: A collapsible flat bread dough capsule before cutting open the sealing foil and before collapsing it;

Figure 42: The collapsible flat bread dough capsule of Figure 41 after cutting open the sealing foil and pressing down the bottom of the capsule by a piston, so the capsule collapsed and the dough fell down;

15

Figure 43: A system for opening a ball-shaped capsule by means of rails that are spreading away from each other;

20

Figure 44: A capsule consisting of two sealingly connected shells with orifices and a system for receiving, opening, discharging and disposing such capsules;

25

Figure 45: The capsule and system of figure 44 while opening and emptying the capsule;

Figure 46: The capsule and system of figure 44 while disposing the capsule;

30

Figure 47: Press plates for a parallel closing and flattening the dough balls;

Figure 48: Press plates with a lower horizontal resting plate and an upper

swiveling plate for flattening the dough balls;

Figure 49: Press plates with an upper horizontal plate and a lower swiveling plate for flattening the dough balls and subsequently releasing the flat dough;

Figure 50: Press plates with an upper and lower swiveling plate for flattening the dough balls and subsequently releasing the flat dough;

Figure 51: Press plates with an upper and lower horizontal plate, the upper plate having a removable stamp for creating a temporary hole for inserting the dough ball;

Figure 52: Press plates which comprise releasable heating plates for cleaning purposes;

Figure 53: A table presenting the pressing and heating process by showing the distance between the heating plates versus the time for three different temperatures.

[0008] The starting point of the invention is a packaging system for the intermediate storage of a suitable dough. The dough is encapsulated in capsules which comprise a single portion for one single flatbread. In this form and shape, the dough portions can be stored for a period of at least three weeks. The capsules are specifically designed for an automatic opening and processing with a flatbread machine. The flatbread machine system is capable of preparing at least one flatbread from dough packed inside capsules fully automatically, without the need for the user to open or remove something of each encapsulated dough by hand.

[0009] As shown in figure 1, the machine or apparatus comprises these elements which are shown in schematic manner: A housing 1, containing a feeding compartement 2 which receives the capsules 3 containing a dough portion each.

The capsules 3 will be transported by a conveyor system 4 toward the baking plates 7,8, then opened and emptied by an opening system 5. The empty capsules 3 are being conveyed into a waste recipient 6, and the dough falls in between the baking plates 7,8 and is then squeezed to a flat shape in between them. Then the heated baking plates 7,8 start the baking process. When completed, the plates 7,8 open and eject or release the fresh made flat bread into a recipient 9 which is equipped with a warm keeping system 10.

[0010] As shown in figure 2 in another execution of the apparatus, the capsules 3 are being conveyed to the apparatus in a chain or row 11. They reach an end position in which they are opened mechanically, hydraulically or pneumatically. In the shown example, a plunger 12 of an actuator 13 moves downward and increases the internal pressure in the capsule. Under this pressure, the sealing foil on the lower side of the capsule 3 will burst and the dough portion then falls through the leading pipe into the housing 1 of the machine and down between the baking plates 7,8. The lower baking plate 8 is swivelable upwards along the indicated arrow, by a pneumatically, hydraulically, electrically or mechanically activated piston 14. After completion of the baking process, the lower baking plate 8 is swiveled down again and the finished flat bread falls into the recipient 9 where the flat breads are kept warm by a warm keeping system 10. Automatically, the next dough capsule 3 is placed underneath the plunger 12 for preparing a next flat bread on request. If the machine contains more capsules 3 inside, the machine begins with the process time and again until the feeding compartment or the row 3 is emptied and all flatbreads have been made. The user can finally remove the flatbread recipient 9 with all finished flatbreads cooked like in a drawer.

[0011] As mentioned earlier, this invention comprises a dough capsule 3, which is defined here as a container, a pad or a package that contains at least one portion of fresh dough for making flatbreads such as tortillas, naan, pita, ruti, piadina, etc. The form of the dough capsule can be round, cubic, cylindrical (can or canister), a pouch, square, rectangular, triangular, etc. Depending of the machine class and its corresponding opening system, the capsule can be composed of at least one single piece that surrounds and encloses the dough mass. The form of the capsule

should allow the machine system to open and separate or liberate the dough from the capsule automatically, without a need for the user to open or remove something. However, the form should be also simple and packable with low volume in order to make sense economically.

5

[0012] The material should primarily maintain the dough as long as possible by both refrigerated and unrefrigerated storage without affecting the consistency and backing characteristics of the dough. The material of the capsule may be for example but not limited to, soft, bio degradable, flexible, rigid, semi-rigid or a combination of them. The following materials or a combination of them (aluminum, paper, paperboard, can or canister, plastic or polymeric material), among others not listed here, may be used depending of the dough product and the class of the flatbread machine. The material and the form of the capsule should interact with the opening system of the machine in a proper way so that the dough does not stick to the capsule and no rest of material is transported together with the dough to the pressing plates.

[0013] The consumer should not open the dough capsule by himself. The dough capsule 3 is being opened by the flatbread machine's system automatically, or it can be opened by closing the machine by a lever or cover which enacts the opening. The machine system opens the capsule 3 only if the capsule 3 has not been opened or damaged before. This can be done, for example but not restricted to, with a code or chip on the capsule 3 that only the flatbread machine recognizes.

25

[0014] The design of the capsule 3 may include for example a weak point that allows the machine to separate the capsule easily from the dough but at the same time enough safely that no material particle of the capsule 3 comes into the dough by the separation and transportation to the next level.

30

[0015] To form a homogeneous dough mass flour, water, salt and other components such as yeasts or other microorganisms, leavening agents, emulsifiers, enzymes, etc. are mixed in adequate amounts. Depending of the

dough product, different kind of flour may be used. For example white, yellow and blue corn (*Zea Maize*) flour for corn tortillas or wheat flour for wheat tortillas, or teff and other basic ingredients can be used for producing even other types of flatbreads. In addition, components such as jalapeños, tomato, cheese, honey, garlic and other herbs and spices as well as taste giving liquids such as wine, beer, soy sauce may be added to the dough mass. The dough may be yeast or chemical leavened and it may be proofed or un-proofed. Natural yeast (*Saccharomyces cerevisiae*), baking powder (*Sodiumbicarbonate*) or other yeasts can be used. It can contain suitable preservation ingredients according to the state of the art. The components of the mass are combined and kneaded under circumstances at which the dough mass is developed. A typical recipe of a Corn Tortilla is this: (All percentages given are related to the weight of the dough).

- Corn-Flour: $46 \pm 5\%$ dried, nixtamalized corn flour, moisture: $13\% \pm 2\%$
- Water: $54 \pm 5\%$ temperature, $80-95^{\circ}\text{C}$ (soft water)
- Additives: $\leq 2\%$ Salt or other preservatives as alcohol, sodium bicarbonate, sodium propionate, potassium sorbate, sorbic acid or other NDA conform ingredients.

A typical recipe for a Wheat Torilla can be: (All percentages given are related to the weight of the dough).

- Wheat-Flour: 68%, white flour type 440, protein content: 9.5-11.5%, water content: 13-14%
- Water: 27.5%
- Salt: 1%
- Fat Vegetable: 2%
- Baking powder: 1%
- Acidulant: 0.3%
- Preservation: 0.13%
- Dough conditioner: variable

[0016] The preservatives used can be those indicated above. Salt or other preservatives as alcohol, sodium bicarbonate, sodium propionate, potassium sorbate, sorbic acid or other NDA conform ingredients can be used, whatever is preferred. A correct Tortilla is not thicker than about 6mm, and it can have a round,

rectangular oval or other shape. Important is mainly its taste which highly depends on its freshness!

[0017] The user turns the machine on by enabling electricity to the machine. Then
5 the user opens the machine's feed compartment for example by pushing a button
or by pulling the compartment out. Then the user puts at least one dough capsule
into the machine's feed compartment without opening the capsule or removing
something of it. This may happen for example, but not limited to, by putting each
10 dough capsule into a specific place of the compartment, for example by a revolver
system, or by putting each dough capsule, for example into a feed system shaped
as rail where the capsules are placed one after one. After this, the user closes the
machine's feed compartment, for example by pushing a button or by pushing the
compartment into the machine.

[0018] The machine opens the dough capsules 3 fully automatically without a need
that the consumer opens or removes something of the capsule 3. This can happen
for example, but not limited to, through pressure to the capsule 3 in different ways
or by cutting a part of the capsule in order to break it and separate it from the
dough. The following examples illustrate possible capsules 3 and their opening
20 systems. If for example the dough capsule 3 is made from a semi-rigid material
such as plastic, e.g. polypropylene (PP) or aluminum and the form of capsule 3 is
round as shown in figure 3, the machine can push a the top of the dough capsule
with a plunger in order to apply pressure on a special point of the capsule 3, so
that the capsule 3 gets opened and the dough falls down into the next level of the
25 machine in order to be pressed and then baked.

[0019] Figure 4 shows the two halves of a ball-shaped capsule containing a
portion of dough for one single flatbread. The two halves are fitting together and
can be welded or glued together along their round edges by way of common
30 methods.

[0020] Another example with a cylindrical form with special two rigid borders and
with a combination of rigid material from aluminum by the body of the capsule and

a semi-rigid material from aluminum by a special weak point of the capsule in the middle is shown in figure 5. The part on the left side of the figure can be plugged into the part of the capsule shown on the right side of the figure. At left edge of the part on the right side, this part is being welded to the bottom plate of the left part.

5

[0021] The machine feeding-system can push or move the capsules 3 in a feed-system which, at the end of the feed system moves the parts that hold the two rigid borders of the capsule, in such way that they diverge from each other so that the weak point of the capsule breaks which separates the dough 28 from the capsule 3 and the dough 28 falls finally down to the next level of the machine in order to be pressed, while the two pieces of the capsule are removed or transported to the waste container of the machine.

[0022] After the dough has been liberated from the capsule, the dough is transported to next level where the dough is going to be pressed by falling down for example direct to the pressing system or to a passage, for example a tube, that facilitates the exact positioning of the dough before pressing.

[0023] When the dough 28 has reached the appropriate place to be pressed, the dough gets pressed automatically. The pressing may happen for example, but not limited to, through two rollers as shown in figure 12, or two plates as shown in figures 1, 2 and 13, which may be partially heated up to 218° C in order to avoid mis-shaping and the formation of translucent spots. Other press systems comprise a convex press as shown in figure 15, a "toothpaste"-press as shown in figure 14 may be used. The end material of the parts that have contact with the dough may be for example Teflon or any other material that avoids the sticking of the dough to the end material.

[0024] After the dough has been pressed, the machine cooks or bakes the dough and converts it into a desired fresh flatbread. The heating may happen for example, but not limited to, by induction. By using two plates as shown in Figures 1, 2 and 13 for example, that can be heated with induction technology, the dough can be pressed and formed into a disc in seconds. As the plates are cold in the

seconds that the dough gets pressed, the dough will not suffer formation of translucent spots and the shape remains stable. As induction reaches higher temperatures significantly quicker, in this case, after the two plates come together by pressing the dough into a flatbread, the plates reach a cooking temperature of more than 260 C° in seconds and the pressed dough gets cooked instantaneously and reaches desirable toast marks.

[0025] While the dough get's pressed and heated, the material of the opened capsules is removed or transported to the waste recipient automatically. After the flatbread is cooked and ready to eat, it is transported to the removable flatbread recipient, which retains at least one flatbread warm by a warm keeping system. The transportation of the cooked flatbread to the removable warm recipient may happen for example, but not limited to, by moving the plate of the bottom in one of the sides down, in order that the flatbread falls down from that side as shown in figure 16, or by separating the plate from the bottom in two parts, so that the tortilla falls down in the middle as shown in figure 17.

[0026] If the machine contains more capsules inside, the machine begins with the process again until the feed compartment get's empty and all flatbreads have been made. The user can finally remove the flatbread recipient with all flatbreads cooked ready to eat.

[0027] In the following, particular executions of the method and machine are being disclosed. Figure 18 does show a more sophisticated flat bread machine in a view open on one side. Side 15 is the front side of the machine, side 16 is the rear side of the machine. The machine comprises a housing 1, and on top of it, a container 17 for the capsules to be fed into the machine is shown. One side of the machine housing 1 is here opened since the respective cover plate of the housing 1 was removed in order to give free sight into the interior of the machine. What can be seen in this drawing is the mechanism by which the capsules 3 are being handled once they are feeded into the machine from the container 17 in which they are stacked. The capsules 3 used here have the shape of a collapsible cup. The upper opening of the cup is sealed with a gas-tight foil 18, and the cup contains a portion

of dough for the single flat bread to be prepared. Capsule and dough must not be form-fitted in order to ensure an easy emptying of the capsule, rather, the dough should not fill the cup-shaped capsule but leave a distance of approx. 5mm to the covering foil 18. The cups are stacked upside up in the container 17. The lowest cup or capsule 3 can be seen partly. It is being hold by two fingers 19 which are extending perpendicularly from a rotatable disc 20 which is rotatable around a horizontal axis 21. This disc 20, when activated, does rotate in counterclock direction in the shown drawing, around 180° each time when the rotation is initiated. While rotating, the discs's fingers 19 hold a cup-shaped capsule 3 between them, and rotate the same around the central axis 21. The foil-side of the cup is then gliding along a cylindrical wall 22. This cylindrical wall 22 is being hold by several struts 23 that are connected to an inner cylindrical wall 24 having a smaller radius. The disc 20 and its fingers 19 rotate until the cup is placed upside down on a holding plate having a central hole (not shown in this drawing). The edge of the cup-opening rests on the edge of the hole and then, a plunger (not shown in this drawing) moves down, collapses the cup by pressing onto its bottom side, thereby cutting or bursting open the sealing foil 18. Consequently, the dough portion in the capsule 3 will fall down through that hole onto the lower baking plate 8. An optical sensor recognizes when the dough has fallen down onto said plate 8. This baking plate 8 is movable in horizontal direction to the left, in order to reach the horizontal displaced position in which it is ready to serve as lower pressing plate. An upper pressing and baking plate 7 (not shown in this drawing) is then moving from above downward and squeezes the dough portion between the two plates 7,8 until the dough assumes a flat bread shape. Then, heating means will act and the dough is being baked. This heating means can comprise electrical heating coils within the plates 7,8, or induction heating coils, or even gas burners that heat up the plates 7,8. Once the baking process is finished, the lower plate 8 is being pulled back. This lower plate 8 is swivelable around a moving axis 25 at its rear end, and that is indicated with a dotted line, and that is movable in its entirety in horizontal direction toward the front side 15 of the machine. In the position of the lower plate 8, when displaced to the left from the position as shown in figure 18 -, the plate 8 is first supported by upper rails (not shown) in order to resist the pressing force to be applied, and when pulled back, it will be swiveled

down around its axis 25 since its front end is then being guided along lower guiding rails 26 that describe a bow as will be explained in connection with figure 19. When the lower plate 8 is swiveled down temporarily, the finished flat bread will glide away from the lower plate 8 and ultimately being dispensed through the slit 27 in the front side 15 of the housing 1 of the machine. In the lower back of the machine, a recipient container 6 can be recognized. Once the cup or capsule 3 is emptied, disc 20 will further rotate counterclock-wise and shift the capsule 3 toward the backside 16 of the machine where it will fall down into this recipient container 6 for waste capsules.

[0028] Figure 19 does show a similar machine when seen from the opposite side, that is from the left side, with opened left side panel of the housing 1. Here, one can see the feeding container 17 and the capsules 3 in the form and shape of cups piled up within the container 17 to a stack. The disc 20 which is arranged here rotatable around an axis 21 which does extend to the rear wall 16 of the housing 1, and the fingers 19 on the disc 20 are extending in horizontal direction from the disc 20, arranged perpendicularly on said disc 20. The lowest cup 3' in the container 17 already rests between two fingers 19 of the disc 20, while another cup 3'' has already been rotated around axis 21 in an upside down position onto the holding plate 29 having a central hole. The dough has already fallen down and is now resting on the lower pressing and baking plate 8. When the disc 20 further rotates, it will move the upper cup 3' into the lower upside-down position, and the lower cup 3'' will be disposed into the recipient container 6 for the emptied cups or capsules 3. Once the dough is placed on the pressing and baking plate 8, said plate 8 will be moved horizontally toward the front side 15 of the machine. On its side at the front end, bolts 30 are extending to the side and these bolts 30 are being guided in guiding rails 26,31. In a first movement, here from the left to the right, the pressing and baking plate 8 will be moved by a motor in horizontal position while its side bolts 30 are guided along the upper guide rails 31 until the bolts 30 reached the front end of these guide rails 31. In the front end area 32, there are spring-loaded separators 33 arranged. The bolts 30, when moving from the left to the right, will swivel these separators 33 from the shown position into a horizontal position so they give way for the bolts 30 to pass them and ultimately

reach the front end 32 of the guide rails 31. In such position of the bolts 30, the pressing and baking plate 8 has reached its operating position for the pressing and baking process. For pressing the dough which is placed on this pressing and baking plate 8, an upper pressing and baking plate 7 is arranged parallel to the lower pressing and baking plate 8. Said upper plate 7 is hanging on a knee-knuckle press mechanism 34. In the shown example, there are two levers 35,36 on each side. When their central joints 37 are being pushed away from each other, e.g. by a mechanical mandrel/spindle, or linear guide unit, or by a hydraulic or pneumatic piston/cylinder arrangement, the upper pressing and baking plate 7 will be lowered down and ultimately press with increasing force onto the dough portion laying on the lower plate 8. The pressing force will increase due to the knee-knuckle effect of the chosen arrangement 34. It is though clear that other mechanism for actuating such a pressing can be chosen. Once the dough portion is pressed into the shape of a flat bread, the baking process starts by the ready heated baking plates 7,8. The actual baking will be performed at a selected temperature, e.g. between 200°C and 220°C for tortilla dough. These temperatures are only given as examples and are not to be understood as definite limits. Depending on the dough used, lower or higher temperatures may be suitable. The machine can offer a temperature range from 200°C to 350°C depending on what is required. Once the dough baking process is finished, the baking process is stopped by moving the baking plates apart from each other and by dispensing the finished flat bread. The upper plate 7 will be lifted up, and the lower plate 8 will be pulled back. Now, when pulling the lower plate 8 back, its side bolts 30 are being guided along the bow-like shaped lower guide rails 26 since the spring loaded separators 33 on both sides of the plate 8 reassumed the shown position that ensures that the bolts 30 are guided downward into the lower bow-shaped guiding rails 26. Another such separators 38 ensure that the bolts 30 are reaching their initial position as shown in figure 19, and for the next movement to the right, they will glide over these separators 38 into the horizontal guide rails 31.

[0029] Basically, the feeding compartment 17 can be either integrated into the machine or form an external compartment, e.g. it can be just the container in which the capsules are being distributed. The machine's compartment can easily

be refilled in any case. It can cooperate with the conveyer system for feeding the single capsules to the opening and emptying system. The recipient container 6 is designed releasable from the machine, e.g. like a drawer so the empty capsules can easily be removed from the machine.

5

[0030] Figure 20 discloses another flat bread machine in a view open on one side, functioning with another method for opening the dough capsules. The also cup-like shaped capsules 3 with sealing foil 18 over their opening are being inserted upside down into the machine by lifting up a swivable cover plate 39. The capsules 3 are placed on a conveyor belt 40 that runs around two shafts 41,42. At the front end of said conveyor belt 40, two shafts 43,44 with rubber theeths extending away radially from the circumference of the shafts 43,44 move in different directions, the first one 43 clockwise, the adjacent one 44 at the front end in counterclock-wise direction. These shafts have a diameter of approx. 20mm which proved to work fine. The foils 18 of the capsules 3 have an overlap of approx. 5mm that is always bent away from the capsules 3 upper edge. Therefore, when the capsules 3 are laying upside down on the conveyer belt 40, these overlaps are under a tension to bend downward. Once the overlap of a capsule 3 reaches the shafts 43,44 with the rubber teeth, this overlap will be packed. The second shaft 44 is positioned a bit higher so it will surely grip the foil overlap. The foil is then pulled down between the two shafts 43,44 and torn away from the edge of the opening of the capsule 3, and the capsule is forced to move over the two shafts 43,44 and to pass them. Therefore, the foil 18 will be torn away from the capsule 3 and the open capsule 3 will glide onto the inclined holding ring 45. Instantely, the dough will fall out of the capsule and fall in between the two pressing and baking plates 7,8. An optical sensor recognizes when the dough has fallen down in between the plates 7,8. The upper pressing and baking plate 7 is swivelable around an exentrically arranged axis 46, and an actuator 47 can then swivel the upper pressing and baking plate 7 down onto the lower plate 8. The excentric arrangement of the axis 46 will ensure an increasing pressing force, the more the pressing plate 7 did already swivel in downward direction. After pressing the plates will move up a little bit again. After cooking the flatbread, the upper pressing plate will lift, that the ready to eat flatbread slides out of the machine by gravity. In this case, there is no warm

keeping container for the flatbreads.

[0031] Figures 21 to 29 show various types of suitable capsules 3. Figure 21 e.g. does show a dough capsule 3 in the shape of a cup with its top sealed by a foil 18.

5 The dough portion is being filled into such a capsule under an atmosphere of an inert gas such as Nitrogen. The capsules are made of a gas-tight plastic as known in the food and beverage industry, and the foil is a laminate of aluminum foil that is gas-tight. Semi-permeable foils can be used which allow O₂ to permeate from within the capsule but not in opposite direction. For special purposes, these
10 capsules and foils can even be made in oxygen tight manner as known in the state of the art. This type of cup-like capsule 3 can be piled up in empty state, and even a re-use may be an option. In such case, the capsules should be piled up in a recipient container for the emptied cups so they can be easily recycled and brought back to the seller in the original cardboard box in which they have been
15 sold.

[0032] Figure 22 shows a collapsible dough capsule 3 in the shape of a cup with predetermined folding lines 48. Else the capsule 3 is similar or equal to the one shown in figure 21. But this collapsible capsule 3 allows it to reliably empty it from
20 the containing dough since it then collapses in a defined form. In figure 23, the collapsed dough capsule 3 of figure 22 is shown in the collapsed state. In order to reach this state, the upside down placed capsule 3 will be pressed from above by a plunger or piston while its opening edge rests on a ring which leaves the space under the opening free so the dough can freely fall through said ring opening once
25 the sealing foil 18 has been opened. For better opening of such capsules, the foil 18 may be equipped with prepared weakening lines, as explained later.

[0033] Figure 24 does show a dough capsule 3 in the shape of a cup with its top sealed by a foil 18, and with an upper edge 49 forming a surrounding groove 50.
30 The purpose of this particularly shaped edge 49 and said groove 50 will be explained later, in connection with the opening process as shown in figures 41 and 42. Advantageously, this cup-like capsule 3 is also equipped with folding lines 48 as already described to figure 22 and shown here in figure 25.

[0034] Figure 26 shows a circular disc shaped foil piece 18 with a weakening line 51, for sealing a cup-shaped dough capsule 3. Such weaking line can be reached making the foil thinner along this line, as already know in the state of the art, e.g. by a hot welding knife that is pressed down onto the foil, against a hard support plate. In an alternative way, the weakening lines can be obtained by a fine perforation of a two-layer foil while only one layer of the foil is perforated to keep it airtight. In figure 27 the circular disc shaped foil piece 18 is equipped with several weakening lines 51 across the foil piece, and in figure 28, the weakening lines form a single cross over the circular foil 18. The foil has two basic purposes on such capsules. Firstly, the foil must hermetically close the capsule 3 in order to keep air away from the dough. Secondly, the foil 18 does ensure that in the course of emptying the capsule 3, the dough never gets in touch we a part of the machine, not even with the knife that opens to foil 18 if such knife is being used. The opening of the capsule, however, will be described later, in connection with figures 40, 41 and 42.

[0035] In figure 29, an entirely different typ of a capsule is shown. This is a ball shaped dough capsule 3 consisting of two hollow hemispherical shells 52 that are equipped with little knobs 53 at their zeniths. The two hemispherical shells 52 can be closed and sealed by heat welding or gluing them together. Then, the dough portion is hermetically enclosed. The handling and opening of such capsules 3 is described later, in connection with figure 43.

[0036] The capsules can be sold with a second packaging material or not. If the capsule foil is even perforated, it is best to use a second package, e.g. a cardboard box, for guarding their inner foil 18. As yet another type of capsule, figure 30 shows a ball shaped dough encapsulated in an evaporizable foil 54 that forms the capsule. The foil, once heated up in the baking process, will disappear by evaporation. In figure 31, an already flat bread dough is encapsulated in such an evaporizable foil 54. And in figure 32, yet another way of packaging the dough is shown. Here, an already flat dough is encapsulated in a suitable foil material 55 which can later be torn apart either by the machine or by hand, in order to release

the inlaying dough.

[0037] In a next section, the handling of these capsules 3 is shown and explained. Figure 33 shows flat bread dough capsules 3 piled up and packed in a stack.

5 These stack is then packaged in a cardboard box in which the set of capsules are being sold and handled. From this cardboard box, the capsules 3 can be inserted into the feeding compartment 2 of the machine, or the cardboard box may itself form the feeding compartment of the machine so it simply needs to be opened and put onto an insert of the machine.

10

[0038] In Figure 34, an alternative packaging for the distribution and handling of capsules 3 is shown. Here, the flat bread dough capsules are arranged in a blister packaging which comprises a top foil 57 which extends over all these four capsules 3. For using the capsules 3, this top cover foil 57 will be torn away and
15 the four still sealed capsules 3 are then separated and can be inserted into the machine. According to figure 35, the flat bread dough capsules 3 are arranged in a row in a cardboard box 58. Likewise, the single capsules 3 can be taken out of the box and then inserted into the machine's feeding compartment 2. In figure 36, the insertion of a single capsule 3 into the machine is shown. In this example, the
20 machine and the capsule 3 form a Pokayoke-system that ensures the correct and fool-proved insertion of the capsules 3 into the machine through a particular opening 59 in the housing 2 of the machine.

[0039] In this section, various ways of the conveying of the capsules 3 within the
25 machine are being disclosed. In figure 37, the flat bread dough capsules 3 conveying system consists of a frame 60 which is put down over a row of capsules. This frame 60 is displaceable within the machine in order to feed the capsules for feeding them into the opening system 5 for opening the capsules and emptying them so the dough portion will fall onto the lower pressing and baking
30 plate 8. This frame 60 can be moved by mechanical, hydraulic or pneumatic means. The conveying system according to figure 38 makes use of a carousel 61 which contains wholes 62. The capsules are projecting out of these holes 62 from the lower side of the carousel while they are laying upside down on a lower plate.

When the carousel is rotating, the capsules 3 are being moved respectively, and once a single capsule 3 arrives over a respective hole in the lower plate so only its edge will be supported, a piston can act onto the bottom side of the capsule 3 which is now on the upper side, thereby bursting the sealing foil 18 and pressing the dough out so it will fall onto the baking plate 8. Then, the carousel 61 rotates again until the empty capsule 3 will fall into a recess in the lower plate, and will ultimately being disposed in the recipient container for the empty capsules 3. Figure 39 shows the cardboard box containing a stack or pile of capsules 3 as already shown in figure 33. The cardboard box 56 is here placed on the top side of the machine housing 1, and the stack is being lowered due to gravity as the lowest capsule is falling into the conveyer system of the machine for further processing said capsule and the dough contained in it. The capsule may e.g. fall onto a conveyor belt 40 as shown in figure 20.

[0040] In this section, various ways of opening the capsules are being disclosed and explained. In figure 40, the opening system as already mentioned and disclosed in figure 20 is shown in a perspective view for better understanding. At the front end of said conveyor belt 40, next to its front shaft 42, two shafts 43,44 with rubber teeth extending away radially from the circumference of these shafts 43,44 move in different directions, the first one 43 clockwise, the adjacent one 44 at the front end in counter clock-wise direction as indicated with the arrows. The capsule 3 is shown here in an elevated state, upside down, as it will lay on the belt 40. Its opening edge 63 does extend radially and is closed and sealed with the foil 18. The foil bends away from the plane of the opening edge, in the upside down position of the capsule 3 it bends downward, as shown in the drawing. Now, when the capsule 3 is being moved on the belt 40 in the direction of the arrow indicated, its foil will ultimately move into the area between the shafts 43,44. These two shafts 43,44 grip it and tear it down in between them, while the capsule 3 further moves in horizontal direction over these two shafts 43,44 and ultimately glides onto a frame 64 or onto a holding ring 45 as shown in figure 20. Since the capsule 3 is now open, the dough will fall due to gravity onto the lower baking plate 8 of the machine.

[0041] Another solution for emptying the capsules 3 is shown in figures 41 and 42. Here, collapsible flat bread dough capsules 3 are being used. They contain folding lines 48. The capsules 3 are positioned upside down on a support plate 68 with a hole that is of a slightly larger diameter than the opening of the capsule 3. The opening edge 49 of the capsule forms a groove 50, and the entire opening edge is covered with a circular foil piece 18 that sealingly closes the capsule 3. For opening the same, a circular stationary knife 66 is arranged underneath the groove 50 which extends almost over the entire circumference, only leaving a section of approx. 20° to 30°. On the inner side of the knife, a circular support 67 defines how low the capsule's opening edge 49 may move against the force of a compression spring 65. For emptying the capsule 3, it will be pressed down onto the support ring 67 by a plunger 12 or piston as shown in figure 42. Once the compression spring 65 is compressed, the circular knife 66 will cut open the foil 18 and move into the groove 50, then the capsule 3 will be compressed and collapse and consequently, the dough in the capsule 3 will fall over the remaining foil 18 that still hangs on its edge over a little remaining material bridge where the circular knife 66 is interrupted and did not act. Thereby, the dough does not touch any part of the machine. This is crucial for keeping the best hygienic level. Not even the circular knife 66 will touch the dough. The dough merely touches the inner side of the capsule 3 and the inner side of the foil 18, and will freely fall onto the lower baking plate 8. In an alternative embodiment, a thermic opening of the foil by using a heated up wire that is being pressed against the foil may be an option.

[0042] Figure 43 shows a system for opening ball-shaped capsules 3. The knobs 53 at the zeniths of the two hemispheres 52 or hemispherical shells 52 are guided by rails 53. For opening the capsule 3, the rails 53 are spreading away from each other and the capsule 3 is mechanically pushed by a plunger in the direction as indicated with an arrow. Therefore, the two hemispherical shells 52 are being pulled apart and the dough falls down. The hemispherical shells 52 will then leave the rails at their ends and fall into the recipient container 28 for the empty capsules 3.

[0043] Figure 44 to 46 disclose yet another method for opening respective

capsules 3. A single capsule 3 consists of two halves 70 that are hermetically sealed along their openings. On the outer side these halves are equipped with orifices 71. The opening system comprises two rails 72, and on their lower end, swivelable rail hooks 73 are attached which can be activated by a motor. As shown in figure 44, a capsule 3 of that sort falls down and its orifices 71 will fall into the hooks 73 of the swivelable rail hooks 73. In a second step, the rail hooks 73 are being swiveled apart from each other as shown in figure 45. This will open the capsule. Its two halves 70 are rotated in a position where their openings are on the lower side. Consequently, the dough falls down due to gravity. Then, the rail hooks 73 are further rotated until they reach the position as shown in figure 46. Now, the empty halves 70 will themselves fall down due to gravity, and they can slide on a pathway down into the recipient 6 for the empty capsules.

[0044] In figure 47, press and baking plates 7,8 for a parallel closing and flattening of the dough balls are shown. It is advantageous if the plates move always parallel to each other for pressing. Only then a ball-like dough will be flattened equally to each of its sides and ultimately, a circular flat dough can be obtained. In figure 48, press and baking plates 7,8 are shown with a lower horizontal resting plate 8 and an upper swiveling plate 7 for flattening the dough balls. In such an arrangement, additional means will be needed in order to remove the finished baked flat bread from the lower plate 8. In figure 49, the press and baking plates 7,8 comprise an upper horizontal plate 7 and a lower swiveling plate 8 for flattening the dough balls and subsequently releasing the flat dough by swiveling the lower plate 8 as shown. In figure 50, the press and baking plates 7,8 are both swiveling plates for flattening the dough balls and subsequently releasing the flat dough. In figure 51, the lower press and baking plate 8 is a horizontal plate 8, as also the upper plate 7. In order to feed the dough onto plate 8, the upper plate 7 comprises a hole and a stamp which fits into this hole in order to obtain a flat lower surface of said upper plate 7. The stamp can move up and down as the entire upper plate 7 can move up and down for pressing and baking. Figure 52 discloses press and baking plates 7,8 which comprise releasable, separate heating plates 76, preferably coated with a Teflon or ceramic layer, so they can easily be removed for cleaning purposes. The dough sticks to the plates, therefore low adhesion plates have to be used to

reduce the resistance and therefore reducing the pressing force. The pressing force for wheat dough is substantially higher than for corn dough. The pressing and heating or baking plates 7,8 can have a ceramic or Teflon coating so the dough is not adhering to them. In general, the press and baking plates must be
5 stiff to sustain forces but also a bit flexible.

[0045] Figure 53 does show a table presenting the pressing and heating process by showing the distance between the heating plates versus the time for three different temperatures, that is for 220°C, for 260°C and for 200°C. Typically, the
10 pressing force will be adjusted by controlling the machine in such manner that the pressing plates are moving toward each other, after they have been heated up to the required temperature, and then moving until a distance between them of only some 2mm will be reached. After a couple of seconds, the pressing force will be lowered so the plates will move apart to a distance of approx. 5mm. This will allow
15 the dough and the wheat in it to release moisture. Ultimately, after a few seconds another increased pressing force is activated to press the plates to a distance of again 2mm. The higher the temperatures of the baking plates, the shorter is the baking time. The temperature of the plates may also be varied during the baking process. This is a matter of experience and control of the heating means, and it
20 depends on the particular composition of the dough. If a resistor heating is being used, approx. 1800 W power is needed in order to reach a temperature of 200 to 260°C in a short enough time. Inductive heating is an option.

Claims

- 5 1. Method for the automatic preparation of flat breads by a machine, comprising the steps of
- a. feeding the machine with capsules (3) which contain each a portion of dough (28) for the production of one single flat bread, the capsules (3) being hermetically closed,
 - 10 b. opening and emptying the first capsule (3) arriving,
 - c. receiving the down-falling dough (28) from the opened capsule (3) on a baking plate (8),
 - d. squeezing or rolling out the dough (28) portion on said baking plate (8) by a second plate (7) or by a roller, or squeezing the dough portion (28) in
15 between two baking plates (7,8) and baking it,
 - e. releasing the finished flat bread into a recipient compartment (9).
2. Method for the automatic preparation of flat breads by a machine according to claim 1, comprising in the steps
- 20 a. feeding the machine with capsules (3) which have the form and shape of cups, the opening of the cups being sealed by a gas-tight foil (18), in upside-down position on a conveyor belt (40) or gliding plate,
 - b. opening the first cup-shaped capsule (3) by tearing off its foil by two adjacently positioned opposite rotating shafts (43,44) while the capsule (3)
25 is conveyed over these shafts (43,44), then positioning the opened capsule (3) on a frame (64) or holding ring (45), followed by the steps c. to e.
3. Method for the automatic preparation of flat breads by a machine according to
30 claim 1, comprising in the steps
- a. feeding the machine with collapsible capsules (3) which have the form and shape of cups, the opening of the cups being sealed by a gas-tight foil (18), stored in upright position in a stack in a feeding compartment (17),

then gripping the lowest capsule (3) of that stack with fingers (19) of a rotating disc (20), then rotating it around 180° to bring the capsule (3) in upside down position on a holding plate with an opening,

- 5 b. opening and emptying the capsule (3) by a plunger (12) which compresses the capsule (3) from above so the foil (18) is cut open by a circular knife (66) or by bursting along weaking lines (51) in the foil (18), followed by the steps c. to e.

- 10 4. Method for the automatic preparation of flat breads by a machine according to claim 1, comprising in the steps

a. feeding the machine with capsules (3) made of two hemispheric shells (52) with knobs (53) at their zeniths, by guiding these knobs (53) along rails (69),

15 b. opening the first such capsule (3) by pulling apart the two hemispheric shells (52) by pushing the capsules (3) along the rails (6) where they are spreading apart so the dough (28) falls down, followed by the steps c. to e.

5. Method for the automatic preparation of flat breads by a machine according to claim 1, comprising in the steps

20 a. feeding the machine with capsules (3) made of two shell-like halves (70) with orifices (71) at the outer side of the shell-like halves (70), so the orifices (71) will hook onto swivelable rail hooks (73), initially in vertical position,

25 b. swiveling these rail hooks (73) away from each other so the halves (70) are being pulled apart, the dough (28) falls down by gravity onto a pressing and baking plate (8) and while the rail hooks (73) further swivel over more than 120° from their initial vertical position, dropping the two halves (70) from the rail hooks (73) by gravity, so they fall into a recipient compartment (6), followed by steps c. to e.

- 30 6. Method for the automatic preparation of flat breads by a machine according to one of the preceding claims, after the steps a., b. and c., comprising the following steps:

- d. squeezing and baking the dough (28) portion between two pressing and baking plates (7,8) which are moving parallel to each other while the upper plate (7) is actuated mechanically, hydraulically or pneumatically by a knee-knuckle mechanism (34) comprising several levers (35,36) connected by joints (37), in order to press it against the lower, stationary plate (8) and baking the dough (38), then lifting the upper plate (7) away,
- e. releasing the finished flat bread into a recipient compartment (9) by pulling the lower plate (8) along guide rails (26) so the plate (8) will be inclined and the finished flat bread therefore glides down through a dispenser slit (27) in the housing (1) of the machine or into a recipient compartment (9).
7. Machine for the automatic preparation of flat breads, comprising a feeding system and compartment (2) for conveying a number of capsules (3) which are hermetically sealed and containing each a portion of dough (28) for producing one single flat bread, an opening system for opening the each first arriving capsule (3) by pressure or by cutting means so the dough (28) inside the capsule (3) falls out of the capsule (3) and down onto a heatable baking plate (8), a second heating plate (7), whereby at least one of the two heating plates (7,8) is moveable for opening and closing and thereby varying the distance in between the two heating plates (7,8), and a recipient compartment (9) for receiving the finished flat breads after opening the heating plates (7,8).
8. Machine for the automatic preparation of flat breads according to claim 7, characterized in that the feeding system comprises a conveyor belt (40) for moving upside-down positioned capsules (3) of cup-like shape, sealed with a foil (18) to an opening system which consists of two adjacent shafts (43,44) that rotate in opposite directions for tearing the foil (18) in downward direction while the respective capsule (3) is moving over them, a holding ring onto which the opened capsule (3) is movable, for the dropping of the dough (28), and at least one of the heatable baking plates (7,8) being swivelable against the other by means of a movable piston, and a conveying system for conveying the emptied capsules (3) into a waste recipient compartment (6).

9. Machine for the automatic preparation of flat breads according to claim 7, characterized in that the feeding system comprises a compartement (2) for receiving a stack of cup-shaped capsules (3), the conveyer and opening system comprising a disc (20) rotatable around a horizontal axis (25) and the disc (20) having several fingers (19) with extend in perpendicular direction from the disc (20) to grip a capsule (3) between two fingers (19), a cylindrical wall (22) for moving the capsules (3) with their foil-side along this wall, and an opening system comprising a holding plate with an opening for positioning the capsule (3) upside down on said holding plate by rotating the disc (20) until such position of the capsule (3) is reached, the opening system further comprising a plunger (12) for pressing from above onto the bottom side of the capsule (3), further a circular knife (66) with a diameter of more than the opening of the capsule (3), for pressing the capsule (3) over this knife and partly opening the foil, and a knee-knuckle press mechanism (34) with several levers (35,36) connected with joints (37) for pressing the pressing and baking plates (7,8) by a mechanical, hydraulic or pneumatic actuator parallel to each other, and heating means in the baking plates (7,9) comprising resistive heating coils, inductive coils, or a the heating means comprising a gas burner for heating up said plates (7,8).
10. Machine for the automatic preparation of flat breads according to one of claims 7 to 10, characterized in that the heatable baking plates (7,8) are made of induction heatable material and equipped with induction coils, and the apparatus further comprising an HF-generator for the induction coils.
11. Machine for the automatic preparation of flat breads according to one of the preceding claims 7 to 9, characterized in that the heatable baking plates are made electrically heatable by corresponding electrical resistive heating coils.
12. Capsule (28) for receiving a portion of dough for producing a single flat bread, characterized in that the capsule (28) comprises two parts which are sealingly closable for tightly and gas-tight encapsulating a dough portion (28) for making one single flat bread.

13. Capsule for receiving a portion of dough (28) for producing a single flat bread according to claim 12, characterized in that the capsule comprises a hollow part in form of a dome-like, ball-like part or a cylindrical or conical cup-like can made of a laminate and an even sealing foil (18) to be sealingly welded onto the hollow part, for gas-tightly encapsulating a portion of dough (28), and that the capsule (3) is collapsible along pre-determined folding lines (51).
14. Capsule for receiving a portion of dough (28) for producing a single flat bread according to claim 12, characterized in that the capsule comprises two cylindrical cans of slightly different diameter so the smaller one is pluggable into larger one, and then sealingly closable by welding or gluing, and then encapsulating a portion of dough (28) for one single flat bread.
15. Capsule for receiving a portion of dough (28) for producing a single flat bread according to one of claim 12, characterized in that the capsule consists of soft, bio degradable, flexible, rigid, semi-rigid material or a combination of them.