

METHODS, DEVICES AND COMPUTER READABLE MEDIUM FOR NEW RADIO MANAGEMENT MEASUREMENT

FIELD

- 5 [0001] Embodiments of the present disclosure generally relate to communication techniques, and more particularly, to methods, devices and computer readable medium for new radio management (RRM) measurement.

BACKGROUND

- 10 [0002] In communication systems, such as Long Term Evolved (LTE) communication systems or the 5th generation wireless systems (5G), if a terminal device is to handover from a current serving cell to a target cell, the terminal device may measure a channel quality of the target cell. There are often two situations: (1) the target cell is at the same frequency as the current serving cell and (2) the target cell is at a
15 different frequency from the current serving cell. Further research is still needed regarding the above two situations.

SUMMARY

- [0003] Generally, embodiments of the present disclosure relate to a method for a
20 modulation of downlink transmission and the corresponding network device and terminal device.

- [0004] In a first aspect, embodiments of the present disclosure provide a method implemented at a terminal device for communication. The method comprises: receiving, from a network device, a first configuration at least indicating first set of
25 time slots for an intra-frequency measurement of the terminal device; receiving, from the network device, a second configuration at least indicating a second set of time slots for a measurement gap of the terminal device; in response to the first and second sets of time slots being partially overlapped, determining one or more slots from the first set of time slots for the intra-frequency measurement of the terminal device based
30 on resource control information for sharing overlapped time slots between the intra-frequency measurement and the measurement gap.

[0005] In a second aspect, embodiments of the present disclosure provide a method implemented at a network device for communication. The method comprises: transmitting, to a terminal device, a first configuration at least indicating first set of time slots for an intra-frequency measurement of the terminal device; transmitting,
5 to the terminal device, a second configuration at least indicating a second set of time slots for a measurement gap of the terminal device; and transmitting, to the terminal device, resource control information for sharing overlapped time slots between the intra-frequency measurement and the measurement gap.

[0006] In a third aspect, embodiments of the disclosure provide a terminal device.
10 The terminal device comprises: at least one processor; and a memory coupled to the at least one processor, the memory storing instructions therein, the instructions, when executed by the at least one processor, causing the network device to perform acts including: receiving, from a network device, a first configuration at least indicating first set of time slots for an intra-frequency measurement of the terminal device;
15 receiving, from the network device, a second configuration at least indicating a second set of time slots for a measurement gap of the terminal device; in response to the first and second sets of time slots being partially overlapped, determining one or more slots from the first set of time slots for the intra-frequency measurement of the terminal device based on resource control information for sharing overlapped time
20 slots between the intra-frequency measurement and the measurement gap.

[0007] In a fourth aspect, embodiments of the disclosure provide a network device. The network device comprises: at least one processor; and a memory coupled to the at least one processor, the memory storing instructions therein, the instructions, when executed by the at least one processor, causing the arbitrating terminal device to
25 perform acts including: transmitting, to a terminal device, a first configuration at least indicating first set of time slots for an intra-frequency measurement of the terminal device; transmitting, to the terminal device, a second configuration at least indicating a second set of time slots for a measurement gap of the terminal device; and transmitting, to the terminal device, resource control information for sharing
30 overlapped time slots between the intra-frequency measurement and the measurement gap.

[0008] In a fifth aspect, embodiments of the disclosure provide a computer readable

medium. The computer readable medium stores instructions thereon, the instructions, when executed by at least one processing unit of a machine, causing the machine to implement: receiving, from a network device, a first configuration at least indicating first set of time slots for an intra-frequency measurement of the terminal device; receiving, from the network device, a second configuration at least indicating a second set of time slots for a measurement gap of the terminal device; in response to the first and second sets of time slots being partially overlapped, determining one or more slots from the first set of time slots for the intra-frequency measurement of the terminal device based on resource control information for sharing overlapped time slots between the intra-frequency measurement and the measurement gap.

[0009] In a sixth aspect, embodiments of the disclosure provide a further computer readable medium. The further computer readable medium stores instructions thereon, the instructions, when executed by at least one processing unit of a machine, causing the machine to implement: transmitting, to a terminal device, a first configuration at least indicating first set of time slots for an intra-frequency measurement of the terminal device; transmitting, to the terminal device, a second configuration at least indicating a second set of time slots for a measurement gap of the terminal device; and transmitting, to the terminal device, resource control information for sharing overlapped time slots between the intra-frequency measurement and the measurement gap.

[0010] Other features and advantages of the embodiments of the present disclosure will also be apparent from the following description of specific embodiments when read in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of embodiments of the disclosure.

25

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Embodiments of the disclosure are presented in the sense of examples and their advantages are explained in greater detail below, with reference to the accompanying drawings, where

[0012] Fig. 1 illustrates a schematic diagram of a communication system according to embodiments of the present disclosure;

[0013] Fig. 2 illustrates a schematic diagram of fully overlapping in time slots

between the intra-frequency measurement and the measurement gap;

[0014] Fig. 3 illustrates a schematic diagram of non-overlapping in time slots between the intra-frequency measurement and the measurement gap;

5 [0015] Fig. 4 illustrates a schematic diagram of partially overlapping in time slots between the intra-frequency measurement and the measurement gap according to embodiments of the present disclosure;

[0016] Fig. 5 illustrates an interaction operation between a terminal device and a network device according to embodiments of the present disclosure;

10 [0017] Fig. 6 illustrates a flow chart of a method implemented at a terminal device for communication according to embodiments of the present disclosure;

[0018] Fig. 7 illustrates a flow chart of a method implemented at a network device for communication according to embodiments of the present disclosure; and

[0019] Fig. 8 illustrates a schematic diagram of a device according to embodiments of the present disclosure.

15 [0020] Throughout the figures, same or similar reference numbers indicate same or similar elements.

DETAILED DESCRIPTION OF EMBODIMENTS

20 [0021] The subject matter described herein will now be discussed with reference to several example embodiments. It should be understood these embodiments are discussed only for the purpose of enabling those skilled persons in the art to better understand and thus implement the subject matter described herein, rather than suggesting any limitations on the scope of the subject matter.

25 [0022] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of example embodiments. As used herein, the singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises,” “comprising,” “includes” and/or “including,” when used herein, specify the presence of stated features, integers, steps, operations,
30 elements and/or components, but do not preclude the presence or addition of one or

more other features, integers, steps, operations, elements, components and/or groups thereof.

[0023] It should also be noted that in some alternative implementations, the functions/acts noted may occur out of the order noted in the figures. For example,
5 two functions or acts shown in succession may in fact be executed concurrently or may sometimes be executed in the reverse order, depending upon the functionality/acts involved.

[0024] As used herein, the term “communication network” refers to a network following any suitable communication standards, such as Long Term Evolution (LTE),
10 LTE-Advanced (LTE-A), Wideband Code Division Multiple Access (WCDMA), High-Speed Packet Access (HSPA), and so on. Furthermore, the communications between a terminal device and a network device in the communication network may be performed according to any suitable generation communication protocols, including, but not limited to, the first generation (1G), the second generation (2G),
15 2.5G, 2.75G, the third generation (3G), the fourth generation (4G), 4.5G, the future fifth generation (5G) communication protocols, and/or any other protocols either currently known or to be developed in the future.

[0025] Embodiments of the present disclosure may be applied in various communication systems. Given the rapid development in communications, there
20 will of course also be future type communication technologies and systems with which the present disclosure may be embodied. It should not be seen as limiting the scope of the present disclosure to only the aforementioned system.

[0026] The term “network device” includes, but not limited to, a base station (BS), a gateway, a management entity, and other suitable device in a communication system.
25 The term “base station” or “BS” represents a node B (NodeB or NB), an evolved NodeB (eNodeB or eNB), a Remote Radio Unit (RRU), a radio header (RH), a remote radio head (RRH), a relay, a low power node such as a femto, a pico, and so forth.

[0027] The term “terminal device” includes, but not limited to, “user equipment (UE)” and other suitable end device capable of communicating with the network device.
30 By way of example, the “terminal device” may refer to a terminal, a Mobile Terminal (MT), a Subscriber Station (SS), a Portable Subscriber Station, a Mobile Station (MS), or an Access Terminal (AT).

[0028] The term “intra-frequency measurement” used herein refers to measuring a signal quality of a target cell if the target cell is at the same frequency as the current serving cell of the terminal device. The term “inter-frequency measurement” used herein refers to measuring a signal quality of a target cell if the target cell is at a different frequency from the current serving cell of the terminal device.

[0029] The term “measurement gap” used herein refers to a gap during which no transmission and reception happens. Since there is no signal transmission and reception during the gap, the terminal device can switch to the target cell and perform the signal quality measurement and come back to the current cell.

[0030] As described above, there are often two situations in measuring a channel quality of the target cell: (1) the target cell is at the same frequency as the current serving cell and (2) the target cell is at a different frequency from the current serving cell. Further research is still needed regarding the above two situations. The above situation (1) refers to an intra-frequency measurement and the situation (2) refers to an inter-frequency measurement.

[0031] As introduced above, the measurement gap is a gap during which no transmission and reception happens. In the situation of inter-frequency measurement, the measurement gap is needed since the terminal device needs to switch a different frequency to perform the inter-frequency measurement. In the situation of intra-frequency measurement, the measurement gap may still be needed in some scenarios. For example, even in the situation of intra-frequency measurement, if synchronization signal blocks (SSBs) of the serving cell are not completely within the terminal downlink operating bandwidth, the measurement gap is needed to allow the terminal device to switch to the frequency to be measured.

[0032] Generally speaking, the network device usually only configure one measurement pattern to the terminal device. From the view of time domain, the time slots for performing intra-measurement may be overlapped with the time slots for the measurement gap. 3GPP standard 38.133 has introduced gap sharing mechanism between the intra-frequency measurement and the inter-frequency measurement in the time slots for performing intra-measurement are fully overlapped with the time slots for the measurement gap. However, it has not been discussed that how the overlapped time slots being shared between the intra-frequency and the measurement

gap if the time slots for performing intra-measurement are partially overlapped with the time slots for the measurement gap.

[0033] In order to at least in part solve above and other potential problems, embodiments of the present disclosure provide a salutation for new radio management measurement. Now some example embodiments of the present disclosure are described below with reference to the figures. However, those skilled in the art would readily appreciate that the detailed description given herein with respect to these figures is for explanatory purpose as the present disclosure extends beyond theses limited embodiments.

[0034] Fig. 1 illustrates a schematic diagram of a communication system in which embodiments of the present disclosure can be implemented. The communication system 100, which is a part of a communication network, includes a network device 120 and one or more terminal devices 110-1 and 110-2. It is to be understood that the communication system 100 may include any suitable number of terminal devices. . It should be noted that the communication system 100 may also include other elements which are omitted for the purpose of clarity. The network device 120 may communicate with the terminal devices 110. It is to be understood that the number of network devices and terminal devices shown in Fig. 1 is given for the purpose of illustration without suggesting any limitations. The communication system 100 may include any suitable number of network devices and terminal devices.

[0035] Communications in the communication system 100 may be implemented according to any proper communication protocol(s), including, but not limited to, cellular communication protocols of the first generation (1G), the second generation (2G), the third generation (3G), the fourth generation (4G) and the fifth generation (5G) and on the like, wireless local network communication protocols such as Institute for Electrical and Electronics Engineers (IEEE) 802.11 and the like, and/or any other protocols currently known or to be developed in the future. Moreover, the communication may utilize any proper wireless communication technology, including but not limited to: Code Divided Multiple Address (CDMA), Frequency Divided Multiple Address (FDMA), Time Divided Multiple Address (TDMA), Frequency Divided Duplexer (FDD), Time Divided Duplexer (TDD), Multiple-Input Multiple-Output (MIMO), Orthogonal Frequency Divided Multiple Access (OFDMA)

and/or any other technologies currently known or to be developed in the future.

[0036] Fig. 2 illustrates a schematic diagram of fully overlapping in time slots between the intra-frequency measurement and the measurement gap. The time slot set 210 for the measurement may include time slots 210-1, 210-2, 210-3, 210-4, 210-5 and 210-6. It is to be understood that the time slot set 210 may include any suitable number of time slots. The time slots set 220 for intra-frequency measurements may include time slots 220-1, 220-2, 220-3, 220-4, 220-5 and 220-6. It is to be understood that the time slot set 220 may include any suitable number of time slots. As shown in Fig. 2, the time slot set 210 are fully overlapped with the time slot set 220.

[0037] As described above, 3GPP standard 38.133 has introduced gap sharing mechanism between the intra-frequency measurement and the inter-frequency measurement in the time slots for performing intra-measurement are fully overlapped with the time slots for the measurement gap. The network device may transmit a parameter "X" (for example, gap sharing factor) via a radio resource control (RRC) signaling to indicate how the fully overlapped time slots shared between the intra-frequency measurement and the measurement gap. Table 1 below in the 3GPP standard 38.133 defines the parameter "X."

TABLE 1

Network signaling ParameterName	Value of X (%)
"00"	X_1
"01"	X_2
"10"	X_3
"11"	X_4

[0038] By way of example, if the parameter "00" is transmitted via the RRC signaling, $X_1\%$ of the fully overlapped time slots are to be used for the intra-frequency measurement. If the parameter "01" is transmitted via the RRC signaling, $X_2\%$ of the fully overlapped time slots are to be used for the intra-frequency measurement. If the parameter "10" is transmitted via the RRC signaling, $X_3\%$ of the fully overlapped time slots are to be used for the intra-frequency measurement. If the parameter "11" is transmitted via the RRC signaling, $X_4\%$ of the fully overlapped

time slots are to be used for the intra-frequency measurement. In this scenario, the performance of intra-frequency defined in section 9.2 of the 3GPP standard 38.133 is scaled by $K_{\text{intra}}=1/X * 100$ and the performance of inter-frequency defined in section 9.2 of the 3GPP standard 38.133 is scaled by $K_{\text{inter}}=1/(100-X)*100$.

5 [0039] Fig. 3 illustrates a schematic diagram of non-overlapping in time slots between the intra-frequency measurement and the measurement gap. The time slot set 310 for the measurement gap may include time slot 310-1, 310-2, 310-3, 310-4, 310-5 and 310-6. It is to be understood that the time slot set 310 may include any suitable number of time slots. The time slot set 320 for intra-frequency measurements may
10 include time slot 320-1, 320-2, 320-3, 320-4, 320-5 and 320-6. It is to be understood that the time slot set 320 may include any suitable number of time slots. As shown in Fig. 3, time slot set 310 is non-overlapped with time slot set 320. In such situation, there is no need sharing time slots between the intra-frequency measurement and the measurement gap. Due to signaling overheads, the network may unlikely configure
15 non-overlapping in time slots between the intra-frequency measurement and the measurement gap.

[0040] Fig. 4 illustrates a schematic diagram of partially overlapping in time slots between the intra-frequency measurement and the measurement gap according to embodiments of the present disclosure. Fig. 5 illustrates an example interaction
20 diagram of operation 500 between the terminal device 110 and the network device 120 according to embodiments of the present disclosure. The interaction operation 500 will be described with reference to Fig. 4 below.

[0041] In some embodiments, the terminal device 110 may measure a channel quality of a target cell for handover. The terminal device 110 may measure reference signals
25 strength to obtain information of the channel quality of the target cell. For example, the terminal device 110 may obtain the channel quality of the target cell for handover based on reference signal receiving power (RSRP). As mentioned above, there are two types of measurements, that is, the intra-frequency measurement and inter-frequency measurement. In the situation of inter-frequency measurement, the
30 measurement gap is needed since the terminal device needs to switch a different frequency to perform the inter-frequency measurement. In the situation of intra-frequency measurement, the measurement gap may still be needed in some

scenarios.

[0042] The network device 120 transmits 510 a configuration for the intra-frequency measurement (referring to as “a first configuration”) to the terminal device 110. In an example embodiment, the first configuration may be transmitted via a RRC signaling. By way of example, the network device 120 may send SS block based RRM measurement timing configuration (SMTC) to the terminal device 110 for intra-frequency measurement. In some embodiments, the first configuration may include information of a measuring window for the intra-frequency measurement. In an example embodiment, the first configuration may indicate duration of the measuring window. For example, the first configuration may indicate that duration of one measuring window is 5ms. It is to be understood that the duration of one measuring window may be any suitable value. Additionally or alternatively, the first configuration may include the periodicity of the measuring window. That is to say, the first configuration may indicate how long the measuring windows should be repeated.

[0043] In some embodiments, the first configuration may also indicate the starting position of the measured window in the time slots of the serving cell for intra-frequency measurement. For example, since every cell has its own clock, the first configuration may indicate a time slot at which the first measured window starts. By way of example, the first configuration may indicate that the measuring window is to start from the 100th time slot. The first configuration indicates a set of time slots 420 (referring to as “first set of time slots”) is to be used for performing the intra-frequency measurement.

[0044] In a further embodiment, the terminal device 110 may determine the first set of time slots 420 based on the information of the measuring window. For example, the information of the measuring window may include that the duration of one measuring window is 5ms and the measuring window may be repeated every 40ms. The information of the measuring window may also include that the measuring window starts from the 100th time slot. In this example, the terminal device 110 may determine time slots 420-1, 420-2, 420-3, 420-4, 420-5, 420-6 and 420-7 as the first set of time slots 420. It is to be understood that the first set of time slots 420 may include any suitable number of time slots. Each of the time slots 420-1, 420-2,

420-3, 420-4, 420-5, 420-6 and 420-7 has duration of 5ms and the time interval between any adjacent two of them is 40ms.

[0045] In some embodiment, the network device 120 may also transmit configuration for inter-frequency measurement. By way of example, the network device 120 may send SS block based RRM measurement timing configuration (SMTC) to the terminal device 110 for inter-frequency measurement via a RRC signaling. In some embodiments, the configuration may include information of a measuring window for the inter-measurement. In an example embodiment, the configuration may indicate duration of the measuring window. For example, the configuration may indicate that duration of one measuring window is 40ms. It is to be understood that the duration of one measuring window may be any suitable value. Additionally or alternatively, the configuration may include the periodicity of the measuring window. That is to say, the configuration may indicate how long the measuring windows should be repeated. In some embodiments, the configuration may also indicate the starting position of the measured window in the time slots of the serving cell for inter-frequency measurement.

[0046] The network device 120 transmits a configuration for the measurement gap (referring to as “a second configuration”) to the terminal device 110. In an example embodiment, the second configuration may be transmitted via a RRC signaling. By way of example, the second configuration may indicate duration of the measurement gap. For example, the second configuration may indicate that duration of one measurement gap is 40ms or 80ms. It is to be understood that the duration of one measurement gap may be any suitable value. Additionally or alternatively, the second configuration may include the periodicity of the measurement gap. That is to say, the second configuration may indicate how long the measurement gap should be repeated.

[0047] In some embodiments, the second configuration may also indicate the starting position of the measurement gap in the time slots of the serving cell. For example, since every cell has its own clock, the second configuration may indicate a time slot at which the first measurement gap starts.

[0048] In a further embodiment, the terminal device 110 may determine the second set of time slots 410 based on the second configuration for the measurement gap.

For example, the second configuration may include that the duration of one measurement gap is 6ms and the measurement gap may be repeated every 80ms. The second configuration may also include that the first measurement gap starts from the 100th time slot. In this example, the terminal device 110 may determine time slots 410-1, 410-2, 410-3 and 410-4 as the second set of time slots 410. It is to be understood that the second set of time slots 410 may include any suitable number of time slots. Each of the time slots 410-1, 410-2, 410-3 and 410-4 has duration of 6ms and the time interval between any adjacent two of them is 80ms.

[0049] The network device 120 transmits 530 resource control information for sharing overlapped time slots between the intra-frequency measurement and the measurement gap. In some embodiments, the resource control information may be transmitted together with the first configuration or the second configuration. In other embodiment, the resource control information may be transmitted as a new signaling defined in RRC signaling.

[0050] In some embodiments, the resource control information may include a parameter for sharing the overlapped time slots. In an example embodiment, the resource control information may include the parameter "X" (for example, gap sharing factor) shown in Table 1. Alternatively, the resource control information may include another parameter which is defined in a new signaling and is different from the above parameter "X".

[0051] In other embodiments, the resource control information may other information that may affect the behavior of the terminal device 110. For example, the resource control information may include the number of frequencies at which the intra-frequency measurement is performed. The resource control information may also include the number of frequencies at which the inter-frequency measurement is performed. Alternatively, the resource control information may include an overlapping ratio between the first set of time slots 420 and the second set of time slots 410. In a further example, the resource control information may include information regarding whether the intra-frequency measurement is performed without interrupting data scheduling. As described above, the intra-frequency measurement also needs the measurement gap in some situations. For example, the intra-frequency measurement on high frequency bands may lead to interruption to

data scheduling in the serving cell. In such situation, the terminal device 110 may perform the intra-frequency measurement during the time slots that are overlapped with the measurement gap. In this way, since the terminal device 110 does not use the time slots which are not overlapping with the measurement gap for
5 intra-frequency measurement, those time slots can still be used for data scheduling, so the total interruption is reduced.

[0052] The terminal device 110 determines 540 whether the first set of time slots 420 and the second set of time slots 410 are partially overlapped. By way of example, the terminal device 110 may determine that time slots 410-1 and 420-1, time slots
10 410-2 and 420-3, time slots 41-03 and 420-5, and time slots 410-4 and 4207 are overlapped.

[0053] The terminal device 110 determines 550 one or more time slots for intra-frequency measurement based on the resource control information. In this way, the priority of intra-frequency measurement and the inter-frequency measurement
15 may be controlled by the network device. The network device may also know the terminal device behaviors and the expected measurement performances related to the behaviors.

[0054] In some embodiments, the terminal device 110 may determine a parameter for sharing the overlapped time slots. By way of example, the terminal device 110 may
20 extract a specific parameter from the resource control information. As described above, in an example embodiment, the resource control information may include the parameter "X" (for example, gap sharing factor) as introduced in the 3GPP standards 38.133. For example, if the value of the parameter "X" (gap sharing factor) is 50%, the terminal device 110 may determine 50% of the overlapped time slots are used for
25 intra-frequency measurement. In this example, the terminal device 110 may determine that time slots 420-2, 420-3, 420-4, 420-6 and 420-7 for intra-frequency measurement. In this situation, the intra-frequency measurement requirement is scaled by a factor of $1/(Y+Z*(1-Y))$, where Z is the gap sharing factor between the intra-frequency and the inter-frequency measurements and Y is the percentage of time
30 slots for the intra-frequency not overlapped with the time slots for the measurement gap.

[0055] In a further embodiment, the resource control information may not include the

parameter "X". The terminal device 110 may only use the time slots in the first set of time slots 420 which are not overlapped with the second set of time slots 410 for intra-frequency. For example, the terminal device may determine time slots 420-2, 420-4 and 420-6 for intra-frequency measurement. In this situation, the
5 intra-frequency measurement requirement is scaled by a factor of $1/Y$, where Y is the percentage of time slots for the intra-frequency not overlapped with the time slots for the measurement gap.

[0056] Alternatively, the resource control information may the resource control information may include another parameter which is defined in a new signaling for
10 sharing the overlapped time slots. For example, the resource control information may include the parameter indicating that none of the overlapped time slots are used for intra-frequency measurement. In other embodiment, the resource control information may include the parameter indicating that a certain percentage of the overlapped time slots are used for intra-frequency measurement.

[0057] In some embodiments, the terminal device 110 may determine the parameter
15 for sharing the overlapped time slots for intra-frequency measurement based on information included in the resource control information. By way of example, the resource control information may the number of frequencies at which the intra-frequency measurement is performed and number of frequencies at which the
20 inter-frequency measurement is performed. The terminal device 110 may determine a parameter indicating the percentage of the overlapped time slots to be used for the intra-frequency measurement based on the above numbers of frequencies. If the number of frequencies at which the intra-frequency measurement is smaller than the number of frequencies at which the inter-frequency measurement is performed, the
25 terminal device 110 may determine that the percentage of the overlapped time slots for intra-frequency measurement is smaller than the percentage of the overlapped time slots for the measurement gap.

[0058] In another embodiment, the resource control information may include an
30 overlapping ratio between the first set of time slots 420 and the second set of time slots 410. The terminal device 110 may determine a parameter indicating the percentage of the overlapped time slots to be used for the intra-frequency measurement based on the overlapping ratio. If the overlapping ratio is smaller than a

predetermined threshold, the terminal device 110 may determine that the percentage of the overlapped time slots for intra-frequency measurement is smaller than the percentage of the overlapped time slots for the measurement gap.

[0059] In a further example, the resource control information may include information regarding whether the intra-frequency measurement is performed without interrupting data scheduling. As described above, the intra-frequency measurement also needs the measurement gap in some situations. For example, the intra-frequency measurement on high frequency bands may lead to interruption to data scheduling in the serving cell. In such situation, the terminal device 110 may determine that the overlapped time slots are used for intra-frequency measurement based on the information. In this way, since the terminal device 110 does not use the time slots which are not overlapping with the measurement gap for intra-frequency measurement, those time slots can still be used for data scheduling, so the total interruption is reduced.

[0060] Fig. 6 illustrates a flow chart of method 600 in accordance with an example of the present disclosure. The method 600 may be implemented at the terminal device 110.

[0061] At block 610, the terminal device 110 receives a first configuration for an intra-frequency measurement of the terminal device 110 from the network device 120. The first configuration indicates first set of time slots 420 for the intra-frequency measurement. In an example embodiment, the first configuration may be received via the RRC signaling.

[0062] In some embodiments, the first configuration may include information of a measuring window for the intra-frequency measurement. In an example embodiment, the first configuration may indicate duration of the measuring window. Additionally or alternatively, the first configuration may include the periodicity of the measuring window. That is to say, the first configuration may indicate how long the measuring windows should be repeated. In some embodiments, the first configuration may also indicate the starting position of the measured window in the time slots of the serving cell for intra-frequency measurement.

[0063] At block 620, the terminal device 110 receives a second configuration for a measurement gap of the terminal device 110 from the network device 120. The

second configuration indicates second set of time slots 410 for the measurement gap. In an example embodiment, the second configuration may be transmitted via a RRC signaling.

[0064] By way of example, the second configuration may indicate duration of the measurement gap. Additionally or alternatively, the second configuration may include the periodicity of the measurement gap. That is to say, the second configuration may indicate how long the measurement gap should be repeated. In some embodiments, the second configuration may also indicate the starting position of the measurement gap in the time slots of the serving cell.

[0065] At block 630, the terminal device 110 determines whether the first set of time slots 420 and the second set of time slots 410 are partially overlapped. If the first set of time slots 420 and the second set of time slots 410 are partially overlapped, at block 640, the terminal device 110 determines one or more slots from the first set of time slots 420 for the intra-frequency measurement of the terminal device 120 based on resource control information. In some embodiments, the terminal device 110 may determine a parameter for sharing the overlapped time slots based on the resource control information. The terminal device 110 may determine the one or more time slots based on the parameter.

[0066] In some embodiments, the resource control information may be transmitted together with the first configuration or the second configuration. In other embodiment, the resource control information may be transmitted as a new signaling defined in RRC signaling.

[0067] In some embodiments, the resource control information may include a parameter for sharing the overlapped time slots. In an example embodiment, the resource control information may include the parameter "X" (for example, gap sharing factor) as introduced in the 3GPP standards 38.133. Alternatively, the resource control information may include another parameter which is defined in a new signaling and is different from the above parameter "X".

[0068] In other embodiments, the resource control information may include other information that may affect the behavior of the terminal device 110. For example, the resource control information may include the number of frequencies at which the intra-frequency measurement is performed. The resource control information may

also include the number of frequencies at which the inter-frequency measurement is performed. Alternatively, the resource control information may include an overlapping ratio between the first set of time slots 420 and the second set of time slots 410. In other example, the resource control information may include
5 information about whether the intra-frequency measurement is performed without interrupting data scheduling.

[0069] Fig. 7 illustrates a flow chart of method 700 in accordance with an example of the present disclosure. The method 700 may be implemented at the network device 120.

10 [0070] At block 710, the network device 120 transmits a first configuration for an intra-frequency measurement of the terminal device 110 to the terminal device 110. The first configuration indicates first set of time slots 420 for the intra-frequency measurement. In an example embodiment, the first configuration may be received via the RRC signaling.

15 [0071] In some embodiments, the first configuration may include information of a measuring window for the intra-frequency measurement. In an example embodiment, the first configuration may indicate duration of the measuring window. Additionally or alternatively, the first configuration may include the periodicity of the measuring window. That is to say, the first configuration may indicate how long the
20 measuring windows should be repeated. In some embodiments, the first configuration may also indicate the starting position of the measured window in the time slots of the serving cell for intra-frequency measurement.

[0072] At block 720, the network device 120 transmits a second configuration for a measurement gap of the terminal device 110 to the terminal device 110. The second
25 configuration indicates second set of time slots 410 for the measurement gap. In an example embodiment, the second configuration may be transmitted via a RRC signaling.

[0073] By way of example, the second configuration may indicate duration of the measurement gap. Additionally or alternatively, the second configuration may
30 include the periodicity of the measurement gap. That is to say, the second configuration may indicate how long the measurement gap should be repeated. In some embodiments, the second configuration may also indicate the starting position

of the measurement gap in the time slots of the serving cell.

[0074] At block 730, the network device 120 transmits the resource control information for sharing overlapped time slots between the intra-frequency measurement and the measurement gap to the terminal device 110. In some
5 embodiments, the resource control information may be transmitted together with the first configuration or the second configuration. In other embodiment, the resource control information may be transmitted as a new signaling defined in RRC signaling.

[0075] In some embodiments, the resource control information may include a parameter for sharing the overlapped time slots. In an example embodiment, the
10 resource control information may include the parameter "X" (for example, gap sharing factor) as introduced in the 3GPP standards 38.133. Alternatively, the resource control information may include another parameter which is defined in a new signaling and is different from the above parameter "X".

[0076] In other embodiments, the resource control information may other information
15 that may affect the behavior of the terminal device 110. For example, the resource control information may include the number of frequencies at which the intra-frequency measurement is performed. The resource control information may also include the number of frequencies at which the inter-frequency measurement is performed. Alternatively, the resource control information may include an
20 overlapping ratio between the first set of time slots 420 and the second set of time slots 410. In other example, the resource control information may include information about whether the intra-frequency measurement is performed without interrupting data scheduling.

[0077] Fig. 8 is a simplified block diagram of a device 800 that is suitable for
25 implementing embodiments of the present disclosure. The device 800 may be implemented at the network device 120. The device 800 may also be implemented at the terminal device 110. As shown, the device 800 includes one or more processors 810, one or more memories 820 coupled to the processor(s) 810, one or more transmitters and/or receivers (TX/RX) 840 coupled to the processor 810.

30 [0078] The processor 810 may be of any type suitable to the local technical network, and may include one or more of general purpose computers, special purpose computers, microprocessors, digital signal processors (DSPs) and processors based on

multicore processor architecture, as non-limiting examples. The device 600 may have multiple processors, such as an application specific integrated circuit chip that is slaved in time to a clock which synchronizes the main processor.

5 [0079] The memory 820 may be of any type suitable to the local technical network and may be implemented using any suitable data storage technology, such as a non-transitory computer readable storage medium, semiconductor based memory devices, magnetic memory devices and systems, optical memory devices and systems, fixed memory and removable memory, as non-limiting examples.

10 [0080] The memory 820 stores at least a part of a program 830. The TX/RX 840 is for bidirectional communications. The TX/RX 840 has at least one antenna to facilitate communication, though in practice an Access Node mentioned in this application may have several ones. The communication interface may represent any interface that is necessary for communication with other network elements.

15 [0081] The program 830 is assumed to include program instructions that, when executed by the associated processor 810, enable the device 800 to operate in accordance with the embodiments of the present disclosure, as discussed herein with reference to Figs. 4 to 7. That is, embodiments of the present disclosure can be implemented by computer software executable by the processor 810 of the device 800, or by hardware, or by a combination of software and hardware.

20 [0082] While this specification contains many specific implementation details, these should not be construed as limitations on the scope of any disclosure or of what may be claimed, but rather as descriptions of features that may be specific to particular embodiments of particular disclosures. Certain features that are described in this specification in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described
25 in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases
30 be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

[0083] Similarly, while operations are depicted in the drawings in a particular order,

this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various
5 system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

[0084] Various modifications, adaptations to the foregoing exemplary embodiments of
10 this disclosure may become apparent to those skilled in the relevant arts in view of the foregoing description, when read in conjunction with the accompanying drawings. Any and all modifications will still fall within the scope of the non-limiting and exemplary embodiments of this disclosure. Furthermore, other embodiments of the disclosures set forth herein will come to mind to one skilled in the art to which these
15 embodiments of the disclosure pertain having the benefit of the teachings presented in the foregoing descriptions and the associated drawings.

[0085] Therefore, it is to be understood that the embodiments of the disclosure are not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims.
20 Although specific terms are used herein, they are used in a generic and descriptive sense only and not for purpose of limitation.