

WHAT IS CLAIMED IS:

1. A method, comprising:
5 determining a grant for data to be communicated, comprising identifying logical channels to be multiplexed into a medium access control protocol data unit for the data to be communicated,
wherein at least one of a logical channel identifier for at least one logical channel of the multiplexed logical channels and length of at least one logical channel
10 service data unit is configured to be omitted from the medium access control protocol data unit.
2. The method of claim 1, comprising:
determining that the grant is fulfilling at least one pre-established condition, wherein
15 the at least one pre-established condition comprises the grant is for use with only one logical channel, and wherein based on the pre-established condition the grant comprises a logical channel identifier for the one logical channel is omitted from the medium access control protocol data unit.
- 20 3. The method of claim 2, wherein the grant further comprises a Length field of a medium access control subheader is set to all zeros to indicate that no more service data units for the at least one logical channel configured to omit logical channel identity will follow.
- 25 4. The method of claim 2, wherein the grant further comprises a one bit data control field is set to indicate that one of a Length field follows for a service data unit of a logical channel configured with logical channel identity omit, or a logical channel identifier subheader follows for at least one of a control element or a service data unit of a logical channel not configured with omitted logical channel identity.
30
5. The method of claim 2, wherein the at least one pre-established condition comprises the identified logical channels being more than one logical channel and only one logical channel of the more than one logical channel has no data to send, and wherein based on the pre-established condition the grant comprises a logical channel

identifier for the only one logical channel is omitted, and a one-byte length field is set to all zeros.

6. The method of claim 2, wherein logical channel identifier for more than one
5 logical channels configured to be omitted from the medium access control protocol data unit, wherein the grant comprises those logical channels in a pre-established order.

7. The method of claim 2, comprising:
determining a subset of the more than one logical channel with no data to send;
10 and
based on the determining, configuring a Length to be set to all zeros to indicate a start of a next logical channel without a logical channel identifier for the subset of the more than one logical channel.

8. The method of claim 1, comprising omitting the length field from a service data
15 unit of a common control channel service data unit of the medium access control protocol data unit.

9. The method of claim 8, wherein the omitting is based on determining that a
20 length field for the common control channel service data unit of the medium access control meets an exact size criterion.

10. The method of claim 8, wherein the omitting is based on at least one of
determining that a same logical channel identifier is used for common control channel
25 service data units of different sizes and determining that a grant size for Msg3 meets an exact size criterion of a size of the common control channel service data unit + at least one octet.

11. The method of claim 10, wherein the common control channel service data units
30 of different sizes using the same logical channel identifier are indicated by a random access preamble group identifier.

12. The method of claim 1, wherein the common control channel service data unit for the medium access control protocol data unit is configured with several logical channel identifiers linked to different fixed sizes for one or more logical channels of the
5 at least one logical channel of the multiplexed channels.

13. The method of claim 10, wherein the determining that the grant size for Msg3 meets an exact size criterion comprises determining that the common control channel service data unit size plus an R/LCID subheader of the medium access control protocol
10 data unit is equal to Msg3 size.

14. An apparatus, comprising:

means for determining a grant for data to be communicated, comprising
identifying logical channels to be multiplexed into a medium access control protocol
15 data unit for the data to be communicated,

wherein at least one of a logical channel identifier for at least one logical channel of the multiplexed logical channels and length of at least one logical channel service data unit is configured to be omitted from the medium access control protocol data unit.

20

15. The apparatus of claim 14, comprising:

determining that the grant is fulfilling at least one pre-established condition, wherein the at least one pre-established condition comprises the grant is for use with only one logical channel, and wherein based on the pre-established condition the grant comprises
25 a logical channel identifier for the one logical channel is omitted from the medium access control protocol data unit.

16. The apparatus of claim 15, wherein the grant further comprises a Length field of a medium access control subheader is set to all zeros to indicate that no more service

data units for the at least one logical channel configured to omit logical channel identity will follow.

17. The apparatus of claim 15, wherein the grant further comprises a one bit data control field is set to indicate that one of a Length field follows for a service data unit of a logical channel configured with logical channel identity omit, or a logical channel identifier subheader follows for at least one of a control element or a service data unit of a logical channel not configured with omitted logical channel identity.

18. The apparatus of claim 15, wherein the at least one pre-established condition comprises the identified logical channels being more than one logical channel and only one logical channel of the more than one logical channel has no data to send, and wherein based on the pre-established condition the grant comprises a logical channel identifier for the only one logical channel is omitted, and a one-byte length field is set to all zeros.

19. The apparatus of claim 15, wherein logical channel identifier for more than one logical channels configured to be omitted from the medium access control protocol data unit, wherein the grant comprises those logical channels in a pre-established order.

20

20. The apparatus of claim 15, comprising:

means for determining a subset of the more than one logical channel with no data to send; and

means, based on the determining, for configuring a Length to be set to all zeros to indicate a start of a next logical channel without a logical channel identifier for the subset of the more than one logical channel.

25

21. The apparatus of claim 14, comprising omitting the length field from the common control channel service data unit of the medium access control protocol data unit.
- 5 22. The apparatus of claim 21, wherein the omitting is based on determining that a length field for the common control channel service data unit of the medium access control meets an exact size criterion.
- 10 23. The apparatus of claim 21, wherein the omitting is based on at least one of determining that a same logical channel identifier is used for common control channel service data units of different sizes and determining that a grant size for Msg3 meets an exact size criterion of a size of the common control channel service data unit + at least one octet.
- 15 24. The apparatus of claim 23, wherein the common control channel service data units of different sizes using the same logical channel identifier are indicated by a random access preamble group identifier.
- 20 25. The apparatus of claim 14, wherein the common control channel service data unit for the medium access control protocol data unit is configured with several logical channel identifiers linked to different fixed sizes for one or more logical channels of the at least one logical channel of the multiplexed channels.
- 25 26. The apparatus of claim 23, wherein the determining that the grant size for Msg3 meets an exact size criterion comprises determining that the common control channel service data unit size plus an R/LCID subheader of the medium access control protocol data unit is equal to Msg3 size.
27. A method, comprising:

receiving a grant for data to be communicated, comprising logical channels multiplexed into a medium access control protocol data unit for the data to be communicated,

5 wherein at least one of a logical channel identifier for at least one logical channel of the multiplexed logical channels and length of at least one logical channel service data unit is configured to be omitted from the medium access control protocol data unit.

28. The method of claim 27, comprising:

10 determining that the grant is fulfilling at least one pre-established condition, wherein the at least one pre-established condition comprises the grant is for use with only one logical channel, and wherein based on the pre-established condition the grant comprises a logical channel identifier for the one logical channel is omitted from the medium access control protocol data unit.

15

29. The method of claim 28, wherein the grant further comprises a Length field of a medium access control subheader set to all zeros to indicate that no more service data units for the at least one logical channel configured to omit logical channel identity will follow.

20

30. The method of claim 28, wherein the at least one pre-established condition comprises the identified logical channels being more than one logical channel and only one logical channel of the more than one logical channel has no data to send, and wherein based on the pre-established condition the grant comprises a logical channel identifier for the only one logical channel is omitted, and a one-byte length field is set to all zeros.

25

31. The method of claim 28, wherein logical channel identifiers for the more than one logical channels are omitted from the medium access control protocol data unit, wherein the grant comprises those logical channels in a pre-established order.

30

32. The method of claim 31, wherein the grant is omitting the length field from the common control channel service data unit of the medium access control protocol data unit.
- 5 33. The method of claim 32, wherein the omitting is based on at least one of that a same logical channel identifier is used for common control channel service data units of different sizes and that a grant size for Msg3 meets an exact size criterion of a size of the common control channel service data unit + at least one octet.
- 10 34. The method of claim 32, wherein the common control channel service data units of different sizes using the same logical channel identifier are indicated by a random access preamble group identifier.
- 15 35. The method of claim 27, wherein the common control channel service data unit for the medium access control protocol data unit is configured with several logical channel identifiers linked to different fixed sizes for one or more logical channels of the at least one logical channel of the multiplexed channels.
- 20 36. The method of claim 35, wherein the determining that the grant size for Msg3 meets an exact size criterion comprises determining that the common control channel service data unit size plus an R/LCID subheader of the medium access control protocol data unit is equal to Msg3 size.
- 25 37. An apparatus, comprising:
means for receiving a grant for data to be communicated, comprising logical channels multiplexed into a medium access control protocol data unit for the data to be communicated,
wherein based on the grant fulfilling at least one pre-established condition at least one of a logical channel identifier for at least one logical channel of the

multiplexed logical channels and length of at least one logical channel service data unit is configured to be omitted from the medium access control protocol data unit.

38. The apparatus of claim 37, comprising:

- 5 determining that the grant is fulfilling at least one pre-established condition, wherein the at least one pre-established condition comprises the grant is for use with only one logical channel, and wherein based on the pre-established condition the grant comprises a logical channel identifier for the one logical channel is omitted from the medium access control protocol data unit.

10

39. The apparatus of claim 38, wherein the grant further comprises a Length field of a medium access control subheader set to all zeros to indicate that no more service data units for the at least one logical channel configured to omit logical channel identity will follow.

15

40. The apparatus of claim 38, wherein the at least one pre-established condition comprises the grant is for use with more than one logical channel and only one logical channel of the more than one logical channel has no data to send, and wherein based on the pre-established condition the grant comprises a logical channel identifier for the
20 only one logical channel is omitted, and a one-byte length field is set to all zeros.

41. The apparatus of claim 30, wherein logical channel identifiers for the more than one logical channels are omitted from the medium access control protocol data unit, wherein the grant comprises those logical channels in a pre-established order.

25

42. The apparatus of claim 37, wherein the grant is omitting the length field from the common control channel service data unit of the medium access control protocol data unit.

30

43. The apparatus of claim 42, wherein the omitting is based on at least one of that a same logical channel identifier is used for common control channel service data units of different sizes and that a grant size for Msg3 meets an exact size criterion of a size of the common control channel service data unit + at least one octet.

44. The apparatus of claim 42, wherein the common control channel service data units of different sizes using the same logical channel identifier are indicated by a random access preamble group identifier.

5

45. The apparatus of claim 44, wherein the common control channel service data unit for the medium access control protocol data unit is configured with several logical channel identifiers linked to different fixed sizes for one or more logical channels of the at least one logical channel of the multiplexed channels.

10

46. The apparatus of claim 40, wherein the determining that the grant size for Msg3 meets an exact size criterion comprises determining that the common control channel service data unit size plus an R/LCID subheader of the medium access control protocol data unit is equal to Msg3 size.