



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7 : E02D 29/02	A1	(11) International Publication Number: WO 00/61880 (43) International Publication Date: 19 October 2000 (19.10.00)
--	----	---

(21) International Application Number: PCT/CA00/00370

(22) International Filing Date: 7 April 2000 (07.04.00)

(30) Priority Data:

2,268,509	8 April 1999 (08.04.99)	CA
2000/0002413	19 January 2000 (19.01.00)	KR

(71) Applicants (for all designated States except US): BEON TOP ENTERPRISES LTD. [CA/CA]; Suite 519, World Trade Centre Office Complex, 999 Canada Place, Vancouver, British Columbia V6C 3E1 (CA). VERSA-LOK ASIA INC. [MY/MY]; 3 Shenton Way, #03-06B, Shenton House, 068805 Singapore (MY).

(72) Inventor; and

(75) Inventor/Applicant (for US only): KIM, Hun, S. [KR/CA]; Suite 519, World Trade Centre Office Complex, 999 Canada Place, Vancouver, British Columbia V6C 3E1 (CA).

(74) Agent: MCGRUDER, David, J.; Oyen Wiggs Green & Mutala, 480 - The Station, 601 West Cordova Street, Vancouver, British Columbia V6B 1G1 (CA).

(81) Designated States: AE, AG, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, DZ, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: RETAINING WALL SYSTEM WITH INTERLOCKED WALL-BUILDING UNITS

(57) Abstract

A retaining wall structure built of wall-building units such as sand/soil bags or hardenable building units such as clay bricks has interconnecting members placed between adjacent courses of units to attach the adjacent courses to one another. The interconnecting members are plates having projections on both sides which protrude into the wall-building units of the adjacent courses. Sheets of geogrid preferably extend from between some of the courses of wall-building units into the fill retained by the wall-building units. Projections on the interconnecting members protrude through holes in the geogrid sheet, anchoring the wall face to the reinforced soil structure.

