

Household robot and method for operating a household robot

The invention relates to a household robot, in particular an automatically movable cleaning robot for a floor area, having a housing, having a running gear which is arranged on the underside of the housing, having a sensor system for detecting the area surrounding the housing and having a control for automatically controlling the running gear. The invention also relates to a method for operating a household robot, in particular an automatically movable cleaning robot for a floor area.

In the context of this description, a household robot is understood as any automatically movable household appliance which carries out at least one household function. In particular, a household robot is understood as an autonomous ground treatment robot, for example a floor cleaning robot, in particular a vacuuming, mopping and/or sweeping robot. Such floor treatment robots have electrically operated suction-fan units and/or electric motor powered brushes and/or bristle rollers and/or mopping units. A lawn mower can also be understood as a ground treatment robot. In addition, a service robot which carries out a different function than a cleaning function, for example a transporting function, is understood as a household robot. The invention without limiting the disclosure is described below mainly in relation to cleaning robots for a floor area in the household which are mainly used as so-called robot vacuum cleaners in private homes and in business premises.

The energy supply of the automatically movable household robot takes place through rechargeable batteries. In order to charge the batteries and, in addition where necessary, to also dispose of the dirt or rubbish collected in a container inside the appliance, a base station connected to the household mains supply is assigned to the household robot.

The household robot locates the base station automatically, e.g. by means of radio guidance and/or light signal guidance or radio communication between base station and household robot. The request to go to the base station can be effected
5 automatically, thus e.g. by radio communication between base station and household robot. The household robot can equally go to the base station by itself depending on the filling level of the dirt container inside the appliance and/or depending on the charge state of the rechargeable batteries. Furthermore, the household robot can automatically go to the base station after completing a task to be carried out, e.g.
10 cleaning a specified floor area.

The automatic functioning of the household robot is considered a valuable characteristic, since the household robot is autonomous and hence can operate without a person being present. In particular, monitoring the floor area to be driven
15 over, particularly the floor area to be cleaned, is left to the household robot alone.

As a consequence, with household robots up to now, the problem has occurred that the floor area is also driven over and where appropriate treated, in particular cleaned, when excrement from a living being, in particular from an animal, but also from a
20 human being, for whatever reason is present. Both urine and faeces are understood as excrement. In such a case, the excrement is distributed either by the running gear over further sub-areas of the floor area or distributed by a cleaning mechanism, which as appropriate is present, on or in the household robot. As a result, in each case an unpleasant situation occurs which the user of the household robot would like to avoid.

25 Therefore, the invention is based on the technical problem of improving household robots and a method for operating a household robot in such a way that the disadvantages described can be at least partly prevented.

The previously identified technical problem is solved according to the invention by a household robot of the type mentioned at the outset providing detection means for detecting a sub-area of the floor area which has been soiled by excrement from a living being and by the control means changing the operating mode of the household
5 robot in dependency of an output signal from the detection means. In this way, the household robot can autonomously react to the presence of excrement on the floor area and prevent additional distribution and further soiling.

Preferably, the control means control the running gear in order to at least partly
10 prevent the soiled sub-area from being driven over. Consequently, the household robot is to a large extent or possibly even completely prevented from driving over the excrement. The household robot only partly driving over the excrement occurs if the excrement can only be detected and localised too late or imprecisely and the running gear cannot be controlled in time or only imprecisely. However, even with only partial
15 prevention, further spreading of the soiling by the excrement can be kept as low as possible. The control means are set up in such a way that the running gear is either turned off or is controlled in such a way that the household robot moves away from the soiled sub-area of the floor or bypasses it.

20 A further embodiment of the described household robot consists in providing a cleaning mechanism and in the control means at least partly preventing the soiled sub-area from being cleaned in dependency of an output signal from the detection means. In this way, in addition or alternatively to controlling the running gear, it can be ensured that the cleaning device is not or only partly soiled by the excrement.

25 There are various possibilities for designing the detection means, in order to achieve the described effect.

In one preferred embodiment of the household robot, the detection means have at
30 least one infrared camera for recording a thermal image of the surroundings of the

housing and evaluation means are provided for evaluating the thermal image. The control then at least partly prevents the soiled sub-area from being driven over and cleaned if at least one sub-area of the thermal image has a predefined difference in temperature to the further surroundings. At the same time, it is preferred if the
5 temperature difference is equal to or greater than 5°C compared to the further surroundings. Therefore, the evaluation means are an image evaluation unit which evaluates the thermal image taken for deviations in the recorded temperature distribution. The evaluation means can consequently detect in a spatially resolved manner excrement or sub-areas of the floor area which are comparably soiled and in
10 any event not to be travelled over. As a result, the robot can be stopped in a targeted way or can bypass the sub-area when the spatial information is transmitted to the control of the running gear.

In an alternative embodiment of the household robot, the detection means have at
15 least one gas sensor for detecting at least one specific gas concentration and evaluation means for evaluating the specific gas concentration are provided. Preferably, the at least one gas sensor is arranged in the front area of the household robot in the normal direction of travel or in the suction area of a floor cleaning robot. The control then at least partly prevents the soiled sub-area from being driven over
20 and cleaned if the specific gas concentration exceeds a predefined limit value. In this case, it does not come down to a conspicuous temperature but rather to a certain smell, i.e. a specific gas concentration, in order to detect a sub-area of the floor area soiled with excrement. Therefore, excrement which has already taken on the surrounding temperature can be reliably detected. However, the spatial resolution is
25 lower compared to a thermal imaging camera.

Preferably, the at least one sensor detects at least one specific concentration of methane, ammonia, butanoic acid, phenol, caproic acid, mercaptans or of hydrogen sulphides. The named gases are specifically for excrement from living beings and

enable excrement to be reliably detected. It is advantageous if a plurality of sensors is used in parallel for different gas concentrations.

5 The above disclosed technical problem is also solved by a method for operating a household robot, in particular an automatically movable cleaning robot for a floor area, wherein the household robot has running gear, in which the floor area to be travelled over is detected for the presence of excrement from a living being, and in which the setting of a function of the household robot is changed when excrement is detected. Hence, a household robot can be operated in such a way that when
10 excrement occurs on the floor area the household robot itself and/or the rest of the floor area is soiled as little as possible if at all. The application of the household robot is thereby more user-friendly.

A first embodiment of the described method consists in the setting of the running gear
15 being changed when excrement is detected on the floor area. In particular, in such a case the running gear can be stopped. It is equally possible when excrement is detected for the sub-area of the floor area which is soiled with the excrement to be bypassed. In this way, the household robot is actively prevented from travelling over the sub-area of the floor area soiled by the excrement and hence the running gear is
20 prevented from further spreading the soiling.

A further embodiment of the described method which can be applied in addition or alternatively to controlling the running gear consists in switching off a cleaning mechanism when excrement is detected. In this case, the household robot is a floor
25 treatment robot having a cleaning mechanism which in particular is designed as an electrically operated suction-fan unit and/or electric motor powered brushes and/or a bristle roller and/or a mopping unit. By means of the described method, it is actively ensured that the cleaning mechanism does not come into contact with the excrement and that soiling of the cleaning mechanism and hence of the household robot itself is
30 to a large extent, if not completely, prevented.

The previously described method can also be further developed by showing the detection of excrement on a display and/or by showing the position of the sub-area of the soiled floor area on a display. In this way, the user of the household robot can be better informed as to why, for example, the household robot has stopped and interrupted its work to be carried out autonomously.

The invention is explained below by means of exemplary embodiments with reference to the figures.

10

Fig. 1 shows an exemplary embodiment of a household robot according to the invention in a perspective view from above and

Fig. 2 shows the household robot illustrated in Fig. 1 in a perspective view from below.

15

A household robot according to the invention in the form of a floor cleaning robot 2 is illustrated in Figs. 1 and 2. The floor cleaning robot 2 has a housing 4, running gear 6 arranged on the underside of the housing 4, a sensor system 8 for detecting the area surrounding the housing 4 and a control for automatically actuating the running gear 6.

20

The running gear 6 is arranged on the underside of the housing 4 and faces the floor area to be cleaned. The running gear 6 has two electric motor powered drive wheels 10 and an idler wheel 11, so that a three-point support of the floor cleaning robot 2 is obtained on the floor area to be cleaned. By controlling the two drive wheels 10 differently, the floor cleaning robot 2 can be moved in any direction, wherein a forward movement in the direction of arrow r is carried out according to Fig. 1. A rotation on the spot and a backward movement in the opposite direction of the arrow r are equally possible.

25

30

As emerges from Fig. 2 in particular, on the underside of the housing 4 an electric motor powered brush 12 protruding beyond the bottom edge is arranged inside a suction opening 14. In addition, a suction fan motor (not illustrated) is provided which
5 is also electrically powered. A dustpan-like ramp 16 is also provided, via which the brushed-up dirt particles are conveyed into a container-like receptacle (not illustrated).

The electric power is supplied to the individual components of the floor cleaning robot
10 2, i.e. to the electric motor of the of the drive wheels 10, to the electric drive of the brush 12, to the suction fan and to the further electronics of the control by means of a rechargeable battery (not illustrated).

In order to be able to identify the surroundings, room boundaries and possible
15 obstacles and in order in particular to prevent the floor cleaning robot 2 from getting stuck, the sensor system 8, which has already been mentioned, is provided which is designed as a sensory obstacle detection system. This consists of an optical transmitting unit and an optical receiver unit which are both integrated in the sensor system 8 illustrated in Fig. 1. In this exemplary embodiment, the sensor system 8 is
20 arranged rotatable around a vertical axis x of the housing 4, as is illustrated with the arrow c in Fig. 1.

According to the invention, detection means 20 are provided for detecting a sub-area of the floor area soiled by excrement from a living being, on which the floor cleaning
25 robot 2 is located, and the control means change the operating mode of the floor cleaning robot 2 dependent on an output signal from the detection means 20. To that end, the control means can control the running gear 6 in such a way that the floor cleaning robot 2 is at least partly prevented from travelling over the soiled sub-area. Alternatively or in addition, the control means can at least partly prevent the soiled

sub-area from being cleaned dependent on an output signal from the detection means 20.

The detection means 20 can be designed differently, as described below.

5

In the case of the exemplary embodiment illustrated in Fig. 1, the detection means 20 have at least one infrared camera 22 for recording a thermal image of the area surrounding the housing 4. Evaluation means (not illustrated), which can also form part of the control, are provided to evaluate the thermal image and the control then at least partly prevents the soiled sub-area from being travelled over and cleaned if at least one sub-area of the thermal image has a predefined difference in temperature to the rest of the surrounding area. In particular, during evaluation a temperature difference which is greater than or equal to 5°C is looked for in the thermal image taken.

15

The activity of the infrared camera 22 can also be shut down, in order to prevent misinterpretations occurring when evaluating the camera signal in rooms which have underfloor heating. A further option consists in detecting regular contours or edges in the image signal of the infrared camera and assigning them to the room. The floor surface can, for example, be heated by rays of sunshine, electric cables or heating pipes, whereby regular contours and edges exist.

20

A further alternative for the design of the detection means is illustrated in Figs. 1 and 2. In this case, the detection means 20 have a gas sensor 24 and/or 26 for detecting at least one specific gas concentration. The evaluation means already referred to are provided for evaluating the specific gas concentration and the control then at least partly prevents the soiled sub-area from being travelled over and cleaned if the specific gas concentration of at least one sensor 24, 26 exceeds a predefined limit value.

25

30

The gas sensor 24 is arranged on the housing 4 in the main direction of travel r. The alternative gas sensor 26, on the other hand, is arranged on the underside of the housing 4 in the area of the suction mouth 14. Thus, in the illustrated exemplary embodiment, two gas sensors 24 and 26 are provided. However, it is also possible for
5 only one of the two gas sensors to be used or for even more gas sensors to be arranged at different places in or on the housing 4.

The gas sensors 24 and/or 26 are able to analyse the surrounding air with respect to a specific gas concentration. The sensor 24 and/or 26 can detect at least one specific
10 concentration of methane, ammonia, butanoic acid, phenol, caproic acid, mercaptans or of hydrogen sulphides. These specific gases are characteristic for excrement of living beings, so that a corresponding output signal, which indicates the presence of excrement, is produced when a limit value of the specific concentration of the gas to be detected is exceeded.

15

As is additionally shown in Fig. 1, the housing 4 has a display 30 on its upper side, on which, inter alia, it can be displayed whether and as the case may be where excrement has been detected on the floor area.

20

Claims

1. Household robot, in particular an automatically movable cleaning robot for a floor area,
 - having a housing (4),
 - 5 - having a running gear (6) which is arranged on the underside of the housing (4),
 - having a sensor system (8) for detecting the area surrounding the housing (4) and
 - having a control for automatically controlling the running gear (6), characterised
 - 10 - in that detection means (20) for detecting a sub-area of the floor area which has been soiled by excrement from a living being are provided, and
 - in that the control means change the operating mode of the household robot in dependency of an output signal from the detection means (20).
- 15 2. Household robot according to Claim 1, characterised in that the control means control the running gear (6) in order to at least partly prevent the soiled sub-area from being driven over.
- 20 3. Household robot according to Claim 1 or 2, characterised
 - in that a cleaning mechanism (12, 14) is provided, and
 - in that the control means at least partly prevent the soiled sub-area from being cleaned in dependency of an output signal from the detection means (20).

4. Household robot according to any one of Claims 1 to 3,
characterised
- in that the detection means (20) have at least one infrared camera (22) for recording a thermal image of the surroundings of the housing (4),
- 5
- in that evaluation means are provided for evaluating the thermal image, and
 - in that the control then at least partly prevents the soiled sub-area from being driven over and cleaned if at least one sub-area of the thermal image has a predefined difference in temperature to the further surroundings.
- 10
5. Household robot according to any one of Claims 1 to 4,
characterised
- in that the detection means (20) have at least one gas sensor (24, 26) for detecting at least one specific gas concentration,
 - in that evaluation means for evaluating the specific gas concentration are
- 15
- provided, and
 - in that the control then at least partly prevents the soiled sub-area from being driven over and/or cleaned if the specific gas concentration exceeds a predefined limit value.
- 20
6. Household robot according to Claim 5,
characterised
- in that the at least one gas sensor (24, 26) detects at least one specific concentration of methane, ammonia, butanoic acid, phenol, caproic acid, mercaptans or of hydrogen sulphides.
- 25
7. Method for operating a household robot, in particular an automatically movable cleaning robot for a floor area,
- wherein the cleaning device has a cleaning mechanism and a running gear,
 - in which the floor area to be cleaned is detected for the presence of excrement
- 30
- from a living being, and

- in which the setting of a function of the household robot is changed when excrement is detected.
- 8. Method according to Claim 7,
5 in which the setting of the running gear is changed.
- 9. Method according to Claim 8,
in which the running gear is stopped when excrement is detected.
- 10 10. Method according to Claim 8,
in which when excrement is detected the sub-area of the floor area soiled with the excrement is bypassed.
- 11. Method according to any one of Claims 7 to 10,
15 in which a cleaning mechanism is switched off when excrement is detected.
- 12. Method according to any one of Claims 7 to 11,
in which the detection of excrement is shown on a display.
- 20 13. Method according to any one of Claims 7 to 12,
in which the position of the sub-area of the soiled floor area is shown on a display.