

**APPARATUS AND METHOD FOR RECORDING/REPRODUCING  
MOVING PICTURE AND RECORDING MEDIUM**

**BACKGROUND OF THE INVENTION**

1. Field of the Invention

5 The present invention relates to the field of moving pictures, and more particularly, to an apparatus and method for recording and/or reproducing state information associated with audio for moving pictures, and a recording medium for storing audio state information.

2. Description of the Related Art

10 Development in the field of digital compression techniques and increases in the capacity of recording mediums are now enabling moving picture information to be compressed into digital data and recorded. Compression techniques include a variety of standards. In the case of video, the MPEG (moving picture experts group)-2 video (ISO/IEC 13818-2)  
15 MP@ML (Main Profile at Main Level) standard, which has the same image quality as current analog televisions, is now the most widely used. The use of the MPEG-2 MP@HL (Main Profile at High Level) standard, which is capable of achieving the image quality of high definition television (HDTV) is rapidly increasing. In the case of audio, AC (Audio Coding)-3 is generally  
20 used around North America, and MPEG1/2 Audio (ISO/IEC13818-3) standard is being used in Europe. The amount of audio data is less than that of video data, so that the linear pulse coded modulation (LPCM) standard, in which there is no compression can also be used for audio.

In this way, audio data and video data are signal-processed in accordance with respective standards, and then combined into data of a bitstream. At this time, the MPEG-2 System (ISO/IEC 13818-1) standard is generally used. That is, each of the audio data and the video data is packeted, and discrimination information for discriminating between audio and video, buffer control information, and timing information for synchronizing an audio signal with a video signal, are added to each packet. Timing information related to a clock signal to be used by a decoder is also added to each packet, resulting in pack data. Here, the digital versatile disc (DVD) video standard prescribes that the size of one pack of data is 2048 bytes.

A general moving picture recording apparatus includes several important functions among which there is an after recording function of later replacing and overwriting only an audio portion among moving picture data which has already been recorded on a recording medium. Existing analog recording mediums have tracks on which video signals for moving pictures and audio signals are separately recorded, such that the after recording function is easily performed. Also, an analog signal is not recorded in a particular recording unit, so that operations required for the after recording are completed by overwriting a desired portion.

Here, audio which has been originally recorded is called original audio, and audio to be replaced and recorded later is called secondary audio. In order to preserve original audio upon recording of secondary audio, two audio tracks to separately record the original audio and the

secondary audio must be prepared. Accordingly, original audio and secondary audio are discriminated from each another by the positions of their tracks.

While the two tracks are simultaneously played back, the secondary  
5 audio signal is only output when an audio signal exists in the track for secondary audio, and otherwise, an audio signal existing in the track for original audio is output. In this way, secondary audio which has been partially recorded on a track can be reproduced. When reproduction of only the original audio is desired, an audio signal on the original audio track can  
10 be reproduced independently of the existence or non-existence of audio signals on the secondary audio track.

However, in the digital recording medium, audio/video (A/V) signals have been mixed and recorded on a recording area in a predetermined recording unit without classification, such that recording and reproducing of  
15 secondary audio using the overwriting method used by the analog recording medium is not possible.

### **SUMMARY OF THE INVENTION**

To solve the above problem, an objective of the present invention is to provide a recording medium for dividing moving picture data into a  
20 plurality of basic units, generating basic unit information, which is required for reproduction/edition and included in each basic unit, and storing audio state information in the basic unit information.

Another objective of the present invention is to provide a recording apparatus for dividing moving picture data into a plurality of basic units, generating basic unit information related to each basic unit, and storing audio state information in the basic unit information.

5           Still another objective of the present invention is to provide a reproducing apparatus for selectively reproducing original audio or secondary audio on the basis of audio state information.

Yet another objective of the present invention is to provide a recording method of dividing moving picture data into a plurality of basic  
10       units, generating basic unit information related to each basic unit, and storing audio state information in the basic unit information.

Still yet another objective of the present invention is to provide a reproducing method of selectively reproducing original audio or secondary audio on the basis of audio state information.

15           To achieve the first objective of the invention, there is provided a recording medium on which a moving image is divided into a plurality of basic units and recorded, and basic unit information related to the moving image is recorded in each basic unit, wherein the basic unit is comprised of  
20       at least one among video data, audio data and graphic data, and the audio data is comprised of first audio or first audio and second audio; the basic unit information includes the state information on the first audio and the state information on the second audio; the state information on the first audio represents an original audio state in which the first audio is original audio, or a secondary audio state in which the first audio is secondary audio

recorded over part or all of the original audio; and the state information on the second audio represents a state in which the second audio is original audio, a state in which the second audio is secondary audio recorded over part or all of the original audio, a state in which the second audio is dummy audio which is exactly the same as the first audio, or a state in which the second audio is secondary audio recorded over part or all of the dummy audio.

To achieve the second objective of the invention, there is provided a moving picture recording apparatus by which a moving image is divided into a plurality of basic units and recorded, basic unit information related to the moving image is recorded on each basic unit, and the basic unit is comprised of at least one among video data, audio data and graphic data. The apparatus includes a recording controller by which first audio or first audio and second audio is recorded as the audio data, the state information on the first audio and the state information on the second audio are recorded as the basic unit information, the state information on the first audio represents an original audio state in which the first audio is original audio, and when the second audio exists, the state information on the second audio represents a state in which the second audio is original audio, or a state in which the second audio is dummy audio which is exactly the same as the first audio.

To achieve the third objective of the invention, there is provided an apparatus for playing back a recording medium on which a moving picture is divided into a plurality of basic units and recorded, basic unit information

related to the moving image is recorded in each basic unit, each of the basic units is comprised of at least one among video data, audio data and graphic data among which the audio data is comprised of first audio, or first audio and second audio, the basic unit information includes the state information on the first audio and the state information of the second audio, the state information on the first audio represents a state in which the first audio is original audio, or a state in which the first audio is secondary audio recorded over part or all of the original audio, and the state information on the second audio represents a state in which the second audio is original audio, a state in which the second audio is secondary audio recorded over part or all of the original audio, a state in which the second audio is dummy audio which is exactly the same as the first audio, or a state in which the second audio is secondary audio recorded over part or all of the dummy audio. The apparatus includes a reproducing controller for reproducing the original audio and secondary audio according to the first audio state information/second audio state information.

To achieve the fourth objective of the invention, there is provided a moving picture recording method by which a moving image is divided into a plurality of basic units and recorded, basic unit information related to the moving image is recorded on each basic unit, and the basic unit is comprised of at least one among video data, audio data and graphic data. The method includes recording first audio or first audio and second audio as the audio data, and recording the state information on the first audio and the state information on the second audio as the basic unit information,

wherein the state information on the first audio represents an original audio state in which the first audio is original audio, and when the second audio exists, the state information on the second audio represents a state in which the second audio is original audio, or a state in which the second audio is dummy audio which is exactly the same as the first audio.

To achieve the fifth objective of the invention, there is provided a method of playing back a recording medium on which a moving picture is divided into a plurality of basic units and recorded, basic unit information related to the moving image is recorded in each basic unit, each of the basic units is comprised of at least one among video data, audio data and graphic data among which the audio data is comprised of first audio, or first audio and second audio, the basic unit information includes the state information on the first audio and the state information of the second audio, the state information on the first audio represents a state in which the first audio is original audio, or a state in which the first audio is secondary audio recorded over part or all of the original audio, and the state information on the second audio represents a state in which the second audio is original audio, a state in which the second audio is secondary audio recorded over part or all of the original audio, a state in which the second audio is dummy audio which is exactly the same as the first audio, or a state in which the second audio is secondary audio recorded over part or all of the dummy audio. The method includes analyzing the first audio state information/second audio state information, and reproducing the original audio/secondary audio according to the analyzed audio state information.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

The above objectives and advantages of the present invention will become more apparent by describing in detail preferred embodiments thereof with reference to the attached drawings in which:

5           FIG. 1 is a block diagram of an optical recording/reproducing apparatus to which the present invention is applied;

          FIG. 2 shows the hierarchical structure of moving picture data to facilitate understanding of the present invention;

          FIGS. 3A and 3B show the video object (VOB) shown in FIG. 2;

10           FIGS. 4A through 4D show the pack shown in FIG. 3;

          FIG. 5 shows an example of the structure of audio state information within video object information (VOBI) according to the present invention;

          FIG. 6 shows a state variation from before secondary audio is re-recorded, to after the secondary audio has been re-recorded, when only first  
15           audio exists; and

          FIG. 7 shows a state variation from before secondary audio is re-recorded, to after the secondary audio has been re-recorded, when first and second audio exist.

### **DESCRIPTION OF THE PREFERRED EMBODIMENT**

A digital versatile disk (DVD) video recorder and player as shown in FIG. 1 are adopted as a preferred embodiment of a recording apparatus and a reproduction apparatus to which the present invention is applied.

Referring to FIG. 1, blocks 102 through 114 are for reproduction, and  
5 blocks 116 and 126 are for recording. A reproduction apparatus may include only blocks for reproduction, and a recording apparatus may include only blocks for recording. An optical pickup unit 100, a key input unit & display 128 for interfacing with a user and displaying a user interface, and a system controller 130 for controlling the operation of each block, are  
10 included in both the recording apparatus and the reproduction apparatus.

Typical recorders are capable of recording and reproduction, so that all blocks can be installed in one apparatus. Thus, in the present invention, when a recording apparatus operates for reproduction, it can be a reproduction apparatus.

15 In the operations of blocks in a general reproduction apparatus, the optical pickup unit 100 includes an optical system for reading a signal from a recording medium and converting the read signal into an electrical signal, and a mechanism for moving the optical system so that the optical system reads and writes data at desired positions on the recording medium. This  
20 mechanism is controlled by a digital servo unit 102. A radio frequency (RF) amplifier 104 amplifies the electrical signal read from the recording medium by the optical system and provides the resultant signal to a data decoder 106. Also, the RF amplifier 104 provides a servo signal for compensating for the position of the optical system, to the digital servo unit 102.

The data decoder 106 converts the amplified electrical signal output by the RF amplifier 104, into a digital signal expressed by "0" and "1" levels on the basis of an appropriate signal level (which is called a binarization level). The digital signal has been modulated in accordance with the recording characteristics of a typical recording medium. Also, the data decoder 106 demodulates the digital signal in accordance with a demodulation scheme corresponding to a modulation scheme used upon modulation. The demodulated digital signal is an error correction code (ECC) signal to which a parity is attached to correct errors caused by scratches, defects, or the like on a recording medium. The data decoder 106 corrects a generated error by error correction decoding the demodulated data, and provides error correction coded data to an audio/video (A/V) decoder 108.

Data output by the data decoder 106 has a form in which at least one among video data, audio data and graphic data has been compressed. Audio data may not be compressed since it has a smaller amount of information in relation to the amount of video data. Video data is typically compressed in accordance with the MPEG standard. Graphic data is compressed according to a lossless compression scheme in which there is no information loss. The A/V decoder 108 decodes video, audio and/or graphic data in accordance with the respective compressed schemes to restore the video, audio and/or graphic data. In particular, the graphic data is mixed with the video data.

A memory 110 connected to the A/V decoder 108 temporarily stores the data received by the A/V decoder 108, before the data is decoded, or temporarily stores restored data before the data is output. Next, data provided from the A/V decoder 108 is converted to be output to output devices. That is, a video digital-to-analog converter (DAC) 112 converts a restored digital video data into an analog video signal, and outputs the analog video signal to a television or a monitor. An audio DAC 114 converts a restored digital audio data into an analog audio signal, and outputs the analog audio signal to a speaker or an audio amplifier. The TV, monitor, speaker, and audio amplifier, which are final output devices, are not shown in FIG. 1.

In the operation of blocks in a recording apparatus, an audio signal or a video signal is received from an external input device. Here, the external input device can be a TV, a camera or the like, and is not shown in FIG. 1.

Received video and audio signals are of an analog or digital form, and appropriately pre-processed and converted into digital data. In FIG. 1, analog video and audio signals are received. To be more specific, a video preprocessor 116 performs a function such as a filtering operation for minimizing secondary effects which are produced while the analog video signal is converted into digital data, and then converts the analog video signal into a digital video signal. An audio preprocessor 118 performs a function such as a filtering operation for minimizing secondary effects which are produced while the analog audio signal is converted into digital data,

and then converts the analog audio signal into a digital audio signal. An A/V encoder 120 compresses the digital audio and/or video signals to reduce the amount of audio data and/or video data, and appropriately processes the compressed audio and/or video signals. That is, video is typically encoded using a compression scheme called MPEG video (ISO/IEC13818-2), and audio is typically encoded using a compression scheme such as AC-3 or MPEG audio (ISO/IEC13818-3). However, audio may not be compressed since it has a smaller amount of data in relation to the amount of video data. It is common that information based on the MPEG system (ISO/IEC13818-1) standard is added to the encoded video data and encoded audio data. This information is required for decoding each of the video data and audio data, and can be information on buffer occupancy control upon decoding, and timing information required for synchronizing the audio signal with the video signal.

Graphic data is typically received by an exclusive input apparatus. Alternatively, graphic data is produced by the system controller 130 which receives a user input, compressed by an exclusive compressor, and mixed with the A/V data. In the A/V encoder 120, the compression and mixing of graphic data may be performed. However, the graphic data part is not shown in FIG. 1.

A memory 122 connected to the A/V encoder 120 temporarily stores data received by the A/V encoder, before the received data is encoded, or temporarily stores encoded data before the encoded data is output. A data encoder 124 error correction encodes the encoded data output by the A/V

encoder 120, and modulates the error correction encoded data in accordance with the recoding characteristics of a recording medium. A laser diode (LD) power controller 126 emits an optical signal corresponding to data output from the data encoder 124 to the recording medium using a laser beam, thereby achieving recording.

The key input unit & display 128, which is for interfacing a user to the recording or reproduction apparatus, receives a command such as reproduction start, reproduction stop, recording start or recording stop from a user, transmits the received command to the system controller 130, and displays the selection of the user on a menu, an on screen display (OSD), or an on screen graphic (OSG). The system controller 130 transmits functions required according to each operational command set by a user, to all blocks, and controls the blocks, thereby performing the operation set by a user.

The AV decoder 108 and the AV encoder 120 separately installed in FIG. 1 may be integrated in a single block which can perform encoding and decoding. Also, the memory 110 for decoding and the memory 120 for encoding may be integrated in a single memory.

Accordingly, when the optical recording/reproduction apparatus shown in FIG. 1 records a moving image on a recording medium, it divides the moving image information into a plurality of basic units and records the plurality of basic units on the recording medium using the recording blocks 116 through 126 and 100. The system controller 130 produces information required for reproduction/editing for each basic unit, and manages this as

basic unit information. The basic unit information produced by the system controller 130 is recorded on the recording medium via the data encoder 124, the LD power controller 126, and the optical pickup unit 100.

Here, the basic unit includes at least one among video data, audio data, and graphic data. In particular, audio data includes only one type of audio, or includes first audio and second audio. When a user records secondary audio, the secondary audio is recorded over part or all of the first audio or second audio, and the modified state of the first audio or second audio is managed as the state information of the first audio or second audio within the basic unit information. In the case of DVD video recording as a preferred embodiment of the present invention, the basic unit is referred to as video object (VOB) and the basic unit information is referred to as video object information (VOBI).

Upon reproduction, the system controller 130 checks the first or second audio state information stored in the basic unit information which is reproduced via the optical pickup unit 100, the RF AMP 104, and the data decoder 106, and controls the key input unit & display 128 to display the audio state information in the basic unit information on a menu or the like so that the user recognizes the audio state information. Therefore, according to the selection of a user, audio data among moving image data recorded in a plurality of basic units on the recording medium is reproduced by the blocks 100 through 114 for reproduction shown in FIG. 1. This will be described later with reference to FIGS. 5 through 7.

The hierarchical structure of moving image data will now be described with reference to FIG. 2, to facilitate the understanding of the present invention.

When a user records moving image data, the moving image data is actually recorded on a recording medium using the blocks 116 through 126 and 100 for recording shown in FIG. 1. In DVD video recording, each recorded data is divided into units of video objects (VOB). That is, moving image data recorded from when a user presses down on a recording start button until when the user presses down on a recording stop button, is one VOB.

A plurality of VOBs are recorded on a recording medium. For example, VOB#1, VOB#2 and VOB#3 are shown in FIG. 2. As described above, video data, audio data and graphic data are mixed and recorded in one VOB. In the present invention, these VOBs are referred to as real time bitstream data, and each VOB is recorded in a single file in the case of DVD video recording.

Upon reproduction, recorded VOBs are decoded and reproduced by the blocks 100 through 114 for reproduction shown in FIG. 1. It is of use to separately record information required for VOB reproduction. For example, the width and length (resolution) of video data within a corresponding VOB, the encoding scheme of audio data, or the like, can be separately recorded. Also, when a VOB has been encoded at a variable bit rate (VBR), the position of data within the VOB does not match with a reproduction time. Accordingly, separate recording of the position of data according to

reproduction time is useful to accomplish a special reproduction function such as time search. These data constitute VOB. That is, VOB (VOB#1, VOB#2 and VOB#3 shown in FIG. 2) exists in each VOB, and each VOB includes information required to reproduce or edit a corresponding VOB.

5           A program can be a unit of moving image information for a user. That is, the user understands that a plurality of programs are recorded on a recording medium. In the DVD video recording, the relationship between a program and a VOB is determined as follows. That is, a program includes a plurality of cells, and a cell denotes part or all of a VOB. Consequently,  
10          a program includes some or all of a plurality of VOBs.

          In general, a program includes a cell, and a cell corresponds to an entire VOB. Here, when a program undergoes an editing process in response to a command from a user, such as, partial deletion of a program, merging of programs, or production of a program in the order desired by a  
15          user, the shape of the program becomes slightly more complicated than the aforementioned general shape.

          Information related to the plurality of programs constitutes program chain information (PGCI). The VOB and the PGCI constitute navigation data. That is, a real time bitstream which is moving image data, and  
20          navigation data which is information required to reproduce the moving image data, are recorded together on a recording medium.

          As described above, the program is finally recognized by a user. Here, the program is transmitted to the user using a menu or the like. A menu corresponding to each program (e.g., Program #1, Program #2 and

Program #3 shown in FIG. 2) is displayed. When a user selects a program #n, cells pertaining to this selected program are searched for, and corresponding portions of VOBs indicated by these cells are reproduced. Information which is required for this reproduction can be obtained from  
5 corresponding VOBs.

FIGS. 3A and 3B show the internal configuration of a VOB shown in FIG. 2. Referring to FIGS. 3A and 3B, a VOB includes a plurality of video object units (VOBUs), and each VOBV includes a plurality of video packs, audio packs and/or graphic packs. The VOBV relates to a method of  
10 encoding video data. The MPEG standard, which is used as a video encoding method, uses the correlation between frames of moving picture data.

In moving picture data constituted of tens of frames per second, each frame generally includes the same information. For example, in the case of  
15 moving pictures in which a human being moves, the background of each picture remains the same, and there is only a small amount of movement in each frame due to the human being. Hence, the foremost frame is entirely recorded, and in the next frames, only portions that are different from the previous frame are recorded. In this way, the amount of data to be recorded  
20 is sharply reduced.

The MPEG encoding method conceptually uses such a recording method. In this case, there is a disadvantage in that a middle frame requires a previous frame to be restored. Therefore, even when it is desired for a middle frame to be reproduced, previous frames thereof must be

reproduced starting from the foremost frame. MPEG solves this disadvantage using a structure of a group of picture (GOP). That is, a predetermined number of frames constitute a group, and all information on the frames is recorded on the head frame in this group. In this case, in order to reproduce a middle frame, the head frame within a GOP to which the middle frame pertains can start being reproduced. A typical GOP is constituted of 12 to 15 frames. A VOB includes a plurality of GOPs.

A VOB includes a plurality of video packs, audio packs and/or graphic data packs in a form based on the MPEG system standard. Each pack includes information on its type.

FIG. 3A refers to the case in which a type of audio stream exists for one video stream formed as a pack, and FIG. 3B refers to the case in which two types of audio streams exist for one video stream formed as a pack. When there are a plurality of types of audio streams as described above, a user can select and reproduce a desired type of audio stream.

The pack structure will now be described in more detail with reference to FIGS. 4A through 4D. A pack typically includes a packet. In the case of DVD video recording, at most two packets are required for one pack. When two packets are required, one packet among two must be a padding packet for simply occupying a place on data.

Each packet is divided into a packet header and a payload part. In a packet header, information representing the type of a corresponding packet is recorded as a parameter which is referred to as a stream identifier (stream\_id). In the case of video, the stream identifier (stream\_id) is a

binary number "1110 0000b" as shown in FIG. 4A. In the case of audio, only MPEG audio can be represented as a stream identifier (stream\_id) as shown in FIG. 4B, and the stream identifier (stream\_id) is "1100 000xb". Here, x, which is 0 or 1, can provide two types of audio.

5           In the case when audio is AC-3 audio or LPCM audio, a procedure is further required to identify the AC-3 audio or LPCM audio. That is, the AC-3 audio and LPCM audio have the same stream identifier (stream\_id) of "1011 1101b". Header information corresponding to the AC-3 audio or LPCM audio is recorded in the payload part, and real audio data follows the  
10       recorded header information. The header information includes a parameter which is referred to as a substream identifier substream\_id. In the case of AC-3, "1000 000xb" is stored in the substream identifier parameter (substream\_id) as shown in FIG. 4D. In the case of LPCM, "1010 000xb" is stored in the substream identifier parameter (substream\_id) as shown in  
15       FIG. 4C. Here, x can be "0" or "1", thus capable of providing two types of audio. In the present invention, when x is "0", this case refers to first audio (audio 1), and when x is "1", this case refers to second audio (audio 2).

          The first audio is used for recording fundamental original audio. Later, a user can record secondary audio on part of the first audio. In this  
20       case, original audio which is overwritten by the secondary audio, is deleted.

          The second audio can be used for recording original audio or for recording secondary audio. When the second audio is used for recording original audio, there are two original audio together with the first audio. However, original audio is not recorded on only the second audio without

the first audio. When the second audio is original audio, a user recognizes the second audio as original audio from the beginning. Therefore, the first audio and the second audio have the same priority. When secondary audio is recorded, either the first audio or the second audio is selected, and then  
5 the secondary audio is recorded on the selected audio.

When second audio is recorded as secondary audio from the beginning, the following restrictions must be observed. Upon initial recording, second audio having exactly the same content as the content of first audio, must be recorded. That is, the second audio is the same as the  
10 first audio in terms of content, so that a user cannot recognize the second audio. Such a state is called a dummy audio state.

Accordingly, when a user desires to record secondary audio later, the secondary audio is recorded on a corresponding portion of the second audio in a dummy state. When the second audio is overwritten by the secondary  
15 audio in this way, it is recognized by the user for the first time, and the user selects and reproduces one audio among the first audio and the second audio. Since the second audio is the same as the first audio except for the portion on which the secondary audio is recorded, the same content is reproduced even if the selection of audio is changed. The reason why  
20 second audio having the same content as the content of first audio is recorded is that in the case of a digital recording medium, it is difficult to extract and reproduce portions on which secondary audio has been recorded. That is, if the second audio is reserved and only part thereof is occupied by secondary audio, audio is not reproduced from portions on

which secondary audio has not been recorded, when the second audio is selected, which causes a user to be confused.

Alternatively, first audio can be reproduced at empty portions of the second audio, and second audio can be reproduced at portions of the second audio on which secondary audio has been recorded. However, in this case, a determination as to whether audio has been recorded on the second audio must be made, which makes it difficult to achieve the alternative method.

In the present invention, a user is informed of the states of first audio and second audio before the states are recorded on and reproduced from a corresponding VOB in a VOB, or used to perform an appropriate operation when a user has made audio change during reproduction.

FIG. 5 shows an example of the structure of first audio state information and second audio state information within video object information (VOBI) according to the present invention.

The first audio state information A0\_STATUS represents a state (00b) in which original audio has been recorded, or a state (01b) in which part or all of the original audio is secondary audio.

The state 00b represents that first audio is original audio. When second audio is not recorded, a user records secondary audio over part or all of the original audio. At this time, the first audio is overwritten by secondary audio, and the state information of the first audio is changed from "00b" to "01b".

The second audio state information A1\_STATUS can be a dummy state 10b in which the content of the second audio is completely the same

as that of the first audio, or a state 11b in which part or all of the second audio has been overwritten by secondary audio, in addition to the above-described two states. Thus, one state among a total of four states is recorded as the second audio state information A1\_STATUS.

5           Consequently, the first audio state information A0\_STATUS and the second audio state information A1\_STATUS are defined as follows.

A0\_STATUS :

00b... first audio is original audio.

01b... first audio is secondary audio re-recorded over part or all of  
10 original audio.

A0\_STATUS :

00b... second audio is original audio.

01b... second audio is secondary audio re-recorded over part or all  
of the original audio.

15           10b... second audio is dummy audio whose content is exactly the same as the content of the original audio.

11b... second audio is secondary audio re-recorded over part or all of dummy audio.

20           In a method of using the first and second audio information, the case in which the second audio is in a dummy audio state is the most important. When state information representing that second audio is dummy audio is recorded, it is considered to a user as the case in which second audio is not recorded. Thus, this situation can be displayed on a menu or the like. At this time, even when a user performs an audio conversion function, the first

audio can continue being reproduced. That is, in the state "10b" representing dummy audio, reproduction of the first audio can be set as default.

When the second audio is in one of three states 00b, 01b and 11b  
5 other than the dummy audio state 10b, the three states of the second audio indicate that audio data having a different content to the content of the first audio has been recorded. Thus, a user is informed of this state of the second audio, and thus can perform audio change. In particular, when the second audio state information A1\_STATUS is the state 11b in which the  
10 second audio is secondary audio re-recorded on part or all of the dummy audio, reproduction of the second audio can be set as default.

Accordingly, in the present invention, a user is informed of whether the first audio or second audio is original audio, or secondary audio re-recorded on part or all of the first audio or second audio, by means of a  
15 menu or the like, so that the user can recognize the state of audio of a corresponding VOB.

FIG. 6 shows a state variation from before secondary audio is re-recorded, to after the secondary audio is re-recorded, when only first audio exists. That is, the case (A0\_STATUS=00b) of first audio in original audio  
20 state, and the case (A0\_STATUS=01b) in which only some sections a5 through a8 of the original audio are overwritten by secondary audio b1 through b4 through overwriting/edition, are shown in FIG. 6. In this case, the first audio state information A0\_STATUS is renewed from "00b" to "01b", and the variation of the audio state can be displayed through a menu or the

like on the key input unit & display 128 shown in FIG. 1 so that a user is informed of the variation of the audio state.

FIG. 7 shows a state variation from before secondary audio is re-recorded, to after the secondary audio has been re-recorded, when first and second audio exist. When the first audio is original audio (i.e., A0\_STATUS=00b) and the second audio is in the dummy state in which the second audio is the same as the first audio (i.e., A1\_STATUS=10b), reproduction of only first audio is set as default, and the direction of reproduction is indicated by a thick solid arrow.

Second audio in a dummy audio state having some sections a5 through a8 overwritten by secondary audio b1 through b4 is shown in FIG. 7. The second audio state information A1\_STATUS is renewed from "10b" to "11b". Here, the first audio remains in the original audio state (i.e., A0\_STATUS = 00B).

Part of the second audio in a dummy state is overwritten by secondary audio, and, then, audio change by a user through a menu or the like, is performed. At this time, the content of audio reproduced is changed, which is represented by a thick solid arrow indicating the direction of reproduction. That is, as shown in FIG. 7, first audio a1 through a4 are reproduced, second audio b1 through b3 in the second audio are then reproduced due to the audio change by the user, and the first audio is reproduced again from a8 due to the audio change by the user.

As described above, in the present invention, audio state information related to a moving image, obtained through recording/overwriting/editing,

is stored in recording unit information VOB1 for a corresponding recording unit VOB, and reported to a user before the moving image is reproduced, so that the user can recognize the audio state. Also, during reproduction, the user can appropriately cope with audio change.



What is claimed is:

1           1.     A recording medium on which a moving image is divided into  
2     a plurality of basic units and recorded, and basic unit information related to  
3     the moving image is recorded in each basic unit, wherein

4           the basic unit is comprised of at least one among video data, audio  
5     data and graphic data, and the audio data is comprised of first audio or first  
6     audio and second audio;

7           the basic unit information includes the state information on the first  
8     audio and the state information on the second audio;

9           the state information on the first audio represents an original audio  
10    state in which the first audio is original audio, or a secondary audio state in  
11    which the first audio is secondary audio recorded over part or all of the  
12    original audio; and

13          the state information on the second audio represents a state in which  
14    the second audio is original audio, a state in which the second audio is  
15    secondary audio recorded over part or all of the original audio, a state in  
16    which the second audio is dummy audio which is exactly the same as the first  
17    audio, or a state in which the second audio is secondary audio recorded over  
18    part or all of the dummy audio.

1           2.     A recording medium on which an image is divided into a  
2     plurality of basic units and recorded, basic unit information related to the  
3     moving image is recorded in each basic unit, the basic unit is comprised of



4 at least one among video data, audio data and graphic data, and the audio  
5 data is comprised of at least one type of audio stream, wherein

6 the basic unit information includes first audio state information related  
7 to a first-type audio stream, and the first audio state information represents  
8 a state in which the first audio is original audio, or a state in which the first  
9 audio has been modified from the original audio.

1 3. The recording medium of claim 2, wherein the basic unit  
2 information further includes second audio state information related to a  
3 second-type audio stream, and the second audio state information  
4 represents a state in which the second audio is original audio, a state in  
5 which the second audio has been modified from the original audio, a state  
6 in which the second audio is dummy audio which has the same stream as the  
7 original audio, or a state in which the second audio has been modified from  
8 the dummy audio.

1 4. A moving picture recording apparatus by which a moving image  
2 is divided into a plurality of basic units and recorded, basic unit information  
3 related to the moving image is recorded on each basic unit, and the basic  
4 unit is comprised of at least one among video data, audio data and graphic  
5 data, the apparatus comprising:

6 a recording controller by which first audio or first audio and second  
7 audio is recorded as the audio data, the state information on the first audio  
8 and the state information on the second audio are recorded as the basic unit



9 information, the state information on the first audio represents an original  
10 audio state in which the first audio is original audio, and when the second  
11 audio exists, the state information on the second audio represents a state in  
12 which the second audio is original audio, or a state in which the second  
13 audio is dummy audio which is exactly the same as the first audio.

1 5. The recording apparatus of claim 4, wherein the recording  
2 controller updates the state information of the first audio when secondary  
3 audio is recorded over the first audio, and updates the state information of  
4 the second audio when the secondary audio is recorded over the second  
5 audio.

1 6. A moving picture recording/editing apparatus for recording  
2 secondary audio on a recording medium on which a moving image is divided  
3 into a plurality of basic units and recorded, basic unit information related to  
4 the moving image is recorded on each basic unit, the basic unit is comprised  
5 of at least one among video data, audio data and graphic data among which  
6 the audio data is comprised of first audio or first audio and second audio,  
7 and the first audio state information and the second audio state information  
8 are recorded in the basic unit information, the apparatus comprising:

9 a recording controller for recording/editing secondary audio over part  
10 or all of the first audio when only the first audio exists, and recording state  
11 information representing that the first audio is secondary audio recorded over  
12 part or all of the original audio, in the basic unit information.



1           7.     The recording/editing apparatus of claim 6, wherein the  
2     recording controller records/edits secondary audio over part or all of second  
3     audio when the second audio exists, and records state information  
4     representing that the second audio is secondary audio recorded over part or  
5     all of the original audio, or state information representing that the second  
6     audio is secondary audio recorded over part or all of the dummy audio, in the  
7     basic unit information.

1           8.     An apparatus for playing back a recording medium on which a  
2     moving picture is divided into a plurality of basic units and recorded, basic  
3     unit information related to the moving image is recorded in each basic unit,  
4     each of the basic units is comprised of at least one among video data, audio  
5     data and graphic data among which the audio data is comprised of first  
6     audio, or first audio and second audio, the basic unit information includes the  
7     state information on the first audio and the state information of the second  
8     audio, the state information on the first audio represents a state in which the  
9     first audio is original audio, or a state in which the first audio is secondary  
10    audio recorded over part or all of the original audio, and the state information  
11    on the second audio represents a state in which the second audio is original  
12    audio, a state in which the second audio is secondary audio recorded over  
13    part or all of the original audio, a state in which the second audio is dummy  
14    audio which is exactly the same as the first audio, or a state in which the



15 second audio is secondary audio recorded over part or all of the dummy  
16 audio, the apparatus comprising:

17 a reproducing controller for reproducing the original audio and  
18 secondary audio according to the first audio state information/second audio  
19 state information.

1 9. The reproducing apparatus of claim 8, wherein the reproducing  
2 controller reproduces only the first audio when the second audio state  
3 information represents a state in which the second audio is dummy audio,  
4 even when the second audio exists.

1 10. The reproducing apparatus of claim 8, wherein the reproducing  
2 controller reproduces as a default the second audio when the second audio  
3 state information represents a state in which the second audio is secondary  
4 audio recorded over part or all of the dummy audio.

1 11. The reproducing apparatus of claim 8, further comprising a  
2 display controller for displaying whether the first audio remains as original  
3 audio, or part or all of the first audio in the original audio state is overwritten  
4 by secondary audio.

1 12. The reproducing apparatus of claim 8, further comprising a  
2 display controller for displaying whether the second audio remains as  
3 original audio, part or all of the second audio in the original audio state is



4 overwritten by secondary audio, the second audio is in the dummy audio  
5 state, or part or all of the second audio in the dummy audio state is  
6 overwritten by the secondary audio.

1 13. A moving picture recording method by which a moving image  
2 is divided into a plurality of basic units and recorded, basic unit information  
3 related to the moving image is recorded on each basic unit, and the basic  
4 unit is comprised of at least one among video data, audio data and graphic  
5 data, the method comprising:

6 (a) recording first audio or first audio and second audio as the audio  
7 data; and

8 (b) recording the state information on the first audio and the state  
9 information on the second audio as the basic unit information, wherein the  
10 state information on the first audio represents an original audio state in which  
11 the first audio is original audio, and when the second audio exists, the state  
12 information on the second audio represents a state in which the second  
13 audio is original audio, or a state in which the second audio is dummy audio  
14 which is exactly the same as the first audio.

1 14. The recording method of claim 13, further comprising:

2 (c) recording secondary audio over the first audio or second audio;  
3 and

4 (d) updating the state information of the first audio when secondary  
5 audio is recorded over the first audio, and updating the state information of



6 the second audio when the secondary audio is recorded over the second  
7 audio.

1 15. A moving picture recording/editing method of recording  
2 secondary audio on a recording medium on which a moving image is divided  
3 into a plurality of basic units and recorded, basic unit information related to  
4 the moving image is recorded on each basic unit, the basic unit is comprised  
5 of at least one data among video data, audio data and graphic data among  
6 which the audio data is comprised of first audio or first audio and second  
7 audio, and the first audio state information and the second audio state  
8 information are recorded in the basic unit information, the method  
9 comprising:  
10 (a) recording/editing secondary audio over part or all of first audio  
11 when only the first audio exists; and  
12 (b) recording a state in which the first audio is secondary audio  
13 recorded over part or all of the original audio, as the state information on the  
14 first audio within the basic unit information.

1 16. The recording/editing method of claim 15, further comprising:  
2 (c) recording/editing secondary audio over part or all of second audio  
3 when the second audio exists; and  
4 (d) recording a state in which the second audio is secondary audio  
5 recorded over part or all of the original audio, or a state in which the second



6 audio is secondary audio recorded over part or all of the dummy audio, as  
7 the state information on the second audio within the basic unit information.

1 17. A method of playing back a recording medium on which a  
2 moving picture is divided into a plurality of basic units and recorded, basic  
3 unit information related to the moving image is recorded in each basic unit,  
4 each of the basic units is comprised of at least one among video data, audio  
5 data and graphic data among which the audio data is comprised of first  
6 audio, or first audio and second audio, the basic unit information includes the  
7 state information on the first audio and the state information of the second  
8 audio, the state information on the first audio represents a state in which the  
9 first audio is original audio, or a state in which the first audio is secondary  
10 audio recorded over part or all of the original audio, and the state information  
11 on the second audio represents a state in which the second audio is original  
12 audio, a state in which the second audio is secondary audio recorded over  
13 part or all of the original audio, a state in which the second audio is dummy  
14 audio which is exactly the same as the first audio, or a state in which the  
15 second audio is secondary audio recorded over part or all of the dummy  
16 audio, the method comprising:

17 (a) analyzing the first audio state information/second audio state  
18 information; and

19 (b) reproducing the original audio/secondary audio according to the  
20 analyzed audio state information.



1           18.    The reproducing method of claim 17, wherein in the step (b),  
2    only the first audio is reproduced when the analyzed second audio state  
3    information represents a state in which the second audio is dummy audio,  
4    even when the second audio exists.

1           19.    The reproducing method of claim 17, wherein in the step (b),  
2    the second audio is reproduced as a default when the second audio state  
3    information represents a state in which the second audio is secondary audio  
4    recorded over part or all of the dummy audio.

1           20.    The reproducing method of claim 17, further comprising:  
2           (c) displaying whether the first audio remains as original audio, or part  
3    or all of the first audio in the original audio state is overwritten by secondary  
4    audio, as the result of analysis in the step (a).

1           21.    The reproducing method of claim 17, further comprising:  
2           (c) displaying whether the second audio remains as original audio,  
3    part or all of the second audio in the original audio state is overwritten by  
4    secondary audio, the second audio is in a dummy audio state, or part or all  
5    of the second audio in the dummy audio state is overwritten by the  
6    secondary audio, as the result of analysis in the step (a).

1           22.    A method of recording/reproducing data on/from a recording  
2    medium, comprising:



3 (a) dividing an image into a plurality of basic units and recording the  
4 basic units on the recording medium, wherein a basic unit is comprised of at  
5 least one among video data, audio data and graphic data, and the audio data  
6 is comprised of at least one type of audio stream; and

7 (b) recording basic unit information related to a corresponding image  
8 on each basic unit on the recording medium,

9 wherein the basic unit information includes first audio state  
10 information related to a first audio stream, and the first audio state  
11 information represents a state in which the first audio is original audio, or a  
12 state in which the first audio has been modified from the original audio.

1 23. The method of claim 22, wherein the basic unit information  
2 further comprises second audio state information related to a second-type  
3 audio stream, and the second audio state information represents a state in  
4 which the second audio remains as original audio, a state in which the  
5 second audio has been modified from the original audio state, a dummy state  
6 in which the second audio has the same stream as a stream in the original  
7 audio, and a state in which the second audio has been modified from the  
8 dummy state.

1 24. The method of claim 22, further comprising:

2 (c) recording/editing secondary audio on the first audio or second  
3 audio; and



4 (d) updating the state information on the first audio when the  
5 secondary audio has been recorded/edited on the first audio, and updating  
6 the state information on the second audio when the secondary audio has  
7 been recorded/edited on the second audio.

1 25. The method of claim 22, further comprising:

2 (c) analyzing the first audio state information/second audio state  
3 information recorded on the recording medium; and

4 (d) reproducing original audio/secondary audio according to the  
5 analyzed audio state information.

1 26. The method of claim 25, further comprising:

2 (e) displaying the analyzed audio state information; and

3 (f) reproducing original audio/secondary audio while coping with audio  
4 change through user interface, on the basis of the displayed audio state  
5 information.

Abstract of the Disclosure**APPARATUS AND METHOD FOR RECORDING/REPRODUCING  
MOVING PICTURE AND RECORDING MEDIUM**

An apparatus and method of recording/reproducing a moving picture,  
5 and a recording medium are provided. The state information on the first  
audio represents an original audio state in which the first audio is original  
audio, or a secondary audio state in which the first audio is secondary audio  
recorded over part or all of the original audio. The state information on the  
second audio represents a state in which the second audio is original audio,  
10 a state in which the second audio is secondary audio recorded over part or  
all of the original audio, a state in which the second audio is dummy audio  
which is exactly the same as the first audio, or a state in which the second  
audio is secondary audio recorded over part or all of the dummy audio.  
Accordingly, audio state information related to a moving image, obtained  
15 through recording/overwriting/editing, is stored in a recording unit information  
VOBI for a corresponding recording unit VOB, and reported to a user before  
the moving image is reproduced, so that the user can recognize the audio  
state. Also, during reproduction, the user can appropriately cope with audio  
change.

20 FIG. 5

FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D





FIG. 5



7/8

FIG. 6




FIG. 7

