



159159

- 1 -

DESCRIPTION

RE-ENCRYPTION KEY GENERATOR, RE-ENCRYPTION APPARATUS, AND PROGRAM

G00002

5



Technical Field

Embodiments described herein relate generally to a re-encryption key generator, re-encryption apparatus, and program.

10

Background Art

In a file sharing system in which the user uploads a file onto a server, and that file is shared by a plurality of users, as a method of maintaining the secrecy of file with respect to the server, the following three methods (1) to (3) are used.

15

(1) An individual key system for encrypting a file by means of an individual encryption key for each user.

(2) A common key system for encrypting a file by means of an encryption key common to respective users.

20

(3) A re-encryption system for encrypting a file using a proxy re-encryption system.

In the systems (1) to (3), assume that a user A uploads a file onto a server, and the user A shares the file with users B and C.

25

In the individual key system (1), each user has a pair of a private key and public key, which are different for each user. The user A encrypts a file by means of a public

key of the user B, and uploads the encrypted file onto the server. Note that the public key of the user B is an individual encryption key for the user B. Likewise, the user A encrypts a file by means of a public key of the user C, and uploads the encrypted file onto the server. The public key of the user C is an individual encryption key for the user C. That is, the user A encrypts a file individually for the users who share that file.

In the common key system (2), each user shares a pair of a private key and public key, which are common to the respective users. The user A encrypts a file by means of a public key (as an encryption key common to the respective users), and uploads the encrypted file onto the server. The respective users share an identical private key.

In the proxy re-encryption system (3), each user has a pair of a private key and public key, which are different for respective users like in the individual key system (1). However, unlike in the individual key system (1), the user A need only encrypt a file by means of a public key (to be referred to as a group public key hereinafter) of an entity (to be referred to as a group administrator hereinafter) who manages a group of users. The server re-encrypts the encrypted file (uploaded by the user A) based on a re-encryption key. By the re-encryption, an encrypted file which can be decrypted by each user is generated. Details of the proxy re-encryption system will be described later.

In the individual key system (1), when a file is to be

shared also by a new user D, the user A has to encrypt a file by means of a public key of the user D, and has to upload the encrypted file onto the server, thus posing a problem. Note that the public key of the user D is an individual encryption key for the user D. Therefore, the system (1) is not suitable for the file sharing system since troublesome processing is required at the time of addition of a new user when the number of new users or the number of files to be shared is large.

In the common key system (2), when a file sharing permission for a certain user is canceled from a certain timing (to exclude that user from the file sharing system), a mechanism for updating the private key and public key common to the respective users is additionally required, thus posing a problem. In the common key system (2), if the private key common to the respective users has leaked due to some reason, a person who acquired the leaked private key can decrypt all encrypted files, thus posing a problem. For this reason, the common key system (2) is not suitable for the file sharing system.

On the other hand, in the proxy re-encryption system (3), since the server re-encrypts one ciphertext to that which can be decrypted by each user, using a re-encryption key, a configuration which does not notify the users of the re-encryption key is adopted, thus solving the aforementioned problems. For this reason, the proxy re-encryption system (3) is suitable for the file sharing

system.

Citation List

Non-Patent Literature

Non-Patent Literature 1: B. Libert and D. Vergnaud,
5 "Unidirectional Chosen-Ciphertext Secure Proxy
Re-encryption", Proc. PKC 2008, LNCS 4939, pp. 360 - 379,
Springer, 2008.

However, in the proxy re-encryption system (3), when
the server and users collude, a decryption right is re-
10 delegated. More specifically, when the server and users B
and E collude, an authentic re-encryption key ($rk_{A \rightarrow E}$)
required to re-encrypt ciphertext for the user A to that
for the user E is generated without any permission of the
user A using a re-encryption key ($rk_{A \rightarrow B}$) required to
15 re-encrypt ciphertext for the user A to that for the user
B, a private key (sk_B) of the user B, and a private key
(sk_E) of the user E.

A solution to such problem of the present invention is
to provide a re-encryption key generator, re-encryption
20 apparatus, and program, which cannot generate a re-
encryption key without any permission of a transfer source
even when the server and users collude.

Summary of Invention

A re-encryption key generator according to an
25 embodiment generates a re-encryption key required to
re-encrypt, without decrypting, ciphertext data obtained by
encrypting plaintext data by means of a first public key of

a first user device to obtain re-encrypted text data which can be decrypted by a second private key of a second user device.

5 The re-encryption key generator comprises first storage means, second storage means, first random number generation means, and re-encryption key generation means.

 The first storage means stores a first private key corresponding to the first public key.

10 The second storage means stores a second public key corresponding to the second private key.

 The first random number generation means generates a first random number.

15 The re-encryption key generation means generates the re-encryption key based on the first private key, the second public key, and the first random number.

Brief Description of Drawings

 FIG. 1 is a block diagram showing the arrangement of a re-encryption system according to the first embodiment.

20 FIG. 2 is a sequence chart for explaining the operation of key setup processing according to the first embodiment.

 FIG. 3 is a sequence chart for explaining the operation of encryption processing according to the first embodiment.

25 FIG. 4 is a sequence chart for explaining the operation of re-encryption key generation processing according to the first embodiment.

FIG. 5 is a sequence chart for explaining the operation of re-encryption processing according to the first embodiment.

FIG. 6 is a sequence chart for explaining the operation of decryption processing according to the first embodiment.

FIG. 7 is a block diagram showing an example of the arrangement of a file sharing system according to the first embodiment.

FIG. 8 is a diagram of the file sharing system according to the first embodiment.

Description of Embodiments

Embodiments will be described hereinafter with reference to the drawings. Note that each of the following apparatuses can be implemented by either a hardware arrangement or a combined arrangement of hardware resources and software. As the software of the combined arrangement, programs, which are installed from a network or non-transitory computer-readable storage media M1 to M5 in a computer in advance, and are executed by processors of the computer to control the computer to implement functions of corresponding apparatuses, as shown in FIG. 1, are used.

(First Embodiment)

A proxy re-encryption system will be described first. A basic model of the proxy re-encryption system includes five functions (to be also referred to as algorithms hereinafter), that is, key generation, encryption,

decryption, re-encryption key generation, and re-encryption. The key generation, encryption, and decryption functions are the same as those of normal public key cryptosystem.

5 (Key generation) $\text{KeyGen}(1^k) \rightarrow (\text{pk}, \text{sk})$

A key generation algorithm KeyGen outputs a pair (pk, sk) of a public key pk and private key sk when a security parameter 1^k is input.

(Encryption) $\text{Enc}(\text{pk}_A, m) \rightarrow C_A$

10 An encryption algorithm Enc outputs ciphertext C_A for a user A when a public key pk_A of the user A and a message m are input.

(Decryption) $\text{Dec}(\text{sk}_A, C_A) \rightarrow m$

15 A decryption algorithm Dec outputs the message m when a private key sk_A of the user A and the ciphertext C_A for the user A are input.

(Re-encryption key generation) $\text{ReKeyGen}(\text{pk}_A, \text{sk}_A, \text{pk}_B, \text{sk}_B) \rightarrow \text{rk}_{A \rightarrow B}$

20 A re-encryption key generation algorithm ReKeyGen outputs a re-encryption key $\text{rk}_{A \rightarrow B}$ when the public key pk_A of the user A , the private key sk_A of the user A , a public key pk_B of a user B , and a private key sk_B of the user B are input.

(Re-encryption) $\text{ReEnc}(\text{rk}_{A \rightarrow B}, C_A) \rightarrow C_B$

25 A re-encryption algorithm ReEnc outputs ciphertext C_B for the user B when the re-encryption key $\text{rk}_{A \rightarrow B}$ and the ciphertext C_A for the user A are input.

The basic model has been described. However,
according to the re-encryption implementation method used,
models having different inputs to functions, and those
including functions and keys other than those described
5 above have also been proposed.

For example, like in the re-encryption method to be
described in this embodiment, a model called
"non-interactive", which obviates the need for the private
key sk_B of the user B in inputs of the re-encryption key
10 generation algorithm has been proposed. Also, a model in
which the re-encryption key $rk_{A \rightarrow B}$ for the user B and a
private key sk_C of a user C are input in place of the
private key sk_A of the user A has also been proposed.

In addition, a model called "unidirectional" which
15 allows re-encryption of ciphertext $C_A \rightarrow C_B$ by means of the
re-encryption key $rk_{A \rightarrow B}$, while inhibits inverse conversion
of ciphertext $C_B \rightarrow C_A$, and a model called "bidirectional"
which permits that inverse conversion are known. Note that
in the bidirectional model, the re-encryption key $rk_{A \rightarrow B}$ is
20 also expressed as $rk_{A \leftrightarrow B}$.

Furthermore, a system based on ID-based encryption of
the public key cryptosystem has been proposed. In this
case, function setup processing is added for master key
generation, and a master key and ID are added to inputs of
25 the key generation algorithm. In the ID-based encryption,
the public key pk is an ID itself.

The arrangement of a file sharing system according to

this embodiment will be described below with reference to
FIG. 7. The file sharing system includes a server Sv as an
information processing apparatus possessed by a service
provider which provides a service, and user devices A, B,
5 C,... as information processing apparatuses possessed by
users of that service. The server Sv and user devices A,
B, C,... are connected via a communication network. The
communication network includes, for example, a wireless LAN
(Local Area Network), wired LAN, optical communication
10 network, telephone communication network, intranet,
EthernetTM, Internet, and combinations thereof. Note that
FIG. 7 shows only one server Sv connected to the file
sharing system, but a plurality of servers may be
connected. Also, the user devices A, B, C,... will also
15 simply referred to as users A, B, C,..., or will be
referred to as a first user device, second user device,...
hereinafter.

FIG. 8 is a diagram showing the file sharing system.
This file sharing system includes a server Sv, user A, user
20 B, user C, group administrator, and user administrator.
The user administrator is an entity for managing all the
users. The user administrator issues an ID and initial
password which allow each user to log into the file sharing
system for the user.

25 As an advance preparation, assume that each user has a
public key pk_{Gr} of the group administrator. Also, let m be
file of plaintext to be shared. Assume that the server Sv

has a re-encryption key $rk_{Gr \rightarrow A}$ (or $rk_{Gr \rightarrow B}$ or $rk_{Gr \rightarrow C}$) required to re-encrypt ciphertext $E(pk_{Gr}, m)$ for the group administrator to ciphertext $E(pk_A, m)$ (or $E(pk_B, m)$ or $E(pk_C, m)$) for the user A (or the user B or user C).

5 Assume that each user i has a private key sk_i . That is, the user A has a private key sk_A , the user B has a private key sk_B , and the user C has a private key sk_C .

Next, the user C encrypts the file m by means of the public key pk_{Gr} of the group administrator, which is stored
10 in a public key storage unit 1, and uploads obtained ciphertext $E(pk_{Gr}, m)$ onto the server Sv . The server Sv stores this ciphertext in a ciphertext storage unit 2.

Now assume that the user A wants to share the file m . The user A transmits a re-encryption request of the
15 ciphertext $E(pk_{Gr}, m)$ to the server Sv . In response to the request received from the user A, the server Sv re-encrypts the ciphertext $E(pk_{Gr}, m)$ to ciphertext $E(pk_A, m)$ for the user A based on the re-encryption key $rk_{Gr \rightarrow A}$ for the user A stored in a re-encryption key storage unit 3, and
20 transmits the obtained re-encrypted text $E(pk_A, m)$ to the user A. Note that the re-encrypted text is ciphertext obtained by re-encrypting ciphertext.

The user A decrypts the re-encrypted text $E(pk_A, m)$ downloaded from the server Sv by means of the private key
25 sk_A in his or her possession, and uses the obtained file m .

In the aforementioned file sharing system, the file m has never been decrypted from encryption by the user C

until decryption by the user A, thus blocking information leakage during the processes of file sharing.

The user C need not determine file sharing users at the ciphertext upload timing. That is, the user C need
5 only encrypt the file m by means of the public key pk_{Gr} of the group administrator, and requires only the public key pk_{Gr} of the group administrator as a key to be managed in association with encryption, thus reducing the key management cost.

10 In this file sharing system, the server S_v does not have any decryption key sk_{Gr} required to decrypt the ciphertext $E(pk_{Gr}, m)$. Therefore, the server S_v cannot decrypt this ciphertext. This means that there is no threat of leakage of ciphertext decrypted by the illicit
15 server S_v , thus the server S_v need not be managed so strictly, resulting in a management cost reduction of the server S_v .

The same applies to a case of file sharing by the user B.

20 FIG. 1 is a block diagram showing the arrangement of a re-encryption system according to the first embodiment. (The correspondence relationship between FIGS. 1 and 8 will be described later.) This re-encryption system includes a key generator 10, encryption apparatus 20, re-encryption
25 key generator 30, re-encryption apparatus 40, and decryption apparatus 50. Note that the key generator 10 generates various parameters of the re-encryption system,

and a pair of keys; a public key and private key of the apparatuses 40 and 50.

The encryption apparatus 20 transmits ciphertext data obtained by encrypting plaintext data using a public key
5 corresponding to a private key of the re-encryption key generator 30 to the re-encryption apparatus 40.

The re-encryption key generator 30 generates a re-encryption key using the private key of the re-encryption key generator 30, a public key of the
10 decryption apparatus 50, and a random number.

The re-encryption apparatus 40 transmits re-encrypted text data obtained by re-encrypting, without decrypting, the ciphertext data received from the encryption apparatus 20 by means of the re-encryption key to the decryption
15 apparatus 50.

The decryption apparatus 50 verifies the re-encrypted text data using a public key of the re-encryption key generator 30, and decrypts the re-encrypted text data using a private key corresponding to a public key of the
20 apparatus 50, thus obtaining plaintext data. Note that a plurality of apparatuses may be arranged as each of the re-encryption key generator 30, re-encryption apparatus 40, and decryption apparatus 50, but this embodiment will exemplify a case in which the system includes one each as
25 these apparatuses.

The correspondence relationship between FIGS. 1 and 8 will be described below. The apparatuses 10 to 50 are held

by entities which execute the corresponding processes. If a user generates a pair of a public key and private key of himself or herself, the user holds the key generator 10. Note that when, for example, the user administrator or group administrator generates a pair of a public key and private key of each user, the user administrator or group administrator holds the key generator 10. The user holds one or both of the encryption apparatus 20 and decryption apparatus 50. The group administrator holds the re-encryption key generator 30. Note that when, for example, the user administrator or server Sv generates a re-encryption key, it holds the re-encryption key generator 30. The server Sv holds the re-encryption apparatus 40. In the file sharing system exemplified in FIG. 8, the server Sv holds the public key storage unit 1, and the user C who executes encryption acquires a public key used in encryption from the public key storage unit 1. However, the present invention is not limited to this, and the user C may acquire the public key used in encryption from the key generator 10 (which generates the public key used in encryption). Also, the server Sv stores the ciphertext $E(pk_{Gr}, m)$ generated by the user C in the ciphertext storage unit 2. Alternatively, the ciphertext storage unit 2 may be included in the re-encryption apparatus 40 or may be an external storage device which is not included in the re-encryption apparatus 40.

The entities and apparatuses to be held by the

entities are not limited to the aforementioned example, and various variations are possible. The user administrator or group administrator may or may not also serve as the user. The respective user devices used by the respective users
5 may also be referred to as a first user device, second user device,.... Likewise, public keys and private keys of the respective user devices may also be referred to as a first public key and first private key of the first user device, a second public key and second private key of the second
10 user device,....

The arrangements of the respective apparatuses 10 to 50 will be described in detail below.

The key generator 10 includes a key generation parameter storage unit 11, temporary data storage unit 12,
15 public parameter generation unit 13, public key/private key generation unit 14, communication unit 15, and control unit 16.

The key generation parameter storage unit 11 is a storage device which stores key generation parameters.

20 The temporary data storage unit 12 is a storage device which stores temporary data such as intermediate processing data, processing result data, and the like of the respective generation units 13 and 14.

The public parameter storage unit 13 generates public
25 parameters of key generation.

The public key/private key generation unit 14 generates a public key and private key for each user.

The communication unit 15 is a communication interface required to communicate with other apparatuses 20 to 50, and has, for example, the following functions (f15-1) and (f15-2).

5 (f15-1) A function of transmitting public key/private key pairs of 30 and 50 in the temporary data storage unit 12 to the apparatuses 30 and 50 under the control of the control unit 16.

10 (f15-2) A function of transmitting a public key of the re-encryption key generator 30 in the temporary data storage unit 12 to the encryption apparatus 20 under the control of the control unit 16.

15 Note that in the following description, a description about mediation of the communication unit 15 and transmission/reception timings may be omitted to avoid redundant descriptions. The same applies to communication units of other apparatuses 20 to 50.

The control unit 16 has a function of controlling the units 11 to 15 to execute the operations shown in FIG. 2.

20 The encryption apparatus 20 includes a temporary data storage unit 21, communication unit 22, encrypted data generation unit 23, ciphertext generation unit 24, and control unit 25.

25 The temporary data storage unit 21 is a storage device which stores the public key of the re-encryption key generator 30 received from the key generator 10, and tentative data (to be also referred to as temporary data

hereinafter) such as intermediate processing data and processing result data of the generation units 23 and 24.

The communication unit 22 is a communication interface required to communicate with other apparatuses 10 and 30 to 50, and has, for example, the following functions (f22-1) and (f22-2).

(f22-1) A function of acquiring the public key of the re-encryption key generator 30 published by the key generator 10 and writing the acquired public key in the temporary data storage unit 21.

(f22-2) A function of transmitting ciphertext data in the temporary data storage unit 21 to the re-encryption apparatus 40 under the control of the control unit 25.

The encryption parameter generation unit 23 has a function of generating encryption parameters.

The ciphertext generation unit 24 has, for example, the following functions (f24-1) and (f24-2).

(f24-1) A function of generating ciphertext data by encrypting plaintext data using the public key (the first public key of the first user device) of the re-encryption key generator 30, which key is read out from the temporary data storage unit 21.

(f24-2) A function of writing the obtained ciphertext data in the temporary storage unit 21.

The control unit 25 has a function of controlling the respective units 21 to 24 so as to execute operations shown in FIG. 3.

The re-encryption key generator 30 includes a private key storage unit 31, temporary data storage unit 32, communication unit 33, re-encryption key generation unit 34, control unit 35, and random number generation unit 36.

5 The private key storage unit 31 is a storage device which stores the private key of the re-encryption key generator 30 received from the key generator 10.

10 The temporary data storage unit 32 is a storage device which stores the public key of the decryption apparatus 50 received from the key generator 10, and temporary data such as intermediate processing data and processing result data of the re-encryption key generation unit 34.

15 The communication unit 33 is a communication interface required to communicate with other apparatuses 10, 20, 40, and 50, and has, for example, a function of transmitting the re-encryption key in the temporary data storage unit 32 to the re-encryption apparatus 40 under the control of the control unit 35.

20 The re-encryption key generation unit 34 has, for example, the following functions (f34-1) and (f34-2).

25 (f34-1) A function of generating a re-encryption key based on the private key (the first private key of the first user device) of the re-encryption key generator 30, which key is read out from the private key storage unit 31, the public key (the second public key of the second user device) of the decryption apparatus 50, which key is read out from the temporary data storage unit 32, and a random

number generated by the random number generation unit 36
(this function does not require any parameter (more
specifically, a random number) at the time of encryption).

(f34-2) A function of writing this re-encryption key
5 in the temporary data storage unit 32.

The control unit 35 has a function of controlling the
respective units 31 to 34 and 36 so as to execute the
operations shown in FIG. 4.

The random number generation unit 36 has a function of
10 generating and outputting a random number to the
re-encryption key generation unit 34.

The re-encryption apparatus 40 includes a
re-encryption key storage unit 41, temporary data storage
unit 42, communication unit 43, re-encryption processing
15 unit 44, re-encryption parameter generation unit 45, and
control unit 47.

The re-encryption key storage unit 41 is a storage
device which stores the re-encryption key received from the
re-encryption key generator 30.

20 The temporary data storage unit 42 is a storage device
which stores temporary data such as intermediate processing
data and processing result data of the re-encryption
processing unit 44.

The communication unit 43 is a communication interface
25 required to communicate with other apparatuses 10 to 30 and
50, and has, for example, the following functions (f43-1)
and (f43-2).

(f43-1) A function of outputting ciphertext data received from the encryption apparatus 20 to the re-encryption processing unit 44.

5 (f43-2) A function of transmitting re-encrypted text data in the temporary data storage unit 42 to the decryption apparatus 50 under the control of the control unit 47.

The re-encryption processing unit 44 has, for example, the following functions (f44-1) and (f44-2).

10 (f44-1) A function of obtaining re-encrypted text by re-encrypting, without decrypting, ciphertext data received from the encryption apparatus 20 using the re-encryption key read out from the re-encryption key storage unit 41.

15 (f44-2) A function of writing the obtained re-encrypted text data in the temporary data storage unit 42.

20 The control unit 47 has a function of controlling the respective units 41 to 45 so as to execute an operation for delivering a re-encrypted text verification program (not shown) and operations shown in FIG. 5.

The decryption apparatus 50 includes a private key storage unit 51, temporary data storage unit 52, communication unit 53, decryption processing unit 54, and control unit 56.

25 The private key storage unit 51 is a storage device which stores the private key of the apparatus 50 received from the key generator 10.

The temporary data storage unit 52 is a storage device which stores the public key of the apparatus 50 and that of the re-encryption key generator 30, which keys are received from the key generator 10, and temporary data such as
5 intermediate processing data and processing data of the decryption processing unit 54.

The communication unit 53 is a communication interface required to communicate with other apparatuses 10 to 40, and has, for example, the following functions (f53-1) to
10 (f53-3).

(f53-1) A function of writing the private key of the apparatus 50 received from the key generator 10 in the private key storage unit 51.

(f53-2) A function of writing the public key of the
15 apparatus 50 and that of the re-encryption key generator 30, which keys are received from the key generator 10, in the temporary data storage unit 52.

(f53-3) A function of outputting re-encrypted data received from the re-encryption apparatus 40 to the
20 decryption processing unit 54.

The decryption processing unit 54 has, for example, the following functions (f54-1) to (f54-2).

(f54-1) A function of obtaining plaintext data by decrypting re-encrypted text data received from the
25 re-encryption apparatus 40 based on the private key (the second private key of the second user device) of the decryption apparatus 50, which key is read out from the

private key storage unit 51.

(f54-2) A function of writing the obtained plaintext data in the temporary data storage unit 52.

5 The control unit 56 has a function of controlling the respective units 51 to 54 so as to execute operations shown in FIG. 6.

10 The operations of the re-encryption system with the aforementioned arrangement will be described below with reference to the sequence charts shown in FIGS. 2, 3, 4, 5, and 6.

15 The following operations will be described taking, as an example, a case in which they are executed in an order of (1) key setup processing, (2) encryption processing, (3) re-encryption key generation processing, (4) re-encryption processing, and (5) decryption processing. However, the following operations need not always be executed in the aforementioned order. For example, the re-encryption key generation may be executed before the encryption processing. Also, ciphertext data may be decrypted without
20 executing the re-encryption processing.

(1) The key setup processing is executed by the key generator 10, as shown in FIG. 2 and following steps ST1 to ST12.

25 Initially, the public parameter generation unit 13 of the key generator 10 generates or externally acquires public parameters $(p, \lambda, G, G_T, g, g_1, g_2, u, v, \text{Sig}(\hat{G}, \hat{S}, \hat{V}))$ (step ST1). More specifically, the public parameter

generation unit 13 generates, based on a security parameter λ stored in advance in the key parameter storage unit 11, bilinear map groups (G, G_T) which satisfy the prime order $p > 2^\lambda$, members g, g_1, g_2, u , and v of G , and a one-time signature algorithm $\text{Sig}(\hat{G}, \hat{S}, \hat{V})$ which satisfies strong unforgeability. Note that Z_p^* is a set of integers $(= (Z/pZ)^*)$ which are coprime to Z_p and p , and may also be called a multiplicative group Z_p^* for the prime p . Z_p is a set $(= (Z/pZ))$ of integers not less than 0 and less than p .
The term "member" is a term having a mathematical meaning, is also called an element, and indicates each individual one in a set including a plurality of "ones". Also, in the one-time signature algorithm $\text{Sig}(\hat{G}, \hat{S}, \hat{V})$ (to be also referred to as "Sig" hereinafter), $\hat{G}$ means a function of generating a one-time key pair (ssk, svk) , $\hat{S}$ means a function of generating a signature σ for a message M , and $\hat{V}$ means a function of verifying authenticity of the signature σ .

As for details of the one-time signature, please refer to [A. Menezes, P. van Oorschot, S. Vanstone, "Handbook of Applied Cryptography", CRC Press, (1996) pp. 462 - 471, (1996)].

The bilinear map (to be expressed by "e") is a map $e: G \times G \rightarrow G_T$, and satisfies the following three properties.

1. For arbitrary $(g, h) \in G \times G$ and $a, b \in Z$, $e(g^a, h^b) = e(g, h)^{ab}$ holds where Z is a set of integers.

2. For arbitrary $(g, h) \in G \times G$, $e(g, h)$ is calculable.

3. When $g, h \neq 1_G$, $e(g, h) \neq 1_{G_T}$ always holds where 1_G is a unit member of G , and 1_{G_T} is a unit member of G_T .

The bilinear map groups (expressed by G and G_T) are groups of prime orders p including the bilinear map $e: G \times G \rightarrow G_T$. If $g_1 = g^\alpha$ and $g_2 = g^\beta$ for the members g, g_1 , and g_2 of G , the aforementioned definition means that the following equation holds:

$$\begin{aligned} e(g_1 g_2, g) &= e(g, g_1 g_2) = e(g, g^\alpha \cdot g^\beta) = e(g, g^{\alpha+\beta}) \\ &= e(g, g)^{\alpha+\beta} = e(g, g)^\alpha \cdot e(g, g)^\beta \end{aligned}$$

(where α and β are power indices related to the members g, g_1 , and g_2 of G).

Note that the plurality of members g, g_1 , and g_2 of G are a plurality of predetermined system fixed values. The plurality of system fixed values are not limited to the three members of the bilinear map group G , and a plurality of members (for example, two or four or more members) of G can be used as needed. The term "system fixed value" may be read as "fixed value", "member", or "system parameter". The plurality of system fixed values are a plurality of members of a bilinear map group as a group of prime orders including a bilinear map.

This specification adopts a notation which assumes both G and G_T as multiplicative groups. However, the present invention is not limited to this, and G and G_T can be expressed by a notation which regards them as additive groups. That is, for example, G may be expressed as an additive group, and G_T may be expressed as a multiplicative

group. As the bilinear map, a map $e: G_1 \times G_2 \rightarrow G_T$ for bilinear map groups G_1 , G_2 , and G_T (G_1 and G_2 are different groups) may be used. The same applies to other embodiments.

5 Subsequently, the public parameter generation unit 13 writes the generated public parameters in the temporary data storage unit 12. The key generator 10 publishes the public parameters $(p, \lambda, G, G_T, g, g_1, g_2, u, v, \text{Sig})$ in the temporary data storage unit 12 (step ST2). Note that
10 when the public parameters have already been published before execution of step ST1, these public parameters may be written in the temporary data storage unit 12, and steps ST1 and ST2 may be skipped.

 Letting i be identification information of the
15 re-encryption key generator 30, the public key/private key generation unit 14 generates a private key $x_i, y_i, z_i \in \mathbb{Z}_p^*$, and generates a public key $pk_i = (X_i, Y_{1i}, Y_{2i}, Z_i, Z_{1i})$ (for $X_i = g^{x_i}$, $Y_{1i} = g_1^{y_i}$, $Y_{2i} = g_2^{y_i}$, $Z_i = g^{z_i}$, and $Z_{1i} = g_1^{z_i}$) of the re-encryption key generator 30 using
20 this private key $sk_i = (x_i, y_i, z_i)$ (step ST7).

 Subsequently, the public key/private key generation unit 14 writes the generated public key/private key pair in the temporary data storage unit 12. The communication unit 15 transmits the private key sk_i in the temporary data
25 storage unit 12 to the re-encryption key generator 30 under the control of the control unit 16 (step ST8). The key generator 10 publishes the public key pk_i of the

re-encryption key generator 30 in the temporary data storage unit 12 (step ST9).

5 Likewise, letting j be identification information of the decryption apparatus 50, the public key/private key generation unit 14 generates a private key $sk_j = (x_j, y_j, z_j)$ of the decryption apparatus 50, and generates a public key $pk_j = (X_j, Y_{1j}, Y_{2j}, Z_j, Z_{1j})$ (for $X_j = g^{x_j}$, $Y_{1j} = g_1^{y_j}$, $Y_{2j} = g_2^{y_j}$, $Z_j = g^{z_j}$, and $Z_{1j} = g_1^{z_j}$) of the re-encryption key generator 30 using this private key $sk_j =$
10 (x_j, y_j, z_j) (step ST10).

Then, the public key/private key generation unit 14 writes the generated public key/private key pair in the temporary data storage unit 12. The communication unit 15 transmits the private key sk_j in the temporary data storage
15 unit 12 to the decryption apparatus 50 under the control of the control unit 16 (step ST11). The key generator 10 publishes the public key pk_j of the decryption apparatus 50 in the temporary data storage unit 12 (step ST12). Also, if required, the same processes as those in steps ST10 to
20 ST12 may be executed for a private key sk_h and public key pk_h of the encryption apparatus 20, the private key sk_h may be transmitted to the encryption apparatus 20, and the public key pk_h may be published.

With the above processes, the key setup processing is
25 complete. After that, the apparatuses 20, 30, 40, and 50 can acquire and use the public parameters and public keys published in steps ST2, ST6, ST9, and ST12 as needed.

(2) The encryption processing is executed by the encryption apparatus 20, as shown in FIG. 3 and following steps ST21 to ST24.

That is, the encryption parameter generation unit 23
5 of the encryption apparatus 20 generates a key pair (ssk, svk) = $\hat{G}(\lambda)$ of a signature key ssk and verification key svk in the one-time signature using the security parameter λ and the key pair generation function $\hat{G}$ in the public parameters (step ST21), and sets the verification key svk
10 in encrypted data C_1 ($C_1 = \text{svk}$).

Also, the encryption parameter generation unit 23 generates a random number $r \in \mathbb{Z}_p^*$, and outputs it to the ciphertext generation unit 24.

The ciphertext generation unit 24 generates encrypted
15 data C_{2X} , C_{2Y} , C_{2Z} , C_{2Z1} , C_3 , and C_4 for a message $m \in G_T$ as plaintext data using this random number r and the public key pk_i of the re-encryption key generator 30 (step ST22). These encrypted data are respectively given by:

$$C_{2X} = X_i^r, C_{2Y} = Y_{1i}^r, C_{2Z} = Z_i^r, C_{2Z1} = Z_{1i}^r, \\ C_3 = e(g_1 g_2, g)^r \cdot m, C_4 = (u^{svk} \cdot v)^r$$

After completion of step ST22, the ciphertext
20 generation unit 24 generates, for the encrypted data C_3 and C_4 , a one-time signature σ by means of the signature generation function $\hat{S}$ in the public parameters and the signature key ssk generated in step ST21 (step ST23). The signature σ is described by:

$$\sigma = \hat{S}(\text{ssk}, (C_3, C_4))$$

After that, the ciphertext generation unit 24 generates ciphertext data $C_i = (C_1, C_{2X}, C_{2Y}, C_{2Z}, C_{2Z1}, C_3, C_4, \sigma)$ including all the encrypted data C_1 to C_4 and the one-time signature σ , and writes the obtained ciphertext data in the temporary data storage unit 21. Note that the ciphertext data $C_i = (C_1, C_{2X}, C_{2Y}, C_{2Z}, C_{2Z1}, C_3, C_4, \sigma)$ may be modified to ciphertext data $C_i = (C_{2X}, C_{2Y}, C_{2Z}, C_{2Z1}, C_3)$ by omitting verification data (C_1, C_4, σ) which is not used in decryption when verification is skipped. In this case, the processing for generating the verification data (C_1, C_4, σ) is also skipped.

In either case, the communication unit 22 transmits the ciphertext data C_i in the temporary data storage unit 21 to the re-encryption apparatus 40 under the control of the control unit 25 (step ST24).

With the above processes, the encryption processing is complete.

Note that in this embodiment, verification may be skipped and generation of the verification data may be skipped, as described above (or as will be described later). This applies to the following embodiments and modifications.

(3) The re-encryption key generation processing is executed by the re-encryption key generator 30, as shown in FIG. 4 and following steps ST31 to ST33.

That is, the communication unit 33 of the re-encryption key generator 30 acquires the public key pk_j of the decryption apparatus 50 published from the key generator 10 and writes it in the temporary data storage unit 32 under the control of the control unit 35 (step ST31). Also, in step ST5 described above, the communication unit 33 received the private key sk_i of the re-encryption key generator 30 from the key generator 10 and wrote it in the private key storage unit 31.

The random number generation unit 36 generates a random number $\theta \in \mathbb{Z}_p^*$, and outputs it to the re-encryption key generation unit 34.

The re-encryption key generation unit 34 generates a re-encryption key R_{ij} based on this random number θ , the private key sk_i of the re-encryption key generator 30 in the private key storage unit 31, and the public key pk_j of the decryption apparatus 50 in the temporary data storage unit 32 (step ST32). The re-encryption key R_{ij} is described by:

$$R_{ij} = (R_{ij1}, R_{ij2}, R_{ij3})$$

for

$$R_{ij1} = (X_j \cdot g^\theta)^{1/x_i} = g^{\frac{x_j + \theta}{x_i}}, \quad R_{ij2} = (Y_{2j} \cdot g^\theta)^{1/y_i} = g^{\frac{\beta y_j + \theta}{y_i}},$$
$$R_{ij3} = (X_j \cdot Y_{2j} \cdot g^\theta)^{1/z_i} = g^{\frac{x_j + \beta y_j + \theta}{z_i}}.$$

Note that in the above, equations are described by

rewriting $g_1 = g^\alpha$ and $g_2 = g^\beta$.

After that, the re-encryption key generation unit 34 writes the generated re-encryption key R_{ij} in the temporary data storage unit 32. The communication unit 33 transmits
5 the re-encryption key R_{ij} in the temporary data storage unit 32 to the re-encryption apparatus 40 under the control of the control unit 35 (step ST33).

With the above processes, the re-encryption key generation processing is complete.

10 (4) The re-encryption processing is executed by the re-encryption apparatus 40, as shown in FIG. 5 and following steps ST41 to ST43.

The communication unit 43 of the re-encryption apparatus 40 writes the ciphertext data C_i transmitted in
15 step ST24 and the re-encryption key R_{ij} transmitted in step ST33 in the temporary data storage unit 42.

The re-encryption processing unit 44 verifies the ciphertext data C_i in the temporary data storage unit 42 using the public parameters and the following verification
20 formulas (step ST41).

$$\begin{aligned} e(C_{2X}, u^{C_1} \cdot v) &= e(X_i, C_4) \\ e(C_{2Y}, u^{C_1} \cdot v) &= e(Y_{1i}, C_4) \\ e(C_{2Z}, u^{C_1} \cdot v) &= e(Z_i, C_4) \\ e(C_{2Z1}, u^{C_1} \cdot v) &= e(Z_{1i}, C_4) \\ \mathcal{V}(C_1, \sigma, (C_3, C_4)) &= 1 \end{aligned}$$

Note that when all five verification formulas hold,

the verification has succeeded; when at least one verification formula does not hold, the verification has failed.

5 If the verification has succeeded, the re-encryption parameter generation unit 45 generates three random numbers s , t , and $k \in \mathbb{Z}_p^*$, and outputs them to the re-encryption processing unit 44.

10 The re-encryption processing unit 44 generates re-encrypted data C_{2X}' , C_{2X}'' , C_{2Y}' , C_{2Y}'' , C_{2Z}' , C_{2Z}'' , C_{2Z1}' , C_{2Z1}'' , C_2''' , C_{5X} , C_{5Y} , and C_{5Z} using these random numbers s , t , and k , the ciphertext data C_i in the temporary data storage unit 42, and the re-encryption key R_{ij} in the temporary data storage unit 42 (step ST42). These re-encrypted data are respectively described by:

$$\begin{aligned} C_{2X}' &= X_i^s, C_{2X}'' = C_{2X}^s = X_i^{rs}, C_{2Y}' = Y_{1i}^t, C_{2Y}'' = C_{2Y}^t = Y_{1i}^{rt}, \\ C_{2Z}' &= Z_i^k, C_{2Z}'' = C_{2Z}^k = Z_i^{rk}, C_{2Z1}' = Z_{1i}^k, C_{2Z1}'' = C_{2Z1}^k = Z_{1i}^{rk}, \\ C_{5X} &= R_{ij1}^{\frac{1}{s}}, C_{5Y} = R_{ij2}^{\frac{1}{t}}, C_{5Z} = R_{ij3}^{\frac{1}{k}} \end{aligned}$$

15 After completion of step ST42, the re-encryption processing unit 44 replaces the encrypted data C_{2X} , C_{2Y} , C_{2Z} , and C_{2Z1} in the ciphertext data C_i by all the encrypted data re-encrypted data C_{2X}' to C_{5Z} to generate re-encrypted text data $C_j = (C_1, C_{2X}', C_{2X}'', C_{2Y}', C_{2Y}'', C_{2Z}', C_{2X}'', C_{2Z1}', C_{2Z1}'', C_2''', C_{5X}, C_{5Y}, C_{5Z}, C_3, C_4, \sigma)$,
20 and writes the obtained re-encrypted text data C_j in the temporary data storage unit 42. Note that the re-encrypted

text data $C_j = (C_1, C_{2X}', C_{2X}'', C_{2Y}', C_{2Y}'', C_{2Z}', C_{2X}'',$
 $C_{2Z1}', C_{2Z1}'', C_2''', C_{5X}, C_{5Y}, C_{5Z}, C_3, C_4, \sigma)$ may be
modified to $C_j = (C_{2X}'', C_{2Y}'', C_{2X}'', C_{2Z1}'', C_{5X}, C_{5Y}, C_{5Z},$
 $C_3, C_4, \sigma)$ by omitting verification data $(C_1, C_{2X}', C_{2Y}',$
5 $C_{2Z}', C_{2Z1}', C_2''', C_4, \sigma)$ which is not used in decryption
when the verification is skipped. In this case, the
processing for generating the verification data $(C_{2X}',$
 $C_{2Y}', C_{2Z}', C_{2Z1}', C_2''')$ is also skipped.

In either case, the communication unit 43 transmits
10 the re-encrypted text data C_j in the temporary data storage
unit 42 to the decryption apparatus 50 under the control of
the control unit 47 (step ST43).

With the above processes, the re-encryption processing
is complete.

15 (5) The decryption processing is executed by the
decryption apparatus 50, as shown in FIG. 6 and following
steps ST51 and ST52.

That is, the communication unit 53 of the decryption
apparatus 50 receives the re-encrypted text data C_j
20 transmitted in step ST43, and writes it in the temporary
data storage unit 52.

The decryption processing unit 54 verifies the
re-encrypted text data C_j in the temporary data storage
unit 52 using the public parameters, the public key pk_j of
25 the apparatus 50, and the following verification formulas
(step ST51).

$$\begin{aligned}
e(C''_{2X}, u^{C_1} \cdot v) &= e(C'_{2X}, C_4) \\
e(C''_{2Y}, u^{C_1} \cdot v) &= e(C'_{2Y}, C_4) \\
e(C''_{2Z}, u^{C_1} \cdot v) &= e(C'_{2Z}, C_4) \\
e(C''_{2Z1}, u^{C_1} \cdot v) &= e(C'_{2Z1}, C_4) \\
e(C_{5Z}, C'_{2Z}) &= e(C_{5X}, C'_{2X}) \cdot e(Y_{2j}, g) \\
e(C_{5Z}, C'_{2Z1}) &= e(C_{5Y}, C'_{2Y}) \cdot e(X_j, g_1) \\
\mathcal{V}(C_1, \sigma, (C_3, C_4)) &= 1
\end{aligned}$$

If all seven verification formulas hold, the verification has succeeded; if at least one verification formula does not hold, the verification has failed.

5 If the verification has succeeded, the decryption processing unit 54 decrypts the re-encrypted text data C_j using the private key sk_j of the apparatus to obtain the message m (step ST52). This decryption is described by:

$$m = C_3 / \left\{ \left(\frac{e(C_{5Z}, C''_{2Z})}{e(C_{5X}, C''_{2X})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C''_{2Z1})}{e(C_{5Y}, C''_{2Y})} \right)^{\frac{1}{x_j}} \right\}$$

Whether or not the decryption result of the above equation is m can be verified by:

$$\begin{aligned}
 & C_3 / \left\{ \left(\frac{e(C_{5Z}, C_{2Z}'')}{e(C_{5X}, C_{2X}'')} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C_{2Z1}''')}{e(C_{5Y}, C_{2Y}'')} \right)^{\frac{1}{x_j}} \right\} \\
 &= C_3 / \left\{ \left(\frac{e(g^{(x_j + \beta y_j + \theta)/z_i k}, g^{z_i r k})}{e(g^{(x_j + \theta)/x_i s}, g^{x_i r s})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(g^{(x_j + \beta y_j + \theta)/z_i k}, g^{\alpha z_i r k})}{e(g^{(\beta y_j + \theta)/y_i t}, g^{\alpha y_i r t})} \right)^{\frac{1}{x_j}} \right\} \\
 &= C_3 / \left\{ \left(\frac{e(g^{x_j + \beta y_j + \theta}, g^r)}{e(g^{x_j + \theta}, g^r)} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(g^{x_j + \beta y_j + \theta}, g^{\alpha r})}{e(g^{\beta y_j + \theta}, g^{\alpha r})} \right)^{\frac{1}{x_j}} \right\} \\
 &= m \cdot e(g_1 g_2, g)^r / (e(g, g)^{\beta r} \cdot e(g, g)^{\alpha r}) = m.
 \end{aligned}$$

Note that this equation is described by rewriting $g_1 = g^\alpha$ and $g_2 = g^\beta$.

Note that the decryption processing unit 54 may skip the verification processing of step ST51, and may execute the decryption processing of step ST52. Also, when the re-encrypted text data C_j does not include any verification data, the decryption processing unit 54 skips the verification processing of step ST51 and executes the decryption processing of step ST52. Furthermore, m may be a key in place of the message itself. For example, as for a symmetric key "key" in the symmetric key cryptosystem, $m = \text{key}$ may be set to replace m by "key". In this case, ciphertext obtained by encrypting a message using the symmetric key "key" may be appended to the ciphertext data or re-encrypted text data. The same applies to the following embodiments and modifications.

Note that the order of processes may be changed as

needed in this embodiment. For example, the order of the decryption processing and ciphertext verification processing may be changed. Likewise, since the re-encryption key generation processing does not require
5 any parameter (more specifically, a random number) used upon execution of the encryption processing, the re-encryption key generation processing may be executed before the encryption processing.

As described above, according to this embodiment,
10 since the re-encryption key R_{ij} is generated based on the random number θ , even when the server and users collude, the decryption authority can be prevented from being re-transferred without any permission of a transfer source. In this manner, since extremely high reliability need not
15 be required for the server, a file sharing system which can be used by the users more securely can be provided.

[Modification 1]

In the example described in the first embodiment, the encryption apparatus 20 generates ciphertext data, the
20 re-encryption apparatus 40 re-encrypts the ciphertext data to generate re-encrypted text data, and the decryption apparatus 50 decrypts the re-encrypted text data. However, the first embodiment may be modified to a mode in which ciphertext data is decrypted without re-encryption. In
25 this case, only the key setup processing, encryption processing, and decryption processing can be executed. The key setup processing in this modification is the same as

that in the first embodiment. The encryption processing and decryption processing in this modification will be described below.

5 The difference between the encryption processing of this modification and that of the first embodiment is only in the final step. In order to give the following description while using the aforementioned symbols, let i be the identification informant of the decryption apparatus 50 for the sake of convenience. In this case, the
10 communication unit 22 of the encryption apparatus 20 transmits ciphertext data C_i in the temporary data storage unit 21 to the decryption apparatus 50 under the control of the control unit 25 (step ST24').

15 The decryption apparatus 50 verifies the ciphertext data C_i generated by the encryption apparatus 20 in the same manner as in step ST41. If the verification has succeeded, the decryption apparatus 50 decrypts the ciphertext data C_i using the private key sk_i to obtain a message m . This decryption is described by:

$$m = C_3 / e(g_1g_2, C_{2X})^{\frac{1}{x_i}}$$

20 Whether or not the decryption result of the above equation is m can be verified by:

$$\begin{aligned} & m \cdot e(g_1g_2, g)^r / e(g_1g_2, C_{2X})^{\frac{1}{x_i}} \\ &= m \cdot e(g_1g_2, g)^r / e(g_1g_2, g^{x_i r})^{\frac{1}{x_i}} = m \cdot e(g_1g_2, g)^r / e(g_1g_2, g)^r = m. \end{aligned}$$

[Modification 2]

In addition to modification 1, as will be described below, the first embodiment may be modified to a mode in which ciphertext data is decrypted without re-encryption.

5 In this case as well, only the key setup processing, encryption processing, and decryption processing can be executed. The key setup processing and decryption processing of this modification are the same as those in the first embodiment. The encryption processing and
10 decryption processing of this modification will be described below. Note that j refers to identification information of the decryption apparatus 50 in this modification.

The encryption parameter generation unit 23 of the
15 encryption apparatus 20 generates (ssk, svk) (step ST21') in the same manner as in step ST21 and sets the verification key svk in ciphertext data C_1 ($C_1 = svk$).

Also, the encryption parameter generation unit 23 generates five random numbers; r, s, t, k , and $\theta \in \mathbb{Z}_p^*$, and
20 outputs them to the ciphertext generation unit 24.

The ciphertext generation unit 24 generates encrypted data $C_{2X}', C_{2X}'', C_{2Y}', C_{2Y}'', C_{2Z}', C_{2Z}'', C_{2Z1}', C_{2Z1}'', C_2''', C_{5X}, C_{5Y}, C_{5Z}, C_3$, and C_4 with respect to a message $m \in G_T$ as plaintext data using these random numbers r, s, t, k ,
25 and θ , and the public key pk_j of the decryption apparatus 50 (step ST22'). These encrypted data are respectively given by:

$$\begin{aligned}
 C'_{2X} &= Y_{2j}^s, C''_{2X} = Y_{2j}^{rs}, C'_{2Y} = X_j^t, C''_{2Y} = X_j^{rt}, \\
 C'_{2Z} &= Y_{2j}^k, C''_{2Z} = Y_{2j}^{rk}, C'_{2Z1} = X_j^k, C''_{2Z1} = X_j^{rk}, \\
 C_3 &= e(g_1 g_2, g)^r \cdot m, C_4 = (u^{svk} \cdot v)^r, \\
 C_{5X} &= (g_1 \cdot g^\theta)^{\frac{1}{s}}, C_{5Y} = g^{\frac{\theta+1}{t}}, C_{5Z} = (g_1 \cdot g^{\theta+1})^{\frac{1}{k}}
 \end{aligned}$$

After completion of step ST22', the ciphertext generation unit 24 generates a one-time signature σ in the same manner as in step ST23.

After that, the ciphertext generation unit 24 generates ciphertext data $C_j = (C_1, C_{2X}', C_{2X}'', C_{2Y}', C_{2Y}'', C_{2Z}', C_{2Z}'', C_{2Z1}', C_{2Z1}'', C_2''', C_{5X}, C_{5Y}, C_{5Z}, C_3, C_4, \sigma)$ including all the encrypted data C_1 to C_4 and the one-time signature σ , and writes the obtained ciphertext data in the temporary data storage unit 21.

The communication unit 22 transmits the ciphertext data C_j in the temporary data storage unit 21 to the decryption apparatus 50 under the control of the control unit 25.

The decryption apparatus 50 verifies the ciphertext data C_j generated by the encryption apparatus 20 in the same manner as in step ST51. If the verification has succeeded, the decryption apparatus 50 decrypts the ciphertext data C_j using the private key sk_j to obtain a message m . This decryption is described by:

$$m = C_3 / \left\{ \left(\frac{e(C_{5Z}, C''_{2Z})}{e(C_{5X}, C''_{2X})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C''_{2Z1})}{e(C_{5Y}, C''_{2Y})} \right)^{\frac{1}{x_j}} \right\}$$

Whether or not the decryption result of the above equation is m can be verified by:

$$\begin{aligned}
 & C_3 / \left\{ \left(\frac{e(C_{5Z}, C_{2Z}'')}{e(C_{5X}, C_{2X}'')} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C_{2Z1}'')}{e(C_{5Y}, C_{2Y}'')} \right)^{\frac{1}{x_j}} \right\} \\
 &= C_3 / \left\{ \left(\frac{e(g^{(1+\alpha+\theta)/k}, g^{\beta y_j r k})}{e(g^{(\alpha+\theta)/s}, g^{\beta y_j r s})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(g^{(1+\alpha+\theta)/k}, g^{x_j r k})}{e(g^{(\theta+1)/t}, g^{x_j r t})} \right)^{\frac{1}{x_j}} \right\} \\
 &= C_3 / \left\{ \left(\frac{e(g^{1+\alpha+\theta}, g^{\beta r})}{e(g^{\alpha+\theta}, g^{\beta r})} \right) \cdot \left(\frac{e(g^{1+\alpha+\theta}, g^r)}{e(g^{\theta+1}, g^r)} \right) \right\} \\
 &= m \cdot e(g_1 g_2, g)^r / (e(g, g)^{\beta r} \cdot e(g, g)^{\alpha r}) = m.
 \end{aligned}$$

Note that the above equation is described by rewriting $g_1 = g^\alpha$ and $g_2 = g^\beta$.

5 [Modification 3]

In the example described in the first embodiment, the public parameters include the three members g , g_1 , and g_2 of the system fixed values. However, the present invention is not limited to this. For example, the member g_2 may not be generated, and the public parameters may not include the member g_2 . In this case, in the first embodiment, $g_2 = g$ may be set to replace g_2 by g . The same applies to the following embodiments and modifications.

[Modification 4]

15 In the example described in the first embodiment, the public parameters include the three members g , g_1 , and g_2 of the system fixed values. However, the present invention is not limited to this. For example, the public parameters

may include four or more members of the system fixed values. For example, when the public parameters include four members g , g_1 , g_2 , and g_3 , $g_2 = g_2g_3$ may be set to replace g_2 by g_2g_3 in the first embodiment. Also, for
5 example, when the public parameters include five members g , g_1 , g_2 , g_3 , and g_4 , $g_1 = g_1g_3$ and $g_2 = g_2g_4$ may be set to respectively replace g_1 by g_1g_3 and g_2 by g_2g_4 in the first embodiment. The same applies to the following embodiments and modifications.

10 (Second Embodiment)

This embodiment will explain an example in which a re-encryption key is updated every certain period. As a parameter which expresses a period, a time parameter L is used. Of the key setup processing, encryption processing,
15 re-encryption key generation processing, re-encryption processing, and decryption processing, the encryption processing, re-encryption key generation processing, and re-encryption processing use the time parameter. The time parameter is used as follows. For example, when the
20 encryption processing is executed in a certain period t_1 , the encryption processing to be described later is executed to have $L = t_1$; when the encryption processing is executed in the next period t_2 , the encryption processing to be described later is executed to have $L = t_2$. The key setup
25 processing, encryption processing, re-encryption key generation processing, re-encryption processing, and decryption processing of this embodiment will be described

below. Note that parts common to the first embodiment described above will be described using the same reference numerals and a description thereof will not be repeated.

(1) Key Setup Processing

5 Public parameters are the same as those in the first embodiment. Letting i be identification information of a re-encryption key generator 30, a public key/private key generation unit 14 generates a private key $x_i, y_i, z_i, w_i \in \mathbb{Z}_p^*$ of the re-encryption key generator 30, and generates
10 a public key $pk_i = (X_i, Y_{1i}, Y_{2i}, Z_i, Z_{1i}, W_i, W_{1i})$ (for $X_i = g^{x_i}, Y_{1i} = g_1^{y_i}, Y_{2i} = g_2^{y_i}, Z_i = g^{z_i}, Z_{1i} = g_1^{z_i}, W_i = g^{w_i}$, and $W_{1i} = g_1^{w_i}$) of the re-encryption key generator 30 using this private key $sk_i = (x_i, y_i, z_i, w_i)$ (step ST7).

 Likewise, letting j be identification information of a
15 decryption apparatus 50, the public key/private key generation unit 14 generates a private key $sk_j = (x_j, y_j, z_j, w_j)$ of the decryption apparatus 50, and generates a public key $pk_j = (X_j, Y_{1j}, Y_{2j}, Z_j, Z_{1j}, W_j, W_{1j})$ (for $X_j = g^{x_j}, Y_{1j} = g_1^{y_j}, Y_{2j} = g_2^{y_j}, Z_j = g^{z_j}, Z_{1j} = g_1^{z_j}, W_j = g^{w_j}$, and $W_{1j} = g_1^{w_j}$) of the decryption apparatus 50 using
20 this private key sk_j (step ST10).

(2) Encryption Processing

 As in the first embodiment, an encryption parameter generation unit 23 of an encryption apparatus 20 generates
25 (ssk, svk) (step ST21), and sets a verification key svk in ciphertext data C_1 ($C_1 = svk$).

 Also, the encryption parameter generation unit 23

generates a random number $r \in \mathbb{Z}_p^*$, and outputs it to a ciphertext generation unit 24.

5 The ciphertext generation unit 24 generates encrypted data C_{2X} , C_{2Y} , C_{2Z} , C_{2Z1} , C_{2F} , C_3 , and C_4 with respect to a message $m \in G_T$ as plaintext data using this random number r , the public key pk_1 of the re-encryption key generator 30, and the time parameter L (step ST22). These encrypted data are respectively given by:

$$C_{2X} = X_i^r, C_{2Y} = Y_{1i}^r, C_{2Z} = Z_i^r, C_{2Z1} = Z_{1i}^r, \\ C_{2F} = F_i(L)^r, C_3 = e(g_1 g_2, g)^r \cdot m, C_4 = (u^{svk} \cdot v)^r$$

where a function $F_i(L)$ is defined by:

$$F_i(L) = g^L \cdot W_i = g^{L+w_i} \quad (L \in \mathbb{Z})$$

10 After completion of step ST22, the ciphertext generation unit 24 generates, for the time parameter L and the encrypted data C_3 and C_4 , a one-time signature σ by means of a signature generation function $\hat{S}$ in the public parameters and the signature key ssk generated in step ST21
15 (step ST23). The signature σ is described by:

$$\sigma = \hat{S}(ssk, (L, C_3, C_4))$$

After that, the ciphertext generation unit 24 generates ciphertext data $C_i = (L, C_1, C_{2X}, C_{2Y}, C_{2Z}, C_{2Z1}, C_{2F}, C_3, C_4, \sigma)$ including the time parameter L , all the
20 encrypted data C_1 to C_4 , and the one-time signature σ , and writes the obtained ciphertext data in a temporary data

storage unit 21.

(3) Re-encryption Key Generation Processing

A random number generation unit 36 generates three random numbers; θ , δ_x , and $\delta_y \in \mathbb{Z}_p^*$, and outputs them to a re-encryption key generation unit 34.

The re-encryption key generation unit 34 generates a re-encryption key R_{ijL} using these random numbers θ , δ_x , and δ_y , the private key sk_i of the re-encryption key generator 30 in a private key storage unit 31, and the public key pk_j of the decryption apparatus 50 in a temporary data storage unit 32 (step ST32). The re-encryption key R_{ijL} is described by:

$$R_{ijL} = (R_{ijL1}, R_{ijL2}, R_{ijL3}, R_{ijL4}, R_{ijL5})$$

for

$$\begin{aligned} R_{ijL1} &= (X_j \cdot g^\theta)^{1/x_i} \cdot F_i(L)^{\delta_x} = g^{\frac{x_j + \theta}{x_i} + (L + w_i)\delta_x}, \\ R_{ijL2} &= (Y_{2j} \cdot g^\theta)^{1/y_i} \cdot F_i(L)^{\delta_y} = g^{\frac{\beta y_j + \theta}{y_i} + (L + w_i)\delta_y}, \\ R_{ijL3} &= (X_j \cdot Y_{2j} \cdot g^\theta)^{1/z_i} = g^{\frac{x_j + \beta y_j + \theta}{z_i}}, \\ R_{ijL4} &= X_i^{\delta_x} = g^{x_i \delta_x}, R_{ijL5} = Y_{1i}^{\delta_y} = g^{\alpha y_i \delta_y} \end{aligned}$$

Note that in the above, equations are described by rewriting $g_1 = g^\alpha$ and $g_2 = g^\beta$.

(4) Re-encryption Processing

A re-encryption processing unit 44 verifies ciphertext

data C_i in a temporary data storage unit 42 using the public parameters, the time parameter L , and the following verification formulas (step ST41).

$$\begin{aligned}e(C_{2X}, u^{C_1} \cdot v) &= e(X_i, C_4) \\e(C_{2Y}, u^{C_1} \cdot v) &= e(Y_{1i}, C_4) \\e(C_{2Z}, u^{C_1} \cdot v) &= e(Z_i, C_4) \\e(C_{2Z1}, u^{C_1} \cdot v) &= e(Z_{1i}, C_4) \\e(C_{2F}, u^{C_1} \cdot v) &= e(F_i(L), C_4) \\ \mathcal{V}(C_1, \sigma, (L, C_3, C_4)) &= 1\end{aligned}$$

Note that when all the five verification formulas
5 hold, the verification has succeeded; when at least one verification formula does not hold, the verification has failed.

If the verification has succeeded, a re-encryption
parameter generation unit 45 generates four random numbers;
10 s, t, k , and $h \in \mathbb{Z}_p^*$, and outputs them to a re-encryption processing unit 44.

The re-encryption processing unit 44 generates
re-encrypted data $C_{2X}', C_{2X}'', C_{2Y}', C_{2Y}'', C_{2Z}', C_{2Z}'',$
 $C_{2Z1}', C_{2Z1}'', C_{2F}', C_{2F}'', C_{5X}, C_{5Y}, C_{5Z}, C_{5FX},$ and C_{5FY}
15 using these random numbers s, t, k , and h , the ciphertext data C_i in the temporary data storage unit 42, the re-encryption key R_{ijL} in the temporary data storage unit 42, and the time parameter L (step ST42). These re-encrypted data are respectively described by:

$$\begin{aligned} C'_{2X} &= X_i^s, C''_{2X} = C_{2X}^s = X_i^{rs}, C'_{2Y} = Y_{1i}^t, C''_{2Y} = C_{2Y}^t = Y_{1i}^{rt}, \\ C'_{2Z} &= Z_i^k, C''_{2Z} = C_{2Z}^k = Z_i^{rk}, C'_{2Z1} = Z_{1i}^k, C''_{2Z1} = C_{2Z1}^k = Z_{1i}^{rk}, \\ C'_{2F} &= F_i(L)^h, C''_{2F} = C_{2F}^h = F_i(L)^{rh}, \end{aligned}$$

$$C_{5X} = R_{ijL1}^{\frac{1}{s}}, C_{5Y} = R_{ijL2}^{\frac{1}{t}}, C_{5Z} = R_{ijL3}^{\frac{1}{k}}, C_{5FX} = R_{ijL4}^{\frac{1}{h}}, C_{5FY} = R_{ijL5}^{\frac{1}{h}}$$

After completion of step ST42, the re-encryption processing unit 44 replaces the encrypted data C2X, C2Y, C2Z, C2Z1, C2F in the ciphertext data Ci by all the encrypted data re-encrypted data C2X' to C5FY to generate re-encrypted text data Cj = (C1, C2X', C2X'', C2Y', C2Y'', C2Z', C2Z'', C2Z1', C2Z1'', C2F', C2F'', C5X, C5Y, C5Z, C5FX, C5FY, C3, C4, σ), and writes the obtained re-encrypted text data Cj in the temporary data storage unit 42.

(5) Decryption Processing

A decryption processing unit 54 verifies the re-encrypted text data Cj in a temporary data storage unit 52 using the public parameters, the public key pkj of the apparatus 50, and the following verification formulas (step ST51).

$$\begin{aligned}
e(C''_{2X}, u^{C_1} \cdot v) &= e(C'_{2X}, C_4) \\
e(C''_{2Y}, u^{C_1} \cdot v) &= e(C'_{2Y}, C_4) \\
e(C''_{2Z}, u^{C_1} \cdot v) &= e(C'_{2Z}, C_4) \\
e(C''_{2Z1}, u^{C_1} \cdot v) &= e(C'_{2Z1}, C_4) \\
e(C''_{2F}, u^{C_1} \cdot v) &= e(C'_{2F}, C_4) \\
e(C_{5Z}, C'_{2Z}) \cdot e(C_{5FX}, C'_{2F}) &= e(C_{5X}, C'_{2X}) \cdot e(Y_{2j}, g) \\
e(C_{5Z}, C'_{2Z1}) \cdot e(C_{5FY}, C'_{2F}) &= e(C_{5Y}, C'_{2Y}) \cdot e(X_j, g_1) \\
\mathcal{V}(C_1, \sigma, (L, C_3, C_4)) &= 1
\end{aligned}$$

If all the eight verification formulas hold, the verification has succeeded; if at least one verification formula does not hold, the verification has failed.

5 If the verification has succeeded, the decryption processing unit 54 decrypts the re-encrypted text data C_j using the private key sk_j of the apparatus to obtain a message m (step ST52). This decryption is described by:

$$m = C_3 / \left\{ \left(\frac{e(C_{5Z}, C''_{2Z}) \cdot e(C_{5FX}, C''_{2F})}{e(C_{5X}, C''_{2X})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C''_{2Z1}) \cdot e(C_{5FY}, C''_{2F})}{e(C_{5Y}, C''_{2Y})} \right)^{\frac{1}{x_j}} \right\}$$

10 Whether or not the decryption result of the above equation is m can be verified by:

$$\begin{aligned}
& C_3 / \left\{ \left(\frac{e(C_{5Z}, C_{2Z}'') \cdot e(C_{5FX}, C_{2F}'')}{e(C_{5X}, C_{2X}'')} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C_{2Z1}'') \cdot e(C_{5FY}, C_{2F}'')}{e(C_{5Y}, C_{2Y}'')} \right)^{\frac{1}{z_j}} \right\} \\
&= C_3 / \left\{ \left(\frac{e(g^{\frac{x_j + \beta y_j + \theta}{z_i k}}, g^{z_i r k}) \cdot e(g^{\frac{z_j \delta_x}{h}}, g^{(L+w_i) r h})}{e(g^{\frac{((x_j + \theta)/x_i) + (L+w_i) \delta_x}{s}}, g^{x_i r s})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(g^{\frac{z_j + \beta y_j + \theta}{z_i k}}, g^{\alpha z_i r k}) \cdot e(g^{\frac{\alpha y_i \delta_y}{h}}, g^{(L+w_i) r h})}{e(g^{\frac{((\beta y_j + \theta)/y_i) + (L+w_i) \delta_y}{t}}, g^{\alpha y_i r t})} \right)^{\frac{1}{z_j}} \right\} \\
&= C_3 / \left\{ \left(\frac{e(g^{x_j + \beta y_j + \theta}, g^r) \cdot e(g^{x_i \delta_x}, g^{(L+w_i) r})}{e(g^{(x_j + \theta) + (L+w_i) x_i \delta_x}, g^r)} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(g^{x_j + \beta y_j + \theta}, g^{\alpha r}) \cdot e(g^{\alpha y_i \delta_y}, g^{(L+w_i) r})}{e(g^{(\beta y_j + \theta) + (L+w_i) y_i \delta_y}, g^{\alpha r})} \right)^{\frac{1}{z_j}} \right\} \\
&= m \cdot e(g_1 g_2, g)^r / (e(g, g)^{\beta r} \cdot e(g, g)^{\alpha r}) = m.
\end{aligned}$$

Note that this equation is described by rewriting $g_1 = g^\alpha$ and $g_2 = g^\beta$.

Note that the order of processes may be changed as needed in this embodiment. For example, the order of the decryption processing and ciphertext verification processing may be changed. Likewise, the re-encryption key generation processing may be executed before the encryption processing.

As described above, according to this embodiment, since the re-encryption key R_{ijL} is generated based on the random numbers θ , δ_x , and δ_y , and the time parameter L , whether or not to transfer the decryption authority can be decided for each period, thus allowing flexible access control, in addition to the effects of the first embodiment. Thus, even after the decryption authority about ciphertext for a user A is transferred to a user B in a certain period, the decryption authority about ciphertext

for the user A is not given to the user B in the next period, that is, the decryption authority of the user B (about ciphertext for the user A) can be invalidated, thus providing a more convenient file sharing system.

5 [Modification 5]

 In the example described in the second embodiment, the encryption apparatus 20 generates ciphertext data, a re-encryption apparatus 40 re-encrypts the ciphertext data to generate re-encrypted text data, and the decryption
10 apparatus 50 decrypts the re-encrypted text data. However, the second embodiment may be modified to a mode in which ciphertext data is decrypted without re-encryption. In this case, only the key setup processing, encryption processing, and decryption processing can be executed. The
15 key setup processing in this modification is the same as that in the second embodiment. The encryption processing and decryption processing in this modification will be described below.

 The difference between the encryption processing of
20 this modification and that of the second embodiment is only in the final step. In order to give the following description while using the aforementioned symbols, let i be the identification informant of the decryption apparatus 50 for the sake of convenience. In this case, a
25 communication unit 22 of the encryption apparatus 20 transmits ciphertext data C_i in the temporary data storage unit 21 to the decryption apparatus 50 under the control of

a control unit 25 (step ST24').

The decryption apparatus 50 verifies the ciphertext data C_i generated by the encryption apparatus 20 in the same manner as in step ST41. If the verification has
5 succeeded, the decryption apparatus 50 decrypts the ciphertext data C_i using the private key sk_i to obtain a message m . This decryption is described by:

$$m = C_3 / e(g_1 g_2, C_{2X})^{\frac{1}{x_i}}$$

Whether or not the decryption result of the above equation is m can be verified by:

$$\begin{aligned} & m \cdot e(g_1 g_2, g)^r / e(g_1 g_2, C_{2X})^{\frac{1}{x_i}} \\ &= m \cdot e(g_1 g_2, g)^r / e(g_1 g_2, g^{x_i r})^{\frac{1}{x_i}} = m \cdot e(g_1 g_2, g)^r / e(g_1 g_2, g)^r = m. \end{aligned}$$

10 [Modification 6]

In addition to modification 5, as will be described below, the first embodiment may be modified to an aspect in which ciphertext data is decrypted without re-encryption. In this case as well, only the key setup processing,
15 encryption processing, and decryption processing can be executed. The key setup processing and decryption processing of this modification are the same as those in the second embodiment. The encryption processing and decryption processing of this modification will be
20 described below. Note that j refers to identification information of the decryption apparatus 50 in this

modification.

The encryption parameter generation unit 23 of the encryption apparatus 20 generates (ssk, svk) (step ST21') in the same manner as in step ST21 and sets the verification key svk in ciphertext data C_1 ($C_1 = \text{svk}$).

Also, the encryption parameter generation unit 23 generates eight random numbers; $r, s, t, k, h, \theta, \delta_x$, and $\delta_y \in \mathbb{Z}_p^*$, and outputs them to the ciphertext generation unit 24.

The ciphertext generation unit 24 generates encrypted data $C_{2X}', C_{2X}'', C_{2Y}', C_{2Y}'', C_{2Z}', C_{2Z}'', C_{2Z1}', C_{2Z1}'', C_{2F}', C_{2F}'', C_{5X}, C_{5Y}, C_{5Z}, C_{5FX}, C_{5FY}, C_3$, and C_4 with respect to a message $m \in G_T$ as plaintext data using these random numbers $r, s, t, k, h, \theta, \delta_x$, and δ_y , the public key pk_j of the decryption apparatus 50, and the time parameter L (step ST22'). These encrypted data are respectively given by:

$$\begin{aligned} C_{2X}' &= Y_{2j}^s, C_{2X}'' = Y_{2j}^{rs}, C_{2Y}' = X_j^t, C_{2Y}'' = X_j^{rt}, \\ C_{2Z}' &= Y_{2j}^k, C_{2Z}'' = Y_{2j}^{rk}, C_{2Z1}' = X_j^k, C_{2Z1}'' = X_j^{rk}, \end{aligned}$$

$$C_{2F}' = F_i(L)^h, C_{2F}'' = F_i(L)^{rh}$$

$$\begin{aligned}
 C_3 &= e(g_1 g_2, g)^r \cdot m, \quad C_4 = (u^{svk} \cdot v)^r, \\
 C_{5X} &= (g_1 \cdot g^\theta \cdot F_j(L)^{\delta_y})^{\frac{1}{s}} = g^{\frac{\alpha + \theta + (L + w_j)\delta_y}{s}}, \\
 C_{5Y} &= (g^{1+\theta} \cdot F_j(L)^{\delta_x})^{\frac{1}{t}} = g^{\frac{1 + \theta + (L + w_j)\delta_x}{t}}, \\
 C_{5Z} &= (g_1 \cdot g^{1+\theta})^{\frac{1}{k}} = g^{\frac{\alpha + 1 + \theta}{k}}, \\
 C_{5FX} &= (Y_{2j})^{\frac{\delta_y}{h}}, \quad C_{5FY} = (X_j)^{\frac{\delta_x}{h}}
 \end{aligned}$$

After completion of step ST22', the ciphertext generation unit 24 generates a one-time signature σ in the same manner as in step ST23.

After that, the ciphertext generation unit 24
5 generates ciphertext data $C_j = (L, C_{2X}', C_{2X}'', C_{2Y}', C_{2Y}'', C_{2Z}', C_{2Z}'', C_{2Z1}', C_{2Z1}'', C_{2F}', C_{2F}'', C_{5X}, C_{5Y}, C_{5Z}, C_{5FX}, C_{5FY}, C_3, C_4, \sigma)$ including the time parameter L , all the encrypted data C_1 to C_4 and the one-time signature σ , and
10 writes the obtained ciphertext data in the temporary data storage unit 21.

The communication unit 22 transmits the ciphertext data C_j in the temporary data storage unit 21 to the decryption apparatus 50 under the control of the control unit 25.

15 The decryption apparatus 50 verifies the ciphertext data C_j generated by the encryption apparatus 20 in the same manner as in step ST51. If the verification has succeeded, the decryption apparatus 50 decrypts the ciphertext data C_j using the private key sk_j to obtain a

message m . This decryption is described by:

$$m = C_3 / \left\{ \left(\frac{e(C_{5Z}, C_{2Z}'') \cdot e(C_{5FX}, C_{2F}'')}{e(C_{5X}, C_{2X}'')} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C_{2Z1}'') \cdot e(C_{5FY}, C_{2F}'')}{e(C_{5Y}, C_{2Y}'')} \right)^{\frac{1}{x_j}} \right\}$$

Whether or not the decryption result of the above equation is m can be verified by:

$$\begin{aligned} & C_3 / \left\{ \left(\frac{e(C_{5Z}, C_{2Z}'') \cdot e(C_{5FX}, C_{2F}'')}{e(C_{5X}, C_{2X}'')} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C_{2Z1}'') \cdot e(C_{5FY}, C_{2F}'')}{e(C_{5Y}, C_{2Y}'')} \right)^{\frac{1}{x_j}} \right\} \\ &= C_3 / \left\{ \left(\frac{e(g^{\frac{\alpha+1+\theta}{k}}, g^{\beta y_j r k}) \cdot e(g^{\frac{\beta y_j \delta_y}{h}}, g^{(L+w_j) r h})}{e(g^{\frac{\alpha+\theta+(L+w_j)\delta_y}{s}}, g^{\beta y_j r s})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(g^{\frac{\alpha+1+\theta}{k}}, g^{x_j r k}) \cdot e(g^{\frac{x_j \delta_x}{h}}, g^{(L+w_j) r h})}{e(g^{\frac{1+\theta+(L+w_j)\delta_x}{t}}, g^{x_j r t})} \right)^{\frac{1}{x_j}} \right\} \\ &= C_3 / \left\{ \left(\frac{e(g^{\alpha+1+\theta}, g^{\beta r}) \cdot e(g^{\beta \delta_y}, g^{(L+w_j) r})}{e(g^{\alpha+\theta+(L+w_j)\delta_y}, g^{\beta r})} \right) \cdot \left(\frac{e(g^{\alpha+1+\theta}, g^r) \cdot e(g^{\delta_x}, g^{(L+w_j) r})}{e(g^{1+\theta+(L+w_j)\delta_x}, g^r)} \right) \right\} \\ &= m \cdot e(g_1 g_2, g)^r / (e(g, g)^{\beta r} \cdot e(g, g)^{\alpha r}) = m. \end{aligned}$$

Note that the above equation is described by rewriting $g_1 = g^\alpha$ and $g_2 = g^\beta$.

According to at least one of the aforementioned embodiments, since a re-encryption key is generated based on a random number, even when the server and users collude, the decryption authority can be prevented from being re-transferred without any permission of a transfer source.

The method described in each embodiment can also be stored in a storage medium such as a magnetic disk (floppyTM disk, hard disk, or the like), an optical disk (CD-ROM, DVD, or the like), a magneto-optical disk (MO), or

a semiconductor memory as a program which can be executed by a computer and distributed.

As the storage medium, any configuration which is a computer-readable storage medium in which a program can be stored may be used regardless of a storage format.

An OS (operating system) which operates on a computer on the basis of an instruction of a program installed from the storage medium in the computer, database management software, and MW (middleware) such as network software may execute a part of the processes to realize the embodiment.

Furthermore, the storage medium according to each embodiment includes not only a medium independent of a computer but also a storage medium in which a program transmitted through a LAN, the Internet, or the like is downloaded and stored or temporarily stored.

The number of storage media is not limited to one. A case in which the process in each embodiment is executed from a plurality of media is included in the storage medium according to the present invention. Any medium configuration may be used.

A computer according to each embodiment is to execute the processes in each embodiment on the basis of the program stored in a storage medium. The computer may have any configuration such as one apparatus constituted by a personal computer or a system in which a plurality of apparatuses are connected by a network.

A computer in each embodiment includes not only a

personal computer but also an arithmetic processing
apparatus, a microcomputer, or the like included in an
information processing apparatus. The computer is a
generic name of an apparatus and a device which can realize
5 the functions of the present invention by a program.

While certain embodiments have been described, these
embodiments have been presented by way of example only, and
are not intended to limit the scope of the inventions.
Indeed, the novel embodiments described herein may be
10 embodied in a variety of other forms; furthermore, various
omissions, substitutions and changes in the form of the
embodiments described herein may be made without departing
from the spirit of the inventions. The accompanying claims
and their equivalents are intended to cover such forms or
15 modifications as would fall within the scope and spirit of
the inventions.

C L A I M S

1. A re-encryption key generator (30), which generates a re-encryption key required to obtain re-encrypted text data, which is configured to be decrypted
5 by means of a second private key of a second user device, by re-encrypting, without decrypting, ciphertext data obtained by encrypting plaintext data by means of a first public key of a first user device, the generator characterized by comprising:

10 first storage means (31) for storing a first private key corresponding to the first public key;

second storage means (32) for storing a second public key corresponding to the second private key;

15 first random number generation means (36) for generating a first random number; and

re-encryption key generation means (34) for generating the re-encryption key based on the first private key, the second public key, and the first random number.

2. The re-encryption key generator of claim 1,
20 characterized in that the re-encryption key generation means (34) generates the re-encryption key based on the first private key, the second public key, and the first random number independently of ciphertext data before re-encryption.

25 3. The re-encryption key generator of claim 1, characterized in that the first public key is generated based on the first private key and a plurality of system

fixed values, and

the second public key is generated based on the second private key and the plurality of system fixed values.

5 4. The re-encryption key generator of claim 2, characterized in that when the first private key is represented by $sk_i = (x_i, y_i, z_i)$, the second private key is represented by $sk_j = (x_j, y_j, z_j)$, the first random number is represented by θ , the plurality of system fixed value are represented by g, g_1 , and g_2 (for g, g_1 , and $g_2 \in G$ if bilinear map groups as groups of prime orders p including a bilinear map $e: G \times G \rightarrow G_1$ are represented by G and G_T), letting β be a power index related to the respective system fixed values (for $g_2 = g^\beta$), and R_{ij} be
10 the re-encryption key, the re-encryption key R_{ij} is described by:

$$R_{ij} = (R_{ij1}, R_{ij2}, R_{ij3})$$

(for

$$R_{ij1} = g^{\frac{x_j + \theta}{x_i}}, R_{ij2} = g^{\frac{\beta y_j + \theta}{y_i}}, R_{ij3} = g^{\frac{x_j + \beta y_j + \theta}{z_i}}$$

),

when the first public key is represented by pk_i , the
20 first public key pk_i is described by:

$$pk_i = (X_i, Y_{1i}, Y_{2i}, Z_i, Z_{1i})$$

(for

$$X_i = g^{x_i}, Y_{1i} = g_1^{y_i}, Y_{2i} = g_2^{y_i}, Z_i = g^{z_i}, Z_{1i} = g_1^{z_i}$$

),

when the second public key is represented by pk_j , the first public key pk_j is described by:

$$pk_j = (X_j, Y_{1j}, Y_{2j}, Z_j, Z_{1j})$$

(for

$$X_j = g^{x_j}, Y_{1j} = g_1^{y_j}, Y_{2j} = g_2^{y_j}, Z_j = g^{z_j}, Z_{1j} = g_1^{z_j}$$

5),

when the plaintext data is represented by m (for $m \in G_T$), a second random number is represented by r , and the ciphertext data is expressed by C_i (the bilinear map $e: G \times G \rightarrow G_T$ is expressed by $e(,)$), the ciphertext data C_i is

10 described by:

$$C_i = (C_{2X}, C_{2Y}, C_{2Z}, C_{2Z1}, C_3)$$

(for

$$C_{2X} = X_i^r, C_{2Y} = Y_{1i}^r, C_{2Z} = Z_i^r, C_{2Z1} = Z_{1i}^r, C_3 = e(g_1 g_2, g)^r \cdot m$$

),

when the re-encrypted text data is represented by C_j
 15 (third, fourth, and fifth random numbers are represented by s , t , and k), the re-encrypted text data C_j is described by:

$$C_j = (C_{2X}^s, C_{2Y}^s, C_{2Z}^s, C_{2Z1}^s, C_{5X}, C_{5Y}, C_{5Z}, C_3)$$

(for

$$C''_{2X} = C_{2X}^s = X_i^{rs}, \quad C''_{2Y} = C_{2Y}^t = Y_{li}^{rt}, \quad C''_{2Z} = C_{2Z}^k = Z_i^{rk}, \quad C''_{2Z1} = C_{2Z1}^k = Z_{li}^{rk},$$

$$C_{5X} = R_{ij1}^{\frac{1}{s}}, \quad C_{5Y} = R_{ij2}^{\frac{1}{t}}, \quad C_{5Z} = R_{ij3}^{\frac{1}{k}}$$

), and

a relationship among the plaintext data m , the re-encrypted text data C_j , and the second private key sk_j is expressed by:

$$m = C_3 / \left\{ \left(\frac{e(C_{5Z}, C''_{2Z})}{e(C_{5X}, C''_{2X})} \right)^{\frac{1}{y_j}} \cdot \left(\frac{e(C_{5Z}, C''_{2Z1})}{e(C_{5Y}, C''_{2Y})} \right)^{\frac{1}{x_j}} \right\}$$

5

5. A re-encryption apparatus (40) configured to communicate with a re-encryption key generator (30), which generates a re-encryption key required to obtain re-encrypted text data, which is configured to be decrypted by means of a second private key of a second user device, by re-encrypting, without decrypting, ciphertext data obtained by encrypting plaintext data by means of a first public key of a first user device, the apparatus characterized by comprising:

15 storage means (41) for storing the re-encryption key received from the re-encryption key generator;

re-encryption means (44) for obtaining the re-encrypted text data by re-encrypting, without decrypting, the ciphertext data received from the first user device by means of the re-encryption key in the storage means; and

20

means (43) for transmitting the obtained re-encrypted

text data to the second user device,

wherein the re-encryption key is generated based on a first private key corresponding to the first public key, a second public key corresponding to the second private key, and a first random number generated by the re-encryption key generator.

6. The re-encryption apparatus of claim 5, characterized in that the re-encryption key is generated independently of ciphertext data before re-encryption.

7. A program which is executed by a processor of a re-encryption key generator (30), which generates a re-encryption key required to obtain re-encrypted text data, which is configured to be decrypted by means of a second private key of a second user device, by re-encrypting, without decrypting, ciphertext data obtained by encrypting plaintext data by means of a first public key of a first user device, and which is stored in a non-transitory computer-readable storage medium (M3), the program characterized by comprising:

a first program code (33) for controlling the processor to execute processing for writing a first private key corresponding to the first public key in first storage means (31) of the re-encryption key generator;

a second program code (ST31) for controlling the processor to execute processing for writing a second public key corresponding to the second private key in second storage means (32) of the re-encryption key generator;

a third program code (36) for controlling the processor to execute processing for generating a first random number; and

5 a fourth program code (32) for controlling the processor to execute processing for generating the re-encryption key based on the first private key, the second public key, and the first random number.

8. The program of claim 7, characterized in that the processing for generating the re-encryption key is executed
10 by the processor independently of ciphertext data before re-encryption.

9. A program which is executed by a processor of a re-encryption apparatus (40) configured to communicate with a re-encryption key generator (30), which generates a
15 re-encryption key required to obtain re-encrypted text data, which is configured to be decrypted by means of a second private key of a second user device, by re-encrypting, without decrypting, ciphertext data obtained by encrypting plaintext data by means of a first public key
20 of a first user device, and which is stored in a non-transitory computer-readable storage medium (M4), the program characterized by comprising:

a first program code (43) for controlling the processor to execute processing for writing the
25 re-encryption key received from the re-encryption key generator in storage means (41) of the re-encryption apparatus;

a second program code (44) for controlling the processor to execute processing for obtaining the re-encrypted text data by re-encrypting, without decrypting, the ciphertext data received from the first user device by means of the re-encryption key in the storage means; and

a third program code (ST43) for controlling the processor to execute processing for transmitting the obtained re-encrypted text data to the second user device, wherein the re-encryption key is generated based on a first private key corresponding to the first public key, a second public key corresponding to the second private key, and a first random number generated by the re-encryption key generator.

10. A program which is executed by a processor of an encryption apparatus (20) configured to communicate with a re-encryption apparatus (40) using a re-encryption key required to obtain re-encrypted text data, which is configured to be decrypted by means of a second private key of a second user device, by re-encrypting, without decrypting, ciphertext data obtained by encrypting plaintext data by means of a first public key of a first user device, and which is stored in a non-transitory computer-readable storage medium (M2), the program characterized by comprising:

a first program code (22) for controlling the processor to execute processing for writing the first

public key in storage means (21) of the encryption apparatus;

a second program code (ST22) for controlling the processor to execute processing for obtaining the ciphertext data by encrypting the plaintext data using the first public key in the storage means; and

a third program code (ST24) for controlling the processor to execute processing for transmitting the obtained ciphertext data to the re-encryption apparatus,

wherein the re-encryption key is generated based on a first private key corresponding to the first public key, a second public key corresponding to the second private key, and a first random number generated by the re-encryption key generator (30).

11. A program which is executed by a decryption apparatus (50), which decrypts re-encrypted text data received from an re-encryption apparatus (40) after the re-encryption apparatus re-encrypts, without decrypting, plaintext data by means of a first public key of a first user device to obtain the re-encrypted text data configured to be decrypted by means of a second private key of a second user device, and which is stored in a non-transitory computer-readable storage medium (M5), the program characterized by comprising:

a first program code (53) for controlling the processor to execute processing for writing the second private key in storage means (51) of the decryption

apparatus; and

a second program code (54) for controlling the processor to execute processing for decrypting the re-encrypted text data received from the re-encryption apparatus based on the second private key in the storage means to obtain the plaintext data,

wherein the re-encryption key is generated based on a first private key corresponding to the first public key, a second public key corresponding to the second private key, and a first random number generated by a re-encryption key generator (30) which generates the re-encryption key.

12. The program of any one of claims 9 to 11, characterized in that the re-encryption key is generated independently of ciphertext data before re-encryption.