

ANTITRIPPING DEVICE FOR WATCH-ESCAPEMENT

The present invention relates to an anti-trip device for a watch escapement, this escapement comprising, amongst other elements, a balance spring made up of several coils and a balance provided with at least one arm, the balance being pivotably mounted between a plate and a bridge, said device comprising a finger fixed
5 to the balance arm, at least one column by which the finger can pass when the balance is moving, said column being secured to said balance bridge, and a locking arm fixed to the outer coil of the balance spring, the locking arm being able to insert itself between said column and said finger to prevent the sprung balance rotating beyond an angle outside its normal operating angle.

10 Such a device is known. It was disclosed in the work entitled "Der Chronometer Gang" by Professor Alois Irk and published by Deutsche Uhrmacher Zeitung, Berlin 1923. Reference will be made particularly to paragraphs 116 to 120 (pages 74 to 77) and to Figure 25 of the cited work.

This device is implemented in so called detent escapements which are suitable
15 for timepieces of large dimensions such as marine chronometers. These timepieces are appreciated for their high level of precision, which is why they very often use a detent escapement, which itself famed for its high level of precision. This escapement has, however, a significant drawback, namely its sensitivity to shocks. Consequently, it is reputed to be unsuitable for wristwatches. In fact, a shock applied to the timepiece
20 can cause its balance to rotate beyond a normal operating angle. This then produces tripping since unlocking and pulses occur twice in the same vibration.

When one wishes to fit a timepiece of small dimensions, for example a wristwatch, with a detent escapement to replace for example the conventional lever escapement and thus enable it to enjoy the advantages provided by such an
25 escapement, new techniques will have to be used, different to those known to date if one wishes to avoid failure. Various solutions have been proposed recently to overcome the lack of energy developed by the sprung balance of a wristwatch to overcome the forces acting on the detent of a detent escapement. Nonetheless, the problem of tripping remains, and this has to be resolved when a balance spring of
30 small dimensions, such as that mounted in a wristwatch, is used.

If one refers to the aforecited work, it can be seen that the locking arm proposed for the anti-trip device is suitable solely for a balance spring of large dimensions. It is in fact a part that has undergone machining several times including the machining of a bore through which the last coil of the balance spring will pass.

This is ill suited to a balance spring of small dimensions, moreover it is difficult and complicated to make.

In order to overcome the aforecited drawbacks, the present invention, in addition to answering the generic definition of the first paragraph of this description, is
5 characterized in that the locking arm is a clamp hooked onto the outer coil of the balance spring.

The features and advantages of the present invention will appear from the following description, made with reference to the annexed drawings, and giving by way of explanatory but non-limiting example, an advantageous embodiment of an anti-
10 trip device for a wristwatch fitted with a detent escapement, in said drawings:

- Figure 1 is a perspective view of the anti-trip device showing the locking arm according to the invention,

- Figure 2 is a profile view showing together the various elements involved in preventing the escapement from tripping, and

- 15 - Figure 3 is a plan view of the clamp used as locking arm according to the invention.

The anti-trip device will now be described with reference to Figures 1 and 2. This device is for a timepiece escapement, more specifically a detent escapement, of which only those elements necessary for comprehension of the invention are shown in
20 Figures 1 and 2, namely a balance spring 1 made up of several coils 9 and 10 and a balance 2 provided with at least one arm 3 and pivotably mounted between a plate (not shown) and a bridge 4.

The detent escapement further includes the following elements that are not shown in the drawings: an escapement wheel provided with generally pointed teeth
25 which rest in turn on a locking pallet stone, a brake-lever returned by a spring, the brake-lever carrying said locking face of the pallet stone at its first end and, at its second end, a first actuating finger able to be actuated by a second actuating finger carried by a plate secured to the balance, this plate further carrying an impulse pallet stone able to receive impulses from the teeth of the escapement wheel. At each
30 oscillation of the balance, the locking pallet stone is released from the tooth of the escapement wheel and another tooth of the same wheel, acting on the impulse pallet stone, gives an impulse to the balance. It will be observed that the second actuating finger is arranged so as only to actuate the first finger of the brake-lever in one rotational direction of the balance, i.e. during the first vibration of the oscillation after
35 the impulse occurs. When the balance rotates in the other direction, i.e. during the second vibration of the oscillation, the first finger of the brake-lever is not actuated since the second finger carried by the plate is arranged to retract after which no

impulses are produced. It is clear from the explanations that have just been given that if the first vibration makes the balance rotate beyond a normal amplitude which is of the order of 320 degrees, for example following a shock applied to the watch, the first finger of the brake-lever can be actuated a second time. A second impulse is then
5 produced during the same vibration, which causes the escapement to trip.

In order to prevent this phenomenon, the anti-trip device proposed in the
aforecited work and illustrated in Figures 1 and 2 of the present invention, comprises a
finger 5 fixed to the arm of balance 2 and two columns 6 and 7 between which the
finger can pass when the balance is moving, these columns being secured to bridge 4
10 of the balance. The device further includes a locking arm 8 fixed to the outer coil 10 of
balance spring 1. As is shown particularly well in Figure 2, this locking arm 8 is
inserted between columns 6 and 7 and finger 5 to prevent balance 2 from rotating
beyond an angle exceeding its normal rotational angle. In fact, at the end of the first
vibration, a situation shown in Figure 1, balance spring 1 and its last coil 10 are
15 presenting their largest expanse which causes locking arm 8, fixed to the last coil, to
be placed between finger 5 of arm 3 and the two columns 6 and 7 of bridge 4. At this
moment, if a shock is applied to the timepiece and if this shock causes the balance to
continue to rotate in the anti-clockwise direction (arrow A), finger 5 abuts against
locking arm 8, the latter in turn abutting against columns 6 and 7 (a situation illustrated
20 in Figure 2). Balance 2 is then stopped preventing the second vibration discussed
hereinbefore. Tripping is thus prevented. It will be noted that from this moment
onwards, the balance will rotate in the opposite direction to make its second vibration.
Balance spring 1 and the last coil 10 will be compressed again drawing locking arm 8
towards the centre. Locking arm 8 will then no longer be an obstacle to the passage of
25 finger 5 between columns 6 and 7 which it will pass twice per oscillation.

As Figures 1 to 3 show, the present invention is characterized in that the
locking arm 8 is a clamp hooked onto the outer coil 10 of balance spring 1. This
method is perfectly suited to the balance springs of small dimensions encountered, for
example, in wristwatches. The system envisaged does not require any complicated
30 preparation and machining of the locking arm as is the case of the arm of the
aforecited work. The clamp can be arranged on the outer coil without any difficulty, at
the desired location, without it being necessary to thread it onto the balance spring
and fix it thereto as provided in the aforecited work.

Clamp 8 can take different forms, including that illustrated in Figures 2 and 3.
35 Here, the clamp has the shape of an X whose top arms 11 and 12 are shaped to
constrict the balance spring. Figure 3 shows particularly well that the top arms are cut
in the shape of bevelled jaws for gripping the balance spring properly. The bottom

arms 13 and 14 are arranged to act as means for gripping and positioning the clamp. A specially designed tool for gripping and positioning the clamp enables the clamp to be gripped by its arms 13 and 14, allows said arms to be moved towards each other in order to move the top arms 11 and 12 apart elastically to fit them onto the balance
5 spring. It will be understood that clamp 8 could be made from a strip simply by stamping or chemical etching.

It will be noted finally that the two columns 6 and 7 secured to bridge 4 could consist of two pins driven into the bridge. The present invention proposes, however, to simplify this passage by providing, as shown in Figures 1 and 2, a frame 15 whose two columns 6 and 7 are connected by a strut 16, this strut carrying a pin 17 driven into bridge 4 of balance 2.

It will also be noted that the device of the invention can be envisaged with one column fixed to bridge 4.

CLAIMS

1. Anti-trip device for a timepiece escapement, said escapement including, amongst other elements, a balance spring (1) made up of several coils (9, 10) and a balance (2) provided with at least one arm (3), the balance being pivotably mounted between a plate and a bridge (4), said device including a finger (5) fixed to the arm (3)
5 of the balance, at least one column (6, 7) by which the finger (5) can pass when the balance is moving, said column being secured to the bridge (4) of said balance, and a locking arm (8) fixed to the outer coil (10) of the balance spring (1), said locking arm being able to be inserted between said column (6, 7) and said finger (5) to prevent the balance rotating beyond an angle exceeding its normal operating angle, characterized
10 in that the locking arm (8) is a clamp hooked onto the outer coil (10) of the balance spring (1).
2. Anti-trip device according to claim 1, characterized in that said device further comprises a second column and in that said finger (5) can pass between said first and second columns when the balance is moving.
- 15 3. Anti-trip device according to claim 1 or 2, characterized in that the clamp (8) has the shape of an X, one end of whose top arms (11, 12) is shaped to constrict the balance spring elastically and those bottom arms (13, 14) are arranged to act as means for gripping and positioning said clamp (8).
4. Anti-trip device according to claim 3, characterized in that the clamp (8)
20 is a strip whose contours are obtained by chemical etching.
5. Anti-trip device according to claim 2, characterized in that the two columns (6, 7) secured to the balance bridge (4) form a frame (15) with a strut (16) that connects them, said strut carrying a pin (17) driven into the balance bridge (4).