

Description

This invention relates to a pull tab assembly removably mounted on and adapted to manipulate a slider in opening and closing a slide fastener.

The present invention is an improvement in and relating to the invention disclosed in U.S. Patent No. 4,920,615 to the same assignee, Yoshida Kogyo K. K., Tokyo, Japan.

A slider pull tab disclosed in U.S. Patent No. 4,920,615 is represented in Figures 6 - 8 inclusive of the accompanying drawings and shown comprising a clamper 100 pivotally connected to a trunnion 101 on a slider body 102, a hook 103 extending from one end of the clamper 100 and having an aperture 104, a resilient member 105 disposed at the lower portion of the hook 103 and normally closing off the aperture 104 of the hook 103 and a pull tab 106 having an annular link 107 for connecting the pull tab 106 to the clamper 100. While this prior pull tab device has many of its inherent advantages, it has now been found that the resilient member 105 is susceptible to deformation leading to loss of its elastic action, if not to physical damage, when subjected to pressure exerted by the annular link 107 rotating in contact with the resilient member 105 as for example in the case of ironing the garment to which the slide fastener is attached.

The present invention seeks to provide an improved pull tab assembly for slide fastener slider which incorporates structural features tailored to eliminate the foregoing drawbacks of the prior art.

More specifically, the pull tab assembly according to the invention includes means of maintaining a pull tab out of contact with a resilient member even when the pull tab is oriented to underlie a clamper.

The pull tab assembly according to the invention further includes means of facilitating connection and disconnection of the pull tab with respect to a clamper.

The pull tab assembly of the invention also includes means of preventing undue lateral rocking movement of the pull tab.

According to the invention, there is provided a pull tab assembly for slide fastener slider which comprises a clamper including an arcuate peripheral wall defining therein an aperture and a transverse bridge linking the confronting ends of the peripheral wall, a hook extending from the confronting ends and having its distal end terminating short of the bridge so as to define an opening, a resilient member supported in the hook, and a pull tab characterized in that the pull tab is provided at one end with a pair of spaced ears interconnected by a pin, and each of the ears has side peripheral walls and an end surface merging through corners with the side walls, and each of the ears has a geometry such that a distance as measured between the end surface and a tangent line of the pin extending in parallel with the end surface is smaller

than the width of the opening of the hook and that a distance as measured between the side wall adjoining the corner and a tangent line of the pin extending at right angles to the end surface is larger than the width of the opening.

Particular features of the invention are set out in dependent claims 2 to 5

The above and other advantages of the present invention will appear clear from the following detailed description taken in conjunction with the accompanying drawings which illustrate by way of example a preferred embodiment.

Figure 1 is a plan view of a pull tab assembly embodying the invention;

Figure 2 is an exploded, perspective view on enlarged scale of the assembly;

Figure 3 is a cross-sectional view of part of the assembly shown in one operative position;

Figure 4 is a view similar to Figure 3 but showing the assembly in another operative position;

Figure 5 is a plan view on further enlarged scale of the pull tab assembly shown in fully assembled condition; and

Figures 6, 7 and 8 inclusive are views utilized to explain the construction and operation of a prior art pull tab assembly.

Referring now to the drawings and firstly Figure 1, there is shown a pull tab assembly 10 which comprises a clamper 11 and a pull tab 12 releasably connected thereto by a hook 20, the clamper 11 being pivotally connected to a connecting lug or trunnion 14 on a slider body 15 in a well known manner.

As better shown in Figure 2, the clamper 11 includes an arcuate peripheral wall 16 defining therein an aperture 17 through which the trunnion 14 of the slider body 15 is loosely fitted for pivotal connection of the clamper 11 and a transverse bridge 18 linking the confronting ends 16', 16' of the arcuate peripheral wall 16, at which ends are formed shoulders 19, 19 having respective tapered guide surfaces 19', 19'. A hook 20 formed integral with the arcuate peripheral wall 16 has an upper straight wall 21 extending integrally from the confronting ends 16', 16' of the arcuate peripheral wall 16, a lower straight wall 22 and an arcuate wall 23 integrally interconnecting the upper and lower walls 21 and 22 and defining therewith a substantially U-shaped aperture 24 extending transversely of the pull tab body 12. The lower wall 22 of the hook 20 has its distal end terminating short of the transverse bridge 18 so as to define an opening 25 communicating with the aperture 24 and adapted to bring the clamper 11 into and out of engagement with the hook 20. The upper wall 21 of the hook 20 is raised above the level of the arcuate peripheral wall 16 so as to define an opening 26 through which a resilient member 27 is mounted in place in a manner hereafter described.

The hook 20 has a first recess 28 formed in the

inner surface of the upper wall 21 and a second recess 29 formed in the distal end of the lower wall 22 for receptive engagement with the resilient member 27 as better shown in Figures 3 and 4.

The resilient member 27 thus supported in the hook 20 is in the form of a substantially U-shaped leaf spring which has an upper arm 30 and a lower arm 31 merged together by an arcuate joint 32. The upper arm 30 is provided at its distal end with an upwardly projecting claw 30', and the lower arm 31 is provided at its distal end with a downwardly slanted finger 31'.

The claw 30' and the finger 31' are snappingly received in and retained at the first recess 28 and the second recess 29, respectively, of the hook 20, with the arcuate joint 32 held in surrounding relation to the transverse bridge 18 of the clasper 11 as better shown in Figures 3 and 4.

The pull tab body 12 is in the form of a rod provided at one end 12' with a pair of ears 33, 33 diverging toward the clasper 11 and interconnected by a transverse pin 34 with which to displace the lower arm 31 of the resilient member 27 inwardly out of engagement with the second recess 29 of the hook 20 so as to engage the pull tab 12 with the clasper 11 as shown in Figures 3 and 4. The ears 33, 33 each have side peripheral walls 33a, 33a tapering off toward the pull tab end 12' and a substantially straight end surface 33b merging through rounded corners 33c, 33c with the side walls 33a, 33a. The ears 33, 33 are spaced apart by a distance substantially corresponding to the width of the hook 20 such that the pull tab 12 once connected to the clasper 11 is retained in place against lateral displacement.

The provision of the guide surfaces 19', 19' being tapered facilitates smooth sliding movement therealong of the ears 33, 33 of the pull tab 12 into the aperture 24 of the hook 20.

According to an important aspect of the invention, each of the ears 33, 33 has a geometry such that a distance B as measured between the end surface 33b and a tangent line 34a of the pin 34 extending in parallel with the end surface 33b is smaller than the width A of the opening 25 of the hook 20 and that a distance C as measured between the side peripheral wall 33a adjoining the corner 33c and a tangent line 34b of the pin 34 extending at right angles to the end surface 33b is larger than the width A of the opening 25 of the hook 20, as depicted in Figures 3 and 4. This geometric concept contributes to a maximum of ease with which to mount and dismount the pull tab 12 with respect to the clasper 11 and at the same time precludes the possibility of the pin 34 of the pull tab 12 jamming against and injuring the resilient member 27 even in the event the pull tab 12 is flipped down to undie the clasper 11 as shown in Figure 4.

Claims

1. A pull tab assembly (10) for slide fastener slider which comprises a clasper (11) including an arcuate peripheral wall (16) defining therein an aperture (17) and a transverse bridge (18) linking the confronting ends (16', 16') of said peripheral wall (16), a hook (20) extending from said confronting ends (16', 16') and having its distal end terminating short of said bridge (18) so as to define an opening (25), a resilient member (27) supported in said hook (20), and a pull tab (12), characterized in that said pull tab (12) is provided at one end (12') with a pair of spaced ears (33, 33) interconnected by a pin (34), and each of said ears (33, 33) has side peripheral walls (33a, 33a) and an end surface (33b) merging through corners (33c, 33c) with said side walls (33a, 33a), and each of said ears (33, 33) has a geometry such that a distance (B) as measured between said end surface (33b) and a tangent line (34a) of said pin (34) extending in parallel with said end surface (33b) is smaller than the width (A) of said opening (25) of said hook (20) and that a distance (C) as measured between said side wall (33a) adjoining said corner (33c) and a tangent line (34b) of said pin (34) extending at right angles to said end surface (33b) is larger than the width (A) of said opening (25).
2. A pull tab assembly (10) according to claim 1 characterized in that said ears (33, 33) are spaced apart by a distance substantially corresponding to the width of said hook (20).
3. A pull tab assembly (10) according to claim 1 characterized in that said clasper (11) has tapered guide surfaces (19', 19') at said confronting ends (16', 16').
4. A pull tab assembly (10) according to claim 1 characterized in that said pull tab (12) is in the form of a rod.
5. A pull tab assembly (10) according to claim 1 characterized in that said pair of ears (33, 33) diverge toward said clasper (11) and taper off toward said pull tab (12).

Patentansprüche

1. Griffbaugruppe (10) für einen Reißverschlußschieber, umfassend einen Halter (11), der eine bogenförmige Umfangswand (16) aufweist, die eine Öffnung (17) und einen die gegenüberliegenden enden (16', 16') dieser Umfangswand (16) verbindenden Quersteg (18) begrenzt, einen



inner surface of the upper wall 21 and a second recess 29 formed in the distal end of the lower wall 22 for receptive engagement with the resilient member 27 as better shown in Figures 3 and 4.

The resilient member 27 thus supported in the hook 20 is in the form of a substantially U-shaped leaf spring which has an upper arm 30 and a lower arm 31 merged together by an arcuate joint 32. The upper arm 30 is provided at its distal end with an upwardly projecting claw 30', and the lower arm 31 is provided at its distal end with a downwardly slanted finger 31'.

The claw 30' and the finger 31' are snappingly received in and retained at the first recess 28 and the second recess 29, respectively, of the hook 20, with the arcuate joint 32 held in surrounding relation to the transverse bridge 18 of the clamper 11 as better shown in Figures 3 and 4.

The pull tab body 12 is in the form of a rod provided at one end 12' with a pair of ears 33, 33 diverging toward the clamper 11 and interconnected by a transverse pin 34 with which to displace the lower arm 31 of the resilient member 27 inwardly out of engagement with the second recess 29 of the hook 20 so as to engage the pull tab 12 with the clamper 11 as shown in Figures 3 and 4. The ears 33, 33 each have side peripheral walls 33a, 33a tapering off toward the pull tab end 12' and a substantially straight end surface 33b merging through rounded corners 33c, 33c with the side walls 33a, 33a. The ears 33, 33 are spaced apart by a distance substantially corresponding to the width of the hook 20 such that the pull tab 12 once connected to the clamper 11 is retained in place against lateral displacement.

The provision of the guide surfaces 19', 19' being tapered facilitates smooth sliding movement therealong of the ears 33, 33 of the pull tab 12 into the aperture 24 of the hook 20.

According to an important aspect of the invention, each of the ears 33, 33 has a geometry such that a distance B as measured between the end surface 33b and a tangent line 34a of the pin 34 extending in parallel with the end surface 33b is smaller than the width A of the opening 25 of the hook 20 and that a distance C as measured between the side peripheral wall 33a adjoining the corner 33c and a tangent line 34b of the pin 34 extending at right angles to the end surface 33b is larger than the width A of the opening 25 of the hook 20, as depicted in Figures 3 and 4. This geometric concept contributes to a maximum of ease with which to mount and dismount the pull tab 12 with respect to the clamper 11 and at the same time precludes the possibility of the pin 34 of the pull tab 12 jamming against and injuring the resilient member 27 even in the event the pull tab 12 is flipped down to undlie the clamper 11 as shown in Figure 4.

Claims

1. A pull tab assembly (10) for slide fastener slider which comprises a clamper (11) including an arcuate peripheral wall (16) defining therein an aperture (17) and a transverse bridge (18) linking the confronting ends (16', 16') of said peripheral wall (16), a hook (20) extending from said confronting ends (16', 16') and having its distal end terminating short of said bridge (18) so as to define an opening (25), a resilient member (27) supported in said hook (20), and a pull tab (12), characterized in that said pull tab (12) is provided at one end (12') with a pair of spaced ears (33, 33) interconnected by a pin (34), and each of said ears (33, 33) has side peripheral walls (33a, 33a) and an end surface (33b) merging through corners (33c, 33c) with said side walls (33a, 33a), and each of said ears (33, 33) has a geometry such that a distance (B) as measured between said end surface (33b) and a tangent line (34a) of said pin (34) extending in parallel with said end surface (33b) is smaller than the width (A) of said opening (25) of said hook (20) and that a distance (C) as measured between said side wall (33a) adjoining said corner (33c) and a tangent line (34b) of said pin (34) extending at right angles to said end surface (33b) is larger than the width (A) of said opening (25).
2. A pull tab assembly (10) according to claim 1 characterized in that said ears (33, 33) are spaced apart by a distance substantially corresponding to the width of said hook (20).
3. A pull tab assembly (10) according to claim 1 characterized in that said clamper (11) has tapered guide surfaces (19', 19') at said confronting ends (16', 16').
4. A pull tab assembly (10) according to claim 1 characterized in that said pull tab (12) is in the form of a rod.
5. A pull tab assembly (10) according to claim 1 characterized in that said pair of ears (33, 33) diverge toward said clamper (11) and taper off toward said pull tab (12).

Patentansprüche

1. Griffbaugruppe (10) für einen Reißverschluss-schieber, umfassend einen Halter (11), der eine bogenförmige Umfangswand (16) aufweist, die eine Öffnung (17) und einen die gegenüberliegenden enden (16', 16') dieser Umfangswand (16) verbindenden Quersteg (18) begrenzt, einen



- Haken (20) aufweist, der sich von den zugekehrten enden (16', 16') erstreckt und dessen abliegendes Ende kurz vor dem Quersteg (18) endet, um eine Öffnung (25) zu begrenzen, ein in dem Haken (20) abgestütztes elastisches Teil (27) und einen Griff (12), dadurch gekennzeichnet, daß der Griff (12) an einem Ende (12') mit zwei im Abstand angeordneten Ohren (33, 33) versehen ist, die durch einen Stift (34) miteinander verbunden sind und die jeweils seitliche Umfangswände (33a, 33a) und eine Endfläche (33b) aufweisen, die über Ecken (33c, 33c) in die Seitenwände (33a, 33a) übergeht, wobei jedes Ohr (33, 33) eine Geometrie hat, so daß ein Abstand (B) zwischen dieser Endfläche (33b) und einer zu dieser Endfläche (33b) parallelen Tangente (34a) des Stiftes kleiner ist als die Breite (A) der Öffnung (25) des Hakens (20) und daß ein Abstand (C) zwischen dieser an die Ecke (33c) angrenzenden Seitenwand (33a) und einer zu dieser Endfläche (33b) rechtwinkligen Tangente (34b) des Stiftes (34) größer ist als die Breite (A) der Öffnung (25).
2. Griffbaugruppe (10) nach Anspruch 1, dadurch gekennzeichnet, daß die Ohren (33, 33) unter einem Abstand angeordnet sind, der im wesentlichen der Breite des Hakens (20) entspricht.
 3. Griffbaugruppe (10) nach Anspruch 1, dadurch gekennzeichnet, daß der Klemmhalter (11) an den besagten einander zugekehrten enden (16', 16') geneigte Führungsflächen 19', 19') aufweist.
 4. Griffbaugruppe (10) nach Anspruch 1, dadurch gekennzeichnet, daß der Griff (12) die Form eines Stabes hat.
 5. Griffbaugruppe (10) nach Anspruch 1, dadurch gekennzeichnet, daß die beiden Ohren (33, 33) zum Klemmhalter (11) hin divergieren und sich zum Griff (12) hin verjüngen.
- paire de languettes espacées (33, 33) reliées entre elles par un axe (34), et en ce que chaque languette (33, 33) comporte des parois périphériques latérales (33a, 33a) et une surface d'extrémité (33b) reliant par des coins (33c, 33c) lesdites parois latérales (33a, 33a), et en ce que chaque languette (33, 33) a une géométrie telle que la distance (B) mesurées entre ladite surface d'extrémité (33b) et une ligne (34a) tangente audit axe (34) et parallèle à ladite surface d'extrémité (33b) est inférieure à la largeur (A) de ladite ouverture (25) dudit crochet (20), et telle que la distance (C) mesurée entre ladite paroi latérale (33a) à proximité dudit coin (33c) et une ligne (34b) tangente audit axe (34) et perpendiculaire à ladite surface d'extrémité (33b) est supérieure à la largeur (A) de ladite ouverture (25).
2. Ensemble de tirette (10) selon la revendication 1, caractérisé en ce que lesdites languettes (33, 33) sont espacées l'une de l'autre d'une distance qui correspond sensiblement à la largeur dudit crochet (20).
 3. Ensemble de tirette (10) selon la revendication 1, caractérisé en ce que ladite attache (11) comporte des surfaces de guidage (19', 19') biseautées au niveau desdites extrémités en vis-à-vis (16', 16').
 4. Ensemble de tirette (10) selon la revendication 1, caractérisé en ce que ladite tirette (12) a la forme d'une tige.
 5. Ensemble de tirette (10) selon la revendication 1, caractérisé en ce que ladite paire de languette (33, 33) diverge en direction de ladite attache (11) et converge en direction de ladite tirette (12).

Revendications

1. Ensemble de tirette (10) destiné à un curseur de fermeture à glissière qui comporte une attache (11) incluant une paroi périphérique courbe (16) y délimitant une ouverture (17) et un pont transversal (18) qui relie les extrémités en vis-à-vis (16', 16') de ladite paroi périphérique (16), un crochet (20) qui part desdites extrémités en vis-à-vis (16', 16') et dont l'extrémité distale se termine à une certaine distance dudit pont (18) afin de définir une ouverture (25), un élément élastique (27) supporté dans ledit crochet (20), et une tirette (12), caractérisé en ce que ladite tirette (12) comporte en une première extrémité (12') une

5

10

15

20

25

30

35

40

45

50

55

4