

9900531-6



1905

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 41/08, 53/02, 1/20, 1/46, 1/16	A1	(11) International Publication Number: WO 98/06636
		(43) International Publication Date: 19 February 1998 (19.02.98)

(21) International Application Number: PCT/AU97/00504

(22) International Filing Date: 8 August 1997 (08.08.97)

(30) Priority Data:

PO 1560	12 August 1996 (12.08.96)	AU
PO 2566	25 September 1996 (25.09.96)	AU
PO 3288	28 October 1996 (28.10.96)	AU

(71) Applicant (for all designated States except US): RADLEY VALLEY PTY. LIMITED [AU/AU]; 1/12 Jindalee Road, Port Macquarie, NSW 2444 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): McCROSSEN, Peter, Charles [AU/AU]; 109 Riverside Drive, Port Macquarie, NSW 2444 (AU).

(74) Agent: F.B. RICE & CO.; 28A Montague Street, Balmain, NSW 2041 (AU).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: REMOVABLE SEALING CLOSURE WITH CLOSURE ATTACHMENT MEANS

(57) Abstract

A container (40) has a body (41) having an open end (42) surrounded by an outwardly and downwardly extending flange (43). A closure (44) is adapted to be sealed to the container body (41). The closure (44) has a flange clamping portion (48) such that when the closure (44) is mounted to the body (41), the flange clamping portion (48) forms a seal with at least the outer surface of the flange (43) by exerting pressure inwardly against the flange (43). The flange clamping portion (48) can also be adapted to form a seal with the open end (42) of the body (41) and the inner surface of the container body (41) proximate its open end (42). A thread ring (10) adapted to be mounted to the open end of a container is also described. The thread ring has a retaining means comprising a continuous hook (13) that is adapted to sealingly engage the open end of the container and so provide a means for closures to be readily and sealingly attached to containers.

