

DESCRIPTION

Title of Invention: Method of Manufacturing Liquefied Natural Gas Carrier
Technical Field

5 [0001]

The present invention relates to a method of manufacturing a liquefied natural gas carrier.

Background Art

[0002]

10 Types of tank structures of conventional LNG ships are roughly divided into a self-supporting spherical tank, a self-supporting prismatic tank (SPB) type, and a membrane tank. An independent spherical tank is a self-supporting spherical tank made of an aluminum alloy and is supported in a hold formed by a double hull, via a skirt extending from its equatorial
15 portion. A thermal insulation work is done on an outer surface of the tank. Due to its spherical shape, the spherical tank has a disadvantage of not being capable of having a sufficient tank volume comparable to the size of the hull. The tank of this type little suffers damage even when its cargo sloshes at the time of heavy weather.

20 [0003]

The self-supporting prismatic tank is one in which a prismatic tank is housed in a hold having a double hull structure. A cold insulator is provided on an outer surface of the prismatic tank made of an aluminum alloy. Strength members for the prismatic tank are provided on an inner side of the
25 tank. This type requires void space between the prismatic tank and an inner hull, which accordingly reduces volumetric efficiency of the tank. On the

other hand, having the strength members inside the tank, it has an advantage that sloshing of a liquid cargo does not easily occur.

[0004]

Next, regarding the membrane type, on an inner surface of a hold
5 having a double hull structure, thin sheets (membranes) made of nickel steel or stainless steel are affixed, with a cold insulator therebetween, to form a LNG tank. This type has an advantage that almost all the volume of the hold can be used as a tank volume. On the other hand, it has a disadvantage that the membranes and the cold insulator are likely to suffer damage due to the
10 sloshing of a liquid cargo. It also has a problem that a thermal insulation work, in particular, the welding of the membranes is complicated and it requires a long period for the construction.

Summary of Invention

Technical Problem

15 [0005]

It is an object of this invention to provide a method of manufacturing a liquefied natural gas carrier, on which a LNG tank is mounted, the LNG tank not easily suffering damage by sloshing of a liquid cargo at the time of heavy weather and in addition capable of being constructed in a short
20 construction period.

Means for Solving the Problem

[0006]

According to a method of manufacturing a liquefied natural gas carrier of this invention, the LNG tank assembled on land is mounted and
25 fixed in a hold having a double hull structure. This LNG tank has a prismatic tank, and a heat insulator and a membrane are attached on an inner surface of the container. Strength members are attached on an outer surface of the prismatic tank in advance to reinforce the prismatic tank. After the LNG tank is mounted in the hold, the strength members are connected to the
30 hull. Therefore, a characteristic lies in that the weight of a liquid cargo is not supported only by the prismatic tank but is supported by the prismatic tank and the hull structure together.

[0007]

In this LNG ship, the heat insulation and membrane work of the LNG

tank can be done on land, which can greatly shorten a construction period for building the LNG ship as compared with conventional methods. Further, arranging the LNG tanks in two lines in the hold reduces the area of a horizontal cross section of each of the LNG tanks, which has an effect of making the occurrence of sloshing difficult.

Brief Description of Drawings

[0008]

[Fig. 1] is a cross section of a center portion of a hull of a LNG ship.

[Fig. 2] is a horizontal cross-sectional view of the center portion of the hull of the LNG ship.

[Fig. 3] is a cross section of the center portion of the hull of the LNG ship which is under construction.

[Fig. 4] is a cross section of a center portion of a hull of a LNG ship showing another example.

[Fig. 5] is a cross section of a center portion of a hull of a LNG ship remodeled from an oil and ore carrier.

[Fig. 6] is a cross-sectional view of a center portion of a hull of a LNG ship showing still another example.

Description of Embodiments

[0009]

As shown in Fig. 3, this LNG carrier has a double hull structure, and a hold 2 is formed, being surrounded by an inner hull 1 (that is, an inner bottom 1a and longitudinal bulkheads 1b). Space between the inner hull 1 and a shell plate 3 is used as a ballast tank 4.

LNG tanks 5 assembled on land in advance are mounted in each of these holds 2. The smaller a tank of this type, the more easily it is mounted on the ship, and therefore, in this embodiment, four small LNG tanks 5 are mounted in each of the holds 2 as shown in Fig. 1 and Fig. 2. Further, when the tank is small, its horizontal cross sectional area becomes small, which has a merit that a phenomenon that a liquid cargo violently sloshes in the tank (sloshing) at the time of heavy weather does not easily occur and damage to a cold insulator on an inner surface of the tank is reduced.

[0010]

The LNG tanks 5 each include a prismatic tank 6, on whose inner surface a cold insulator 7 (for example, reinforced polyurethane foam) is affixed, and it is further covered by a membrane (primary barrier) 8 made of a cryogenic material such as Invar without leaving any space therebetween. Incidentally, when necessary, the cold insulator 7 can have a double-layer structure and a secondary barrier can be provided therebetween. In a conventional membrane-type LNG tank, a cold insulator and a membrane are affixed directly on a surface of an inner hull (that is, an inner bottom and longitudinal bulkheads) of a double hull structure, but the ship of this embodiment is characterized in that a similar thermal insulation barrier work is done not on the inner hull but on the inner surface of the prismatic tank.

[0011]

In order to prevent the tank from deforming when the LNG tank 5 is lifted up so as to be mounted on the main ship or when a liquid cargo is loaded, the prismatic tank 6 needs to have sufficient rigidity. For this purpose, strength members 9 are longitudinally and vertically provided on outer surfaces of the prismatic tank 6, and for reinforcement, small stiffeners 10 are closely attached between these strength members. The prismatic tank 6 does not come into direct contact with the liquid cargo (LNG) and thus need not be made of a cryogenic material such as an aluminum alloy and can be a steel tank.

[0012]

The LNG tank 5 assembled on land is lifted up by a crane and is mounted on the main ship in a manner that it is hung down into the hold 2 (Fig. 3). Strength members 11 are welded to the inner bottom 1a and the longitudinal bulkheads 1b in the hold in advance, and the strength members 9 attached on the outer surfaces of the LNG tank 5 are welded to these strength members in an overlapping manner or in an abutting manner. Further, as shown in Fig. 2, strength members 11 are attached in advance also on transfer bulkheads 12 each separating the hold 2 and the hold 2, and the strength members 9 attached on a front surface or a rear surface of the

tank are welded to these strength members. Further, the strength members 9 projecting from facing surfaces of the left and right tanks 5, 5 and those projecting from facing surfaces of the front and rear tanks 5, 5 are also welded together. Since in-situ welding is thus necessary at the time of the installment of the LNG tanks, work spaces 13 where a worker performs a welding work are left between the prismatic tanks 6 and the inner hull 1, between the prismatic tanks 6 and the transfer bulkheads 12, and between the adjacent tank 5 and tank 5. The inner bottom 1a and the longitudinal bulkheads 1b are kept away from cold heat of the LNG tanks 5 by these spaces 13 and can be kept at a temperature slightly lower than room temperature. Therefore, as a structural material of the inner bottom and the longitudinal bulkheads, high-tension steel (this has a property that its strength reduces at low temperatures) is usable, which can reduce construction cost.

[0013]

The prismatic tanks 6 of the respective LNG tanks are each coupled to the double-hull structure via the strength members 9, 11 in this manner, so that the LNG tanks 5 are firmly supported by the hull. Further, at places where the tanks 5 are adjacent to each other, the strength members 9 are mutually coupled, so that strength unity is similarly maintained. Since the LNG tanks of this ship each are not a completely independent tank as described above, the prismatic tanks 6 need not have strength as high as that of the aforesaid self-supporting prismatic independent tank.

After the mounting of the LNG tanks 5 in the hold 2 is finished, a steel board 14 is affixed to close the tops of the tanks (Fig. 3).

[0014]

Fig. 4 shows a case where the LNG tanks 5 are housed in the hold 2 in one line, which is a structure suitable for a relatively small ship.

[0015]

The tank structures described above are also applicable when an existing ship is remodeled into a LNG ship. In this case, it is possible to fabricate and prepare the LNG tank 5 that is to be mounted on a main ship,

on a dock before the main ship enters the dock for the remodeling, and this has a characteristic of being capable of greatly shortening a construction period for the remodeling.

[0016]

5 An example of a ship easily remodeled into a LNG ship is an ore carrier or an oil and ore carrier. Fig. 5 shows a case where the oil and ore carrier is remodeled, and an ore hold formed between left and right longitudinal bulkheads 15, 15 is used as a hold 16 as it is, and in the hold 16, several LNG tanks 5, for example, totally four in two columns and two rows,
10 are arranged. The ore carrier has a hatchway 17 on an upper deck, and therefore by using this, the LNG tanks 5 can be mounted in the hold from here. The hatchway is closed later.

[0017]

15 In the above-described structures (Fig. 1 to Fig. 5), the spaces 13 are formed between the LNG tanks 5 and the inner hull 1 and the inner hull 1 is kept away from the cold heat of the LNG tanks 5, so that the inner hull 1 does not easily decrease in temperature. The structure in Fig. 6 further reduces the influence of low temperature to the inner hull 1. In this structure, strength members 9 attached on outer surfaces of a prismatic tank 6 are not
20 connected to an inner hull 1 but are separated therefrom. This prevents the cold heat of a LNG tank from moving directly to the inner hull 1 through the strength members 9. Instead, almost in the same manner as in the case of a self-supporting prismatic LNG tank of an SPB type, a bottom portion of the tank is supported by lower portion support blocks 20 and further, an upper
25 portion of the tank is supported by upper portion support blocks 21 in order to prevent the displacement of the tank in a horizontal direction. As these support blocks 20, 21, materials having a good heat insulating property, for example, a wood or the like is usable. This makes it further difficult for the inner hull 1 to be influenced by the low temperature from the LNG tank and
30 widens a range where high-tension steel is usable.

Brief Description of Reference

[0018]

	1	inner hull
	2	hold
	5	LNG tank
	6	prismatic tank
5	7	cold insulator
	8	membrane
	9	strength member
	11	strength member
	13	space
10		

CLAIMS

1. A method of manufacturing a liquefied natural gas carrier comprising:
 - a first step of forming a liquefied natural gas tank on land by assembling a steel prismatic tank with prismatic tank-side strength members for reinforcement, which are arranged on transversely and longitudinally and welded to an outer surface of the prismatic tank so as to project outwardly therefrom and by performing a thermal insulation barrier work on an inner surface of the prismatic tank so that the inner surface of the prismatic tank is covered by a cold insulator and a membrane provided on the cold insulator;
 - a second step of forming a hold of a ship, the hold having a double hull structure having an inner hull and a shell plate;
 - a third step of mounting the liquefied natural gas tank, which has been formed on the land, in the hold of the ship, the third step being carried out after the second step; and
 - a fourth step of joining the prismatic tank-side strength members, which have been, in advance, arranged on transversely and longitudinally and welded to the outer surface of the prismatic tank, to inner hull-side strength members, which have been, in advance, welded to the inner hull of the ship so as to project inwardly therefrom.
2. The method of manufacturing the liquefied natural gas carrier according to claim 1, wherein the liquefied natural gas tanks are installed in the single hold, being arranged from left to right in a width direction of the hold.