



(51) International Patent Classification:
B29B 17/02 (2006.01) *C08J 11/08* (2006.01)
C08J 11/06 (2006.01)

(21) International Application Number:
PCT/EP2019/064180

(22) International Filing Date:
31 May 2019 (31.05.2019)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1809004.3 01 June 2018 (01.06.2018) GB

(71) Applicant: **SAPERATEC GMBH** [DE/DE]; Ernst-
Graebe-Str. 10, 33611 Bielefeld (DE).

(72) Inventor: **SCHULZE, Marcus**; c/o saperatec GmbH,
Ernst-Graebe-Str. 10, 33611 Bielefeld (DE).


(74) Agent: **HARRISSON, Robert**; Herzogspitalstraße 10a,
80331 Munich (DE).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

(54) Title: SEPARATION FLUID, METHOD AND APPARATUS FOR RECYCLING MULTILAYER MATERIAL USING A PASSIVATION AGENT

Fig. 3



(57) Abstract: A method for recycling of multilayer material is disclosed. The multilayer material (10) comprises a metal layer (30) and at least one further layer (20, 40). The method comprises placing the packaging material in a vat (310) comprising a separation fluid (330) to produce a mixture of metal shreds from the metal layer (30), plastic shreds from the polymer layer (20, 40) and residual components. The separation fluid comprises a mixture comprising a mixture of water, carboxylic acid, carboxylate salt and passivation agent for passivating the surface of the metal layer.

Published:

— *with international search report (Art. 21(3))*