

(11)

2097321.

- 1 -

AUTOMATIC CONTROL OF THE LENGTH  
OF ARTICLE ROW TO BE INJECTION-MOLDED

The present invention relates to injection molding, and more particularly to a method of and apparatus for automatically controlling the length of a row of articles, such as slide fastener coupling elements, to be injection-  
5 molded in a multi-cavity mold.

In the manufacture of slide fasteners, it is known that a row of coupling elements is injection-molded on one longitudinal edge of a fastener stringer tape placed between a pair of mold halves jointly defining an elongate  
10 runner and a plurality of successive cavities spaced at equal intervals along the runner. To this end, various slide fasteners of different lengths require a plurality of multi-cavity molds each having a succession of cavities of a different row length. A suitable one of the molds  
15 must be chosen, depending on the length of a row of coupling elements to be molded, which is laborious and time-consuming. The same problem has been experienced in the production of a series of other thermoplastic articles.

According to a first aspect of the invention, there is provided a method of automatically controlling the length of a row of articles to be injection-molded in a multi-cavity mold having an elongate runner and a plurality of successive cavities spaced equidistantly along the runner, comprising the steps of: detecting an initial position of a control rod inserted in the runner; registering both the direction and the extent to which the control rod is to be moved for longitudinal adjustment with respect to the runner, depending on said initial position of the control rod and a preselected length of the article row to be molded; moving the control rod longitudinally of the runner in said registered direction; detecting the movement of the control rod to said registered extent; and in response to the last-mentioned detecting, terminating the movement of the control rod.

According to a second aspect of the invention, there is provided an apparatus comprising a multi-cavity mold having an elongate runner and a plurality of successive cavities spaced equidistantly along the runner, and means for automatically controlling the length of a row of articles to be injection-molded therein, said means comprising: a slide; means for moving said slide toward and away from the mold; a control rod projecting from said slide into the runner and movable, in response to the movement of said slide, longitudinally of the runner for allowing heated molding material to be filled in only a selected number of the successive cavities that corresponds

to a preselected length of a row of articles to be molded;  
means for detecting an initial position of said slide and  
thus said control rod in the runner and also for detecting  
the extent to which said slide and thus said control rod  
is moved; and a control unit, connected to both said moving  
means and said detecting means, for registering both the  
direction and the extent to which said control rod is to  
be moved for longitudinal adjustment with respect to the  
runner, depending on both said detected initial position  
of said control rod and said preselected length of the  
article row to molded, said control unit being adapted to  
produce a start signal for energizing said moving means  
to move said slide and thus said control rod in said  
registered direction, and a termination signal, when said  
slide and thus said control rod has been moved to said  
registered extent, for de-energizing said moving means  
to terminate the movement of said slide and thus said  
control rod.

It is believed possible by means of the present  
invention to provide a method of and apparatus for auto-  
matically controlling the length of a row of articles to  
be injection-molded on a multi-cavity mold, which can be  
used for the molding of articles of a different series  
length, thus requiring no separate molds having cavities  
of a different series length.

The invention will be described by way of example  
with reference to the accompanying drawings, wherein:-

Figure 1 is a perspective view of an apparatus embodying the present invention, with a pair of mold halves fragmentarily shown; and

5      Figure 2 is a plan view of a surface of one mold half, showing a control rod inserted in a runner of the mold.

10      Figure 1 shows an apparatus 10 for automatically controlling the length of a pair of rows of thermoplastic articles (not shown) to be injection-molded on a multi-cavity mold including a pair of first and second mold halves 11,12. The first mold half 11 is stationary, and the second mold half 11 is movable toward and away from the first mold half 12 to close and open the mold. As better shown in Figure 2, the illustrated mold 11,12 is  
15      for use in the manufacture of slide fastener coupling elements and hence has a pair of rows of equidistantly spaced cavities 13,13 disposed one row on each side of an elongate straight runner 14, each cavity 13 having a contour corresponding to the shape of a single coupling  
20      element. The cavities 13 may have any other shape. When heated thermoplastic molding material is injected into the closed mold with a pair of fastener stringer tapes (not shown) placed between the first and second mold halves 11,12, a pair of rows of thermoplastic coupling

elements is formed on the stringer tapes along their respective inner longitudinal edges, as is well known in the art.

The apparatus 10 comprises a pair of vertical posts 15,15 supported on the first mold half 11, a threaded spindle or shaft 16 rotatably supported on the first mold half 11 and extending parallel to the posts 15,15, a suitable drive means 17 for rotating the threaded shaft 16 in either direction, and a slide 18 slidably mounted on the posts 15,15 and having a threaded hole 19 through which the threaded shaft 16 threadedly extends. The slide 18 is vertically movable, in response to rotation of the threaded shaft 16, toward and away from the first mold half 11, depending on the direction of rotation of the threaded shaft 16.

A control rod 20 is supported at the upper end 20a by the slide 18 and projects into the runner 14. The control rod 20 is movable, in response to the vertical movement of the slide 18, longitudinally of the runner 14 for allowing heated thermoplastic molding material to be filled in only a selected number of the successive cavities 13 that are disposed below the lower or free end 20b of the control rod 20, the selected number corresponding to the length of a row of articles to be molded. At that time, the remaining cavities 13 that are disposed above the free end 20b of the control rod 20 are prevented from being filled with heated molding material.

A scale 21 extends parallel to the threaded shaft 16 and has a plurality of equidistantly spaced marks 22, e.g. in the form of openings, indicative of the corresponding positions of the free end 20b of the control rod 20 in the runner 14. A detector 23 is mounted on the slide 18 at such a position that the marks 22 are moved past the detector 23 successively as the slide 18 is moved vertically, for producing a signal pulse every time each mark 22 is moved past the detector 23. Preferably, the detector 23 comprises a light source and a photoelectric transducer element disposed one on each side of the scale 21. Alternatively, the detector 23 may be proximity switch or a limit switch.

The apparatus 10 also comprises a control unit 24, operatively connected to both the detector 23 and the drive means 17, for producing a start signal for energizing the drive means 17 to rotate the threaded shaft 16 in a selected direction, depending on both a preselected length of the article row to be molded and an initial position of the free end 20b of the control rod 20 in the runner 14, and a termination signal, when the number of successive signal pulses produced by the detector 23 is equal to a preselected number that corresponds to the preselected length of the article row, for de-energizing the drive means 17 to terminate the rotation of the threaded shaft 16. At the same time, the control unit 24 controls injection starting time, quantity of articles to be manufactured, and feed speed of the fastener stringer tapes or fastener chain.

When a preselected number corresponding to the length of the article row to be molded is set in the control unit 24, the control unit 24 compares the preselected number with a signal from the detector 23 and  
5 then produces a start signal for energizing the drive means 17 to rotate the threaded shaft 16 in a selected direction, depending on the result of that comparison. This rotation of threaded shaft 16 causes the slide 18 together with the control rod 20 to be moved upwardly or  
10 downwardly, depending on the direction of rotation of the threaded shaft 16. During that time the marks 22 are moved past the detector 23 successively, which produces a signal pulse every time each mark 22 is moved past the detector 23.

15 When the number of the successive signal pulses produced by the detector 23 is equal to the preselected number that corresponds to the length of the article row to be obtained, the control unit 24 produces a termination signal for de-energizing the drive means 17 to terminate  
20 the rotation of the threaded shaft 16. At the same time the vertical movement of the slide 18 is terminated. As a result, the control rod 20 is placed in a selected position that corresponds to the preselected length of the article row. Finally, heated thermoplastic molding  
25 material is injected into the closed mold 11,12; the molding material having been injected flows into only a selected number of the successive cavities 13 disposed below the free end 22b of the control rod 22 and does

not flow into the remaining cavities 13 disposed above the free end 22b of the control rod 22. Thus the pre-selected length of the article row has been obtained under automatic control.

5        According to the present invention, it is possible to use a single multi-cavity mold for the molding of articles of a different series length, thus requiring no separate molds having cavities of a different series length that corresponds to that different length of

10 articles.

19



- 9 -

CLAIMS:-

1. A method of automatically controlling the length of a row of articles to be injection-molded in a multi-cavity mold having an elongate runner and a plurality of successive cavities spaced equidistantly along the runner, comprising the steps of:

- (a) detecting an initial position of a control rod inserted in the runner;
- (b) registering both the direction and the extent to which the control rod is to be moved for longitudinal adjustment with respect to the runner, depending on said initial position of the control rod and a preselected length of the article row to be molded;
- (c) moving the control rod longitudinally of the runner in said registered direction;
- (d) detecting the movement of the control rod to said registered extent; and
- (e) in response to the last-mentioned detecting, terminating the movement of the control rod.

2. An apparatus comprising a multi-cavity mold having an elongate runner and a plurality of successive cavities spaced equidistantly along the runner, and means for automatically controlling the length of a row of articles to be injection-molded therein, said means comprising:

- (a) a slide;
- (b) means for moving said slide toward and away from the mold;



- 5 (c) a control rod projecting from said slide into the runner and movable, in response to the movement of said slide , longitudinally of the runner for allowing heated molding material to be filled in only a selected number of the successive cavities that corresponds to a preselected length of a row of articles to be molded;
- 10 (d) means for detecting an initial position of said slide and thus said control rod in the runner and also for detecting the extent to which said slide and thus said control rod is moved; and
- 15 (e) a control unit connected to both said moving means and said detecting means , for registering both the direction and the extent to which said control rod is to be moved for longitudinal adjustment with respect to the runner , depending on both said detected
- 20 initial position of said control rod and said preselected length of the article row to molded, said control unit being adapted to produce a start signal for energizing said moving means to move said slide and thus said control rod in said registered
- 25 direction, and a termination signal, when said slide and thus said control rod has been moved to said registered extent, for de-



- 11 -

energizing said moving means to terminate  
the movement of said slide and thus said  
control rod.

3. An apparatus according to claim 2, said  
5 moving means including at least one post  
supported on the mold , a threaded shaft rotatably  
supported on the mold and extending parallel to said  
post , and drive means for rotating said threaded  
shaft in either direction, said slide being  
10 slidably mounted on said post and having a threaded  
hole through which said threaded shaft threadedly  
extends, said slide being movable, in response to  
rotation of said threaded shaft , toward and away from  
the mold , depending on the direction of rotation of  
15 said threaded shaft.

4. An apparatus according to claim 3, said detecting  
means including: a scale extending parallel  
to said threaded shaft and having a plurality of  
equidistantly spaced marks indicative of the corres-  
20 ponding positions of a free end of said control rod  
in the runner ; and a detector , mounted on  
said slide at such a position that said marks ~~(22)~~ are  
moved past said detector successively as said slide  
is moved, for producing a signal pulse every time each  
25 said mark is moved past said detector , said  
termination signal being produced from said control unit  
when the number of the successive signal pulses produced  
by said detector is equal to a preselected number that



22

- 12 -

corresponds to said preselected length of the article row.

---