CLAIMS

1. A lubricating composition at least comprising:

- a base oil; and

- a detergent;

wherein the detergent comprises at least 30 mol%, based on the total amount of detergent, of a sulphonate detergent having a BN (Base Number) of from 0.1 to 80 mg KOH/g;
wherein the detergent comprises from 30 to 70 mol%, based on the total amount of detergent, of a phenate detergent, wherein the phenate detergent is an over-based detergent having a BN of at least 190 mg KOH/g;
wherein the lubricating composition comprises at least 8 wt.% of detergent, based on the total weight of the composition; and
wherein the lubricating composition has a TBN (total base number) according to ASTM D 2896 of at least 10 mg KOH/g.

2. Lubricating composition according to claim 1, wherein the detergent comprises at least 35 mol% of the sulphonate detergent.

3. Lubricating composition according to claim 1 or 2, wherein the sulphonate detergent has a BN of at most 50 mg KOH/g.

4. Lubricating composition according to any of claims 1 to 3, wherein the detergent comprises at least 35 mol% of the phenate detergent.

5. Lubricating composition according to any of claims 1 to 4, wherein the phenate detergent is an over-based detergent having a BN of at least at least 200mg KOH/g.

6. Lubricating composition according to any of claims 1 to 5, wherein the composition comprises at least 12 wt.% of detergent, based on the total weight of the composition.

7. Lubricating composition according to any of claims 1 to 6, wherein the composition has a TBN (Total Base Number) value of at most 75 mg KOH/g.

8. Lubricating composition according to any of claims 1 to 7, wherein the base oil comprises at least 50 wt.% of a Group II base oil, based on the total amount of base oil.

9. Lubricating composition according to any of claims 1 to 8, wherein the composition is a marine diesel engine oil.

10. Use of a lubricating composition according to any of claims 1 to 9, in order to improve deposit formation control properties.