

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 January 2003 (16.01.2003)

PCT

(10) International Publication Number
WO 03/004782 A2

(51) International Patent Classification⁷: **E02F**
(21) International Application Number: PCT/US02/19794
(22) International Filing Date: 3 July 2002 (03.07.2002)
(25) Filing Language: English
(26) Publication Language: English

(30) Priority Data:
09/899,535 6 July 2001 (06.07.2001) US
60/369,846 5 April 2002 (05.04.2002) US

(71) Applicant: **ESCO CORPORATION** [US/US]; 2141
N.W. 25th Avenue, Portland, OR 97210 (US).

(72) Inventors: **JONES, Darren, F.**; P.O. Box 10024, Portland,
OR 97296 (US). **CARPENTER, Christopher, M.**; 19047
SW Chesapeake Drive, Tualatin, OR 97062 (US). **GRAF,**
David, M.; 33397 Wikstrom Road, Scappoose, OR 97056
(US).

(74) Agent: **SCHAD, Steven, P.**; Banner & Witcoff, Ltd., 11th
Floor, 1001 G Street N.W., Washington, DC 20001-4591
(US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN,
YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished
upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: COUPLING FOR EXCAVATING WEAR PART

(57) Abstract: A wear assembly provided with tapered opening and a complementary tapered lock wherein the lock can be pried into and from the opening to thereby eliminate the need for hammering. The lock is formed with a body and a latch that is movable between a hold position where the latch is engageable with a stop in the opening to releasably retain the lock in the opening and a release position where the latch disengages the stop.



WO 03/004782 A2