

Description

5 Title of Invention: IMAGING INVESTIGATION SYSTEM AND IMAGING
INVESTIGATION METHOD

Technical Field

[0001]

10 The present invention relates to a shooting (imaging, taking of
pictures) inspection (investigation) system and a shooting inspection method.
More specifically, the present invention relates to a system for and a method
of performing shooting inspection using an unmanned flying object in an
inspection space including the inside of a closed-type space such as the inside
15 of a tubular space or the inside of a rectangular space.

Background Art

[0002]

The useful life of a sewage pipeline (sewer conduit) is set to
20 approximately 50 years, and it is assumed that facilities that have reached
the end of their useful life will exponentially increases in the future. For
efficient maintenance and management, it is essential to grasp a state of the
sewage pipeline.

[0003]

25 As a method of inspecting the state of the sewage pipeline, a method
of an inspector moving in a pipe to perform direct visual inspection, a method
of arranging a television camera connected to the ground via a cable in a pipe
to perform shooting, a method of loading a television camera connected to the
ground via a cable into a self-propelled vehicle and arranging the television
30 camera in a pipe to perform shooting while traveling, and the like have been

used. However, in the method of the direct visual inspection by the inspector, there are various problems such as a risk of a toxic gas being produced in the sewage pipeline to affect a human body and a risk from immersion at the time of sudden rainfall. In the method of arranging the television camera in the pipe, there are also problems that a sufficient inspection speed is not obtained and a vehicle is difficult to control when a water level in the sewage pipeline rises.

[0004]

In flying an unmanned aerial vehicle in not only the sewage pipeline but also an environment where a collision with any boundary surface such as a wall surface or a ceiling may occur, controllability of the unmanned aerial vehicle may be deteriorated by the collision with the boundary surface, or a vehicle body may be damaged in some cases.

Citation List

Patent Literature

[0005]

Patent Literature 1: Japanese Patent Laid-Open No. 2017-087917

Patent Literature 2: Japanese Patent Laid-Open No. 2017-226259

Patent Literature 3: Japanese Patent Laid-Open No. 2018-001967

Patent Literature 4: Japanese Patent Laid-Open No. 2014-239665

Patent Literature 5: Japanese Patent Laid-Open No. 2014-236728

Patent Literature 6: Japanese Patent Laid-Open No. 2013-000059

Summary

[0005a]

In an aspect, the present disclosure refers to a shooting inspection system comprising:

- a flight start stage on which an unmanned flying object can be placed;

- the unmanned flying object that is connected to a line-type member, comprises an inspection camera, a traveling direction shooting camera, and an unmanned flying object-side communication unit, and starts to fly from a state where the unmanned flying object is placed on the flight start stage in an inspection space, shoots in a traveling direction in the inspection space using the traveling direction shooting camera, and flies in the inspection space while transmitting traveling direction shooting data obtained by shooting in the traveling direction from the unmanned flying object-side communication unit;

- an external control device that comprises a display unit and an external control device-side communication unit, receives the traveling direction shooting data by the external control device-side communication unit, accepts an input of a control instruction to the unmanned flying object while displaying a moving image or a still image obtained based on the traveling direction shooting data on the display unit, and transmits a signal representing the control instruction from the external control device-side communication unit; and

- a draw device that is connected to the line-type member and draws the unmanned flying object,

wherein the unmanned flying object comprises:
a frame having a shape elongated along a forward direction;
four rotary wings, wherein a first pair of the four rotary wings is positioned on a front-half side of the frame and a second pair of the four rotary wings is positioned on a back-half side of the frame, and wherein the four rotary wings are positioned inside the frame;
a driver that drives the four rotary wings;
a control signal generation unit that is configured to generate a control signal for causing the driver to drive the four rotary wings, wherein the control signal generation unit is positioned between the first pair of the four rotary wings and the second pair of the four rotary wings,
wherein the first pair of the four rotary wings and the second pair of the four rotary wings are arranged apart from each other in the forward direction inside the frame and the control signal generation unit is positioned in an area between the first pair of the four rotary wings and the second pair of the four rotary wings, the area resulting from the apart arrangement, so that the first pair of the four rotary wings, the control signal generation unit, and the second pair of the four rotary wings are arranged apart from each other in the forward direction in the order of the first pair of the four rotary wings, the control signal generation unit, and the second pair of the four rotary wings,
wherein the traveling direction shooting camera is placed at a position on the vehicle body of the unmanned flying object, the position being between the first pair of the four rotary wings and the second pair of the four rotary wings.

[0005b]

In an aspect, the present disclosure refers to a shooting inspection method comprising:

putting an unmanned flying object that is connected to a line-type member and comprises an inspection camera, a traveling direction shooting camera, and an unmanned flying object-side communication unit into an inspection space with the unmanned flying object placed on a flight start stage;

by the unmanned flying object, starting to fly from a state where the unmanned flying object is placed on the flight start stage in the inspection space, shooting in a traveling direction in the inspection space using the traveling direction shooting camera, and flying in the inspection space while transmitting traveling direction shooting data obtained by shooting in the traveling direction from the unmanned flying object-side communication unit;

by an external control device which includes a display unit and an external control device-side communication unit, receiving the traveling direction shooting data using the external control device-side communication unit, accepting an input of a control instruction to the unmanned flying object while displaying a moving image or a still image obtained based on the traveling direction shooting data on the display unit, and transmitting a signal representing the control instruction from the external control device-side communication unit; and

by a draw device, connected to the line-type member, drawing the unmanned flying object,

wherein the unmanned flying object comprises:

a frame having a shape elongated along a forward direction;
four rotary wings, wherein a first pair of the four rotary wings is

positioned on a front-half side of the frame and a second pair of the four rotary wings is positioned on a back-half side of the frame, and wherein the four rotary wings are positioned inside the frame;

a driver that drives the four rotary wings;

a control signal generation unit that is configured to generate a control signal for causing the driver to drive the four rotary wings, wherein the control signal generation unit is positioned between the first pair of the four rotary wings and the second pair of the four rotary wings,

wherein the first pair of the four rotary wings and the second pair of the four rotary wings are arranged apart from each other in the forward direction inside the frame and the control signal generation unit is positioned in an area between the first pair of the four rotary wings and the second pair of the four rotary wings, the area resulting from the apart arrangement, so that the first pair of the four rotary wings, the control signal generation unit, and the second pair of the four rotary wings are arranged apart from each other in the forward direction in the order of the first pair of the four rotary wings, the control signal generation unit, and the second pair of the four rotary wings,

wherein the traveling direction shooting camera is placed at a position on the vehicle body of the unmanned flying object, the position being between the first pair of the four rotary wings and the second pair of the four rotary wings.

[0006]

The present disclosure is to provide an apparatus configuration, a method, and the like for performing shooting inspection in an inspection space including the inside of a sewage pipeline using

an unmanned flying object.

[0007]

To solve the above-described problems, the present disclosure provides, in an example, a shooting inspection system including a flight start stage (flight start platform) on which an unmanned flying object can be placed, the unmanned flying object that is connected to a line-type member, includes an inspection camera, a traveling direction shooting camera, and an unmanned flying object-side communication unit, and starts to fly from a state where the unmanned flying object is placed on the flight start stage in an inspection space, shoots a traveling direction in the inspection space using the traveling direction shooting camera, and flies in the inspection space while transmitting traveling direction shooting data obtained by shooting the traveling direction from the unmanned flying object-side communication unit, an external control device that includes a display unit and an external control device-side communication unit, receives the traveling direction shooting data by the external control device-side communication unit, accepts an input of a control instruction to the unmanned flying object while displaying a moving image (movie) or a still image obtained based on the traveling direction shooting data on the display unit, and transmits a signal representing the control instruction from the external control device-side communication unit, and a draw device that is connected to the line-type member and draws the unmanned flying object.

[0008]

The present disclosure provides, in an example, a shooting inspection method including putting an unmanned flying object that is connected to a line-type member and includes an inspection camera, a traveling direction shooting camera, and an unmanned flying object-side communication unit into an inspection space with the unmanned flying object placed on a flight start

stage, the unmanned flying object starting to fly from a state where the
unmanned flying object is placed on the flight start stage in the inspection
space, shooting a traveling direction in the inspection space using the
traveling direction shooting camera, and flying in the inspection space while
5 transmitting traveling direction shooting data obtained by shooting the
traveling direction from the unmanned flying object-side communication
unit, an external control device, including a display unit and an external
control device-side communication unit, receiving the traveling direction
shooting data using the external control device-side communication unit,
10 accepting an input of a control instruction to the unmanned flying object
while displaying a moving image or a still image obtained based on the
traveling direction shooting data on the display unit, and transmitting a
signal representing the control instruction from the external control
device-side communication unit, and a draw device, connected to the
15 line-type member, drawing the unmanned flying object.
[0009]

The draw device may be an automatic winding device that winds the
line-type member to draw the unmanned flying object.

[0010]

20 The draw device may draw the unmanned flying object with the
unmanned flying object stopping traveling in the traveling direction and
floating.

[0011]

The method may include the inspection camera performing shooting
25 in the inspection space while the unmanned flying object is being drawn by
the draw device.

[0012]

The method may further include generating a developed view
(development view) or expanded (developed) image data corresponding to a
30 boundary surface of the inspection space from inspection camera shooting

data obtained by the shooting using the inspection camera, and displaying the developed view or the expanded image data as an image.

[0013]

5 An antenna may be attached to the flight start stage, and communication between the unmanned flying object-side communication unit and the external control device-side communication unit may be performed according to a wireless LAN (local area network) communication standard using the antenna.

[0014]

10 Resolution of the moving image or the still image obtained based on the traveling direction shooting data may be lower than resolution of a moving image or a still image obtained based on shooting data obtained by the shooting using the inspection camera.

[0015]

15 The flight start stage may be attached to a distal end portion of a rod-shaped body, and the rod-shaped body may be inserted into the inspection space from the side of the flight start stage on which the unmanned flying object is placed to put the unmanned flying object into the inspection space.

20 [0016]

The unmanned flying object can be put into the inspection space by placing the flight start stage that is attached to the distal end portion of the rod-shaped body and on which the unmanned flying object is placed on a carriage (caddie, trolley) and inserting the rod-shaped body into the inspection space from an opening provided in the carriage.

25

Advantageous Effect of Invention

[0017]

30 The present invention proposes a specific procedure, apparatus, and the like for performing shooting inspection using an unmanned flying object.

As a result, safe shooting inspection in a sewage pipeline can be performed.

Brief Description of Drawings

[0018]

5 [Figure 1A] Figure 1A is a perspective view of an unmanned aerial vehicle according to an embodiment of the present embodiment.

[Figure 1B] Figure 1B is a diagram of the unmanned aerial vehicle illustrated in Figure 1A in a positive direction of z.

[Figure 1C] Figure 1C is a diagram of the unmanned aerial vehicle
10 illustrated in Figure 1A in a positive direction of y.

[Figure 1D] Figure 1D is a perspective view of the unmanned aerial vehicle illustrated in Figure 1A from behind in a traveling direction.

[Figure 1E] Figure 1E is a perspective view of the unmanned aerial vehicle illustrated in Figure 1A in a negative direction of z.

15 [Figure 1F] Figure 1F is a perspective view of the unmanned aerial vehicle illustrated in Figure 1A in the negative direction of z and in a direction different from that in Figure 1E.

[Figure 2] Figure 2 is a diagram illustrating a holding member that holds preceding collision members (a rotary member such as a wheel or a roller)
20 and a holding member attachment member to which the holding member is attached.

[Figure 3A] Figure 3A is a diagram illustrating the holding member with the preceding collision members removed.

[Figure 3B] Figure 3B is a diagram illustrating the holding member, the
25 preceding collision member (a rotary member such as a wheel or a roller) to be attached to the holding member, and a shaft section for preceding collision member as viewed in an arrow direction indicated by A in Figure 3A.

[Figure 4] Figure 4 is a diagram illustrating the holding member to which the preceding collision members other than a rotary member such as a wheel
30 or a roller is attached.

[Figure 5A] Figure 5A is a diagram illustrating a positional relationship when a holding member is attached to an vehicle body to rotate around a position lower than a corresponding set of rotors.

5 [Figure 5B] Figure 5B is a diagram illustrating a positional relationship when the holding member illustrated in Figure 5A is inclined with respect to the vehicle body.

[Figure 5C] Figure 5C is a diagram illustrating a force to be exerted on each of the rotors when the inclination illustrated in Figure 5B has occurred during flight and a rotational direction of the vehicle body caused by the
10 force.

[Figure 5D] Figure 5D is a diagram illustrating a positional relationship when the vehicle body is inclined by a function of the force to the rotor illustrated in Figure 5C.

15 [Figure 5E] Figure 5E is a conceptual diagram illustrating a principle of the inclination of the vehicle body described with reference to Figures 5A to 5D.

[Figure 6A] Figure 6A is a diagram illustrating a positional relationship when a holding member is attached to an vehicle body to rotate around a position higher than a corresponding set of rotors.

20 [Figure 6B] Figure 6B is a diagram illustrating a positional relationship when the holding member illustrated in Figure 6A is inclined with respect to the vehicle body.

[Figure 6C] Figure 6C is a diagram illustrating a force to be exerted on each of the rotors when the inclination illustrated in Figure 6B has occurred during flight and a rotational direction of the vehicle body caused by the
25 force.

[Figure 6D] Figure 6D is a diagram illustrating a positional relationship when the vehicle body is inclined by the function of the force to the rotor illustrated in Figure 6C.

30 [Figure 6E] Figure 6E is a conceptual diagram illustrating a principle of the inclination of the vehicle body described with reference to Figures 6A to 6D.

[Figure 7A] Figure 7A is a perspective view illustrating a positional relationship between rotors and motor members in a comparative example.

[Figure 7B] Figure 7B is a diagram of the rotors and the motor members illustrated in Figure 7A in a positive direction of x.

5 [Figure 7C] Figure 7C is a diagram illustrating a cross section cut along a plane A - A in Figure 7B of the motor members illustrated in Figure 7A and each of the motor members.

[Figure 8] Figure 8 is a perspective view illustrating a positional relationship between rotors and motor members in the present embodiment.

10 [Figure 9] Figure 9 is a block diagram illustrating a functional configuration of the unmanned aerial vehicle illustrated in Figure 1A.

[Figure 10] Figure 10 is a diagram illustrating a structure of a sewage pipeline facility capable of flying the unmanned aerial vehicle illustrated in Figure 1A.

15 [Figure 11] Figure 11 is a diagram illustrating the unmanned aerial vehicle illustrated in Figure 1A that flies in a tubular space in the sewage pipeline facility illustrated in Figure 10.

[Figure 12A] Figure 12A is a diagram illustrating how a preceding collision member collides with an inner wall of a sewage pipeline during flight
20 illustrated in Figure 11.

[Figure 12B] Figure 12B is a diagram illustrating how the holding member rotates in response the collision illustrated in Figure 12A and the other preceding collision member to be held by the holding member also collides with the inner wall in response to rise of the vehicle body.

25 [Figure 12C] Figure 12C is a diagram illustrating how the vehicle body is inclined after the holding member illustrated in Figure 12B is inclined.

[Figure 13A] Figure 13A is a diagram illustrating how the preceding collision member collides with the inner wall of the sewage pipeline (at a position different from a collision position illustrated in Figure 12A) during flight
30 illustrated in Figure 11.

[Figure 13B] Figure 13B is a diagram illustrating how the holding member rotates in response the collision illustrated in Figure 13A and the other preceding collision member to be held by the holding member also collides with the inner wall in response to rise of the vehicle body.

5 [Figure 14] Figure 14 is a diagram illustrating how the unmanned aerial vehicle illustrated in Figure 1A is inclined by rotating (rolling) around an x-axis.

[Figure 15] Figure 15 is a diagram illustrating an example of an image in the sewage pipeline shot by a front camera.

10 [Figure 16A] Figure 16A is a perspective view of an unmanned flying object according to an embodiment of the present invention (a coordinate axis is defined, like in Figure 1A).

[Figure 16B] Figure 16B is a diagram of the unmanned flying object illustrated in Figure 16A in a positive direction of z.

15 [Figure 16C] Figure 16C is a diagram of the unmanned flying object illustrated in Figure 16A in a positive direction of y.

[Figure 16D] Figure 16D is a perspective view of the unmanned flying object illustrated in Figure 1A from behind in a traveling direction.

[Figure 16E] Figure 16E is a perspective view of the unmanned flying object
20 illustrated in Figure 16A in a negative direction of z.

[Figure 16F] Figure 16F is a perspective view of the unmanned flying object illustrated in Figure 16A in the negative direction of z and in a direction different from that in Figure 16E.

[Figure 16G] Figure 16G is a diagram illustrating an example in which the
25 unmanned flying object and a line-type member are connected to each other using a wire such as a piano wire as a variant of a mode illustrated in Figure 16D.

[Figure 17] Figure 17 is a block diagram illustrating a functional configuration of the unmanned flying object illustrated in Figure 16A.

30 [Figure 18] Figure 18 is a diagram illustrating a configuration example of a

shooting inspection system, including the unmanned flying object, for performing shooting inspection.

[Figure 19] Figure 19 is a diagram illustrating apparatuses other than the unmanned flying object and a flight start stage in an example of the shooting inspection system.

[Figure 20] Figure 20 is a diagram illustrating how the shooting inspection system has entered a state where a window provided in a carriage is opened and an opening for putting the unmanned flying object into an inspection space can be seen in the configuration example illustrated in Figure 19.

[Figure 21] Figure 21 is a block diagram illustrating a functional configuration of a laptop PC (personal computer) as an example of an external control device.

[Figure 22] Figure 22 is a conceptual diagram for describing an operation of an automatic winding device that winds a line-type member such as a fishing line or a string.

[Figure 23A] Figure 23A is a diagram of the flight start stage viewed from the side (in a similar direction to that in Figure 18).

[Figure 23B] Figure 23B is a perspective view of the flight start stage illustrated in Figure 23A.

[Figure 23C] Figure 23C is a diagram when the flight start stage illustrated in Figure 23A is swung with respect to a rod-shaped body.

[Figure 24A] Figure 24A is a design drawing of one example of the flight start stage (corresponding to a diagram viewed from above in Figure 18).

[Figure 24B] Figure 24B is a design drawing of one example of the flight start stage (corresponding to a diagram viewed in a similar direction to that in Figure 18).

[Figure 24C] Figure 24C is a design drawing of an antenna illustrated in Figures 24A and 24B.

[Figure 24D] Figure 24D is a design drawing of the antenna illustrated in Figures 24A and 24B (illustrating connection with the rod-shaped body in

the flight start stage).

[Figure 25] Figure 25 is a diagram illustrating how the flight start stage loaded with the unmanned flying object is inserted into an underground space (Figure 10, etc.) in an example of the shooting inspection according to the present invention.

[Figure 26] Figure 26 is a diagram illustrating how the flight start stage loaded with the unmanned flying object is landed on the ground in an example of the shooting inspection according to the present invention.

[Figure 27] Figure 27 is a diagram illustrating a state immediately after the unmanned flying object has started to fly away from the flight start stage in an example of the shooting inspection according to the present invention.

[Figure 28] Figure 28 is a diagram illustrating the unmanned flying object illustrated in Figure 16A that flies in a tubular space in the sewage pipeline facility illustrated in Figure 10.

[Figure 29] Figure 29 is a diagram illustrating how the automatic winding device winds the line-type member to pull the unmanned flying object backward with the unmanned flying object stopping advancing in an x-direction in Figure 28 and floating.

[Figure 30] Figure 30 is a diagram illustrating how the unmanned flying object has been pulled by the automatic winding device to return to the top of the flight start stage.

[Figure 31] Figure 31 is a diagram illustrating a screen in which an expanded image is drawn on a display section of the external control device using data of a still image or a moving image shot by an inspection camera.

Description of Embodiments

[0019]

(First Embodiment)

An unmanned aerial vehicle, a flight control mechanism for the unmanned aerial vehicle, and a method using these according to an

embodiment of the present invention will be described below with reference to the drawings. Note that the unmanned aerial vehicle, the flight control mechanism for the unmanned aerial vehicle, and the method using these are not limited to a specific mode described below, but are appropriately
5 changeable within the scope of the present invention. For example, the unmanned aerial vehicle according to the present invention is not necessarily an autonomous flight type unmanned aerial vehicle, and a functional configuration of the unmanned aerial vehicle is not limited to that illustrated in Figure 9, but is also arbitrary if a similar operation can be
10 performed. For example, operations to be performed by a plurality of components may be performed by a single component, for example, a function of a communication unit is integrated with a main operation unit. Alternatively, an operation to be performed by a single component as illustrated may be performed by a plurality of components, for example, a
15 function of a main operation unit is distributed among a plurality of operation units. An autonomous control program of the unmanned aerial vehicle may be recorded on a recording device such as a hard disk drive and read out and executed by the main operation unit (The autonomous control program as illustrated may be decomposed into a plurality of program
20 modules, or any other programs may be executed by the main operation unit or the like.), or a similar operation may be performed by a built-in type system using a microcomputer or the like. All components illustrated in the following embodiment need not be included in the unmanned aerial vehicle and the flight control mechanism for the unmanned aerial vehicle according
25 to the present invention (For example, the unmanned aerial vehicle and the flight control mechanism for the unmanned aerial vehicle need not include a thrust generation propeller 25 when propulsion of the unmanned aerial vehicle is controlled under control of rotors 13 to 16 illustrated in Figure 1B and need not include an autonomous control program and various types of
30 databases if the unmanned aerial vehicle is completely flown under control

from outside without performing autonomous control.), and the method according to the present invention need not include all method steps as illustrated. A rotary wing for floating the unmanned aerial vehicle is not limited to four rotors 13 to 16 as illustrated in Figure 1B, for example, but
5 may be any number of (four or more) rotary wings. A propeller for generating a thrust is not limited to the thrust generation propeller 25 illustrated in Figure 1D, for example, but may be any propeller. The flight control mechanism for the unmanned aerial vehicle according to the present invention can be used for controlling any unmanned aerial vehicle such as a
10 rotorcraft or a fixed-wing craft, and the unmanned aerial vehicle according to the present invention is not limited to the rotorcraft. An vehicle body size of the unmanned aerial vehicle is also arbitrary. Although an example in which the unmanned aerial vehicle performs shooting flight (flight while taking pictures) in a closed-type space is illustrated in the following
15 embodiment, the unmanned aerial vehicle according to the present invention can be flown in not only the closed state but also any environment and for any purpose, and the flight control mechanism can be used in not only the closed-type space but also any environment. Note that the closed-type space need not be completely closed, but may be a space that is at least
20 partially closed and where flight of the unmanned aerial vehicle is at least partially restricted. For example, a tubular space in a sewage pipeline connected to the outside via a manhole is also a closed-type space, and a tunnel of a highway is also a closed-type space, as described in the following embodiment. The number of preceding collision members to be held by the
25 holding member is not limited to two, but is also arbitrary, and the number of flight control mechanisms to be attached to the vehicle body is also arbitrary. Note that although the holding member can be formed of a metal or plastic, for example, the holding member may be formed of any material such as an elastic body if it can exhibit a function as the holding member. Other
30 members and components may be composed of any material if they can

exhibit functions of the present invention.

[0020]

Configuration of Unmanned aerial vehicle

Figures 1A to 1F illustrate an appearance of an unmanned aerial
5 vehicle according to an embodiment of the present invention. Figure 1A is a
perspective view, Figure 1B is a diagram viewed in a positive direction of z
illustrated in Figure 1A, Figure 1C is a diagram viewed in a positive
direction of y, Figure 1D is a perspective view viewed from behind in a
traveling direction, and Figures 1E and 1F are perspective views viewed in a
10 negative direction of z (but in different directions) illustrated in Figure 1A.
An unmanned aerial vehicle 1 is designed in dimensions of an overall width
(a width in a y-direction in Figure 1A) of approximately 250 mm and an
overall length (a width in an x-direction in Figure 1A) of approximately 550
mm to be able to fly in a closed-type space having a bore diameter of
15 approximately 400 mm in an example, and includes a main body section 2
(housed in a waterproof case 3), five motors 17 to 21 (see Figures 9) that are
driven in response to a control signal from the main body section 2, four
rotors (rotary wings) 13 to 16 that respectively rotate by drives of the motors
17 to 20 to float the unmanned aerial vehicle 1 (The adjacent rotors
20 respectively rotate in opposite directions, for example, the rotors 13 and 16
rotate in a clockwise direction viewed in the positive direction of z, and the
rotors 14 and 15 rotate in a counterclockwise direction viewed in the positive
direction of z.), a thrust generation propeller 25 that rotates by a drive of the
motor 21 to generate a thrust of the unmanned aerial vehicle 1, an inspection
25 camera 22, a front camera 23, and a ultrasonic sensor 24, and each of the
components are integrated using a frame 4.

[0021]

The unmanned aerial vehicle 1 further includes a holding member 9
that separates preceding collision members (a rotary member such as a
30 wheel or a roller) 5 and 6 to hold the preceding collision members 5 and 6

above an vehicle body of the unmanned aerial vehicle 1 (the positive direction of the z-axis) and can be inclined with respect to the vehicle body by rotating toward the lateral side of the vehicle body around a predetermined position in the vehicle body or on the vehicle body (in the positive direction of y or in a negative direction of y, which need not be completely parallel to the y-direction but may intersect the x-direction) and a holding member 10 that similarly holds preceding collision members (a rotary member such as a wheel or a roller) 7 and 8 and can be similarly inclined with respect to the vehicle body with the holding member 9 and the holding member 10 separated from each other in a front-rear direction (A positive direction of x in Figure 1A is a forward direction, and the positive direction of y and the negative direction of y in Figure 1A are respectively a leftward direction and a rightward direction.). The holding member 9 is attached to the waterproof case 3 by a holding member attachment member 11 (Figure 1E), as illustrated in Figure 1E, and the holding member 10 is also similarly attached to the waterproof case 3 by a holding member attachment member 12 (Figure 1F). Note that the number of holding members to be attached to the vehicle body is arbitrary. For example, one of the holding members 9 and 10 may be detached, only one holding member may be used by being attached to the vicinity of a center of gravity 26 of the vehicle body, or three or more holding members may be used by being attached. Note that in the present embodiment, the components of the unmanned aerial vehicle 1 illustrated in Figure 1A, excluding the holding members 9 and 10 and the preceding collision members 5 to 8 held thereby or excluding shaft sections for preceding collision member 5A to 8A and preceding collision member attachment members 9B-1, 9B-2, 10B-1, and 10B-2 when the preceding collision members 5 to 8, are each a rotary member such as a wheel or a roller are referred to as an "vehicle body".

[0022]

Figure 2 illustrates the holding member 9 that holds the preceding

collision members 5 and 6 and the holding member attachment member 11 to which the holding member 9 is attached. The same may apply to a configuration of the holding member 10 that holds the preceding collision members 7 and 8 and the holding member attachment member 12 to which the holding member 10 is attached. As illustrated in Figures 1E and 1F, the holding member attachment members 11 and 12 are fixed to the waterproof case 3. The holding member 9 is provided with a hole 9A. When a shaft section for holding member 11A in the holding member attachment member 11 is inserted into the hole 9A (See Figure 1E. Although the shaft section for holding member 11A extends along the paper in Figure 2, the shaft section for holding member 11A is inserted into the hole 9A with the shaft section 11A extending in a direction perpendicular to the paper.), the holding member 9 is attached to the vehicle body. The holding member 9 can be inclined with respect to the vehicle body by rotating toward the lateral side of the vehicle body around a position of the hole 9A with the shaft section for holding member 11A used as a rotation axis (fixing axis). To prevent the holding member 9 from separating from the holding member attachment member 11, a member for separation prevention (a cap, etc.) may be further fitted in the shaft section for holding member 11A after the holding member 9 is attached. Note that "rotation" herein is not limited to rotation in one direction but may be rotation in both directions (in positive and negative directions in the y-direction in Figure 1A in an example) or may not be complete rotation by 360 degrees (The same applies to subsequent "rotation"). As illustrated in Figure 1E, although the holding member 9 is exposed to the top of the vehicle body (in the positive direction of z) from a hole provided in the frame 4 as illustrated in Figure 1A while being attached to the waterproof case 3 by the holding member attachment member 11, rotational motion of the holding member 9 is prevented at a boundary position (rotation stop positions 4A and 4B) on the lateral side of the hole. Thus, the rotational motion is limited to rotation up to a predetermined

maximum angle. The holding member 10 is also similarly exposed to the top of the vehicle body (in the positive direction of z) from a hole provided in the frame 4 while being attached to the waterproof case 3 by the holding member attachment member 12, and rotational motion of the holding member 10 is prevented at a boundary position (rotation stop positions 4C and 4D (see Figure 1D)) on the lateral side of the hole. Thus, the rotational motion of the holding member 10 is also limited to rotation up to a predetermined maximum angle (The respective maximum rotational angles of the holding members 9 and 10 may differ from each other.).

[0023]

The holding member 9 with the preceding collision members 5 and 6 removed is illustrated in Figure 3A. The same may apply to the holding member 10 with the preceding collision members 7 and 8 removed. The holding member 9 is provided with preceding collision member attachment members 9B-1 and 9B-2. The holding member 9, the preceding collision member 5 to be attached to the holding member 9, and the shaft section for preceding collision member 5A as viewed in an arrow direction indicated by A in Figure 3A are illustrated in Figure 3B. Here, the preceding collision member 5 as a rotary member such as a wheel or a roller is fixed to the shaft section for preceding collision member 5A, and the shaft section for preceding collision member 5A is inserted into a hole 9C-1 provided in the preceding collision member attachment member 9B-1 in the holding member 9 (It may be passed through the hole 9C-1, as illustrated in Figure 2. The same applies to insertion of the shaft section for holding member 11A into the above-described hole 9A.) (although the shaft section for preceding collision member 5A extends along the paper in Figure 3B, the shaft section for preceding collision member 5A is inserted into the hole 9C-1 with the shaft section 5A extending in the direction perpendicular to the paper.) so that the shaft section 5A is held in the holding member 9. Note that "holding" herein does not require that the preceding collision member 5 is

completely fixed to the holding member 9 but may prevent the preceding collision member 5 from completely separating from the holding member 9 and freely moving (The same applies to the other holding member and the other preceding collision members.). In a configuration illustrated in Figure 3B, the preceding collision member (rotary member) 5 and the shaft section for preceding collision member 5A can rotate in an integrated manner with the shaft section for preceding collision member 5A held in the holding member 9 using the shaft section for preceding collision member 5A as a rotation axis. To prevent the preceding collision member 5 from separating from the holding member 9, a member for separation prevention (a cap, etc.) may be further fitted in the shaft section for preceding collision member 5A after the preceding collision member 5 is attached to the holding member 9 as described above. The same may apply to a mode in which the holding member 9 holds the preceding collision member 6 and a mode in which the holding member 10 holds the preceding collision members 7 and 8.

[0024]

Note that a member other than a rotary member such as a wheel or a roller may be used as the preceding collision members 5 to 8. An example in which a preceding collision member fixed to a holding member is used is illustrated in Figure 4 as an example. In Figure 4, the preceding collision members 5 and 6 are each configured as a member fixed to the holding member 9, and are each formed of a low friction plastic material or the like. Even if the preceding collision member and the holding member each having such a configuration are used, flight control of an unmanned aerial vehicle as described below can be performed. Note that the preceding collision member advances while sliding on a boundary surface (like, e.g., a sled), unlike when a rotary member such as a wheel or a roller is used. Thus, the preceding collision member is preferably formed of a material having a low friction between itself and the boundary surface. The same may apply in a mode in which the holding member 10 holds the preceding collision members

7 and 8. When the preceding collision members 5 to 8 wear out by advancing while sliding in contact with the boundary surface, the preceding collision members 5 to 8 are preferably replaced with new ones.

[0025]

5 The inspection camera 22 is a camera for shooting a still image or a moving image during flight in a closed-type space by the unmanned aerial vehicle 1. In an example of the inspection camera 22, a commercially available camera such as a GoPro session (Tajima MOTOR CORPORATION) can be used. The front camera 23 is a camera for shooting a still image or a
10 moving image in a traveling direction during flight in the closed-type space by the unmanned aerial vehicle 1. Data of the shot still image or moving image is transmitted to an external apparatus (e.g., a computer including a display), as needed, and an operator can steer the unmanned aerial vehicle 1 while confirming the data. The ultrasonic sensor 24 is a sensor for
15 detecting an obstacle or the like ahead thereof, and can transmit a ultrasonic wave in the traveling direction during flight in the closed-type space by the unmanned aerial vehicle 1 and measure a distance from the obstacle or the like by receiving a reflected wave. The inspection camera 22 and the front
20 camera 23 may be each a camera such as an infrared camera or a ultraviolet camera.

[0026]

 The above-described rotation center position in each of the holding members 9 and 10 is preferably below (in the negative direction of z in Figure 1A) a position of the set of rotors corresponding to the holding
25 member with the vehicle body not inclined. A reason for that will be described below with reference to Figures 5A to 5E. Note that although description is made hereinafter using a model in which the rotation center position of the holding member 9 (10) and the rotation center position of the rotors 13 (15) and 14 (16) are coplanar (a yz plane in Figure 1A) (respective x
30 coordinates illustrated in Figure 1A are equal to each other) for the purpose

of simplifying the description (The same applies in a comparative example illustrated in Figures 6A to 6E.), an operation can be basically described in a similar principle otherwise.

[0027]

5 A positional relationship when the holding member is attached to be rotatable around a position lower than the corresponding set of rotors (in the negative direction of z in Figure 1A) with the vehicle body not inclined is illustrated in Figure 5A (viewed in the positive direction of x in Figure 1A). Although description is made below using the holding member 9 and the
10 corresponding set of rotors 13 and 14, an operation can also be described in a similar principle in the holding member 10 and the corresponding set of rotors 15 and 16. Although it is assumed that respective distances between a center line of the holding member, which remains not inclined with respect to the vehicle body, and center lines of the two rotors in the corresponding set
15 are equal to each other (l in Figure 5A), and respective distances from a branch portion of the holding member 9 (10) to the preceding collision members 5 (7) and 6 (8) on both sides are also equal to each other (d in Figure 5A), the operation can be basically described in a similar principle even when the respective distances are not equal to each other.

20 [0028]

 As illustrated in Figure 5B, the holding member 9 is inclined toward the lateral side of the vehicle body due to any reason. When the rotors 13 and 14 continue to rotate in this state, forces f are respectively exerted (respectively act) on the rotors 13 and 14, as indicated by arrows in Figure
25 5C. Note that although an entire configuration illustrated in Figure 5B is drawn in an inclined manner for convenience of illustration in Figure 5C, a relative inclination between the holding member 9 and the vehicle body does not change from the configuration illustrated in Figure 5B. Although it is assumed that the forces respectively exerted on the rotors 13 and 14 are
30 equal to each other for simplicity, the operation can also be basically

described in a similar principle even when the forces respectively exerted on the rotors 13 and 14 differ from each other due to a difference in number of rotations, for example.

[0029]

5 At this time, a "distance" between the rotor 14 and the center line of the holding member 9 (a distance in a direction perpendicular to the center line of the holding member 9 between a rotation center of the rotor 14 and the center line) is b, while a "distance" between the rotor 13 and the center line of the holding member 9 (a distance in the direction perpendicular to the center line of the holding member 9 between a rotation center of the rotor 13 and the center line) is a, and a is larger than b (It is assumed that respective magnitudes of distances and the angles from a position on the holding member attachment member 11 as a rotation center of the holding member 9 to the rotation centers of the rotors 13 and 14 are equal to each other in Figure 5A. Even in a configuration deviating from such a configuration, an operation can be basically described in a similar principle.). Accordingly, a force (torque) to rotate the vehicle body in an arrow direction indicated by R in Figure 5C is exerted as a whole on the vehicle body. The force is a force to be exerted in a direction in which the inclination of the holding member 9 with respect to the vehicle body is canceled. When the vehicle body is inclined in a similar direction to that of the inclination of the holding member 9, as illustrated in Figure 5D, a relative inclination between the holding member 9 and the vehicle body can be at least partially canceled. A positional relationship between the holding member 9 and the rotors 13 and 14, including an attachment position of the holding member 9 (a position of the holding member attachment member 11), is illustrated in Figure 5E if conceptually drawn, and a principle in which the above-described relative inclination can be at least partially canceled can be understood. In the holding member 10, when the holding member 10 is also attached to be rotatable around a position lower than a position of the corresponding set of

10

15

20

25

30

rotors 15 and 16 (in the negative direction of z in Figure 1A), a relative inclination between the holding member 10 and the vehicle body can also be at least partially canceled in a similar principle.

[0030]

5 Then, as a comparative example, a positional relationship when a holding member is attached to be rotatable around a position higher than a corresponding set of rotors with an vehicle body not inclined (in the positive direction of z in Figure 1A) is illustrated in Figure 6A (viewed in the positive direction of x in Figure 1A). Although description is made below using a
10 holding member 9 and a corresponding set of rotors 13 and 14, an operation can also be described in a similar principle in a holding member 10 and a corresponding set of rotors 15 and 16. Although it is assumed that respective distances between a center line of the holding member and center
15 lines of the two rotors in the corresponding set with the vehicle body not inclined are equal to each other (1 in Figure 6A), the operation can be basically described in a similar principle even when the distances are not equal to each other.

[0031]

As illustrated in Figure 6B, it is assumed that the holding member 9
20 is inclined toward the lateral side of the vehicle body due to any reason. When the rotors 13 and 14 continue to rotate in this state, forces f are respectively exerted (respectively act) on the rotors 13 and 14, as indicated by an arrow in Figure 6C. Note that although an entire configuration illustrated in Figure 6B is drawn in an inclined manner for convenience of
25 illustration in Figure 6C, a relative inclination between the holding member 9 and the vehicle body does not change from the configuration illustrated in Figure 6B. Although it is assumed that the forces respectively exerted on the rotors 13 and 14 are equal to each other for simplicity, an operation can be basically described in a similar principle even when the forces
30 respectively exerted on the rotors 13 and 14 differ from each other due to a

difference in number of rotations, for example.

[0032]

At this time, although a "distance" between the rotor 14 and a center line of the holding member 9 (a distance in a direction perpendicular to the center line of the holding member 9 between a rotation center of the rotor 14 and the center line) is c , while a "distance" between the rotor 13 and the center line of the holding member 9 (a distance in the direction perpendicular to the center line of the holding member 9 between a rotation center of the rotor 13 and the center line) is d , and c is larger than d (It is assumed that respective magnitudes of distances and angles from a position on a holding member attachment member 11 as a rotation center of the holding member 9 to the rotation centers of the rotors 13 and 14 are equal to each other in Figure 6A. In a configuration deviating from such a configuration, the operation can also be basically described in a similar principle.). Accordingly, a force (torque) to rotate the vehicle body in an arrow direction indicated by R in Figure 6C is exerted as a whole on the vehicle body. The force is a force to be exerted in a direction in which inclination of the holding member 9 with respect to the vehicle body is increased. When the vehicle body is inclined in a direction opposite to the direction of the inclination of the holding member 9, as illustrated in Figure 6D, a relative inclination between the holding member 9 and the vehicle body increases. A positional relationship between the holding member 9 and the rotors 13 and 14, including an attachment position of the holding member 9 (a position of the holding member attachment member 11), is illustrated in Figure 6E if conceptually drawn, and a principle in which the above-described relative inclination increases can be understood. In the holding member 10, when the holding member 10 is also attached to be rotatable around a position higher than a position of the corresponding set of rotors 15 and 16 (in the positive direction of z in Figure 1A), a relative inclination between the holding member 10 and the vehicle body increases in

a similar principle. Although a configuration corresponding to Figure 5A is preferably adopted to cancel the relative inclination, it should be noted that the present invention can be implemented even if a configuration corresponding to Figure 6A is adopted.

5 [0033]

As illustrated in Figure 1C, the motors 17 and 19 are configured to be respectively positioned above rotors 13 and 15 (at a position where a gravity potential is high) to drive the rotors 13 and 15. The motors 18 and 20 (see Figure 9) are also similarly configured to be respectively positioned on the
10 rotors 14 and 16 to drive the rotors. An advantage of adopting such a configuration will be described while comparing the configuration with that in the comparative example in which motors are positioned below the rotors, as illustrated in Figures 7A to 7C. Note that the unmanned aerial vehicle, the flight control mechanism for the unmanned aerial vehicle, and the
15 method of using these can also be implemented even if a positional relationship between the rotors and the motors as in the comparative example is adopted.

[0034]

Figure 7A is a perspective view illustrating a positional relationship
20 between rotors and motor members in the comparative example, Figure 7B is a diagram of the rotors and the motor members illustrated in Figure 7A as viewed in a positive direction of x in Figure 7A, and Figure 7C is a diagram illustrating a cross section cut along a plane A - A in Figure 7B and each of the motor members. The rotors 13, 14, 15, and 16 are fixed to a rod-shaped
25 protrusion (see Figure 7C) of a motor member 27A (see Figure 7B), and rotate with the rod-shaped protrusion as a rotation axis. The rotors 13, 14, 15, and 16 receive a force in an arrow direction (in a positive direction of z) in Figure 7A by rotating, to pull the motor member 27A in the same direction. As illustrated in Figure 7C, the motor member 27A and a motor member 27B
30 are fitted to each other, and do not necessarily adhere to each other.

Therefore, if the motor member 27A is pulled in the positive direction of z, the motor member 27A may separate from the motor member 27B. To prevent the separation, a motor member 27C is used as a fastener in the configuration in the comparative example (see Figures 7B and 7C). As
5 illustrated in Figure 7C, when the motor member 27C is fitted in a groove 27A-1 provided in the motor member 27A (After the motor member 27A and the motor member 27B are fitted to each other.), the motor member 27A can be prevented from separating from the motor member 27B. However, the motor member 27C needs to be detached when the motors are maintained.

10 [0035]

A positional relationship between rotors and motor members in the present embodiment is illustrated in a perspective view of Figure 8. The present embodiment is similar to the comparative example except that the rotors 13, 14, 15, and 16 are positioned below the motor members 27A and
15 27B and that the motor member 27C is not used. The rotors 13, 14, 15, and 16 are fixed to a rod-shaped protrusion (see Figure 7C) of the motor member 27A (see Figure 7B), and rotate with the rod-shaped protrusion as a rotation axis. The rotors 13, 14, 15, and 16 receive a force in an arrow direction (in a positive direction of z) in Figure 8A by rotating, to press the motor member
20 27A in the same direction. As a result, since the motor member 27A is pressed against the motor member 27B, the motor member 27A need not be prevented from separating from the motor member 27B. Therefore, in a configuration illustrated in Figure 8, the motor member 27C is not required so that the motors are easily maintained.

25 [0036]

Figure 9 is a block diagram illustrating a functional configuration of the unmanned aerial vehicle illustrated in Figure 1A. The main body section 2 in the unmanned aerial vehicle 1 includes a main operation unit 28a including a processor, a temporary memory, and the like to perform
30 various types of operations, a signal conversion unit 28b including a

processor, a temporary memory, and the like, which performs processing for converting control command value data obtained by an operation by the main operation unit 28a into a pulse signal (PWM: a pulse width modulation signal) (An operation unit including the main operation unit 28a and the
5 signal conversion unit 28b is referred to as a control signal generation unit 29.), speed controllers (ESC: electric speed controllers) 30 to 34 that convert the pulse signal generated by the control signal generation unit 29 into driving currents, respectively, to the motors 17 to 21, a communication antenna 35 and a communication unit (including a processor, a temporary
10 memory, and the like) 36 that transmit and receive various types of data signals to and from outside, a sensor unit 37 including various types of sensors such as a GPS (global positioning system) sensor, an attitude sensor, an altitude sensor, and a direction sensor, a recording apparatus 39 including a recording device such as a hard disk drive that records an autonomous
15 flight program 38a, various types of databases 38b, and the like, and a power supply system 40 including a battery device such as a lithium polymer battery or a lithium ion battery and a power distribution system to each of elements.

[0037]

20 In addition, the unmanned aerial vehicle 1 may include any functional unit, information, and the like depending on a functional use. As an example, if the unmanned aerial vehicle 1 autonomously flies according to a flight plan, flight plan information, which is data representing a flight plan as any rule to follow during flight, such as a flight plan path as a set of a
25 start position and a destination of flight, and a check point position (a latitude, a longitude, and an altitude) through which the unmanned aerial vehicle 1 is to pass until it reaches the destination after starting at the start position, a speed limit, and an altitude limit is recorded in the recording apparatus 39, and the main operation unit 28a reads the flight plan
30 information to execute the autonomous control program 38a so that the

unmanned aerial vehicle 1 flies according to the flight plan. Specifically, the flight of the unmanned aerial vehicle 1 is controlled by determining a current position, a speed, and the like of the unmanned aerial vehicle 1 based on information obtained from the various types of sensors in the sensor unit 37, comparing the determined current position, speed, and the like with respective target values of the flight plan path, the speed limit, the altitude limit, and the like determined in the flight plan to operate respective control command values for the rotors 13 to 16 and the thrust generation propeller 25 in the main operation unit 28a, converting data respectively representing the control command values into pulse signals (generating control signals) and transmitting the pulse signals to the speed controllers 30 to 34 in the signal conversion unit 28b, respectively converting the pulse signals into driving currents and outputting the driving currents to the motors 17 to 21 in the speed controllers 30 to 34, and controlling drives of the motors 17 to 21 to control respective rotational speeds and the like of the rotors 13 to 16 and the thrust generation propeller 25. As an example, control is performed to increase the respective numbers of rotations of the rotors 13 and 16 for a control command to increase the altitude of the unmanned aerial vehicle 1 (decrease the numbers of rotations when the altitude is decreased), increase the number of rotations of the thrust generation propeller 25 for a control command to accelerate the unmanned aerial vehicle 1 in a forward direction (in the position direction of x in Figure 1A) (decrease the numbers of rotations when the unmanned aerial vehicle 1 is decelerated), and decrease the respective numbers of rotations of the rotors 14 and 16 for a control command to incline the unmanned aerial vehicle 1 by rolling around the x-axis illustrated in Figure 1A (in a counterclockwise direction as viewed in the positive direction of x) to maintain the respective numbers of rotations of the rotors 13 and 15, for example. Note that the acceleration (deceleration) in the forward direction of the unmanned aerial vehicle 1 can also be performed by controlling the

respective numbers of rotations of the rotors 13 to 16, for example, decreasing the respective numbers of rotations of the rotors 13 and 14 to increase the respective numbers of rotations of the rotors 15 and 16 (opposite control when the unmanned aerial vehicle 1 is decelerated), and the
5 unmanned aerial vehicle 1 can also be flown without using the thrust generation propeller 25. Note that simplified control can be performed. For example, the speed of the unmanned aerial vehicle 1 in the forward direction (in the positive direction of x in Figure 1A) can be performed by making all the respective numbers of rotations of the rotors 13 to 16 equal to
10 one another (performing control to only equally increase or decrease the respective numbers of rotations of all the four rotors 13 to 16) to float and land (or land on water) the unmanned aerial vehicle 1 and controlling the number of rotations of the thrust generation propeller 25. Flight recording information such as a flight path through which the unmanned aerial vehicle
15 1 has actually flown (e.g., a position of the aircraft of the unmanned aerial vehicle 1 at each time point) and various types of sensor data are recorded on various types of databases 38b, as needed, during flight.

[0038]

As examples of the autonomous flight type unmanned aerial vehicle,
20 Mini Surveyor ACSL-PF1 (Autonomous Control Systems Laboratory Ltd.), Snap (Vantage Robotics), AR. Drone 2.0 (Parrot), and Bebop Drone (Parrot), for example, are commercially available.

[0039]

Note that when the unmanned aerial vehicle 1 flies under control
25 from outside, the unmanned aerial vehicle 1 receives data representing a control command value received from a controller device or the like of the operator using the communication antenna 35 and the communication unit 36, converts the data into a pulse signal using the signal conversion unit 28b (generates a control signal), and controls respective rotational speeds of the
30 rotors 13 to 16 and the thrust generation propeller 25 using the speed

controllers 30 to 34 and the motors 17 to 21, to perform flight control. Even in this case, when the main operation unit 28a reads data representing attitude information of the unmanned aerial vehicle 1 obtained from the attitude sensor (a gyro sensor or a magnetic sensor) among the various types of sensors in the sensor unit 37 to execute the autonomous control program 38a, partial autonomous control and control from outside can also be combined with each other. For example, a command value of attitude control is operated by comparing the data from the attitude sensor with a target value of an attitude, for example, to perform attitude control (In this case, the main operation unit 28a operates a final control command value by executing the autonomous control program 38a based on data representing a control command value received from an external controller device or the like and data representing the command value of the attitude control. When the signal conversion unit 28b converts data representing the control command value into a pulse signal, a control signal including an attitude control signal is generated.). Although it is assumed that the unmanned aerial vehicle 1 basically flies in response to a control signal from the external controller device or the like in shooting flight described below, and only an attitude is autonomously controlled, similar shooting flight can also be performed by the unmanned aerial vehicle 1 that performs fully autonomous control flight and fully external control flight.

[0040]

Shooting Flight in Closed-type space by Unmanned aerial vehicle

As an example of shooting flight in a closed-type space by the unmanned aerial vehicle 1, shooting flight in a sewage pipeline will be described below with reference to Figures 10 to 14. Note that a use of the unmanned aerial vehicle, the flight control mechanism for the unmanned aerial vehicle, and the method using these according to the present invention as already described is not limited to such shooting flight, but an unmanned aerial vehicle, a flight control mechanism for the unmanned aerial vehicle,

and a method using these according to the present invention can be used in any environment and for any purpose.

[0041]

Figure 10 illustrates a structure of a sewage pipeline facility capable of flying the unmanned aerial vehicle illustrated in Figure 1A. A manhole 42a provided on a ground surface 41 leads to the sewage pipeline 43, and follows the sewage pipeline 43 in a rightward direction in Figure 10 to reach another manhole 42b (Although the sewage pipeline 43 is drawn by being cut at two points in the middle in Figure 10, this is a representation used for convenience and is actually formed as a consecutive sewage pipeline 43 longer than that illustrated.). A boundary surface of the closed-type space is defined by an inner wall 44 in the sewage pipeline 43, and a connection section 45 exists for each predetermined distance in the rightward direction in Figure 10 in the sewage pipeline 43.

[0042]

In performing the shooting flight in the sewage pipeline 43 by the unmanned aerial vehicle 1, the unmanned aerial vehicle 1 is advanced into the manhole 42a and dropped to a depth of the sewage pipeline 43. In an example, a holding table is provided at a distal end of a pole having approximately the same length as the depth of the manholes 42a and 42b, and the pole is inserted into the manhole 42a with the unmanned aerial vehicle 1 loaded on the holding table to drop the unmanned aerial vehicle 1. If the autonomous flight type unmanned aerial vehicle 1 is used, a position of the manhole 42a, the depth of the sewage pipeline 43, and the like may be previously recorded as a flight plan path on the recording apparatus 39, and the main operation unit 28a may read the flight plan information including data of the flight plan path and execute the autonomous control program 38a to autonomously fly the unmanned aerial vehicle 1 and guide the unmanned aerial vehicle 1 to one end of the sewage pipeline 43 (a left end in the sewage pipeline 43 in Figure 10, which is hereinafter referred to as a shooting flight

start position S), or may transmit a control signal to the unmanned aerial vehicle 1 from the external controller device and steer the unmanned aerial vehicle 1 to guide the unmanned aerial vehicle 1 to the shooting flight start position S.

5 [0043]

The unmanned aerial vehicle 1 starts the shooting flight in the rightward direction in Figure 10 (with the direction used as the positive direction of x in Figure 1A, i.e., the traveling direction) from the shooting flight start position (Figure 11). With manual control by the operator from
10 the external controller, the inspection camera 22 and the front camera 23 shoot a still image or a moving image within the sewage pipeline 43 while the unmanned aerial vehicle 1 is flying in the traveling direction upon receiving a control signal for issuing a forward instruction. Note that although water 46 normally exists in the sewage pipeline 43, and its water
15 level varies, as needed, a float force can also be obtained by a water surface effect produced by rotation of the rotors 13 to 16 can also be obtained (If there is no water 46, a similar effect can also be obtained from the inner wall 44.).

[0044]

20 Data of the still image or the moving image shot by the inspection camera 22 is recorded in a built-in memory in the inspection camera 22, and data of the still image or the moving image shot by the front camera 23 is transmitted, as needed, to an external computer of the operator from the communication antenna 35 by the communication unit 36 after being
25 recorded in a built-in memory in the front camera 23. The operator displays the still image or the moving image shot by the front camera 23 on a display provided in the external computer using the received data, and steers the unmanned aerial vehicle 1 by the external controller while confirming the still image or the moving image (If a communication quality between the
30 external controller and the communication antenna 35 is not sufficient, a

radio relay station is preferably previously installed in the sewage pipeline 43. A GPS signal can also be received similarly via the radio relay station.). In an example, the unmanned aerial vehicle 1 is steered while a distance by which the unmanned aerial vehicle 1 has advanced with the connection section 45 reflected on the displayed still image or moving image used as a landmark.

[0045]

During the shooting flight, the unmanned aerial vehicle 1 may excessively rise to collide with the inner wall 44 of the sewage pipeline 43 due to any reason such as an accuracy problem of manual control by the external controller or an accuracy problem of autonomous attitude control. A situation at this time is illustrated in Figure 12A. The preceding collision member 6 (as a rotary member such as a wheel or a roller) held by the holding member 9 in the unmanned aerial vehicle 1 contacts the boundary surface 47 between the sewage pipeline 43 and the inner wall 44, and a force in an arrow direction indicated by F in Figure 12A is exerted on the preceding collision member 6 from the inner wall 44. This force is exerted as a force for rotating the holding member 9 (with the shaft section for holding member 11A as a fixed rotation axis) in an arrow direction indicated by R in Figure 12A.

[0046]

When the holding member 9 rotates as described above, and the vehicle body further rises, both the rotary members 5 and 6 to be held by the holding member 9 contact the boundary surface 47, as illustrated in Figure 12B. The rotary members 7 and 8 to be held by the holding member 10 also contact the boundary surface 47 in a similar principle (Some of the rotary members may not contact the boundary surface 47 depending on a shape of the boundary surface.). Assuming that the holding member 9 is attached to be rotatable around a position lower than the corresponding set of rotors 13 and 14 (in the negative direction of z in Figure 1A) with the vehicle body not

inclined, and the holding member 10 is attached to be rotatable around a position lower than the corresponding set of rotors 15 and 16 (in the negative direction of z in Figure 1A) with the vehicle body similarly not inclined, the vehicle body is inclined in a similar direction to the direction of the inclination of the holding members 9 and 10, as described with reference to Figures 5A to 5E (Figure 12C). In this state, if the unmanned aerial vehicle 1 is flown in an x-direction in Figure 12C, for example, (In the present specification, "fly" also includes the unmanned aerial vehicle moving while floating with the components of the unmanned aerial vehicle contacting the boundary surface.), the unmanned aerial vehicle 1 flies along the boundary surface 47 while the rotary member, which contacts the boundary surface 47, among the rotary members 5 to 8 is rotating (see Figure 3B). Note that it is not essential to incline the vehicle body, as illustrated in Figure 12C. The unmanned aerial vehicle 1 can also fly along the boundary surface 47 with the vehicle body not inclined. Alternatively, the unmanned aerial vehicle 1 can fly along the boundary surface 47 even if the vehicle body is inclined in an opposite direction, as described with reference to Figures 6A to 6E. If the preceding collision members 5 to 8 are not each a rotary member such as a wheel or a roller, but are each a member fixed to the holding member, as described with reference to Figure 4, for example, the unmanned aerial vehicle 1 flies along the boundary surface 47 while the preceding collision member, which contacts the boundary surface 47, among the preceding collision members 5 to 8 is sliding.

[0047]

Note that although description has been made assuming that the boundary surface 47 is inclined in one direction in a region with which the preceding collision member collies in an example illustrated in Figures 12A to 12C, even if the preceding collision member collies with a flat region on the boundary surface 47, a region symmetrically inclined in both directions, or the like, the unmanned aerial vehicle 1 can basically be flown along the

boundary surface 47 in a similar principle. As an example, when the preceding collision member 5 contacts the region on the boundary surface 47 illustrated in Figure 13A, a force is exerted on the preceding collision member 5 from the inner wall 44 in an arrow direction indicated by F in Figure 13A, and the holding member 9 rotates in an arrow direction indicated by R in Figure 13A. When the vehicle body further rises, both the preceding collision members 5 and 6 to be held by the holding member 9 contact the boundary surface 47, as illustrated in Figure 13B. The preceding collision members 7 and 8 to be held by the holding member 10 also contact the boundary surface 47 in a similar principle (Some of the rotary members may not contact the boundary surface 47 depending on a shape of the boundary surface.). Hereinafter, the unmanned aerial vehicle 1 can fly along the boundary surface 47 in a similar principle. If the preceding collision member is a rotary member such as a wheel or a roller, the unmanned aerial vehicle 1 flies along the boundary surface 47 while rotating the rotary member that has contacted the boundary surface 47. With a member described with reference to Figure 4, the unmanned aerial vehicle 1 flies along the boundary surface 47 while sliding the member on the boundary surface 47.

[0048]

Note that the unmanned aerial vehicle 1 may be inclined due to any reason such as an accuracy problem of manual control and autonomous attitude control during the shooting flight in addition to or in a case other than a case where the preceding collision member collides with the boundary surface 47, as described above. As an example, Figure 14 illustrates how the unmanned aerial vehicle 1 is inclined by rotating (rolling) around the x-axis illustrated in Figure 1A. If the preceding collision member does not contact the boundary surface 47, for example, the lower side (the side in the positive direction of y) of the vehicle body can be raised by increasing the respective numbers of rotations of the rotors 13 and 15 to recover the

attitude of the vehicle body to be horizontal. However, in this case, the vehicle body rises so that the unmanned aerial vehicle 1 may collide with an upper surface of the inner wall 44. As described with reference to Figures 12A to 13B, if the unmanned aerial vehicle 1 flies along the boundary surface 47 with the inner wall 44, the collision need not particularly be prevented. However, if the unmanned aerial vehicle 1 is desired to be flown while avoiding contact with the boundary surface 47, the respective numbers of rotations of the rotors 14 and 16 are preferably reduced to lower the higher side (the side in the negative direction of y) of the vehicle body and recover the attitude to be horizontal. Although such attitude control is typically performed when the main operation unit 28a reads data representing the attitude information of the unmanned aerial vehicle 1 obtained from the attitude sensor, as described above, and executes the autonomous control program 38a, the attitude control may be performed by transmitting a control signal representing a control command value of an attitude from the external controller device (a control signal including an attitude control signal for issuing an instruction to roll in an opposite direction to that of the inclination illustrated in Figure 14), receiving the control signal in the unmanned aerial vehicle 1, and executing the autonomous control program 38a in the main operation unit 28a. The attitude can be recovered by similarly reducing the respective numbers of rotations of some of the rotors for the inclination of the unmanned aerial vehicle 1 by any rotation such as rotation around a y-axis (a pitch) or a z-axis (a yaw).

[0049]

The unmanned aerial vehicle 1 reaches the other end of the sewage pipeline 43 (a right end in the sewage pipeline in Figure 10, which is hereinafter referred to as a shooting flight end position G), the shooting flight ends. A pole having a holding table provided at its distal end is inserted into the manhole 42b, and the unmanned aerial vehicle 1 is loaded on the holding table and is pulled up, for example, to recover the unmanned

aerial vehicle 1. The unmanned aerial vehicle 1 may be pulled up from the end position G by autonomous flight, like when the unmanned aerial vehicle 1 is guided into a shooting flight start position S. Respective states of the sewage pipeline 43, the inner wall 44, and the like can be confirmed by
5 detaching the inspection camera 22 from the recovered unmanned aerial vehicle 1 and seeing a still image or a moving image recorded in the memory of the inspection camera 22.

[0050]

Figure 15 illustrates an example of an image in the sewage pipeline
10 shot by the front camera. A similar image can be obtained by the shooting flight of the unmanned aerial vehicle 1 loaded with the front camera 23. The operator can steer the unmanned aerial vehicle 1 using the external controller device while seeing a still image or a moving image at a first person view shot by the front camera 23 as illustrated in Figure 15. After
15 the shooting flight, the state of the sewage pipeline 43, for example, a crack of the inner wall 44 or a shift of a packing in the connection section 45 can be confirmed by detaching the inspection camera 22 from the recovered unmanned aerial vehicle 1 and seeing a still image or a moving image recorded in the memory.

20 [0051]

(Second Embodiment)

Then, an unmanned flying object, a shooting inspection system, and a shooting inspection method according to an embodiment of the present invention will be described with reference to the drawings. Note that the
25 shooting inspection system and the shooting inspection method according to the present invention are not limited to a specific mode described below, but are appropriately changeable within the scope of the present invention. For example, the unmanned flying object used for shooting inspection according to the present invention is not necessarily an unmanned flying object of a
30 type illustrated in Figure 16A, for example, but may be the unmanned flying

object (unmanned aerial vehicle) illustrated in Figure 1A, for example, or may be any other unmanned flying object. The unmanned flying object illustrated in Figure 16A, for example, may be an unmanned flying object that operates in a similar principle to that of the unmanned flying object
5 illustrated in Figure 1A, for example, except that it does not include a flight control mechanism including preceding collision members 5 to 8, holding members 9 and 10, and the like, and a functional configuration may be as illustrated in Figure 9. However, the unmanned flying object usable for the preset invention is not limited to that but may be arbitrary. For example,
10 the unmanned flying object illustrated in Figure 16A, for example, may include the flight control mechanism illustrated in Figure 1A, for example. The other configuration may also be arbitrary. Operations to be performed by a plurality of components may be performed by a single component, for example, a function of a communication unit is integrated with a main
15 operation unit. Alternatively, an operation to be performed by a single component as illustrated may be performed by a plurality of components, for example, a function of the main operation unit is distributed among a plurality of operation units. An autonomous control program of the unmanned flying object may be recorded on a recording device such as a hard
20 disk drive and read out and executed by the main operation unit (The autonomous control program as illustrated may be decomposed into a plurality of program modules, or any other programs may be executed by the main operation unit or the like), or a similar operation may be performed by a built-in type system using a microcomputer or the like. All components
25 illustrated in the following embodiment need not be included in the unmanned flying object (For example, the unmanned flying object need not include a thrust generation propeller 25 when propulsion of the unmanned flying object is controlled under control of rotors 13 to 16 illustrated in Figure 16B and need not include an autonomous control program and
30 various types of databases if the unmanned aerial vehicle is completely flown

under control from outside without performing autonomous control.), and the method according to the present invention need not include all method steps as illustrated. A rotary wing for floating the unmanned flying object is not limited to the four rotors 13 to 16 as illustrated in Figure 16B, for example, but may be any number of (four or more) rotary wings. A propeller for generating a thrust is not limited to the thrust generation propeller 25 illustrated in Figure 16D, for example, but may be any propeller. The unmanned flying object usable in the present invention is not limited to a rotorcraft. An vehicle body size of the unmanned flying object is also arbitrary. Although an example in which the unmanned flying object performs shooting flight in a closed-type space such as a sewage pipeline is illustrated in the following embodiment, the shooting inspection according to the present invention can be performed in not only the closed-type space but also any inspection space and for any purpose. Note that the closed-type space need not be completely closed, but may be a space that is at least partially closed and where flight of the unmanned flying object is at least partially restricted. For example, a tubular space in the sewage pipeline connected to the outside via a manhole is also a closed-type space, and a tunnel of a highway is also a closed-type space, as described in the following embodiment. Other members and components included in the shooting inspection system may be composed of any material if they can exhibit functions of the present invention. In addition, arbitrariness of the configuration described in association with the unmanned aerial vehicle according to the first embodiment similarly holds true for the unmanned flying object used in the shooting inspection according to the second embodiment. Elements and the like that may be similar to the elements and the like described in Figures 1A to 15 are respectively assigned similar reference characters in Figure 16A and subsequent figures.

[0052]

Configuration of Unmanned flying object

Figures 16A to 16F illustrate an appearance of an unmanned flying object that can be used for shooting inspection according to the present invention. Figure 16A is a perspective view, Figure 16B is a diagram viewed in a positive direction of z illustrated in Figure 16A (a coordinate system is defined, like in Figure 1A), Figure 16C is a diagram viewed in a positive direction of y, Figure 16D is a perspective view viewed from behind in a traveling direction, and Figures 16E and 16F are perspective views viewed in a negative direction of z (but in different directions) illustrated in Figure 16A. An unmanned flying object 1 is designed in dimensions of an overall width (a width in a y-direction in Figure 16A) of approximately 250 mm and an overall length (a width in an x-direction in Figure 16A) of approximately 570 mm to be able to fly in a closed-type space (inspection space) having a bore diameter of approximately 400 mm in an example, and includes a main body section 2 (housed in a waterproof case 3), five motors 17 to 21 (see Figure 17) that are driven in response to a control signal from the main body section 2, four rotors (rotary wings) 13 to 16 that respectively rotate by drives of the motors 17 to 20 to float the unmanned flying object 1 (The adjacent rotors respectively rotate in opposite directions, for example, the rotors 13 and 16 rotate in a clockwise direction viewed in the positive direction of z, and the rotors 14 and 15 rotate in a counterclockwise direction viewed in the positive direction of z), a thrust generation propeller 25 that rotates by a drive of the motor 21 to generate a thrust of the unmanned flying object 1, an inspection camera 22, a front camera 23, and an illumination light 48 that performs forward illumination (may further include a ultrasonic sensor 24 not illustrated at any position), and each of the components are integrated using a frame 4. A line-type member 49 is connected to a frame rear section 4a as illustrated in Figure 16D (the line-type member 49 is appropriately omitted in figures other than Figure 16D).

[0053]

The inspection camera 22 is a camera for shooting a still image or a moving image during flight in the inspection space by the unmanned flying object 1. In an example of the inspection camera 22, a commercially available camera such as a GoPro session (Tajima MOTOR CORPORATION) can be used. As described below, in an example of the shooting inspection, shooting by the inspection camera 22 is performed while the unmanned flying object 1 stops flying forward, and a draw device 50 winds the line-type member 49 to draw the unmanned flying object 1 toward a flight start stage 52 (The shooting by the inspection camera 22 may be started before the unmanned flying object 1 is put into the inspection space, the shooting by the inspection camera 22 may be continued until the unmanned flying object 1 is recovered from the inspection space, or start and stop of the shooting may be controlled at any timing by a remote operation.). The front camera 23 is a camera for shooting a still image or a moving image in the traveling direction during flight in the inspection space by the unmanned flying object 1. Data of the shot still image or moving image is transmitted to an external control device (e.g., a computer including a display), as needed, and an operator can steer the unmanned flying object 1 while confirming the data. The ultrasonic sensor 24 is a sensor for detecting an obstacle or the like ahead thereof, and can transmit a ultrasonic wave in the traveling direction during flight in the inspection space by the unmanned flying object 1 and measure a distance from the obstacle or the like by receiving a reflected wave. The inspection camera 22 and the front camera 23 may be each a camera such as an infrared camera or a ultraviolet camera. In an example of the shooting inspection, the unmanned flying object 1 is steered while the still image or the moving image shot by the front camera 23 is being confirmed in real time, and the still image or the moving image shot by the inspection camera 22 is confirmed after the unmanned flying object 1 is recovered from the inspection space, and the inspection camera 22 is then removed, to acquire shooting data from a memory of the inspection camera 22. Accordingly,

when resolution of the moving image or the still image obtained based on shooting data from the front camera 23 is made lower than resolution of the moving image or the still image obtained based on the shooting data from the inspection camera 22, the moving image or the still image can be examined, for example, using the shooting data (by the inspection camera 22) having a high resolution after shooting flight ends while making a communication data amount in data transmission/reception performed in real time during flight of the unmanned flying object 1 relatively low.

[0054]

Here, the inspection camera 22 is loaded at a position on the vehicle body of the unmanned flying object 1 and between the rotors 13 and 14 positioned on the side in the traveling direction (in a positive direction of x) and the rotors 15 and 16 positioned on the opposite side in the traveling direction (in a negative direction of x) among the four rotors 13 and 16, as illustrated in Figure 16A, for example. When the unmanned flying object 1 flies in a space, on a surface where a liquid (water, etc.) exists at least partially, such as a sewage pipeline, the liquid is scattered by rotation of the rotors 13 to 16. Accordingly, when the inspection camera 22 is loaded below the vehicle body or ahead of the vehicle body, the liquid is splashed on the inspection camera 22 so that the liquid (water splashes, water droplets, etc.) may also be reflected on the moving image or the still image shot by the inspection camera 22. However, if the inspection camera 22 is arranged, as illustrated in Figure 16A, for example, the rotors 13 to 16 at least partially prevent the scattered liquid from reaching a position above the vehicle body (The liquid is at least partially prevented from reaching a position of the inspection camera 22 by the liquid adhering to the rotors 13 to 16 and by a flow of gas below the vehicle body (in the negative direction of z) caused by the rotation of the rotors 13 to 16.). Accordingly, a moving image or a still image obtained by more favorably shooting a state inside the sewage pipeline can be obtained. The front camera 23 is also preferably arranged in a

similar position (a position different from the position of the inspection camera 22).

[0055]

Note that a method of connecting the unmanned flying object 1 and the line-type member 49 is arbitrary regardless of a mode illustrated in Figure 16D. As illustrated in Figures 16E and 16F, for example, the unmanned flying object 1 and the line-type member 49 can also be connected to each other by forming a through hole 4b and a through hole 4c in the frame 4, passing one wire 49a such as a piano wire through the through holes 4b and 4c to fasten the wire 49a to the through holes 4b and 4c and coupling the line-type member 49 to the wire 49a using a snap, a carabiner, or the like (Figure 16G).

[0056]

Figure 17 is a block diagram illustrating a functional configuration of the unmanned flying object illustrated in Figure 16A. The main body section 2 in the unmanned flying object 1 includes a main operation unit 28a, including a processor, a temporary memory, and the like, to perform various types of operations, a signal conversion unit 28b including a processor, a temporary memory, and the like, which performs processing for converting control command value data obtained by an operation by the main operation unit 28a into a pulse signal (PWM: a pulse width modulation signal) (An operation unit including the main operation unit 28a and the signal conversion unit 28b is referred to as a control signal generation unit 29.), speed controllers (ESC: electric speed controllers) 30 to 34 that convert the pulse signal generated by the control signal generation unit 29 into driving currents, respectively, to the motors 17 to 21, a communication antenna 35 and a communication unit (including a processor, a temporary memory, and the like) 36 that transmit and receive various types of data to and from outside, a sensor unit 37 including various types of sensors such as a GPS (global positioning system) sensor, an attitude sensor, an altitude sensor, and

a direction sensor, a recording apparatus 39 including a recording device such as a hard disk drive that records an autonomous flight program 38a, various types of databases 38b, and the like, and a power supply system 40 including a battery device such as a lithium polymer battery or a lithium ion battery and a power distribution system to each of elements, and an illumination light 48. In an example, respective functions of the main operation unit 28a, the recording apparatus 39, the communication unit 36, and the like may be implemented by storing a computer such as a laptop PC in the unmanned flying object 1. For example, a communication unit 67 (a communication circuit, a communication antenna, etc.) in an external control device 51 and the communication antenna 35 and the communication unit 36 (a communication circuit, etc.) in the laptop PC loaded on the unmanned flying object communicate with each other at a communication frequency of 5 GHz via a wireless LAN relay device 56.

[0057]

In addition, the unmanned flying object 1 may include any functional unit, information, and the like depending on a functional use. As an example, when the unmanned flying object 1 autonomously flies according to a flight plan, flight plan information, which is data representing a flight plan as any rule to follow during flight, such as a flight plan path as a set of a start position and a destination of flight, and a check point position (a latitude, a longitude, and an altitude) through which the unmanned flying object 1 is to pass until it reaches the destination after starting from the start position, a speed limit, and an altitude limit is recorded in the recording apparatus 39, and the main operation unit 28a reads the flight plan information to execute the autonomous control program 38a so that the unmanned flying object 1 flies according to the flight plan. Specifically, the flight of the unmanned flying object 1 is controlled by determining a current position, a speed, and the like of the unmanned flying object 1 based on information obtained from the various types of sensors in the sensor unit 37,

comparing the current position, the speed, and the like with respective target values of the flight plan path, the speed limit, the altitude limit, and the like determined by the flight plan to operate respective control command values for the rotors 13 to 16 and the thrust generation propeller 25 in the main operation unit 28a, respectively converting data representing the control command values into pulse signals (generating control signals) and transmitting the pulse signals to the speed controllers 30 to 34 in the signal conversion unit 28b, respectively converting the pulse signal into driving currents and outputting the driving currents to the motors 17 to 21 in the speed controllers 30 to 34, and controlling drives of the motors 17 to 21 to control respective rotational speeds and the like of the rotors 13 to 16 and the thrust generation propeller 25. As an example, control is performed to increase the respective numbers of rotations of the rotors 13 and 16 for a control command to increase the altitude of the unmanned flying object 1 (decrease the numbers of rotations when the altitude is decreased), increase the number of rotations of the thrust generation propeller 25 for a control command to accelerate the unmanned flying object 1 in a forward direction (in the position direction of x in Figure 16A) (decrease the number of rotations when the unmanned flying object 1 is decelerated), and decrease the respective numbers of rotations of the rotors 14 and 16 for a control command to incline the unmanned flying object 1 by rolling around the x-axis illustrated in Figure 16A (in a counterclockwise direction as viewed in the positive direction of x) to maintain the respective numbers of rotations of the rotors 13 and 15, for example. Note that the acceleration (deceleration) in the forward direction of the unmanned flying object 1 can also be performed by controlling the respective numbers of rotations of the rotors 13 to 16, for example, decreasing the respective numbers of rotations of the rotors 13 and 14 to increase the respective numbers of rotations of the rotors 15 and 16 (opposite control when the unmanned flying object 1 is decelerated), and the unmanned flying object 1 can also be flown without

using the thrust generation propeller 25. Note that simplified control can also be performed. For example, the speed control of the unmanned flying object 1 in the forward direction (in the positive direction of x in Figure 16A) can be performed by making all the respective numbers of rotations of the
5 rotors 13 to 16 equal to one another (performing control to only equally increase or decrease the respective numbers of rotations of all the four rotors 13 to 16) to float and land (or land on water) the unmanned flying object 1 and controlling the number of rotations of the thrust generation propeller 25. Flight recording information such as a flight path through which the
10 unmanned flying object 1 has actually flown (e.g., a position of the vehicle body of the unmanned flying object 1 at each time point) and various types of sensor data are recorded on various types of databases 38b, as needed, during flight.

[0058]

15 As examples of the autonomous flight type unmanned flying object, Mini Surveyor ACSL-PF1 (Autonomous Control Systems Laboratory Ltd.), Snap (Vantage Robotics), AR. Drone 2.0 (Parrot), and Bebop Drone (Parrot), for example, are commercially available.

[0059]

20 Note that when the unmanned flying object 1 flies under control from outside, the unmanned flying object 1 receives data representing a control command value received from a controller device or the like of the operator using the communication antenna 35 and the communication unit 36, converts the data into a pulse signal using the signal conversion unit 28b
25 (generates a control signal), and similarly controls respective rotational speeds of the rotors 13 to 16 and the thrust generation propeller 25 using the speed controllers 30 to 34 and the motors 17 to 21, to perform flight control. Even in this case, when the main operation unit 28a reads data representing attitude information of the unmanned flying object 1 obtained from the
30 attitude sensor (a gyro sensor or a magnetic sensor) among various types of

sensors in the sensor unit 37 to execute the autonomous control program 38a, partial autonomous control and control from outside can also be combined with each other. For example, a command value of attitude control is operated by comparing the data from the attitude sensor with a target value of an attitude, for example, to perform the attitude control (In this case, the main operation unit 28a operates a final control command value by executing the autonomous control program 38a based on data representing a control command value received from an external controller device or the like and data representing the command value of the attitude control. When the signal conversion unit 28b converts the data representing the control command value into a pulse signal, a control signal including an attitude control signal is generated.). Although it is assumed that the unmanned flying object 1 basically flies in response to a control signal from the external controller device or the like in shooting flight described below, and only the attitude is autonomously controlled, similar shooting flight can also be performed by the unmanned flying object 1 that performs fully autonomous control flight and fully external control flight.

[0060]

Shooting Inspection Using Unmanned flying object

As an example of shooting inspection in an inspection space using the unmanned flying object 1, shooting flight in a sewage pipeline will be described below with reference to Figures 18 to 30.

[0061]

A structure of a sewage pipeline facility is, for example, a structure as illustrated in Figure 10 also described in the first embodiment. A manhole 42a provided on a ground surface 41 leads to a sewage pipeline 43, and follows the sewage pipeline 43 in a rightward direction in Figure 10 to reach another manhole 42b (Although the sewage pipeline 43 is drawn by being cut at two points in the middle in Figure 10, this is a representation used for convenience and is actually formed as a consecutive sewage pipeline

43 longer than that illustrated.). A boundary surface of the inspection space is defined by an inner wall 44 in the sewage pipeline 43, respective wall surfaces of vertical holes continuing into the ground from the manholes 42a and 42b, and the like, and a connection section 45 exists for each
5 predetermined distance in the rightward direction in Figure 10 in the sewage pipeline 43.

[0062]

Shooting Inspection System

Figure 18 is a diagram illustrating a configuration example of a
10 shooting inspection system, including an unmanned flying object, for performing shooting inspection. The shooting inspection system includes an unmanned flying object 1, a flight start stage (launcher) 52 on which the unmanned flying object 1 can be placed, an external control device 51 such as a laptop PC, and a draw device 50 such as an automatic winding device that
15 automatically winds a line-type member 49 such as a fishing line in a similar principle to that of an electric reel for fishing. In an example, the shooting inspection is performed using the shooting inspection system by three workers such as (1) an operator who controls flight of the unmanned flying object 1 using the external control device 51, (2) a launcher/winder operator
20 who performs work for inserting the flight start stage 52 loaded with the unmanned flying object 1 into an inspection space and work for drawing the unmanned flying object 1, which has reached a destination in the inspection space or cannot advance due to any reason such as a damage to a sewer or existence of a deposit, to the flight start stage 52 using the draw device 50
25 and recovering the flight start stage 52 and the unmanned flying object 1 to the ground, and (3) an assistant.

[0063]

Figure 19 is a diagram illustrating apparatuses other than the unmanned flying object and the flight start stage in an example of the
30 shooting inspection system. A carriage 54 is loaded with the draw device 50,

the external control device 51, a wireless LAN (local area network) relay device (Wi - Fi relay device) 56, and external power supply apparatuses 57a and 57b, and is also provided with a window 55. The draw device 50 and the external control device 51 are loaded respectively using pillar-shaped members, and the wireless LAN relay device 56 is attached to the pillar-shaped member to which the draw device 50 is attached. The external control device 51 and the wireless LAN relay device 56 are supplied with electric power from the external power supply apparatus 57a via a power supply cable, and the draw device 50 is supplied with electric power from the external power supply apparatus 57b via a power supply cable. The external control device 51 and the wireless LAN relay device 56 are connected to each other via a LAN cable, and are communicable with each other. The window 55 can be opened, as illustrated in Figure 20, the window 55 is opened after the carriage 54 with the flight start stage 52 on which the unmanned flying object 1 is placed such that a position of the window 55 is just above the manhole 42a is moved, and the flight start stage 52 loaded with the unmanned flying object 1 is put into the inspection space (underground space) via the manhole 42a.

[0064]

Figure 21 is a block diagram illustrating a functional configuration of the laptop PC (personal computer) as an example of the external control device. The external control device 51 includes a processing unit 64 including a CPU (central processing unit) (the processing unit 64 controls an operation of each of elements included in the external control device 51), a storage unit 65 including a storage device such as a hard disk drive or an SSD (solid state drive), a display unit 66 including a display device such as a liquid crystal display device, a communication unit 67 that includes a communication circuit and the like and communicates with the wireless LAN relay device 56 via a LAN cable and further communicates (via the communication antenna 35) with the communication unit 36 in the

unmanned flying object 1 via the wireless LAN relay device 56 (may further communicate therewith via an antenna attached to the flight start stage 52) or wirelessly communicates with the unmanned flying object 1 directly without via the wireless LAN relay device 56, and an input unit 68 including
5 an input key or the like for receiving an input from the operator. The storage unit 65 stores a steering program for generating an instruction signal to the unmanned flying object 1 in response to the input from the operator, a drawing program for displaying shooting data of a moving image or a still image received by the communication unit 67 from the unmanned
10 flying object 1 on the display unit 66, an image processing program for performing image processing of the shooting data of the moving image or the still image acquired from the memory of the inspection camera 22 and stored in the storage unit 65 and generating a developed view or an expanded image of the inner wall 44 or the like of the inspection space, for example,
15 and the processing unit 64 executes the programs, to perform control of the unmanned flying object 1 and image processing.

[0065]

Figure 22 is a conceptual diagram for describing an operation of an automatic winding device that winds a line-type member such as a fishing
20 line or a string as an example of the draw device 50. A cylinder like member (spool) 63 connected to an end of the line-type member 49 rotates in an arrow direction in Figure 22 by a drive of a motor not illustrated so that the line-type member 49 is automatically wound around the cylinder like member 63. The unmanned flying object 1 is connected to an end, on the
25 opposite side to the cylinder like member 63, of the line-type member 49. When the unmanned flying object 1 flies and pulls the line-type member 49, the cylinder like member 63 rotates in the opposite direction to the arrow direction in Figure 22, and the line-type member 49 is unwound (extends) from the cylinder like member 63. However, if the cylinder like member 63
30 is rotated in the arrow direction in Figure 22 by the drive of the motor, to

wind the line-type member 49, the unmanned flying object 1 that has thus flown can be drawn and recovered. As the automatic winding device, various known or new reel apparatuses, for example, can be used. For example, electric reel devices respectively described in Patent Literatures 4
5 to 6 can be used.

[0066]

Figure 23A is a diagram of the flight start stage 52 viewed from the side (in a similar direction to that in Figure 18). The flight start stage 52 is attached to a distal end portion of the rod-shaped body 53 (The start stage 52
10 may be configured to be swingable with respect to the rod-shaped body 53, as indicated by an arrow in Figure 23A, or may be completely fixed to the rod-shaped body 53,) and is provided with an inclination section 61 for easily recovering the unmanned flying object 1. Guide members 59 are attached to the rod-shaped body 53. As illustrated in Figure 23B, each of the guide
15 members 59 is provided with a through hole 62, and has its one end connected to a rear end portion of the unmanned flying object 1 after the line-type member 49 extending from the cylinder like member 63 in the draw device 50 is passed through the through hole 62. As illustrated in Figure 23B, the inclination section 61 is provided with two slits 61a and 61b (for the
20 purpose of not preventing a flow of a solid material (e.g., a polluted material such as tissue paper) or polluted water). Note that when the flight start stage 52 illustrated in Figure 23A or the unmanned flying object 1 loaded on the flight start stage 52 is larger than an insertion port 55a or the manhole 42a, and cannot be inserted into the inspection space as it is, the flight start
25 stage 52 may be configured to be swingable (or rotatable), by being provided with a swing arm 53a, with the swing arm 53a used as an axis around the rod-shaped body 53. If the flight start stage 52 is swung, as illustrated in Figure 23C (The rod-shaped body 53 and the flight start stage 52 may be swung along one straight line, as viewed from a similar angle to that in
30 Figure 23A, or the rod-shaped body 53 and the flight start stage 52 may be at

a certain angle to each other, as illustrated in Figure 23C, in a range where the unmanned flying object 1 is insertable into the inspection space.), the flight start stage 52 loaded with the unmanned flying object 1 can be inserted into the inspection space even when the insertion port 55a and the manhole 42a are relatively small. Note that to prevent the unmanned flying object 1 from dropping when swinging the flight start stage 52, the flight start stage 52 is preferably provided with a stopper 52a (corresponding to a stopper hook in Figure 24B), as illustrated in Figure 23B, and a recess (or a hole, etc.) for hooking the vehicle body of the unmanned flying object 1 on the stopper 52a is preferably provided at the bottom of the vehicle body (for example, a depression is formed in the waterproof case 3 illustrated in Figure 16E). Note that the swing arm, the stopper hook, and the like illustrated in Figures 23A to 23C, for example, are only schematically drawn to describe functions, and a specific configuration for swinging the flight start stage 52 with respect to the rod-shaped body 53 and a specific configuration for preventing the unmanned flying object 1 from dropping from the flight start stage 52 may be each any one of all known configurations, or may be each any one of all new configurations. Alternatively, if the flight start stage 52 and the unmanned flying object 1 are previously configured to be smaller than both the insertion port 55a and the manhole 42a (such that they can pass through both the insertion port 55a and the manhole 42a), the flight start stage 52 can be inserted into the inspection space without being swung (In this case, the flight start stage 52 need not be configured to be swingable, and a swing arm and a stopper are also unnecessary).

[0067]

Figure 24A is a design drawing of one example of the flight start stage (corresponding to a diagram viewed from above in Figure 18), and Figure 24B is a design drawing of the one example of the flight start stage (corresponding to a diagram viewed in a similar direction to that in Figure

18). The flight start stage 52 is swingable with respect to the rod-shaped body 53. When the flight start stage 52 is swung in a direction along the rod-shaped body 53, for example, the unmanned flying object 1 is insertable into the inspection space even when the manhole is small (The unmanned flying object 1 can be fixed to the flight start stage 52 using a stopper base illustrated in Figure 24A and a stopper hook illustrated in Figure 24B.). As illustrated in Figures 24A and 24B, communication between the external control device 51 and the unmanned flying object 1 may be performed, by loading the rod-shaped body 53 to which the flight start stage 52 is attached with an antenna, using the antenna, communication may be performed by the external control device 51, the wireless LAN relay device 56, and the unmanned flying object (the communication antenna 35 and the communication unit 36) without loading the rod-shaped body 53 with an antenna), or the communication unit 67 in the external control device 51 (including a communication antenna, a communication circuit, or the like, if necessary) and the unmanned flying object 1 (the communication antenna 35 and the communication unit 36) may directly communicate with each other without using the wireless LAN relay device 56. Figure 24C is a design drawing of an antenna illustrated in Figures 24A and 24B, and Figure 24D is also a design drawing of the antenna illustrated in Figures 24A and 24B (illustrating connection with the rod-shaped body in a flight start stage). In Figures 24A to 24D, a unitless numerical value of a length is indicated in millimeters.

[0068]

Shooting Inspection Method

Then, a shooting inspection method performed using the shooting inspection system will be described. First, the launcher/winder operator inserts the rod-shaped body 53 into the inspection space from the insertion port 55a and the manhole 42a from the side of the flight start stage 52 with the rod-shaped body 53 held in his or her hand, to put the flight start stage

52 loaded with the unmanned flying object 1 into the inspection space (underground space) (Figure 25). When the unmanned flying object 1 or the flight start stage 52 is larger than at least one of the insertion port 55a and the manhole 42a, as already described, the flight start stage 52 is swung to
5 be along the rod-shaped body 53 or such that a certain angle is formed between the rod-shaped body 53 and the flight start stage 52, as illustrated in Figure 23C, in a range where it can pass through the insertion port 55a and the manhole 42a (The flight start stage 52 is provided with the stopper hook (Figure 24B), for example, to fix the unmanned flying object 1 to the
10 flight start stage 52. Note that at the time of start of subsequent flight, a method of releasing the unmanned flying object 1 from the stopper hook when flight is started is arbitrary. For example, the unmanned flying object 1 can be released from the stopper hook by being appropriately steered to take off. Alternatively, the unmanned flying object 1 is configured to start
15 to fly after the stopper hook moves and comes off the unmanned flying object 1 by remote control.). Then, the flight start stage 52 and the rod-shaped body 53 are inserted into the inspection space, and the flight start stage 52 that has swung after being inserted is returned to its original state (may be returned to its original state electrically by remote control, or may be
20 returned to its original state by being simply pressed downward, for example). Alternatively, if the flight start stage 52 and the unmanned flying object 1 are previously configured to be smaller than both the insertion port 55a and the manhole 42a (such that they can pass through both the insertion port 55a and the manhole 42a), the flight start stage 52 can be
25 inserted into the inspection space without being swung (In this case, the flight start stage 52 need not be configured to be swingable, and a stopper is also unnecessary.). After the flight start stage 52 lands in the inspection space (Figure 26), the operator inputs a control instruction from the input unit 68 in the external control device 51 (It is assumed that the steering
30 program stored in the storage unit 65 is being executed by the processing

unit 64), to start flight of the unmanned flying object 1 (Figure 27). The line-type member 49 is connected to the rear end portion of the unmanned flying object 1, and the unmanned flying object 1 flies in the inspection space while pulling the line-type member 49. Accordingly, the cylinder like member (spool) 63 in the draw device 50 rotates in the opposite direction to the arrow direction in Figure 22 so that the line-type member 49 is unwound (extends).

[0069]

The unmanned flying object 1 flies in an x-direction in Figure 28 in the sewage pipeline 43 while pulling the line-type member 49 according to a control instruction indicated by a control signal to be transmitted from the external control device 51. At this time, the unmanned flying object 1 shoots a still image or a moving image in the sewage pipeline 43 using the inspection camera 22 and the front camera 23 while flying in the traveling direction upon receiving a control signal for issuing an advance instruction (may not perform shooting using the inspection camera 22 while flying in the traveling direction). Note that although water 46 normally exists in the sewage pipeline 43, and its water level varies, as needed, a float force can also be obtained by a water surface effect caused by rotation of the rotors 13 to 16 (Even when there is no water 46, a similar effect can be obtained from the inner wall 44.).

[0070]

During flight, data of the still image or the moving image shot by the front camera 23 is transmitted, as needed (preferably in real time), to the external control device 51 of the operator from the communication antenna 35 by the communication unit 36 after being recorded in a built-in memory in the front camera 23. The external control device 51 receives the data of the still image or the moving image shot by the front camera 23 in the communication unit 67, and displays the still image or the moving image shot by the front camera 23 on a display (the display unit 66) included in the

external control device 51 using the received data (The processing unit 64 executes the drawing program stored in the storage unit 65 to control an operation of the display unit 66, and the display unit 66, which has been controlled by the processing unit 64, displays the still image or the moving
5 image.). The operator steers the unmanned flying object 1 by inputting a control instruction to the external control device 51 (The input unit 68 in the external control device 51 receives the input of the control instruction) at a first person view (FPV) while confirming the still image or the moving image displayed on the display unit 66 (A signal representing the control
10 instruction inputted by the operator is transmitted to the unmanned flying object 1 from the communication unit 67 in the external control device 51, and the unmanned flying object 1 receives the signal using the communication antenna 35 and the communication circuit 36, and flies according to the control instruction represented by the signal. As already
15 described, the communication unit 67 in the external control device 51 and the communication antenna 35 and the communication circuit 36 in the unmanned flying object 1 may directly communicate with each other, or may communicate with each other according to a wireless LAN communication standard while using an antenna or the like attached to the wireless LAN
20 relay device 56 or the rod-shaped body 53.). In an example, a distance by which the unmanned flying object 1 has advanced can be determined based on a length of the line-type member 49 pulled out of the draw device 50.

[0071]

When the unmanned flying object 1 finishes flying in the traveling
25 direction (in the x-direction in Figure 28) when it has reached a destination or when it cannot further advance due to any reason, for example, the unmanned flying object 1 receives the signal representing the control instruction inputted to the external control device 51 by the operator from the external control device 51, and performs hovering in situ according to the
30 control instruction represented by the signal. In an example, the

unmanned flying object 1 performs hovering by stopping the rotation of the thrust generation propeller 25 and controlling all respective rotational speeds of the rotors 13 to 16 to be an equal rotational speed (The adjacent rotors respectively rotate in opposite directions, for example, the rotors 13 to 16 rotate in a clockwise direction as viewed in the positive direction of z, and the rotors 14 and 15 rotate in a counterclockwise direction as viewed in the positive direction of z). When the launcher/winder operator operates the draw device 50 with the unmanned flying object 1 performing hovering, the draw device 50 winds the line-type member 49, and therefore the unmanned flying object 1 is drawn in a direction toward the flight start stage 52 (Figure 29).

[0072]

While the unmanned flying object 1 is being drawn in the direction toward the flight start stage 52 (while it is retreating or while it advancing in an arrow direction in Figure 29), the inspection camera 22 continues to shoot a still image or a moving image in the sewage pipeline 43 (The shooting by the inspection camera 22 may be started before the unmanned flying object 1 is put into the inspection space, the shooting by the inspection camera 22 may be continued until the unmanned flying object 1 is recovered on the ground, or the shooting by the inspection camera 22 may be performed only while the unmanned flying object 1 is being drawn by remote control.). An amount of water splashes scattered around the unmanned flying object 1 is small because the rotation of the thrust generation propeller 25 is stopped when the unmanned flying object 1 is retreating than when the unmanned flying object 1 is advancing. Accordingly, when the inspection camera 22 performs front shooting while the unmanned flying object 1 is retreating, a moving image or a still image that are less affected by the water splashes is obtained. Data of the still image or the moving image shot by the inspection camera 22 is recorded in a built-in memory in the inspection camera 22. Note that the front camera 23 also continues to shoot a still image or a

moving image at this time, and data of the still image or the moving image shot by the front camera 23 is transmitted, as needed (preferably in real time), to the external control device 51 of the operator from the communication antenna 35 by the communication unit 36 after being
5 recorded in the built-in memory in the front camera 23. As already described, the external control device 51 receives the data of the still image or the moving image shot by the front camera 23 in the communication unit 67, and displays the still image or the moving image shot by the front camera 23 on the display (the display unit 66) provided in the external control device
10 51 using the received data.

[0073]

As illustrated in Figure 30, the unmanned flying object 1 is drawn toward the flight start stage 52. When the unmanned flying object 1 returns to the top of the flight start stage 52 (It may be judged that the
15 unmanned flying object 1 has returned to the top of the flight start stage 52 based on the moving image or the still image, which has been shot by the front camera 23, to be displayed on the display unit 66, or it may be judged that the unmanned flying object 1 has returned to the top of the flight start stage 52 because the length of the line-type member 49 pulled out of the
20 draw device 50 becomes a predetermined length or less.), the launcher/winder operator operates the draw device 50 to stop winding the line-type member 49 by the draw device 50. When the operator inputs a control instruction to issue an instruction to finish hovering of the unmanned flying object 1 to the external control device 51, a signal representing the
25 control instruction is transmitted to the unmanned flying object 1 from the external control device 51, and the unmanned flying object 1 finishes hovering according to the control instruction represented by the signal to land on the flight start stage 52. Further, the launcher/winder operator pulls up the rod-shaped body 53 to the ground, to pull up the launcher 52 and
30 the unmanned flying object 1 to the ground and recover the launcher 52 and

the unmanned flying object 1 (The flight start stage 52 is swung with respect to the rod-shaped body 53, if necessary, like when the unmanned flying object 1 is inserted into the inspection space, to enable the flight start stage 52 loaded with the unmanned flying object 1 to pass through the manhole 42a and the insertion port 55a. In an example, the flight start stage 52 may be swung manually in a stage where the unmanned flying object 1 has approached the ground (At this time, the vehicle body of the unmanned flying object 1 may be manually hooked on the stopper 52a.), or the flight start stage 52 may be swung electrically by remote control (A specific method is arbitrary. For example, the flight start stage 52 is similarly swung after the stopper 52a is electrically moved by remote control to hook the vehicle body of the unmanned flying object 1 on the stopper 52a). Alternatively, if the flight start stage 52 and the unmanned flying object 1 are previously configured to be smaller than both the insertion port 55a and the manhole 42a (such that they can pass through both the insertion port 55a and the manhole 42a), the flight start stage 52 can be recovered without being swung (In this case, the flight start stage 52 need not be configured to be swingable, and a stopper is also unnecessary). Respective states of the sewage pipeline 43, the inner wall 44, and the like can be confirmed by removing the inspection camera 22 from the recovered unmanned flying object 1 and seeing a still image or a moving image recorded on the memory. After the data of the still image or the moving image shot by the inspection camera 22 is stored in the storage unit 65 in the external control device 51, the processing unit 64 executes the image processing program stored in the storage unit 65 to perform image processing of the data of the still image or the moving image, generates a developed view or expanded image data of the inner wall 44 or the like of the inspection space, and displays the developed view or the expanded image data as a developed view or an expanded image on the display unit 66 so that an inner state of the sewage pipeline facility can be more appropriately grasped (See Figure 31. Although an expanded

image 69 is displayed on the display unit 66 in Figure 31, the expanded image 69 may be displayed as a developed view such as a line diagram by being appropriately processed.).

5 Industrial Applicability

[0074]

The present invention can be used for shooting inspection in any inspection space such as the inside of a water supply pipeline, the inside of a sewage pipeline, the inside of a drainage channel, the inside of a tunnel of a highway, the inside of a drainage pipe of the highway, the inside of a cave passage, the inside of a duct, the inside of a pipe shaft, or the inside of a gas pipeline. The present invention is also usable when an unmanned aerial vehicle (unmanned flying object) is flown for any purpose in any space.

15 Reference Signs List

[0075]

- 1 unmanned aerial vehicle, unmanned flying object
- 2 main body section
- 3 waterproof case
- 20 4 frame
- 4a frame rear section
- 4b, 4c through hole
- 4A to 4D rotation stop position
- 5 to 8 preceding collision member
- 25 5A to 8A shaft section for preceding collision member
- 9, 10 holding member
- 9A, 10A hole
- 9B-1, 9B-2, 10B-1, 10B-2 preceding collision member attachment member
- 30 9C-1, 9C-2, 10C-1, 10C-2 hole

	11, 12	holding member attachment member
	11A, 12A	shaft section for holding member
	13 to 16	rotor
	17 to 21	motor
5	22	inspection camera
	23	front camera
	24	ultrasonic sensor
	25	thrust generation propeller
	26	center of gravity
10	27A	motor member
	27B	motor member
	27C	motor member
	27A-1	groove
	28A	main operation unit
15	28b	signal conversion unit
	29	control signal generation unit
	30 to 34	speed controller
	35	communication antenna
	36	communication unit
20	37	various types of sensors
	38a	autonomous control program
	38b	various types of databases
	39	recording apparatus
	40	power supply system
25	41	ground surface
	42a, 42b	manhole
	43	sewage pipeline, inspection space
	44	inner wall
	45	connection section
30	46	water

	47	boundary surface
	48	illumination light
	49	line-type member
	49a	wire (piano wire, etc.)
5	50	draw device
	51	external control device
	52	flight start stage (launcher)
	52a	stopper
	53	rod-shaped body
10	53a	swing arm
	54	carriage
	55	window
	55a	insertion port
	56	wireless LAN (Wi - Fi) relay device
15	57a, 57b	external power supply apparatus
	58	wheels (four wheels)
	59	guide member
	60	wheels (four wheels)
	61	inclination section
20	61a, 61b	slit
	62	through hole
	63	cylinder like member (spool)
	64	processing unit
	65	storage unit
25	66	display unit
	67	communication unit
	68	input unit
	69	expanded image

Claims

[Claim 1]

A shooting inspection system comprising:

5 a flight start stage on which an unmanned flying object can be placed;

the unmanned flying object that is connected to a line-type member, comprises an inspection camera, a traveling direction shooting camera, and an unmanned flying object-side communication unit, and starts to fly from a state where the unmanned flying object is placed on the flight start stage in an inspection space, shoots in a traveling direction in the inspection space using the traveling direction shooting camera, and flies in the inspection space while transmitting traveling direction shooting data obtained by shooting in the traveling direction from the unmanned flying object-side communication unit;

10 15

an external control device that comprises a display unit and an external control device-side communication unit, receives the traveling direction shooting data by the external control device-side communication unit, accepts an input of a control instruction to the unmanned flying object while displaying a moving image or a still image obtained based on the traveling direction shooting data on the display unit, and transmits a signal representing the control instruction from the external control device-side communication unit; and

20

a draw device that is connected to the line-type member and draws the unmanned flying object,

25

wherein the unmanned flying object comprises:

a frame having a shape elongated along a forward direction;

four rotary wings, wherein a first pair of the four rotary wings is positioned on a front-half side of the frame and a second pair of the four rotary wings is positioned on a back-half side of the frame, and wherein the

30

four rotary wings are positioned inside the frame;

a driver that drives the four rotary wings;

a control signal generation unit that is configured to generate a control signal for causing the driver to drive the four rotary wings, wherein
5 the control signal generation unit is positioned between the first pair of the four rotary wings and the second pair of the four rotary wings,

wherein the first pair of the four rotary wings and the second pair of the four rotary wings are arranged apart from each other in the forward direction inside the frame and the control signal generation unit is positioned
10 in an area between the first pair of the four rotary wings and the second pair of the four rotary wings, the area resulting from the apart arrangement, so that the first pair of the four rotary wings, the control signal generation unit, and the second pair of the four rotary wings are arranged apart from each other in the forward direction in the order of the first pair of the four rotary
15 wings, the control signal generation unit, and the second pair of the four rotary wings,

wherein the traveling direction shooting camera is placed at a position on the vehicle body of the unmanned flying object, the position being between the first pair of the four rotary wings and the second pair of the four rotary
20 wings.

[Claim 2]

A shooting inspection method comprising:

putting an unmanned flying object that is connected to a line-type member and comprises an inspection camera, a traveling direction shooting
25 camera, and an unmanned flying object-side communication unit into an inspection space with the unmanned flying object placed on a flight start stage;

by the unmanned flying object, starting to fly from a state where the unmanned flying object is placed on the flight start stage in the inspection
30 space, shooting in a traveling direction in the inspection space using the

traveling direction shooting camera, and flying in the inspection space while transmitting traveling direction shooting data obtained by shooting in the traveling direction from the unmanned flying object-side communication unit;

5 by an external control device which includes a display unit and an external control device-side communication unit, receiving the traveling direction shooting data using the external control device-side communication unit, accepting an input of a control instruction to the unmanned flying object while displaying a moving image or a still image obtained based on the
10 traveling direction shooting data on the display unit, and transmitting a signal representing the control instruction from the external control device-side communication unit; and

 by a draw device, connected to the line-type member, drawing the unmanned flying object,

15 wherein the unmanned flying object comprises:

 a frame having a shape elongated along a forward direction;

 four rotary wings, wherein a first pair of the four rotary wings is positioned on a front-half side of the frame and a second pair of the four rotary wings is positioned on a back-half side of the frame, and wherein the
20 four rotary wings are positioned inside the frame;

 a driver that drives the four rotary wings;

 a control signal generation unit that is configured to generate a control signal for causing the driver to drive the four rotary wings, wherein the control signal generation unit is positioned between the first pair of the
25 four rotary wings and the second pair of the four rotary wings,

 wherein the first pair of the four rotary wings and the second pair of the four rotary wings are arranged apart from each other in the forward direction inside the frame and the control signal generation unit is positioned in an area between the first pair of the four rotary wings and the second pair
30 of the four rotary wings, the area resulting from the apart arrangement, so

that the first pair of the four rotary wings, the control signal generation unit, and the second pair of the four rotary wings are arranged apart from each other in the forward direction in the order of the first pair of the four rotary wings, the control signal generation unit, and the second pair of the four rotary wings,

wherein the traveling direction shooting camera is placed at a position on the vehicle body of the unmanned flying object, the position being between the first pair of the four rotary wings and the second pair of the four rotary wings.

[Claim 3]

The method according to claim 2, wherein the draw device is an automatic winding device that winds the line-type member to draw the unmanned flying object.

[Claim 4]

The method according to claim 2 or 3, wherein the draw device draws the unmanned flying object with the unmanned flying object stopping traveling in the traveling direction and floating.

[Claim 5]

The method according to any one of claims 2 to 4, wherein the inspection camera performs shooting in the inspection space while the unmanned flying object is being drawn by the draw device.

[Claim 6]

The method according to any one of claims 2 to 5, further comprising generating a developed view or expanded image data corresponding to a boundary surface of the inspection space from inspection camera shooting data obtained by the shooting using the inspection camera, and displaying the developed view or the expanded image data as an image.

[Claim 7]

The method according to any one of claims 2 to 6, wherein an antenna is attached to the flight start stage, and communication between the

unmanned flying object-side communication unit and the external control device-side communication unit is performed according to a wireless LAN (local area network) communication standard using the antenna.

[Claim 8]

5 The method according to any one of claims 2 to 7, wherein resolution of the moving image or the still image obtained based on the traveling direction shooting data is lower than resolution of a moving image or a still image obtained based on shooting data obtained by the shooting using the inspection camera.

10 [Claim 9]

 The method according to any one of claims 2 to 8, wherein the flight start stage is attached to a distal end portion of a rod-shaped body, and the rod-shaped body is inserted into the inspection space from the flight start stage on which the unmanned flying object is placed to put the unmanned
15 flying object into the inspection space.

[Claim 10]

 The method according to claim 9, wherein the unmanned flying object is put into the inspection space by placing the flight start stage that is attached to the distal end portion of the rod-shaped body and on which the
20 unmanned flying object is placed on a carriage and inserting the rod-shaped body into the inspection space from an opening provided in the carriage.