164164

G00001

Claims

1. An apparatus for containing fluid, the apparatus comprising:

a first portion;

a second portion;

a third portion extending between the first and second portions, the third portion being collapsible for enabling displacement of the first portion one of towards and away from the second portion; and

a body adapted for enclosing the first, second and third portions,

wherein the first, second and third portions are shaped and inter-configured for defining a volume for liquid containment, the volume being variable by displacing the first portion one of towards and away from the second portion.

2. The apparatus of claim 1, at least one of the first portion and the second portion being substantially rigid.

3. The apparatus of claim 1, wherein a plurality of pleats is formed on the third portion for facilitating folding of the third portion.

4. The apparatus of claim 1, wherein one of the first and second portions has at least one opening for at least one of receiving fluid into and dispensing fluid from the volume.

5. The apparatus of claim 1, wherein at least one of the first and second portions has an opening adapted for connecting to a nozzle for fluid communicating the nozzle to the opening.

6. The apparatus of claim 1, further comprising a pump mechanism for extracting fluid contained within the volume.

7. The apparatus of claim 6, wherein the pump mechanism comprises a centrifugal pump.

8. The apparatus of claim 7, wherein the centrifugal pump is direct current (DC) powered.

9. The apparatus of claim 6, wherein one of the first and second portions has a cavity adapted for receiving the pump mechanism.

10. The apparatus of claim 1, wherein the first, second and third portions are removably positionable in the body.

11. The apparatus of claim 1, wherein the body is configured for enclosing the first, second and third portions when the apparatus is at one of an expanded and compressed position.

12. The apparatus of claim 1, wherein the body is configured for matching the outer shape of at least one of the first, second and third portions.

13. The apparatus of claim 1, wherein the body has a fastener for facilitating the first, second and third portions in one of inserting into and removing from the body.

14. The apparatus of claim 13, wherein the fastener is a zip.

15. The apparatus of claim 1, wherein the body is adapted for receiving at least one of a handle and wheels.